

# IEEE P1394.1 SCAT

## SCAT summary, sorted by status

	Task	Status	Assigned to
11.	Reset notification	Wait	(pending tasks 4&5)
4.	Setting-up of the routing table	Open	Wooten
8.	Device/Node discovery mechanism	Open	
14.a.	Commands & responses - Delivery mechanism	Open	James
14.b.	Commands & responses - Actual list of commands & responses	Open	
16.	Congestion	Open	James
19.	Minimum requirements for remote transaction capable nodes	Open	James (ed)
20.	Response packet synthesis	Open	James, Johansson
21.	Error & retry handling	Open	James, Johansson
23.	Isoch connection management	Open	Toguchi
29.	Isoch required or optional	Open	
30.	Identify portals during self-id	Open	Johansson
31.	Virtual node id lifetime issues	Open	
1.	Multiple bridges may not actively connect a pair of buses	Closed	
2.	Asynch response & request packets shall follow the same path	Closed	
3.	Sub-net architecture	Closed	
5.	Virtual Node Ids	Closed	Johansson, Wooten
6.	Clock synchronization via go-fast, go-slow mechanism	Closed	
7.	Quarantine	Closed	(part of task 9)
9.	Async packet time-of-death	Closed	
10.	Arbitration fairness	Closed	Johansson
12.	Isoch timestamp adjustment	Closed	Johansson
13.	Initial & forwarding speed of async packets, maximum packet size	Closed	
14.c.	Commands & responses - Use command model	Closed	
15.	Role of bridge manager	Closed	
17.	Virtual bus behavior	Closed	wireless group
18.	Handling of short interruptions	Closed	wireless group
22.	Eavesdropping (packets addressed to self)	Closed	
24.	EUI-64 per bridge or per portal	Closed	Johansson
25.	Not require a separate bridge manager?	Closed	
26.	Maintain order of subactions through bridges	Closed	Johansson
27.	Go-fast / go-slow duration	Closed	
28.	Async stream format with modifiable source id	Closed	Passed to P1394a
32.	Net clock source preference	Closed	

# IEEE P1394.1 SCAT

## SCAT summary, sorted by task number

	Task	Status	Assigned to
1.	Multiple bridges may not actively connect a pair of buses	Closed	
2.	Asynch response & request packets shall follow the same path	Closed	
3.	Sub-net architecture	Closed	
4.	Setting-up of the routing table	Open	Wooten
5.	Virtual Node Ids	Closed	Johansson, Wooten
6.	Clock synchronization via go-fast, go-slow mechanism	Closed	
7.	Quarantine	Closed	(part of task 9)
8.	Device/Node discovery mechanism	Open	
9.	Async packet time-of-death	Closed	
10.	Arbitration fairness	Closed	Johansson
11.	Reset notification	Wait	(pending tasks 4&5)
12.	Isoch timestamp adjustment	Closed	Johansson
13.	Initial & forwarding speed of async packets, maximum packet size	Closed	
14.a.	Commands & responses - Delivery mechanism	Open	James
14.b.	Commands & responses - Actual list of commands & responses	Open	
14.c.	Commands & responses - Use command model	Closed	
15.	Role of bridge manager	Closed	
16.	Congestion	Open	James
17.	Virtual bus behavior	Closed	wireless group
18.	Handling of short interruptions	Closed	wireless group
19.	Minimum requirements for remote transaction capable nodes	Open	James (ed)
20.	Response packet synthesis	Open	James, Johansson
21.	Error & retry handling	Open	James, Johansson
22.	Eavesdropping (packets addressed to self)	Closed	
23.	Isoch connection management	Open	Toguchi
24.	EUI-64 per bridge or per portal	Closed	Johansson
25.	Not require a separate bridge manager?	Closed	
26.	Maintain order of subactions through bridges	Closed	Johansson
27.	Go-fast / go-slow duration	Closed	
28.	Async stream format with modifiable source id	Closed	Passed to P1394a
29.	Isoch required or optional	Open	
30.	Identify portals during self-id	Open	Johansson
31.	Virtual node id lifetime issues	Open	
32.	Net clock source preference	Closed	

# IEEE P1394.1 SCAT

## SCAT detail

- 1) Should multiple bridges be allowed to actively connect a pair of buses (loop topology).  
Approved motion: Between any two buses there shall be only one path for async traffic.  
[Original wording: Async routing decisions shall be based only on destination bus\_id]  
Noted: We are not limiting the number of physically present bridges, just which are enabled in the routing.
- 2) Asynch response & request packets shall follow the same path.  
(Covered by the decision in item 1.)
- 3) Sub-net architecture  
Closed. It was noted that the virtual node id concept eliminated the proposer's desire for subnets.
- 4) Setting-up of the routing table (vs. routing bounds as in draft v0.3)  
Partly designed, needs more design & text.
- 5) Virtual Node Ids  
Text is in draft 0.04 Needs review.  
Peter Johansson & David Wooten volunteered to work on this.
  - Handle change of alpha portal
  - Synchronization of virtual node id maps between portals
  - Store bus\_id value in bus\_id field of NODE\_IDS register in non-portal nodes, or leave 3FF
  - Reassign same virtual node id (if possible) when reconnect a device
  - Time to not re-use virtual node id is from:
    - disconnect, or
    - last packet addressed to the id, if any after disconnect
- 6) Clock synchronization via go-fast, go-slow mechanism  
Consensus: Use preallocated isoch channel method. The tag or sy header field will indicate go-fast or go-slow. All P1394.1-aware and P1394b nodes that are cycle master capable must be IRM capable and handle these adjustment commands. Node must indicate that it supports the commands in its config rom. P1394.1 specification will predefine a channel number. The cycle master/root must preallocate this channel & bandwidth before making the channels / bandwidth available registers available after reset.
- 7) Quarantine  
(This is part of time of the death task, item 9.)
- 8) Device/Node discovery mechanism  
(Wait until the virtual node id stuff is done.)

## IEEE P1394.1 SCAT

- 9) Async packet time-of-death  
(This includes split timeout.)  
Text is in virtual node ids draft document.  
Consensus so far:
  - no wrapper
  - each bridge has a limit for how long it may take to forward a packet
    - fixed?
    - configurable?
    - use split timeout value of bus the bridge accepted the packet from?
    - use split timeout value of bus the bridge is placing the packet on?
- 10) Arbitration fairness  
Consensus: All bridge portals shall implement 1394a unfair arbitration.  
Peter Johansson to add text to draft.
- 11) Reset notification  
(Wait until the virtual node id stuff is done.)
- 12) Isoch timestamp adjustment  
Text from SBP-2 was inserted in P1394.1 draft 0.03. This will need some updating to reflect bus times only frequency locked.
- 13) Initial & forwarding speed of async packets, and maximum packet size  
Simple method proposed in document BR047R00. If people want something more capable, they can write a proposal.
- 14) Commands & responses
  - a) Delivery mechanism  
P1212r has discussed enhancing the message passing mechanisms.  
P1394.1 discussed what requirements we may have for P1212r, consensus was "not much".  
Needs design & text.
  - b) Actual list of commands & responses  
Wait until the functions using commands are better defined.  
Build as various sections are done
  - c) Command model  
Consensus: We will use a command model for bridge setup & control rather than CSR model.
- 15) Role of bridge manager  
Inclusive list of possibilities recorded. We will try not to have a bridge manager.
- 16) Congestion  
Proposal in document BR047R00. Needs review.
- 17) Virtual bus behavior (wireless)  
This topic is handed off to the people who want to work on nonstandard physical layers, and closed in this working group.
- 18) Handling of short interruptions (wireless)  
This topic is handed off to the people who want to work on nonstandard physical layers, and closed in this working group.
- 19) Minimum requirements for remote transaction capable nodes  
Inclusive list of possibilities recorded.

## IEEE P1394.1 SCAT

- 20) Response packet synthesis  
Proposal in document BR047R00.
- 21) Error & retry handling  
Dave James & Peter Johansson volunteered to work on this.
- 22) Eavesdropping (packets addressed to self)  
Concept agreed. Needs to be written in the specification.
- 23) Isoch connection management  
Toguchi-san will work on design & some specification text.
- 24) EUI-64 per bridge or per portal  
Consensus: There shall be a separate EUI-64 for each portal of a bridge.  
Peter Johansson to put (one sentence???) in draft.
- 25) Should bridges be smart enough to not require a separate bridge manager?  
Consensus: Try to do this, if possible.
- 26) Maintain order of subactions through bridges  
Consensus: This will not be required. Peter Johansson to add clarifying comment in draft.
- 27) Go-fast / go-slow duration  
Should go-fast / go-slow stay in effect for: one cycle, n cycles, until another command is received? Decided: Only in effect for the current cycle. Need to add text (in conjunction with item 6 above).
- 28) Async stream format  
Approved motion to recommend to P1394a to include in that specification.
- 29) Isoch required or optional  
We need to decide whether all bridges will be required to route isochronous traffic, or if the capability will be optional.
- 30) Identify portals during self-id  
Peter Johansson volunteered to determine the best way to identify bridge portals during self-id.
- 31) Virtual node id lifetime issues  
Resolve issues regarding the lifetime of virtual node ids, including whether bridge forwarding time limits should be variable or fixed..
- 32) Net clock source preference  
Should any device be given preference in the selection of a net clock source? If so, how is this done?  
Decision: Net clock source will be cycle master of prime bus