

9. Alternative low cost, long distance physical media dependent layer -- CAT 5 UTP

The alternative low cost long distance physical layer specified by this section (CAT-5 UTP) enables signaling over 50m of cable while keeping interoperability with the IEEE P1394b interface at a data rate of 100Mbps.

9.1 Overview

This clause specifies the physical media dependent (PMD) sublayer of CAT-5 UTP links for the data rate of 100Mbps. This PMD provides a digital baseband point-to-point interconnection among IEEE P1394b equipment for a distance extension over 50m, which meets the requirements for a IEEE P1394b long distance link. The PMD provides all of the services required to transport a suitably coded digital bit stream across the link segment.

The PMD sublayer specified in this clause has the following general characteristics:

- Provides full duplex line transmission of P1394b beta mode packets at 125 MBaud
- Supports operation over at least 50 meters of Category 5 cabling
- Bit Error Rate of less than or equal to 10^{-10}

9.2 Glossary of Terms

- BER - Bit Error Ratio
- UTP - Unshielded Twisted Pair
- CAT-5 - Category 5 cabling

9.3 Operation of CAT-5 links

P1394b CAT-5 links employ full-duplex baseband transmission over two pairs of Category 5 Unshielded twisted-pair wiring. The signals are NRZ binary symbols sent at 125 MBaud according to the standard P1394b symbol encodings. Connection between the CAT-5 cable system and the P1394b PHY I/O pads may be accomplished by means of pulse transformers which ensure impedance matching and fully differential signal launch/reception over the useful spectrum of the bit stream.

9.4 Media specification

The UTP link may consist of cable, end connectors and intermediate connection devices such as patch panels and wall plates.

9.4.1 100 ohm UTP link segment specification

All components of a link segment shall meet the requirements specified by ISO/IEC 11801 for category 5 compliance. In addition, the link shall meet the requirements specified by ISO/IEC 11801 chapter 7 for a 100 ohm balanced class D link, adjusted for a maximum channel length of 50m. This adjustment shall be made by subtracting the maximum permitted attenuation of 50m of category 5 100 ohm balanced UTP from the maximum attenuation value. This implies that the maximum attenuation at 62.5 MHz is 9.85 dB.

A link segment containing a combination of no more than 40m of category 5 UTP, no more than 10m of category 5 flexible cord and no more than four category 5 connectors is compliant with this specification.

9.4.2 100 ohm UTP cable specification

The transmission medium for a UTP PMD channel shall be two pair or four pair 100 ohm balanced UTP meeting all the requirements for 100 ohm balanced category 5 cables specified by ISO/IEC 11801:1995 chapter 8.

9.4.3 Connection hardware

All connecting hardware used within a UTP PMD channel (including outlets, transition connectors, patch panels and cross connect fields) shall meet or exceed the requirements specified in chapter 9 of ISO/IEC 11801 for category 5 100 ohm balanced cabling.

The procedures described in Annex A.2 of ISO/IEC 11801 shall be used to make all measurements verifying the compliance of connection hardware. The connector termination practices and UTP cable practices described in chapter 10 of EIA/TIA-568-A shall be followed.

Editorial note: Is the reference to EIA 568 chapter 10 correct?

9.4.4 Media Interface Connector

An eight pin receptacle (jack), meeting the requirements of IEC 603-7, shall be used as the mechanical interface between the PMD and the UTP link segment. Figure [tbd] and table [tbd] describe the pin assignment that shall be used for this connector

The link segment shall be terminated at each end with an eight pin plug, meeting the requirements of IEC 603-7. The link segment shall include a crossover function. The crossover shall connect pins 1 and 2 of the media interface connector at one end of a link segment to pins 7 and 8 respectively at the other end of the link segment. The fashion in which this crossover is implemented (for example, within a patchcord or within connection hardware) is beyond the scope of this standard.




Figure 9-1—Media Interface Connector

Editorial note: is IEC 603-7 the most up to date reference for the RJ45 spec?

Table 9-1—Media Interface Connector pin assignments

Pin	Circuit
1	Tx+
2	Tx-
3	
4	
5	
6	
7	Rx+
8	Rx-

9.5 PMD electrical specifications

9.5.1 Galvanic isolation

A coupling transformer is normally used within a UTP PMD to electrically isolate the 1394b PHY and the UTP cable plant. The UTP PMD shall provide electrical isolation according to at least one of the following electrical strength tests:

- a) 1500 V rms at 50 Hz to 60 Hz for 60 seconds, applied as specified in Section 5.3.2 of IEC Publication 950.
- b) 2250 Vdc for 60 seconds, applied as specified in Section 5.3.2 of IEC Publication 950.
- c) A sequence of ten 2400 V impulses of alternating polarity, applied at intervals of not less than 1 second. The shape of the impulses shall be 1.2/50 ms (1.2 ms virtual front time, 50 ms virtual time or half value) as defined in IEC Publication 60.

There shall be no insulation breakdown, as defined in Section 5.3.2 of IEC Publication 950, during the test. The resistance after the test shall be at least 2 Megaohms, measured at 500 Vdc.

9.5.2 Transmitter specifications

The signal measured at the output of the UTP PMD media interface connector shall meet the requirements of table [tbd]. In addition, the signal shall satisfy the requirements of the eye diagram mask shown in figure [tbd].

Table 9-2—UTP transmitter electrical specifications

Parameter	Requirement	Units
Differential amplitude		
Max	763	mV
Min	510	mV
Max(OFF)	162	mV
Rise/fall time		
Max	3,336	ps
Min	tbd	ps
Differential skew	200	ps
Jitter	tbd	ps
Output balance		
0.1-30MHz	>45	dB
30-60MHz	>40	dB
60-100MHz	>35	dB
Return loss	tbd	dB

NOTE 1—The transmitter differential amplitude specification may be met by a transmitter compliant with table [tbd] coupled through a transformer having a turns ratio of $\sqrt{\frac{110}{100}}$ and an insertion loss of 1 dB.

NOTE 2—Whilst this specification is intended to enable compliance with regulations concerning RF emissions, it is not intended to ensure compliance with these regulations. The implementor should consider any applicable local, national or international regulations. The implementor's attention is also drawn to the information contained within Annex A of EIA/TIA 568-A.

NOTE 3—Output balance is defined as the ratio of differential voltage to common mode voltage at the output of the transmitter.

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66




Figure 9-2—Eye diagram mask for transmitted signal.

9.5.3 Receiver specifications

9.5.3.1 Receiver input signals

A UTP PMD receiver shall be capable of recovering data with a Bit Error Rate of better than or equal to 1 in 10^{10} when receiving signals from the output of a worst case link segment. The link segment shall consist of an appropriate length of cable and number of connectors, such that the link attenuation is equivalent to the sum of the maximum attenuation specified in ISO/IEC 11801 chapter 8 for 50m of category 5 UTP and the maximum attenuation specified in ISO/IEC 11801 chapter 9 for four category 5 connectors.

The receiver shall also be capable of recovering data with a Bit Error Rate of better than or equal to 1 in 10^{10} when receiving signals from the output of a link segment comprising any length of category 5 UTP cable up to 50m, and any number of connectors up to a maximum of 4.

In addition to this, the receiver shall comply with the requirements of table [tbd].

Table 9-3—UTP receiver electrical specifications

Parameter	Requirement	Units
Minimum differential sensitivity	100	mV
Input impedance	100 +/- 15	ohm
Return loss	tbd	dB

9.6 Testing

TBD -- various cable, transmitter and receiver test modes and templates.