

IEEE 1722a

Assumptions

Dave Olsen
dave.olsen@harman.com

Green Text = Agreed to at a Face 2 Face (was Blue or Red)

Black Text = Not Decided

Changes Marked with Red from last version

Subtype Assignment

- New subtypes
 - 0x02 AVTP Audio Format
 - 0x03 AVTP Video Format
 - 0x04 Control Streams (Automotive/TSCS)
 - 0x7a AVDECC Discovery
 - 0x7b AVDECC Enumeration and Control
 - 0x7c AVDECC Connection Management
 - 0x7d Media Clock Negotiation
- Divide the subtype table between C and D to clarify that these are different subtype domains
- May need a new type for arbitrary clocking stream

Mac Address Assignment

- MCN needs MAC address (91:E0:F0:00:FF:01)
- 1722.1 has requested a block of 16k MAC addresses to be assigned by 1722a from the 1722 OUI (91:E0:F0:01:00:00 – 91:E0:F0:01:FF:FF)

Changes to current standard

- Redefine gateway info to only be valid for 61883 formats
- Gateway info field to be replaced by a protocol specific field that can be used in new protocols
- GV bit to also be redefined to be available for use in new protocol types or reserved where not used
- Update reference to 802.1AS-2011
- Update other references???

AVTP Audio Format

- Support PCM audio
 - Support more channels
 - Simpler data parsing
- Event Markers
- Link Protection field to indicate encryption
 - Encryption will be indicated by the new Version 1 security header

AVTP Audio Format LPCM Format

- Timestamp in every packet
 - Always the presentation time of the first sample
- Supported formats
 - 32 bit float (IEEE 754)
 - 32 bit integer
 - 24 bit integer, packed
 - 16 bit integer, packed
 - Interleaved only for all formats
- All packets in a single stream are the same size (i.e. Each frame contains the same number of samples)
 - All frames including the final stream frame must contain valid sample data
 - Any extra sample data that does not fill up a complete frame should be dropped

AVTP Video

- Support new native AVTP formats
 - Pro Video Formats as per 1722a-rsilfvast-pro_video_formats_v3_22-Oct-2012
 - Support RAW sensor data (no one is claiming a desire for this, will be dropped if no further interest)
 - IIDC formats currently support this functionality.
- Support RTP Payload formats
 - Support MJPEG (RFC 2435)
 - Support MJPEG2000 (RFC 5372)
 - Support H.264 (RFC 6184)
- Event Markers
 - Proposal to increase the number to >2
 - SOF/EOF Markers used in RTP and other formats (We don't know what this means???)
- Encryption is part of Version 1 Header
- HDCP is available for use in PES with no further work in 1722a

Media Clock Negotiation

- Frequency multipliers to match 1722.1
 - 1.001, 1/1.001, 24/25, 25/24
- Clock Quality field(s) to be added between priority1 and priority2
 - Media Clock variance should be determined by PTPDEV (16 bit field)
 - gptp_clock_period field related to gPTP interval typically 8ns or 40ns (8 bit field)
- Required Crystal GUID to be added for informational purposes to MCN Advertise packet

Media Clock Stream

- Need to define an optimized media clock stream frame format
- May need separate definitions for audio and video

Real Time Format Change (the HDMI problem)

- Include markers to indicate change
 - Prechange indication??
 - Format identifier??
 - Formats are prenegotiated
 - One bit could set to indicate a change is coming and then reset to indicate the change is here
- Required in AVTP audio/video formats
- Add bits to 61883 base formats
- Could this be used by the 802.1 multitalker problem??
- This feature relies on HDCP and so we should put this on hold until we solve the HDCP Problem

Diagnostics

- Diagnostic Counter to be included with 1722a
 - List included in current draft

1722/1722a PICS

- 1722/1722a only (no PICS **will be** derived from IEC 61883 specific standards)
- Need PICS for AVTP audio/video
- Need PICS for MCN

DTCP/HDCP

- Only support for HDCP IIA can possibly be included in this standard.
 - Everything else requires approval by DTLA
 - HDCP will be indicated in the PES
- 1722a will not work with the DTLA to get approval
- HDCP IIA APM protocol moved into 1722.1

Control Streams

- Automotive base format
 - Flexray Protocol
 - CAN Protocol
 - LIN Protocol
- TSCS Protocol (Time Sensitive Control Stream)
- We will not be defining FlexRay synchronization

Security with minimal latency

- Informative Annex
- MacSec – per link encryption
- 802.1X – per LAN authentication
- How do I secure a live performance?
 - Class A Stream latency
- Need a volunteer or this will be dropped

Synchronization bits

- Need Synchronization Marker bits
- Currently M0 and M1
- Do we need more bits? Maybe 4 bits
- M0 used for format change
- M1 used to synchronize external events
- Can we add these same bits to the 61883 streaming formats? No

Version 1 Format

- New format to support security header
 - See [koftinoff_1722a-V1b.pdf](#)
 - Packet signing
 - ECC
 - Encryption
 - AES-GCM encryption
 - ECC
 - Make use of IEEE 1363a

Other items?

- We have been contacted by IEC100 (IEC 61883 group) for a formal liaison
- New draft of 61883-6 that is coming. Do we want support it?

Goals

- Next draft before December F2F 2012
 - Update Automotive Control Streams – Dave
 - Update TSCS – Jeff
 - Header Version 1 draft – Dave/Jeff
 - Update all diagrams, including all in 1722
 - Pending technical closure
 - Update AAF – Ashley/Jeff
 - Add Pro Video Formats – Rob
- Later draft
 - HDCP Annex (moved to 1722.1)
 - MCN State Machine
 - AVTP formats and MCN PICS