

2005/05/25

IEEE 802.16-05/015r3

Document under Review: **P802.16-2004/Cor1/D1**

Ballot Number: **17**

Comment Date

Comment # **135**

Comment submitted by: **Lalit**

Kotecha

Comment Type **Technical, Binding**

Starting Page # **59**

Starting Line # **3**

Fig/Table#

Section **8.4.4.7**

Suggested Remedy

Deletion of this section is not acceptable. It deteriorates specificatins by removing an imporatant part of standard using Advanced Antenna system - beamforming method.

Proposed Resolution

Recommendation:

Recommendation by

Reason for Recommendation

Resolution of Group

Decision of Group: Rejected

Reason for Group's Decision/Resolution

When the group decided on the deletion of section 8.4.4.7, the group's feeling was that the section is erroneous, does not comply with the rest of the spec and is incomplete.

Group's Notes

Group's Action Items

Editor's Notes

Editor's Actions

Editor's Questions and Concerns

Editor's Action Items

2005/05/25

IEEE 802.16-05/015r3

Document under Review: **P802.16-2004/Cor1/D1**

Ballot Number: **17**

Comment Date

Comment # **173**

Comment submitted by: Ran

Yaniv

Comment Type **Technical, Binding** Starting Page # **91** Starting Line # Fig/Table# Section **8.4.6.1.2.1**

A well-designed permutation should minimize the hit ratio between any two subchannels. However, the hit ratio of PUSC in reuse 1/3 configuration is such that a single subchannel in one cell may be hit by the same subchannel in the neighbor cell in as many as 38% of its tones.

Additional problems with PUSC permutation:

The standard deviation of the hit count on a subchannel is high and itself varies widely between different subchannels and IDcell pairs. The number of different permutation sequences is restricted to 8 due to the size of the odd major groups.

Suggested Remedy

Adopt contribution 802.16maint-05/083 ("Hit Ratio Problems with PUSC Permutation").

Proposed Resolution

Recommendation:

Recommendation by

Reason for Recommendation

Resolution of Group

Decision of Group: Out of Scope

Reason for Group's Decision/Resolution

Motion to rule the comment in scope by Tal Kaitz seconded by Shlomo Ovadia

Vote:

In favour: 12

Against: 28

Abstain: 1

Fails

Group's Notes

Group's Action Items

Editor's Notes

Editor's Actions

Editor's Questions and Concerns

Editor's Action Items

2005/05/25

IEEE 802.16-05/015r3

Document under Review: **P802.16-2004/Cor1/D1**

Ballot Number: **17**

Comment Date

Comment # **175**

Comment submitted by: Ran

Yaniv

Comment	Type Technical, Binding	Starting Page # 92	Starting Line # 17	Fig/Table#	Section 8.4.6.1.2.1.1
---------	--------------------------------	---------------------------	---------------------------	------------	------------------------------

Several changes to the PUSC permutation IDcell values were adopted in session #35 as a result of contribution maint-04/72r3. As a result, the IDcell for the outer permutation in the first DL zone is now 0 and for the inner permutation it is now specified by the preamble IDcell.

The accepted solution is not satisfactory in the sense that it forces a reuse-3 deployment on the first zone, while the standard is clearly built to support unplanned frequency reuse-1 in other zones (FUSC, PUSC with 'use all SC', optional FUSC). The need to plan the deployment for the first zone takes most of the sting about of the standard's support for reuse-1.

A possible solution is to have the outer permutation in the first zone behave differently based on the LSB of the preamble IDcell. For example:
IDcell of outer permutation for 1st DL zone = 0 if LSB = 0;
IDcell of outer permutation for 1st DL zone = preamble IDcell (as is the case for zones with 'use all SC=1') if LSB = 1

Suggested Remedy

clarify the support for reuse-1 on the first DL zone:

[modify the text on page 92, lines 17-20 as follows:]

In the first PUSC zone of the downlink (first downlink zone), the default used DL_PermBase is equal to 0 when the LSB of the preamble IDcell is 0, and is equal to the preamble IDcell when the LSB is 1. When the 'Use all SC indicator=0' in the STC_DL_Zone_IE(), DL_PermBase is replaced with 0. For All other cases DL_PermBase parameter in the STC_DL_Zone_IE() shall be used.

Proposed Resolution

Recommendation:

Recommendation by

Reason for Recommendation

Resolution of Group

Decision of Group: Out of Scope

Reason for Group's Decision/Resolution

Motion to rule the comment in scope by Tal Kaitz, seconded by Ran Yaniv

Vote:

In favor: 10

Against: 12

Abstain: 1

Fails

2005/05/25

IEEE 802.16-05/015r3

Group's Notes

Group's Action Items

Editor's Notes

Editor's Actions

Editor's Questions and Concerns

Editor's Action Items

Document under Review: **P802.16-2004/Cor1/D1**Ballot Number: **17**

Comment Date

Comment # **179**

Comment submitted by: Ran Yaniv

Comment	Type	Technical, Binding	Starting Page #	93	Starting Line #	38	Fig/Table#	Section	8.4.6.1.2.2.2
---------	------	--------------------	-----------------	----	-----------------	----	------------	---------	---------------

The in-slot subcarrier rotations in both DL-PUSC and UL-PUSC permutations are clearly not suited for repetition codes. When repetition occurs over time, repeated bits are placed on the same subcarrier rather than on different subcarriers. As a result, repetition does not combat the fading properties of the channel.

This problem occurs with DL-PUSC and with UL-PUSC when the subchannel rotation scheme is not applied (optional UL PUSC, AAS mode).

Suggested Remedy

change PUSC so that in-slot rotation takes both time and frequency into account:

1) [modify the text on page 569, lines 59-61 of 802.16-REVd/D5 as follows:]

s is the index number of a subchannel, from the set [0...Nsubchannels-1]

t is the index number of the slot-duration within the zone; the first slot-duration has index 0

$nk = (k + 13 \cdot (s + t)) \bmod N_{\text{subcarriers}}$

2) [modify the text on page 573, lines 21-29 of 802.16-REVd/D5 as follows:]

$\text{subcarrier}(n, s) = (n + 13 \cdot (s + t)) \bmod N_{\text{subcarriers}}$

where

n is a running index 0...47

s is the subchannel number.

t is the index number of the slot-duration within the zone; the first slot-duration has index 0

Nsubcarriers is the number of subcarriers per subchannel.

Proposed Resolution

Recommendation:

Recommendation by

Reason for Recommendation

Resolution of Group

Decision of Group: **Out of Scope**

Reason for Group's Decision/Resolution

2005/05/25

IEEE 802.16-05/015r3

Reason for Group's Decision/Resolution

Motion to rule the comment in scope by Ran Yaniv, seconded by Tal Kaitz

Vote:

In favor: 8

Against: 10

Abstain: 2

Fails

Group's Notes

Group's Action Items

Editor's Notes

Editor's Actions

Editor's Questions and Concerns

Editor's Action Items

2005/05/25

IEEE 802.16-05/021r3

Document under Review: **P802.16-2004/Cor1/D2**

Ballot Number: **17a**

Comment Date

Comment # **004**

Comment submitted by: Jing

Wang

2005-04-22

Comment	Type	Starting Page #	Starting Line #	Fig/Table#	Section
	Technical, Binding				8.4.4.2

In the current standard how pilot tones are modulated using the PRBS generation is not specified. For example, is PRBS assigned in physical or logical numbering? It is not clear, in PUSC mode, whether PRBS is assigned to only specific segments or all the sub-carriers, including DC.

Suggested Remedy

One solution is to apply PRBS to all the sub-carriers, starting from first used one, in physical number ordering. Alternatively, in the downlink, for PUSC, FUSC, AMC, and optional FUSC permutation, pilot tones are logically renumbered frequency-domain first (starting from the lowest numbered subcarrier) then time (starting from the lowest numbered OFDMA symbol). In PUSC only pilot tones of clusters assigned to the specific segments are logically sequenced and pilot tones are not subject to cluster renumbering. After pilot tones are logically sequenced, the PRBS sequence described in 8.4.9.4.1 are mapped to the pilot tones.

Proposed Resolution **Recommendation:** **Recommendation by**

Reason for Recommendation

Resolution of Group **Decision of Group: Accepted-Modified**

On page 144, line 48, append the sentence:

"A new value shall be generated by the PRBS for every subcarrier up to the highest numbered usable subcarrier, in order of physical subcarriers, including the DC subcarrier and usable subcarriers that are not allocated."

Reason for Group's Decision/Resolution

Group's Notes

Deferred until 4:30 pm

Group's Action Items

Editor's Notes **Editor's Actions** k) done

Editor's Questions and Concerns

Editor's Action Items

2005/05/25

IEEE 802.16-05/021r3

Document under Review: **P802.16-2004/Cor1/D2**

Ballot Number: **17a**

Comment Date

Comment # **026**

Comment submitted by: Jing

Wang

2005-04-22

Comment	Type	Starting Page #	Starting Line #	Fig/Table#	Section
Since 6.3.10.1 is no longer applicable for OFDMA PHY, should this message still be supported for OFDMA PHY	Technical, Binding	20			6.3.2.3.20

Suggested Remedy

Add sentence to the first paragraph: " This message is not applicable for OFDMA PHY" and also add the same sentence for section 6.3.2.3.21

Proposed Resolution

Recommendation:

Recommendation by

Reason for Recommendation

Resolution of Group

Decision of Group: Accepted-Modified

On page 20, line 47, insert the following:

"Add the following sentence at the beginning of the section:

This mechanism is not applicable to OFDMA PHY.

On page 20, line 65, insert the following:

"6.3.2.3.21 Downlink Burst Profile Change Response (DBPC-RSP) message

"Add the following sentence at the beginning of the section:

This mechanism is not applicable to OFDMA PHY.

Reason for Group's Decision/Resolution

Group's Notes

Group's Action Items

Editor's Notes

Editor's Actions k) done

Editor's Questions and Concerns

Editor's Action Items

2005/05/25

IEEE 802.16-05/021r3

Document under Review: **P802.16-2004/Cor1/D2**

Ballot Number: **17a**

Comment Date

Comment # **117**

Comment submitted by: Tal

Kaitz

2005-04-22

Comment Type **Technical, Satisfied** Starting Page # **128** Starting Line # Fig/Table# Section **8.4.7**

As shown in contribution 802.16maint-05/094, the performance of the ranging codes in noise limited conditions is not satisfactory.

Suggested Remedy

Adopt the changes recommended in 802.16maint-05/094

Proposed Resolution

Recommendation:

Recommendation by

Reason for Recommendation

Resolution of Group

Decision of Group: Rejected

Motion to rule the comment as out of scope, by Zion Hadad, seconded by Frank Draper:

In favor: 15

Against: 8

Fails

Vote to accept the comment:

In favor: 3

Against: 16

Fails

Reason for Group's Decision/Resolution

The group believes that the contribution is an improvement and thus out of scope of the project, in addition, the suggestions in the contribution might not provide improvement in an interference limited scenarios.

Group's Notes

Group's Action Items

Editor's Notes

Editor's Actions |) none needed

Editor's Questions and Concerns

Editor's Action Items

2005/05/25

IEEE 802.16-05/021r3

Document under Review: **P802.16-2004/Cor1/D2**

Ballot Number: **17a**

Comment Date

Comment # **118**

Comment submitted by: Ran

Yaniv

2005-04-22

Comment Type **Technical, Binding** Starting Page # **128** Starting Line # Fig/Table# Section **8.4.7**

802.16-2004 defines an initial ranging scheme that is based on transmitting either one or two CDMA codes over 6 subchannels (8 with optional PUSC).

However, these schemes do not work when the deployment consists of a multiple-antenna BS (a supported configuration of 802.16-2004) and a power limited SS that requires either repetition or mini-subchannels for its operation. In such scenarios, the code misdetection rate goes as high as 25% misdetection rate for a 1% false alarm rate. With a single-antenna BS, detection performance is only marginal.

These results are obtained under unrealistically optimistic assumptions: time offset is perfectly known, a single code hypothesis, and that there is no contention on the ranging slot.

Suggested Remedy

Consider and adopt contribution C802.16maint-05/094.

Proposed Resolution

Recommendation:

Recommendation by

Reason for Recommendation

Resolution of Group

Decision of Group: Superseded

By comment #117

Reason for Group's Decision/Resolution

Group's Notes

Group's Action Items

Editor's Notes

Editor's Actions l) none needed

Editor's Questions and Concerns

Editor's Action Items

2005/05/25

IEEE 802.16-05/021r3

Document under Review: **P802.16-2004/Cor1/D2**

Ballot Number: **17a**

Comment Date

Comment # **124**

Comment submitted by: Sean

Cai

2005-04-22

Comment Type **Technical, Binding**

Starting Page # **130**

Starting Line # **17-2**

Fig/Table#

Section **8.4.7.3**

In the ranging codes initial clock count should not be multiple of 144 to avoid wrap around. The original 120 was fine.

Suggested Remedy

In the ranging codes initial clock counter formula, the 120 should not be changed to 144.

Proposed Resolution

Recommendation:

Recommendation by

Reason for Recommendation

Resolution of Group

Decision of Group: Rejected

Reason for Group's Decision/Resolution

The author requests the comment to be rejected due to lack of harmonization

Group's Notes

Deferred until Thursday 08:00

Group's Action Items

Editor's Notes

Editor's Actions |) none needed

Editor's Questions and Concerns

Editor's Action Items

2005/05/25

IEEE 802.16-05/021r3

Document under Review: **P802.16-2004/Cor1/D2**

Ballot Number: **17a**

Comment Date

Comment # **157**

Comment submitted by: **Ran**

Yaniv

2005-04-22

Comment Type **Technical, Binding** Starting Page # **150** Starting Line # Fig/Table# Section **8.4.11.3**
The section on CINR reporting contains several problems:

1. The text does not specify to what the CINR measurement relates.
2. The text states that CINR is measured on "messages". It is not clear to which "messages" the text refers.
3. It is not clear whether the averaging factor alpha applies to measurements reported through CQICH.
4. CINR estimates derived for CQICH should be kept distinct from reports triggered by REP-REQ/RSP.
etc.

Suggested Remedy

Adopt contribution 802.16maint-05/082r1.

Proposed Resolution Recommendation: Recommendation by

Reason for Recommendation

Resolution of Group Decision of Group: Rejected

Reason for Group's Decision/Resolution

The author requested the comment to be rejected due to lack of harmonization

Group's Notes

Defer until Wednesday morning and tie to Comment #18.

Group's Action Items

Editor's Notes Editor's Actions l) none needed

Editor's Questions and Concerns

Editor's Action Items

Document under Review: **P802.16-2004/Cor1/D2**

Ballot Number: **17a**

Comment Date

Comment # **180**

Comment submitted by: Ran

Yaniv

2005-04-22

Comment Type **Technical, Binding** Starting Page # **163** Starting Line # Fig/Table# **358** Section **11.4.1**

Contribution maint-04/72r3, which was accepted during session #35, clarifies the values of 'IDcell' used for the two equations that define the PUSC permutation (cluster permutation and eq. (111), aka 'inner permutation'). The clarification states that for zones with indicator 'use all SC=1', the DL_PermBase value specified in the zone_switch_IE is the one used for both the inner and cluster permutations of PUSC (same DL_PermBase value for both).

I object to the accepted solution since it adds an unneeded restriction to the system. For zones with 'use all SC=1', a separate PermBase value should be used for inner/cluster permutations of PUSC without any additional complexity. This has merit because it can be shown that PUSC permutation hit-ratio properties depend on the DL_PermBase value used; hence better optimization of hit-ratio can be achieved by selecting distinct PermBase values for the different components of the permutation

Suggested Remedy

[Add the following field to table 358 (DCD channel encodings):]

<u>DL ClusterPermBase</u>	<u>21</u>	<u>1</u>	<u>Value used in the clustering renumbering formula described in section 8.4.6.1.2.1.1, for PUSC zones for which the indicator 'use all SC' = 1.</u>	<u>OFDMA</u>
----------------------------------	------------------	-----------------	---	---------------------

[modify text on page 92, lines 16-21]

LogicalCluster = RenumberingSequence((PhysicalCluster+13*IDcell~~DL_PermBase~~ **DL ClusterPermBase**) mod 120)
~~In the first PUSC zone of the downlink (first downlink zone), the default used IDcell is 0. In the first PUSC zone of the downlink (first downlink zone) the default used DL_PermBase is 0. When the 'Use all SC indicator=0' in the STC_DL_Zone_IE(), DL_PermBase is replaced with 0. For All other cases~~ **DL ClusterPermBase parameter transmitted in the DCD message shall be used, or, if the parameter was not transmitted in a DCD message, the DL_PermBase parameter in the STC_DL_Zone_IE() shall be used.**

Proposed Resolution Recommendation: Recommendation by

Reason for Recommendation

[Add the following field to table 358 (DCD channel encodings):]

<u>DL ClusterPermBase</u>	<u>21</u>	<u>1</u>	<u>Value used in the clustering renumbering formula</u>
----------------------------------	------------------	-----------------	--

described in section 8.4.6.1.2.1.1, for PUSC zones for which the indicator 'use all SC' = 1.

[modify text on page 92, lines 16-21]

LogicalCluster = RenumberingSequence((PhysicalCluster+13*IDcell~~DL_PermBase~~ **DL_ClusterPermBase**) mod 120)

~~In the first PUSC zone of the downlink (first downlink zone), the default used IDcell is 0. In the first PUSC zone of the downlink (first downlink zone) the default used DL_ClusterPermBase is 0. When the 'Use all SC indicator=0' in the STC_DL_Zone_IE(), DL_ClusterPermBase is replaced with 0. For All other cases~~ **DL_ClusterPermBase parameter transmitted in the DCD message shall be used, or, if the parameter was not transmitted in a DCD message, the DL_PermBase parameter in the STC_DL_Zone_IE() shall be used.**

Resolution of Group

Decision of Group: Rejected

Reason for Group's Decision/Resolution

Vote to accept the comment:

In favor: 2
Against: 4
Fails

Reason:

Use of the same permutation is to enable macro-diversity multicast/broadcast services when 'use all SC=1'

Group's Notes

Group's Action Items

Editor's Notes

Editor's Actions |) none needed

Editor's Questions and Concerns

Editor's Action Items