

Project	IEEE 802.16 Broadband Wireless Access Working Group < http://ieee802.org/16 >	
Title	WirelessMAN-SCa Support For Overlapped Uplink Transmissions	
Date Submitted	2003-07-22	
Source(s)	Bob Nelson MacPhy Modems Inc. 1104 Pittsburgh Landing Richardson, TX 75080 Brian Eidson Conexant Systems, Inc. 9868 Scranton Road San Diego, CA 92121-1762	Voice: 972-239-9224 MailTo: bob_nelson@ieee.org Voice: 858-713-4720 brian.eidson@conexant.com
Re:	Call for Reply Comments on Letter Ballot #11a	
Abstract	Alters SCa MAC/PHY interface to support overlapped uplink transmissions	
Purpose	Suggested remedy for comment 160	
Notice	This document has been prepared to assist IEEE 802.16. It is offered as a basis for discussion and is not binding on the contributing individual(s) or organization(s). The material in this document is subject to change in form and content after further study. The contributor(s) reserve(s) the right to add, amend or withdraw material contained herein.	
Release	The contributor grants a free, irrevocable license to the IEEE to incorporate material contained in this contribution, and any modifications thereof, in the creation of an IEEE Standards publication; to copyright in the IEEE's name any IEEE Standards publication even though it may include portions of this contribution; and at the IEEE's sole discretion to permit others to reproduce in whole or in part the resulting IEEE Standards publication. The contributor also acknowledges and accepts that this contribution may be made public by IEEE 802.16.	
Patent Policy and Procedures	The contributor is familiar with the IEEE 802.16 Patent Policy and Procedures < http://ieee802.org/16/ipr/patents/policy.html >, including the statement "IEEE standards may include the known use of patent(s), including patent applications, provided the IEEE receives assurance from the patent holder or applicant with respect to patents essential for compliance with both mandatory and optional portions of the standard." Early disclosure to the Working Group of patent information that might be relevant to the standard is essential to reduce the possibility for delays in the development process and increase the likelihood that the draft publication will be approved for publication. Please notify the Chair < mailto:chair@wirelessman.org > as early as possible, in written or electronic form, if patented technology (or technology under patent application) might be incorporated into a draft standard being developed within the IEEE 802.16 Working Group. The Chair will disclose this notification via the IEEE 802.16 web site < http://ieee802.org/16/ipr/patents/notices >.	

WirelessMAN-SCa Support For Overlapped Uplink Transmissions

*Brian Eidson (Conexant Systems Inc)
Bob Nelson (MacPhy Modems Inc)*

In IEEE Std 802.16a-2003

Replace the contents of section 8.3.1.4.5.3 UL Information Element formats up to but not including Table 116y with the following:

The Information Elements of Table 116y are used in UL-MAP messages. The format for these UL-MAP messages is specified in Table 116x.

Table 116x – SCa UL-MAP Information Element format

Syntax	Size	Notes
UL-MAP_Information_Element() {		
CID	16 bits	
UIUC	4 bits	
If (UIUC == 15) {		
Extended UIUC dependent IE	variable	AAS_UL_IE()
} else {		
Offset	12 bits	
If (Modulation Type is Spread BPSK) {		
Duration	12 bits	
}		
}		
}		

Connection Identifier (CID):

Represents the assignment of the IE to a unicast, multicast, or broadcast address. When specifically addressed to allocate a bandwidth grant, the CID may be either the Basic CID of the SS or a Traffic CID for one of the connections of the SS.

Uplink Interval Usage Code (UIUC):

A four-bit code used to define the type of uplink access and the burst type associated with that access. A Burst Descriptor shall be included in an UCD message for each Uplink Interval Usage Code that is to be used in the UL-MAP. The UIUC shall be one of the values defined in Table 1116y.

Offset:

Indicates the start time, in units of minislots, of the burst relative to the Allocation Start Time given in the UL-MAP message. Consequently, the first IE shall have an offset of 0. The end of the last allocated burst is indicated by

allocating a NULL burst (CID = 0 and UIUC = 10) with zero duration. The time instants indicated by offsets are the transmission times of the first symbol of the burst including preamble.

Duration:

For bursts with one of the spread BPSK modulation types, this parameter specifies the length of the associated burst in minislots. (For bursts not assigned one of the spread BPSK modulation types, the duration of the burst is determined by the Offset appearing in the following IE entry and the offset of the current IE entry.)

In document P802.16d_D2/200, section 8.3.1.2.1, page 11, beginning at line 24, replace the final two paragraphs on page 11 (before Table 116c1) with the following text:

The PN sequence generator shall be preset at the beginning of a spread BPSK allocation with one of the seeds listed in Table 116c1. The burst profile setting for spreading is used to select the seed to be used.

On the UL, a BS is not required to make, but may make multiple time-overlapping spread BPSK allocations. Each allocation must be to a different SS, and each must use the same seed. These allocations shall not time-overlap a non-spread allocation. To insure that spreading sequence phases and preambles of overlapping spread BPSK do not time-overlap at the BS receiver, the allocation start-time of a burst preamble shall commence at least one UW length of symbols after the end of the preamble of any other spread-BPSK allocation that it may time-overlap.

Multiple time-overlapping spread BPSK allocations (from a single BS, over a single sector) shall not be transmitted on the DL. A recommended practice within a coordinated cell plan is for each BS to assign the same seed for all spread BPSK transmissions, and for different BSs in nearby cells or sectors to assign different seeds.