

Project	<b>IEEE 802.16 Broadband Wireless Access Working Group</b> < <a href="http://ieee802.org/16">http://ieee802.org/16</a> >	
Title	<b>Macro-MIMO Enhancements for Cellular OFDMA Systems</b>	
Date Submitted	<b>2004-06-25</b>	
Source(s)	<p>Wonil Roh, JeongTae Oh, Chan-Byoung Chae, Kyunbyoung Ko, Hongsil Jeong, Sung-Ryul Yun, Seungjoo Maeng, Panyuh Joo, Jaeho Jeon</p> <p>Samsung Electronics Co., Ltd.</p> <p>416, Maetan-3, Yeongtong, Suwon, Gyeonggi, Korea 442-600</p>	<p><a href="mailto:wonil.roh@samsung.com">wonil.roh@samsung.com</a></p> <p>Voice: +82-31-279-3868</p>
Re:	Contribution supporting TGe WG ballot #14b	
Abstract	Macro-MIMO Enhancements for Cellular OFDMA Systems	
Purpose	Adoption of proposed changes into P802.16e	
Notice	This document has been prepared to assist IEEE 802.16. It is offered as a basis for discussion and is not binding on the contributing individual(s) or organization(s). The material in this document is subject to change in form and content after further study. The contributor(s) reserve(s) the right to add, amend or withdraw material contained herein.	
Release	The contributor grants a free, irrevocable license to the IEEE to incorporate material contained in this contribution, and any modifications thereof, in the creation of an IEEE Standards publication; to copyright in the IEEE's name any IEEE Standards publication even though it may include portions of this contribution; and at the IEEE's sole discretion to permit others to reproduce in whole or in part the resulting IEEE Standards publication. The contributor also acknowledges and accepts that this contribution may be made public by IEEE 802.16.	
Patent Policy and Procedures	<p>The contributor is familiar with the IEEE 802.16 Patent Policy and Procedures (Version 1.0) &lt;<a href="http://ieee802.org/16/ipr/patents/policy.html">http://ieee802.org/16/ipr/patents/policy.html</a>&gt;, including the statement "IEEE standards may include the known use of patent(s), including patent applications, if there is technical justification in the opinion of the standards-developing committee and provided the IEEE receives assurance from the patent holder that it will license applicants under reasonable terms and conditions for the purpose of implementing the standard."</p> <p>Early disclosure to the Working Group of patent information that might be relevant to the standard is essential to reduce the possibility for delays in the development process and increase the likelihood that the draft publication will be approved for publication. Please notify the Chair &lt;<a href="mailto:r.b.marks@ieee.org">mailto:r.b.marks@ieee.org</a>&gt; as early as possible, in written or electronic form, of any patents (granted or under application) that may cover technology that is under consideration by or has been approved by IEEE 802.16. The Chair will disclose this notification via the IEEE 802.16 web site &lt;<a href="http://ieee802.org/16/ipr/patents/notices">http://ieee802.org/16/ipr/patents/notices</a>&gt;.</p>	

# Macro-MIMO Enhancements for Cellular OFDMA Systems

*Wonil Roh, JeongTae Oh, Chan-Byoung Chae, Kyunbyoung Ko,  
Hongsil Jeong, Sung-Ryul Yun, Seungjoo Maeng, Panyuh Joo, Jaeho Jeon*  
**Samsung Electronics**

## 1 Introduction

This document describes macro-MIMO enhancements for cellular OFDMA system that improve soft handoff performance and/or overall cell throughput. Once a SHO Zone is defined where a common IDcell is used, BSs in an active set shall transmit data in the data region defined in DL\_MAP. A pre-determined antenna selection formula can be used. A total of N antennas from SHO-BSs constitute an antenna pool. The anchor BS selects certain amount of antennas from the antenna pool, and decides MIMO transmission mode based on SS capability and channel condition. The antennas selection can be varied from sub-channel to sub-channel to maximize spatial diversity. For a particular subchannel, the allocated antennas in the BSs in the active set concurrently transmit the data for the same packet with the same CID and use the same data randomizer. The SS receives the RF-combined MIMO signal from the same data region and demodulates it, and then decodes the packet based on the combined soft bits between the different data region. When the source data in different subchannels are different, this macro-MIMO scheme intends to achieve higher cell throughput.

To sum up, the following three levels of macro-MIMO operations can be combined to improve overall handoff performance and cell throughput:

1. Macro-MIMO with RF combining :  
The packet delivering to SHO SS is duplicated and all or some antennas in the antenna pool formed with SHO BSs transmit the data for the same packet in the same data region such as a subchannel. RF combined signal is received at SS and MIMO decoding follows.
2. Macro-MIMO with diversity combining :  
The packet delivering to SHO SS is duplicated and some antennas in the antenna pool formed with SHO BSs transmit the data for the same packet in the same data region for RF combining. In addition, the data for the same packet is transmitted through another set of antennas in another data region with the same size, and these two can be soft-combined in order to achieve diversity combining.
3. Macro-MIMO with data rate enhancement :  
The packet delivering to SHO SS is duplicated and some antennas in the antenna pool formed with SHO BSs transmit the data for the same packet in the same data region for RF combining. In addition, the data for the different packet is transmitted through another set of antennas in another data region, and these two can be separately decoded in order to achieve data rate increase. Note that for this scheme, two data regions shall be different.

For a certain SS, these three schemes may be implemented simultaneously. Note also that this macro-MIMO enhancement operation is transparent to SS, which mean each SHO SS does not have to know which BSs are transmitting in order to decode the transmitted data.

### 1.1 The example of Macro-MIMO operation

Two antennas per BS is assumed for the following example.

A general expression for Macro-MIMO operation is shown in Figure 1. Where N is the number of antenna used for Macro-MIMO and K is the number of allocated frequency region for the SS. The '0' in the matrix indicates 'no data transmission' and 'S' is 'data transmission'.

Figure 1

		Antenna Index				
		1	2	3	...	N
Frequency Region Index	1	0/S	0/S	0/S	...	0/S
	2	0/S	0/S	0/S	...	0/S
	3	0/S	0/S	0/S	...	0/S
	.			.		
	.			.		
	K	0/S	0/S	0/S	...	0/S

\* S = [ a or a' or b or b' ... k or k' ]  
 \* N = (# of BS)\*(# of Antenna per a BS)

A simple example is given in Figure 2 for Macro-MIMO with RF combining. In this example, after RF combining from three BSs, the received data is further STC decoded.

Figure 2

		N=6					
		1	2	3	4	5	6
K=1		a	a'	a	a'	a	a'

Figure 3 is an example for Macro-MIMO with diversity combining and STC decoding.

Figure 3

		N=4			
		1	2	3	4
K=2	1	a	a'	0	0
	2	0	0	a	a'

Figure 4 is an example for Macro-MIMO with data rate enhancement combined with STC.

Figure 4

$$\begin{array}{c}
 \mathbf{N=4} \\
 \begin{array}{c} 1 \\ 2 \end{array} \begin{array}{c} \mathbf{K=2} \\ \mathbf{K=2} \end{array} \begin{array}{cccc} 1 & 2 & 3 & 4 \\ \left[ \begin{array}{cccc} a & a' & 0 & 0 \\ 0 & 0 & b & b' \end{array} \right]
 \end{array}$$

Finally, Figure 5 shows an example for three schemes combined.

Figure 5

$$\begin{array}{c}
 \mathbf{N=6} \\
 \begin{array}{c} 1 \\ 2 \\ 3 \\ 4 \\ 5 \end{array} \begin{array}{c} \mathbf{K=5} \\ \mathbf{K=5} \end{array} \begin{array}{cccccc} 1 & 2 & 3 & 4 & 5 & 6 \\ \left[ \begin{array}{cccccc} a & a' & 0 & 0 & a & a' \\ a & 0 & 0 & 0 & 0 & a' \\ a & a' & 0 & 0 & a & a' \\ b & b' & b & b' & 0 & 0 \\ b & b' & 0 & 0 & 0 & 0 \end{array} \right]
 \end{array}$$

## 2 Specific Text Changes

*[Add a new section in 8.4.5.3.xx on page 531]*

### 8.4.5.3.xx Macro-MIMO DL Basic IE format

To enhance soft handoff (SHO) and/or improve cell throughput in cellular OFDMA system, MIMO may be applied in the macroscopic level, once a certain SS enters a SHO Zone where a common IDcell is used among BSs in the active set. DL data transmission from BSs in the active set is transparent to the SHO SS. Table aaa specifies DL-MAP IE for this functionality.

Table aaa – Macro MIMO DL Basic IE()

<u>Syntax</u>	<u>Size (bits)</u>	<u>Notes</u>
<u>Macro_MIMO_DL_Basic_IE() {</u>		
<u>  Extended DIUC</u>	<u>4</u>	<u>0x09</u>
<u>  Length</u>	<u>4</u>	<u>Length in bytes</u>
<u>  Num_Region</u>	<u>4</u>	
<u>  For (i=0;i&lt;Num_Region;i++) {</u>		
<u>    OFDMA Symbol offset</u>	<u>8</u>	

<u>Subchannel offset</u>	<u>6</u>	
<u>Boosting</u>	<u>3</u>	
<u>No. OFDMA symbols</u>	<u>7</u>	
<u>No. Subchannels</u>	<u>6</u>	
<u>Packet index</u>	<u>4</u>	<u>Packet index for each region</u>
<u>Matrix indicator</u>	<u>2</u>	<u>STC matrix (see 8.4.8.1.4)</u> <u>STC = STC mode</u> <u>indicated in the latest STC_Zone_IE().</u>  <u>if (STC == 01) {</u> <u>  00 = Matrix A</u> <u>  01 = Matrix B</u> <u>  10-11 = Reserved }</u> <u>elseif (STC == 10) {</u> <u>  00 = Matrix A</u> <u>  01 = Matrix B</u> <u>  10 = Matrix C</u> <u>  11 = Reserved</u> <u>}</u>
<u>Num_layer</u>	<u>2</u>	
<u>for (j=0;j&lt;Num_layer;j++) {</u>		
<u>  If (INC_CID == 1) {</u>		
<u>    CID }</u>	<u>16</u>	
<u>  Layer_index</u>	<u>2</u>	
<u>  DIUC</u>	<u>4</u>	<u>0-11 burst profiles</u>
<u>  }</u>		
<u>}</u>		
<u>}</u>		

**Packet Index**

Indicates the packet index for the particular region. The regions with the same packet index shall be diversity combined at SS.

**References:**

[1] IEEE P802.16e/D3 Air Interface for Fixed and Mobile Broadband Wireless Access Systems – Amendment for Physical and Medium Access Control Layers for Combined Fixed and Mobile Operation in Licensed Bands