

Project	IEEE 802.16 Broadband Wireless Access Working Group < http://ieee802.org/16 >	
Title	Initial Ranging Overhead Reduction	
Date Submitted	2004-06-25	
Source(s)	Hang Zhang, Mo-Han Fong, Peiyong Zhu, Wen Tong Nortel Networks 3500 Carling Avenue, Ottawa Ontario, Canada K2H 8E9	mhfong@nortelnetworks.com Voice: +1-613-765-8983 Fax: +1-613-765-6717
Re:	IEEE P802.16e/D3-2004	
Abstract	In this contribution, a method of reducing initial ranging overhead is proposed	
Purpose	Review and Adopt the suggested changes into P802.16e/D3	
Notice	This document has been prepared to assist IEEE 802.16. It is offered as a basis for discussion and is not binding on the contributing individual(s) or organization(s). The material in this document is subject to change in form and content after further study. The contributor(s) reserve(s) the right to add, amend or withdraw material contained herein.	
Release	The contributor grants a free, irrevocable license to the IEEE to incorporate material contained in this contribution, and any modifications thereof, in the creation of an IEEE Standards publication; to copyright in the IEEE's name any IEEE Standards publication even though it may include portions of this contribution; and at the IEEE's sole discretion to permit others to reproduce in whole or in part the resulting IEEE Standards publication. The contributor also acknowledges and accepts that this contribution may be made public by IEEE 802.16.	
Patent Policy and Procedures	The contributor is familiar with the IEEE 802.16 Patent Policy and Procedures < http://ieee802.org/16/ipr/patents/policy.html >, including the statement "IEEE standards may include the known use of patent(s), including patent applications, provided the IEEE receives assurance from the patent holder or applicant with respect to patents essential for compliance with both mandatory and optional portions of the standard." Early disclosure to the Working Group of patent information that might be relevant to the standard is essential to reduce the possibility for delays in the development process and increase the likelihood that the draft publication will be approved for publication. Please notify the Chair < mailto:chair@wirelessman.org > as early as possible, in written or electronic form, if patented technology (or technology under patent application) might be incorporated into a draft standard being developed within the IEEE 802.16 Working Group. The Chair will disclose this notification via the IEEE 802.16 web site < http://ieee802.org/16/ipr/patents/notices >.	

1 Introduction

In 802.16e/D3, to accelerate the HO procedure, a Fast_Ranging_IE was introduced to provide non-contention based initial ranging when a MSS handovers to a selected target BS. The Fast_Ranging_IE is placed in the UL-MAP message. Since the UL-MAP message is a broadcast message which must be transmitted with high robustness to the MSS, the over-the-air resource required by a broadcast message is usually high. Careful design of broadcast messages is necessary to ensure the overhead can be minimized. Here we propose a method to reduce the UL and DL overhead incurred by a MSS who is performing initial ranging with the target BS.

This proposed method includes the following steps:

- After receiving HO-pre-notification-request message, the target BS assigns a HO_ID (8 bits) to the MSS if the target BS is able to support the requested HO.
- The target BS indicates the assigned HO_ID in the HO-pre-notification-response message
- The serving BS then indicates this assignment to the MSS in MOB-BSHO-RSP (if the HO is initiated by the MSS) or MOB-BSHO-REQ (if the HO is initiated by the BS)
- After the estimated HO start time, the target BS can use HO_ID, instead of the MSS' 48-bit MAC address in Fast_Ranging_IE to provide a contention-free ranging opportunity
- The subsequent procedure is the same as in the current D3 text with one exception that the MAC address shall be replaced by the HO_ID in the RNG_REQ and RNG_RSP messages

2 Proposed Text Change

The proposed text change is based on p802.16e/D3. The text change is on the following messages: Fast_Ranging_IE, RNG_REQ, RNG_RSP and MOB_BSHO_REQ/RSP.

[Modify the Fast Ranging Information Element]

8.4.5.4.15 Fast ranging Information Element

[...]

Table 300a – OFDMA Fast Ranging IE format IE

Syntax	Size	Notes
Fast_UL_ranging_IE() {		
Extended UIUC	4 bits	
MAC Address <u>HO_ID</u>	48 bits <u>8 bits</u>	
UIUC	4 bits	
OFDM Symbol offset	10 bits	
Subchannel offset	6 bits	
No. OFDM symbols	10 bits	
No. subchannels	6 bits	
Reserved	4 bits	
}		

[...]

HO_ID – An identifier assigned to a MSS for use during initial ranging to the selected target BS

[...]

[Modify BS-BSHO-RSP message]

6.3.2.3.56 BS HO Response (MOB-BSHO-RSP) message

[...]

Table 92j- MOB-BSHO-RSP Message Format

Syntax	Size	Notes
MOB-BSHO-RSP_Message_Format() {		
Management Message Type = 54	8 bits	
Network Assisted HO supported	1 bit	Indicate that the BS supports Network assisted HO
For (i= 0;i<N_Recommended; i++) {		
Neighbor BS_ID	48 bits	Base station ID
Service level prediction	8 bits	
<u>HO_ID_included_indicator</u>	<u>1 bit</u>	<u>To indicate if the field HO_IND is included</u>
<u>If (HO_ID_included_indicator == 1) {</u>		
<u>HO_ID</u>	<u>8 bits</u>	<u>ID assigned for use in initial ranging to the target BS once this BS is selected as the target BS</u>
<u>}</u>		
}		
Reserved	Variable	As required
HMAC tuple	21 bytes	
}		

[...]

HO_ID - ID assigned for use in initial ranging to the target BS once this BS is selected as the target BS

[Modify MOB_BSHO_REQ message]

6.3.2.3.54 BS HO Request (MOB-BSHO-REQ) message

[...]

Table 92h- MOB-BSHO-REQ message Format

Syntax	Size	Notes
MOB-BSHO-REQ_Message_Format() {		
Management Message Type = 52	8 bits	
Network Assisted HO supported	1 bit	Indicate that the BS supports Network assisted HO
For (i= 0;i<N_Recommended; i++) {		
Neighbor BS_ID	48 bits	Base station ID
Service level prediction	8 bits	
<u>HO_ID_included_indicator</u>	<u>1 bit</u>	<u>To indicate if the field HO_IND is included</u>
<u>If (HO_ID_included_indicator == 1) {</u>		
<u>HO_ID</u>	<u>8 bits</u>	<u>ID assigned for use in initial ranging to the target BS once this BS is selected as the target BS</u>
<u>}</u>		
}		

}		
Reserved	Variable	As required
HMAC tuple	21 bytes	
}		

[...]

HO_ID – Assigned an identifier to a MSS for use during initial ranging to the selected target BS

[...]

[Insert the following to the end of section 6.3.2.3.5]

6.3.2.3.5. Ranging Request (RNG_REQ) message

[...]

The following TLV parameter may be included in RNG_REQ message when a MSS is performing initial ranging to the selected target BS:

HO_ID.

[Insert the following to the end of section 6.3.2.3.6]

6.3.2.3.6 Ranging Response (RNG_RSP) message

[...]

When a BS sends RNG-RSP message as a reply to the RNG-REQ message from a MSS who is performing initial ranging during HO, the RNG-RSP message may include the following TLV parameter:

HO_ID.

[Modify RNG-REQ message encoding. Add the following row to Table 318a]

11.5 RNG-REQ message encoding

Table 318a – RNG-REQ Message Encoding

Name	Type (1byte)	Length	Value
<u>HO_ID</u>	<u>5</u>	<u>1</u>	<u>The identifier assigned to a MSS during HO by a target BS.</u>

[Modify RNG-RSP Encoding. Add the following row to Table 320a]

11.6 RNG-RSP message encoding

Table 320a- RNG-RSP Message Encoding

Name	Type (1byte)	Length	Value
<u>HO_ID</u>	<u>TBD</u>	<u>1</u>	<u>The identifier assigned to</u>

			<u>a MSS during HO by a target BS.</u>
--	--	--	--