

Project	IEEE 802.16 Broadband Wireless Access Working Group < <a href="http://ieee802.org/16">http://ieee802.org/16</a> >		
Title	Extension of collaborative spatial multiplexing in OFDMA		
Date Submitted	2005-01-26		
Source(s)	Bin-Chul Ihm, Yongseok Jin, Jinyoung Chun, Kyuhyuk Chung	Voice: 82-31-450-7187 Fax: 82-31-450-7912	
	LG Electronics, Inc. 533, Hoge-1dong, Dongan-gu, Anyang-shi, Kyongki-do, Korea		<a href="mailto:{bcihm, jayjay, jychun03, kyuhuk}@lge.com">[mailto: {bcihm, jayjay, jychun03, kyuhuk} @lge.com]</a>
	<b>Chan-Byoung Chae, Wonil Roh</b> <b>Samsung Electronics Co., Ltd.</b>		<a href="mailto:ch.chae@samsung.com">[mailto: ch.chae@samsung.com]</a>
	Ran Yaniv, Tal Kaitz Alvarion Ltd.		<a href="mailto:{ran.yaniv, tal.kaitz}@alvarion.com">[mailto: {ran.yaniv, tal.kaitz} @alvarion.com]</a>
Re:	This is a response to a Call for Comments on IEEE P802.16e-D5a		
Abstract	The collaborative spatial multiplexing can be applied to the case in OFDMA.		
Purpose	This document is submitted for review by 802.16e Working Group members. <b>Pink line indicates the revised text.</b>		
Notice	This document has been prepared to assist IEEE 802.16. It is offered as a basis for discussion and is not binding on the contributing individual(s) or organization(s). The material in this document is subject to change in form and content after further study. The contributor(s) reserve(s) the right to add, amend or withdraw material contained herein.		
Release	The contributor grants a free, irrevocable license to the IEEE to incorporate material contained in this contribution, and any modifications thereof, in the creation of an IEEE Standards publication; to copyright in the IEEE's name any IEEE Standards publication even though it may include portions of this contribution; and at the IEEE's sole discretion to permit others to reproduce in whole or in part the resulting IEEE Standards publication. The contributor also acknowledges and accepts that this contribution may be made public by IEEE 802.16.		
Patent Policy and Procedures	The contributor is familiar with the IEEE 802.16 Patent Policy and Procedures < <a href="http://ieee802.org/16/ipr/patents/policy.html">http://ieee802.org/16/ipr/patents/policy.html</a> >, including the statement "IEEE standards may include the known use of patent(s), including patent applications, provided the IEEE receives assurance from the patent holder or applicant with respect to patents essential for compliance with both mandatory and optional portions of the standard." Early disclosure to the Working Group of patent information that might be relevant to the standard is essential to reduce the possibility for delays in the development process and increase the likelihood that the draft publication will be approved for publication. Please notify the Chair < <a href="mailto:chair@wirelessman.org">mailto:chair@wirelessman.org</a> > as early as possible, in written or electronic form, if patented technology (or technology under patent application) might be incorporated into a draft standard being developed within the IEEE 802.16 Working Group. The Chair will disclose this notification via the IEEE 802.16 web site < <a href="http://ieee802.org/16/ipr/patents/notices">http://ieee802.org/16/ipr/patents/notices</a> >.		

# Extension of Collaborative Spatial Multiplexing in OFDMA

*Bin-chul Ihm, Jinyoung Chun, Yongseok Jin, and Kyuhyuk Chung*  
*LG Electronics*

## 1. Introduction

In OFDMA of the current 802.16e standard, collaborative spatial multiplexing mode is supported through MIMO\_UL\_Basic\_IE(). Two single transmit antenna MSSs can perform collaborative spatial multiplexing onto the same subchannel. This mode can result in capacity increment by assigning same uplink resource to two MSSs simultaneously.

When BS has two or more receive antennas, the collaborative spatial multiplexing can be applied to the case where two MSSs have 2 transmit antennas.

In this contribution, we suggest to modify the MIMO\_UL\_Basic\_IE() or add the new MIMO\_UL\_Enhanced\_IE() to achieve the above case.

## 2. Feasible collaborative SM modes

There are various feasible collaborative SM modes according to the following combinations of # of transmit antennas in MSS and STC configuration (STTD or SM). The current collaborative SM corresponds to the first example of the followings.

- Collaborative SM example #1





Figure 1. The case of two SSs with single transmit antenna

SS1 and SS2 share the BW resource, but a SS1 uses the uplink tile with pilot pattern A and a SS2 uses the uplink tile with pilot pattern B in PUSC mode.

- Collaborative SM example #2



**Figure 2. The case of two SSs with dual transmit antennas**

A SS1 uses the uplink tile with pattern A and B, and a SS2 uses the uplink tile with pattern C and D.

### 3. Proposition

The second example of the aforementioned collaborative SM examples requires four pilot patterns to distinguish the channels from each antenna of MSSs. For the purpose of realizing the above configurations, more pilot patterns are needed to support the various collaborative SM modes. Therefore, we propose to add new pilot pattern C, D to current pilot pattern A, B as shown in Figure 2.

In addition, we suggest to modify the `MIMO_UL_Basic_IE()` **or to add the `MIMO_UL_Enhanced_IE()`** to indicate the various collaborative SM modes and to support that MSS has two transmit antennas.

### 4. Simulation result

The figures below show the performance results of the collaborative SM. We assume that there are two MSSs with dual antennas and a BS with 4 antennas, and a MSS uses pilot pattern A and B in each antenna and another MSS uses pilot pattern C and D for STTD structure.

Figure 3 and 4 are BER and FER for CC 1/2 rate, UL PUSC mode and Pedestrian B channel with 10km/h. The  $E_b/N_0$  of the proposed pilot pattern are about -2.8dB in QPSK, 2.6dB in 16QAM, and 7.7dB in 64QAM at 10% FER. And figure 5 and 6, which are simulated in Vehicular A channel with 60km/h, show a little worse performance than figure 3 and 4.




Figure 3. BER of two MSSs with dual antennas and BS with 4 antennas (Pedestrian B with 10km/h)




Figure 4. FER of two MSSs with dual antennas and BS with 4 antennas (Pedestrian B with 10km/h)




Figure 5. BER of two MSSs with dual antennas and BS with 4 antennas (Vehicular A with 60km/h)




Figure 6. FER of two MSSs with dual antennas and BS with 4 antennas (Vehicular A with 60km/h)

### 5. Proposed Text Change

----- Start of Option 1 and Option 2 -----

[Option 1]

We propose to change the reserved field to Pilot pattern field in the MIMO UL basic IE and we refer to the IEEE std 802.16-2004.

#### 8.4.5.4.11 MIMO UL basic IE format

*[Change Table 297 as follows:]*

Table 297 – MIMO UL basic IE () format

Syntax	Size	Notes
MIMO_UL_basic_IE () {		
Extended_UIUC	4bits	MIMO=0x02
Length	4bits	Length of the message in bytes (variable)
Num_Assign	4bits	Number of burst assignment
For (j=0; j< Num_assign; j++){		
CID	16bits	SS basic CID
UIUC	4bits	
MIMO_Control	1bit	For dual transmission capable SS 0: STTD 1: SM  For Collaborative SM capable SS 0 : pilot pattern A 1 : pilot pattern B
Duration	10bits	In OFDMA slots (see 8.4.3.1)
<del>Reserved</del> <u>Pilot pattern / <del>Reserved</del></u>	1bit	<u>If SS has dual transmission, BS indicates pilot pattern.</u> <u>0 : pilot pattern A/-B</u> <u>1 : pilot pattern C/-D</u>  <u>Otherwise : <del>reserved</del> Shall be set to zero</u>
}		
Padding	variable	Number of bits required to align to byte length, shall be set to zero.
}		

Num\_assign

This field specifies the number of assignments in this IE.

MIMO\_Control

MIMO\_Control field specifies the MIMO mode of UL burst. For a dual transmission capable SS, the value of 0 indicates STTD mode, the value of 1 indicates SM mode; For a collaborative SM capable SS, the value of 0 indicates pilot pattern A, the value of 1 indicates pilot pattern B.

Pilot pattern

This field specifies the Collaborative SM mode for a dual transmission capable MSS. The value of 0 indicates pilot pattern A, B and the value of 1 indicates pilot pattern C, D.

[Option 2]

*[Add a new Section 8.4.5.4.19]*

#### 8.4.5.4.19 MIMO UL Enhanced IE format

In the UL-MAP, a MIMO-enabled BS may transmit UIUC=15 with the MIMO\_UL\_Enhanced\_IE() to indicate the MIMO configuration and pilot patterns of the subsequent uplink allocation to a specific MIMO-enabled MSS CID. The MIMO mode indicated in the MIMO\_UL\_Enhanced\_IE() shall only apply to the subsequent uplink allocation until the end of frame.

Table xxx – MIMO UL Enhanced IE () format

<u>Syntax</u>	<u>Size</u>	<u>Notes</u>
<u>MIMO_UL_Enhanced_IE () {</u>		
<u>Extended UIUC</u>	<u>4bits</u>	<u>Enhanced MIMO=0x??</u>
<u>Length</u>	<u>4bits</u>	<u>Length of the message in bytes (variable)</u>
<u>Num_Assign</u>	<u>4bits</u>	<u>Number of burst assignment</u>
<u>For (j=0; j&lt; Num_assign; j++){</u>		
<u>Num_CID</u>	<u>2bits</u>	
<u>For ( i=0; i &lt;Num_CID; i++){</u>		
<u>CID</u>	<u>16bits</u>	<u>MSS basic CID</u>
<u>UIUC</u>	<u>4bits</u>	
<u>Matrix Indicator</u>	<u>1 bit</u>	<u>For MSS with dual antenna</u> <u>0: Matrix A (STTD, see 8.4.8.4.3)</u> <u>1: Matrix B (SM, see 8.4.8.4.3)</u>  <u>For MSS with single antenna</u> <u>Skip this field</u>
<u>Pilot Pattern Indicator</u>	<u>1 bit</u>	<u>For MSS with single antenna</u> <u>0: pilot pattern A</u> <u>1: pilot pattern B</u>  <u>For MSS with dual antenna</u> <u>0 : pilot pattern A/B</u> <u>1 : pilot pattern C/D</u>
<u>}</u>		
<u>Duration</u>	<u>10bits</u>	<u>In OFDMA slots (see 8.4.3.1)</u>
<u>}</u>		
<u>Padding</u>	<u>Variable</u>	
<u>}</u>		

#### Num\_Assign

This field specifies the number of assignments in this IE.

#### Matrix Indicator

This field specifies the MIMO mode of UL burst. For MSS with dual antenna it indicates STC Matrix and for MSS with single antenna it is skipped.

#### Pilot Pattern Indicator

This field indicates pilot patterns to MSS with single antenna or to MSS with dual antenna (see 8.4.8.1.5).

----- End of Option 1 and Option 2 -----

### 8.4.8.1.5 Uplink using STC

*[Insert Figure 249a after Figure 249 as follows:]*




Figure 249a – Pilot Patterns in UL PUSC tile

*[Add text in section 8.4.8.1.5.1 as follows:]*

Two single transmit antenna SS's can perform collaborative spatial multiplexing onto the same subchannel. In this case, the one SS should use the uplink tile with pattern-A and the other SS should use the uplink tile with pattern-B. Also, two dual transmit antenna SS's can perform collaborative spatial multiplexing onto the same subchannel. In this case, the one SS should use the uplink tile with the pilot pattern A, B and the other SS should use the uplink tile with the pilot pattern-C, D through ~~MIMO-UL Basic IE~~ **MIMO UL Enhanced IE**. Pilot patterns are illustrated in the Figure 249 and 249a.

## 6. References

- [1] IEEE P802.16-2004