

Project	IEEE 802.16 Broadband Wireless Access Working Group < http://ieee802.org/16 >	
Title	End-of-MAP IE Reuse	
Date Submitted	2005-01-24	
Source(s)	Yigal Eliaspur Dov Andelman Yuval Lomnitz Intel Corp.	Voice: +972-54-7884877 mailto: yigal.eliaspur@intel.com
Re:	IEEE P802.16e/D5a	
Abstract	End-of-MAP IE has no real use in OFDMA phy. As for that it can be reused as a new type of extended D/UIUC..	
Purpose	Adopt changes.	
Notice	This document has been prepared to assist IEEE 802.16. It is offered as a basis for discussion and is not binding on the contributing individual(s) or organization(s). The material in this document is subject to change in form and content after further study. The contributor(s) reserve(s) the right to add, amend or withdraw material contained herein.	
Release	The contributor grants a free, irrevocable license to the IEEE to incorporate text contained in this contribution, and any modifications thereof, in the creation of an IEEE Standards publication; to copyright in the IEEE's name any IEEE Standards publication even though it may include portions of this contribution; and at the IEEE's sole discretion to permit others to reproduce in whole or in part the resulting IEEE Standards publication. The contributor also acknowledges and accepts that this contribution may be made public by IEEE 802.16.	
Patent Policy and Procedures	<p>The contributor is familiar with the IEEE 802.16 Patent Policy and Procedures (Version 1.0) <http://ieee802.org/16/ipr/patents/policy.html>, including the statement "IEEE standards may include the known use of patent(s), including patent applications, if there is technical justification in the opinion of the standards-developing committee and provided the IEEE receives assurance from the patent holder that it will license applicants under reasonable terms and conditions for the purpose of implementing the standard."</p> <p>Early disclosure to the Working Group of patent information that might be relevant to the standard is essential to reduce the possibility for delays in the development process and increase the likelihood that the draft publication will be approved for publication. Please notify the Chair <mailto:r.b.marks@ieee.org> as early as possible, in written or electronic form, of any patents (granted or under application) that may cover technology that is under consideration by or has been approved by IEEE 802.16. The Chair will disclose this notification via the IEEE 802.16 web site <http://ieee802.org/16/ipr/patents/notices>.</p>	

End-of-MAP IE Reuse

Yigal Eliaspur

Intel Corp.

1. The Document's Goal

DIUC 14 and UIUC 11 are to be consider End-of-MAP for 802.16-2004 devices.

However, this End-of-MAP IE has no real use in OFDMA phy. As for that it can be reused as a new type of extended D/UIUC.

Backward capability can be maintained by the BS by using this IE in non-compressed MAPs or in compressed MAP in frames that does not include UL allocation for 16d users.

2. Specific changes in the Standard

[Add new section to section 8.4.5.4]

8.4.5.4.x UL-MAP extended 2 IE format

A UL-MAP IE entry with a UIUC value of 15, indicates that the IE carries special information and conforms to the structure shown in Table xxx. A station shall ignore an extended IE entry with an extended UIUC value for which the station has no knowledge. In the case of a known extended UIUC value but with a length field longer than expected, the station shall process information up to the known length and ignore the remainder of the IE.

Table xxx—OFDMA UL-MAP extended 2 IE format

Syntax	Size	Notes
UL_Extended_2_IE() {		
Extended UIUC	6 bits	
Length	8 bits	Length in bytes of Unspecified data field
Unspecified data	<i>variable</i>	
}		

[In section 8.4.5.4.1 UIUC Allocation]

Replace “End-of-Map IE” with “Extended UIUC 2 IE”

[Add new section to section 8.4.5.3]

8.4.5.3.x DL-MAP extended IE format

A DL-MAP IE entry with a DIUC value of 15, indicates that the IE carries special information and conforms to the structure shown in Table 275. A station shall ignore an extended IE entry with an extended DIUC value for which the station has no knowledge. In the case of a known extended DIUC value but with a length field longer than expected, the station shall process information up to the known length and ignore the remainder of the IE.

Table xxx—OFDMA DL-MAP extended 2 IE format

Syntax	Size	Notes
DL_Extended_2_IE() {		
Extended DIUC	6 bits	
Length	8 bits	Length in bytes of Unspecified data field
Unspecified data	<i>variable</i>	
}		

[In section 8.4.5.3.1 DIUC allocation]

Replace “End-of-Map IE” with “Extended UIUC 2 IE”