

# HSSG Objectives (1 of 2)

- **Preserve the 802.3/Ethernet frame format at the MAC Client service interface.**
- **Meet 802 Functional Requirements, with the possible exception of Hamming Distance.**
- **Preserve minimum and maximum FrameSize of current 802.3 Std.**
- **Support full-duplex operation only.**
- **Support star-wired local area networks using point-to-point links and structured cabling topologies.**
- **Specify an optional Media Independent Interface (MII).**
- **Support proposed standard P802.3ad (Link Aggregation)**
- **Support a speed of 10.000 Gb/s at the MAC/PLS service interface**

# HSSG Objectives (2 of 2)

## **Define two families of PHYs**

- A LAN PHY, operating at a data rate of 10.000 Gb/s
- A WAN PHY, operating at a data rate compatible with the payload rate of OC-192c/SDH VC-4-64c

## **Define a mechanism to adapt the MAC/PLS data rate to the data rate of the WAN PHY**

## **Provide Physical Layer specifications which support link distances of:**

- At least 300 m over installed MMF
- At least 65 m over MMF
- At least 2 km over SMF
- At least 10 km over SMF
- At least 40 km over SMF

## **Support fiber media selected from the second edition of ISO/IEC 11801 (802.3 to work with SC25/WG3 to develop appropriate specifications for any new fiber media).**