

Multi-Vendor Agreement on Precoder Proposal

A Channel Equalization Approach for 10GBASE-T

**IEEE P802.3an Interim
May 2004**

Scott Powell, [Broadcom](#) Presenter

**[Independent](#), Sailesh Rao
[Keyeye](#), Hiroshi Takatori
[Marvell](#), Xiaopeng Chen
[NEC Electronics](#), Katsutoshi Seki**

**[Plato Labs](#), Joseph Babanezhad
[Teranetics](#), Jose Tellado
[Vativ](#), P.J. Sallaway
[Vitesse](#), Kishore Kota**


Multi-Vendor Precoder Proposal

Benefits of Precoding

- Common Criticisms of Precoding
- Summary, Q&A
- Motion/Straw Poll

Channel Equalization via DFE


- Decision feedback equalization (DFE) is known to be asymptotically optimum for band limited channels*
 - Optimally equalizes ISI and simultaneously whitens noise
 - DFE cascaded with FEC obtains same coding gain over ISI channel as over an ideal AWGN channel
 - This is true only in the absence of slicer decision errors



* Cioffi, et.al., "MMSE Decision-Feedback Equalizers and Coding," *IEEE Trans. On Comm.*, Oct. 1995

Required Coding Gain

Relationship of Slicer SNR to Error Rate




- * Matlab model from "solarsep_varlen7a.m"
- * Channel models from kasturia_2_0304.pdf & 11801

- Channel model includes NEXT/ECHO/FEXT/ANEXT/Bkn
- Channel model excludes ADC/DAC/ISI/jitter/distortion/...

Required Coding Gain

Relationship of Slicer SNR to Error Rate




* Matlab model from
"solarsep_varlen7a.m"

* Channel models from
kasturia_2_0304.pdf & 11801

- Channel model includes NEXT/ECHO/FEXT/ANEXT/Bkn
- Channel model excludes ADC/DAC/ISI/jitter/distortion/...

Required Coding Gain

Relationship of Slicer SNR to Error Rate



* Matlab model from "solarsep_varlen7a.m"

* Channel models from kasturia_2_0304.pdf & 11801


More powerful coding than TCM necessary

- Channel model includes NEXT/ECHO/FEXT/ANEXT/Bkn
- Channel model excludes ADC/DAC/ISI/jitter/distortion/...

Rx-Based DFE and Channel Coding

- **DFE/FEC cascade is known to cause problems with severe ISI channels***

- Error propagation substantially reduces coding gain
- Primary reason this configuration was not used in 1000BT



*M.V. Eyuboglu, "Detection of Coded Modulation Signals on Linear, Severely Distorted Channels using Decision Feedback Noise Prediction with Interleaving," IEEE Trans. Comm., Apr. 1988

- **Techniques for mitigation usually require placing some portion of decoder inside the feedback loop**

- Introduces a critical timing path \Rightarrow limits max baud rate
- Incompatible with high performance block or iterative codes
- Restricts asymptotic coding gain to <4.1 dB (PAM-10 DFSE)


Decoupling FEC from Equalization

- **Precoding is a well-known technique for decoupling channel equalization from channel coding**
 - Necessary for LDPC or concatenated coding schemes
- **Previously proposed to task/study group**
 - www.ieee802.org/3/10GBT/public/nov03/rao_1_1103.pdf
 - www.ieee802.org/3/10GBT/public/mar04/powell_1_0304.pdf
 - www.ieee802.org/3/10GBT/public/mar04/rao_1_0304.pdf
- **Implicit to block code presentations**
 - www.ieee802.org/3/10GBT/public/mar04/dabiri_1_0304.pdf
 - www.ieee802.org/3/10GBT/public/mar04/powell_1_0304.pdf
 - www.ieee802.org/3/10GBT/public/mar04/ungerboek_1_0304.pdf
 - www.ieee802.org/3/10GBT/public/mar04/seki_1_0304.pdf

Tx-Based Equalization

- **Precoding moves postcursor equalization to the transmitter** M. Tomlinson March 1971, H. Harashima & H. Miyakawa August 1972

Forces filter to
be stable




- Flat transmit spectrum
- Does not preclude further filtering for EMI or capacity reasons

- **Precoding achieves similar performance as DFE with correct decisions**
 - Precoder feedback symbols are known, not estimated
 - Equalization is independent of channel coding performance

Fundamental Benefits of Precoding

1. Permits more powerful channel codes required to meet 10Gbps
 - Decouples equalization from channel coding
2. Retains asymptotic optimality of decision feedback equalization without error propagation
3. Does not affect transmitted spectrum (EMI)
 - Does not preclude any form of transmit filtering
4. Removes DFSE timing loop - simplifies timing closure



Arbitrary type, complexity, latency

(TCM, Reed-Solomon, Concatenated w/ or w/o iteration, LDPC, Turbo, etc)

Multi-Vendor Precoder Proposal

- **Benefits of Precoding**

- 👉 **Common Criticisms of Precoding**

- **Summary, Q&A**

- **Motion/Straw Poll**

Echo/NEXT Cancellation Complexity

- **Precoding is compatible with echo, NEXT, and FEXT cancellation**


- Input to cancellers moved to output of precoder

- **Complexity impact**

- Number of taps unchanged
- Wordlength of input increased

- **Potential for reduction**

- Little/no impact on frequency domain schemes
- Investigate use of effective data symbols as input




Transmit Peak-Average Power (PAR)

- Small average power increase
- The peak power increase is approx 1dB

MPAM Levels	Average Power Increase (dB)	Peak Power Increase (dB)	PAR increase (dB)
5	0.18	1.9	1.8
8	0.07	1.2	1.1
10	0.04	0.9	0.9
12	0.03	0.8	0.7

Dynamic Range of Received Signal



• **By Definition:** $y(n) = \sum_{k=0}^{N-1} x(n-k)h(k)$

$$|y|_{\max} \text{ occurs when } x(n-k) = |x|_{\max} \text{ sign}(h(k))$$

$$\Rightarrow |y(n)| \leq |x|_{\max} \sum_{k=0}^{N-1} |h(k)|$$

• **Precoded $X_{\max} = M$, non-precoded $X_{\max} = M-1$**

— Rx dynamic range increase < 1dB for PAM-10

Constellation expansion from precoding does not significantly increase the dynamic range of the received signal

DAC Complexity*

*Sandeep Gupta

- **DAC area and power similar for precoded or non-precoded system**
 - Assume current steering DAC
 - Non-precoded PAM-8: INL/DNL \approx 60dB, reduced number of levels
 - Precoded: INL/DNL \approx 60dB, 10b DAC all levels
- **Total area dominated by area of current sources**
 - Similar for both cases
 - Small increase for 10b DAC due to increased digital logic complexity
- **Power determined by full scale current, output loading, and swing requirements**
 - Similar for both cases

Interoperability

- **Interoperability and startup issues already solved in multiple standards**
 - V.34, G.SHDSL, HDSL2, 802.3ah (EFM)
- **HDSL2 approach is adopted by several standards**
 - Generic Tomlinson-Harashima precoder (PAM-16)
 - Performance within a dB of optimal DFE achieved
 - Coefficients determined at startup then fixed
 - Reduced constellation (PAM-2) used at startup
- **HDSL2 System validation performed with end-to-end performance tests**
 - Task force will need to develop test modes to allow the transmitter to be checked for compliance

Multi-Vendor Precoder Proposal

- **Benefits of Precoding**
- **Common Criticisms of Precoding**
- 👉 **Summary, Q&A**
- **Motion/Straw Poll**

Summary

- **Precoding permits powerful channel codes to be used for 10GBASE-T**
 - Necessary to capture sufficient portion of available capacity
- **Precoding advantages outweigh disadvantages**
 - Most “disadvantages” are misconceptions or can be mitigated
- **Supported by majority of PHY vendors as best channel equalization strategy for 10GBASE-T**

Questions ???

Broadcom, Scott Powell
Independent, Sailesh Rao
Keyeye, Hiroshi Takatori
Marvell, Xiaopeng Chen
NEC Electronics, Katsutoshi Seki

Plato Labs, Joseph Babanezhad
Teranetics, Jose Tellado
Vativ, P.J. Sallaway
Vitesse, Kishore Kota

Multi-Vendor Precoder Proposal

- **Benefits of Precoding**
- **Common Criticisms of Precoding**
- **Summary, Q&A**
- 👉 **Motion/Straw Poll**

Straw-Poll: Generic Precoding

- **Motion: 10GBASE-T adopt Tomlinson-Harashima precoding as the channel equalization strategy**

- **PHY Vendors by company:**

(“PHY Vendor” \equiv company
planning to possibly develop
10GBASE-T transceivers))

PHY Vendor Company	Yes	No	Abstain
Broadcom			
Hitachi			
Intel			
Keyeye			
NEC			
Marvell			
Plato			
Sailesh Rao (Ind.)			
Solar Flare			
Teranetics			
TI			
Vativ			
Vitesse			
	#DIV/0!	#DIV/0!	#DIV/0!

- **Task Force Members: Y: N: A:**