

# Performance Impacts: MMP and Channel Bonding

Ed Boyd, Broadcom

# Overview


- Multiple modulation profiles above the PHY adds delay and jitter to the EPoC system.
- Packet based Channel Bonding above the PHY adds delay and jitter to the EPoC system.
- Both of these solutions add complexity and make interoperability a challenge.
- These two solutions shouldn't be considered individually.
  - Significant dependencies must be accounted for.

# **MULTIPLE MODULATION PROFILES**

# MMP Overview

- Multiple modulation profiles requires significant functionality above the PHY and in the PHY
- Architectural changes above the PHY
  - LLID scheduler to delay and re-order packets so they can be grouped.
  - Complex Idle insertion equation for channel rate, modulation profile selected, and FEC endings.
  - Fluctuating data rate beyond a simple rate shaper.
  - This is not possible with current EPON MAC devices.
- Architectural changes below the PHY
  - Multiple FEC modes: Different Code word sizes, shortened code words
  - Downstream Modulation Profile pointers
  - Multiple FEC decoders

# MMP and FEC Boundaries



- MMP blocks will require that FEC terminates between packets of different profiles.
- The Best QoS is achieved by alternating packets from different sources.
- FEC code words that are not complete require padding (used in 10G EPON) or shortening (used in 1G EPON).
- Shortening has better efficiency but it is more complicated due to variable size.
- Shortening has different error performance since code word is smaller.
- The data rate after the FEC overhead can change dramatically due to this overhead.
- 90% LDPC (code word of 16000 bits with 1600 bits of parity is considered)


## Fixed Code word with padding

- Alternating 64 byte packets [84 bytes with Preamble/IPG] (GATE frames will commonly look like this)
- 90% Efficient Best Case (always ends on code word boundaries)
- 4.2% Efficient Worst Case (every packet is different profile):  $(84 \times 8 \text{ bits}) / 16000$
- Smaller codes are better with this solution.

## Shortened Last Code word

- 90% Efficient Best Case (always ends on code word boundaries)
- 30% Efficient Worst Case:  $(84 \times 8 \text{ bits}) / (84 \times 8 \text{ bits} + 1600)$
- Longer codes are better off with this answer.


# Packet Sorting



- Based on the wild variations in efficiency from changing profiles, packet sorting is absolutely required for MMP.
- The number of profiles is not the issue, it is the distribution of packets.
- PHY Packet Sorting requires buffering packets at the transmitter for the sorting function.
- The packet sorting function adds a variable delay (jitter) equal to the size of the block. (The second packet could be moved to end of the block if all of the other packets)
- MAC layer packet sorting will be considered.

*Packet Sorting is required for MMP and it adds jitter for application layer packets*


# Mixing GATEs with Sorted Packets



- Frames sorted above the MAC will need to be mixed with the periodically generated GATE frames from the scheduler.
- GATE frame generation is not aligned with the sorting boundaries of the downstream since the GATE destination is a function of the upstream bandwidth request.
- GATE frames are the highest priority for going downstream to decrease delay in the loop from requesting to granting the upstream.
- For 4 profiles, a GATE frame will likely cause (3 in 4, 75% chance) two short code blocks.
- Depending on the size of upstream bursts, the shortened code words would severely drop the efficiency.
- GATE frames must be delayed to align with packets in the profile.
- GATEs will worst case face a sorting period of delay. (subtracts for 1ms PHY RTT limit)

*Adding MMP to the Downstream will increase upstream delay/jitter by sorting time*

# Jitter to higher layer frames



- The jitter specification of MEF23H, Circuit-Emulation-Services, 1588, Y.1731, etc are the most difficult specifications for a point-to-multipoint system to meet.
- The jitter introduced by grouping upstream packets into bursts, contending for upstream access, discovery slots, and polling are significant.
  - End-to-End UNI-to-UNI Jitter requires going upstream and downstream.
  - Downstream jitter is small in EPON.
- If all 2.5ms of MEF-23H are used for upstream. (500us are left for rest of network, OLT switch, and downstream)
  - Polling is 1 to 1.5ms; Upstream Resource of 1ms, 250us for discovery, 250us for polling and granting inaccuracy.

*Additional Jitter in the downstream will cause higher upstream polling rate*




# **CHANNEL BONDING WITH MMP**

# Channel Bonding Overview


- Multiple presentation have expressed interest in channel bonding with the ability to support multiple generations of devices.
- Channel Bonding can have a significant impact on performance including the following:
  - Head of line blocking: Slower channel stops packets from entering other channels.
  - Packet Duplication: Multicast and Broadcast packets are sent multiple times so they are visible on multiple networks.
  - Packet re-ordering on a flow: Not allowed in 802.3 and certain protocols. Lowers IP performance.
  - Packet jitter: MEF23H and other performance specifications for access require low jitter.

# Architecture for Evaluation



- CLT supports multiple generations of CNU's
  - Single channel devices can be on different channels to load balance.
  - Multiple channel devices can be on all or a subset of the channels.
  - Each Channel can independently be full 192MHz or a portion of 192MHz
- MMP (FEC encoding) on each channel
  - Four different modulation profiles on each channel
  - CNU needs to receive two profiles per channel (one for unicast and one for broadcast)
  - Each channel will queue packets for profile and generate pointer/MAP/indicator
- Packet sorting for MMP efficiency
  - LLID Scheduler in MAC will select packets from queues in profile groups to support cluster packets for the same profile


# Channel Bonding



- RS LLID Scheduler selects packet from LLID queue
  - LLID is selected based on channel availability
  - LLID is selected based on MMP grouping for the channel
- IDLE inserter needs to calculate idles and PHY must delete them
  - Duplicate function on both sides of the XGMII
  - Idle count is based on selected channel width
  - Idle count is based on selected modulation profile
  - Idle count is based on FEC rate and shortened code word
  - Scheduling function must be fully defined so MAC and PHY has same data rate

*Idle Insertion is complicated and IOP between PHY & MAC is difficult*


# Packet Re-Ordering



- Packets are re-ordered in a channel based for MMP grouping
- Packets are re-ordered between channels.
  - MMP of different channels will cause re-ordering
  - Different data rate channels causes packet re-ordering
- Packet re-ordering causes application layer and MPCP layer jitter
- Packet re-ordering in a flow will occur
- Packets must be re-ordered on the output

*Packet Re-Ordering requires a receiver shuffling buffer*


# Multicast/Broadcast Packets



- Broadcast LLID must be duplicated to multiple channels so single channel devices can receive them.
- Multiple Copies will be received by multiple channel CNU's. (Only 1 must pass so deletion is required)
- Selective Multicast requires that the PHY look into L2 Multicast DA (Layer violation)
- IDLE insertion for duplicated packets with 2 different rate channels is impossible.
- Duplication of multicast will severely impact the utilization and performance of the system.
- Head of line blocking will occur. Multicast for higher rate channel will block all traffic on lower rate channel.

*Multicast/Broadcast Traffic is not possible in this architecture*

# Multiple Broadcast LLIDs



- Every CNU type and sub-channel will require a unique Broadcast domain.
- CNU will only listen to one Broadcast LLID and avoid duplicated packets.
- Blind Multicast packet duplication and PHY layer duplication avoided.
- 802.1D will switch traffic into multiple broadcast domains.
- Packets are duplicated at higher layer so multicast snooping can be considered.
- Many broadcast domains (13 possible) is significant functionality beyond current OLTs.
- Duplication of traffic at any layer lowers efficiency.


# Performance Impact

- Channel Bonding decreases statistical gain in downstream.
  - Duplication of broadcast packets.
  - Congestion in isolated channels
- Channel Bonding adds significant delay
  - Slowest downstream channel impacts all other channels
  - Packet re-ordering required after MMP and channel bonding
  - Impacts downstream and **upstream performance**
- Upper layers expect constant delay/rate from Ethernet MAC and PHY.
  - 1588, 802.1AS, Y.1731 are examples.
  - Provisioning/Operations are simpler without data capacity dependence based on frame size or frame destination.
- Channel Bonding moves the scheduling and shaping from 802.1D or an external device into the EPoC specification.

***Packet Channel Bonding doesn't make sense for EPoC***



# Simple and Ethernet Friendly



- EPoC should be fully compatible with EPON and continue to provide a single logical channel.
- EPoC should have a fixed rate in the downstream determined by auto-negotiation with the option of periodic adjustments.
- CNU's will receive the entire downstream and there is a single type defined.
- Known and constant performance for network planning.
- Compatible with the higher layers.
- Higher Statistic Gain, Lower Cost, Easy IOP, and Lower Delay.

*Ethernet fits this model and has been very successful*

# Conclusions

- Channel Bonding and Multiple Modulation Profiles are not consistent with Ethernet or compatible with the EPON.
- EPoC will take much longer to standardize and interoperate with these features.
- The economic feasibility of EPoC is in question if it requires new OLT (EPON MAC) silicon and systems.
- DOCSIS 3.1 will have channel bonding and MMP downstream but Ethernet should be simple and compatible with existing EPON.
- The discussion of these features has significantly delayed the standard already.

***Keep it Ethernet and Let's move on***