

802.3bp RTPGE Mode Conversion Measurements for Automotive Link Segments

September 3, 2013

**Mehmet Tazebay
Broadcom Corporation**

Contributors & Supporters

Contributors

Ahmad Chini, Broadcom

Jay Cordaro, Broadcom

Mehmet Tazebay, Broadcom

Neven Pischl, Broadcom

Supporters

Sasha Babenko, Molex

Bert Bergner, TE Connectivity

Stefan Buntz, Daimler

Mike Gardner, Molex

Todd Herman, Commscope

Kirsten Matheus, BMW

Richard Mei, Commscope

Thomas Muller, Rosenberger

Xiaofeng Wang, Qualcomm


Jens Wuelfing, TE Automotive

Overview


- **System EMC Testing (as previously proposed)**
 - Stripline for emissions testing (using 2m UTP cable)
 - BCI for immunity testing (using 2m UTP cable)
- **Critical parameter for RTPGE utilizing UTP solutions**
 - Mode conversion limit line which directly defines the emissions and immunity.
 - The previously proposed value corresponds to the most stringent emission limit line (15dBuV) and BCI immunity level (200mA) using 2m UTP cables as defined by the standard test configurations
 - Need to derive the mode conversion limit lines for RTPGE link segment (15m w/4-inline connectors)
- **Test Setup**
 - DUT 5cm over a ground plane (commonly used by automotive OEMs)
 - Will provide a consistent CM impedance among different measurements & setups
 - Components' Testing (cables, connectors, magnetics, etc.)
 - Designing good test heads & an accurate calibration is crucial for balance measurements.
 - There are two types of inline connectors considered in this study (#1, #2).

Setup: MDI Jig & Inline Connector #1


2-pin MDI jig




Inline Connector#1




Inline Connector#1 with 1-pair UTP




Calibration (Sdc11 for [VNA + SMA Cables])



Calibration Cntd. (Sdc11 for [VNA + SMA Cables + MDI Jig])



Mode Conversion Limit Line for Component Level



$$- 60_{\text{dB}}$$

$$10 < f_{\text{MHz}} < 30$$


$$[5 \log_n (f_{\text{MHz}}) - 77]_{\text{dB}}$$

$$30 < f_{\text{MHz}} < 600$$


Sdc21 for 2m UTP




Sdc21 for 2m UTP w/1-inline#2



Sdc21 for 4m UTP w/2-inline#2




15m UTP w/4-inline#2 (setup1)



Proposed limit line for RTPGE Link Segment


15m UTP w/4-inline#1 (setup2)



Proposed limit line for RTPGE Link Segment

Baseline Proposal for Mode Conversion

- The mode conversion limit line is proposed for a 15m UTP link segment with 4-inline connectors



$$- 50_{\text{dB}} \quad 10 < f_{\text{MHz}} < 80$$

$$[5 \log_n (f_{\text{MHz}}) - 72]_{\text{dB}} \quad 80 < f_{\text{MHz}} < 600$$