


PoDL Detection and Classification Presentation

Andy Gardner

July 2014




Presentation Objectives

- Review the requirements for PoDL detection and classification.
- Review the detection and classification scheme for PoE.
- Propose a new detection and classification scheme for PoDL.
- Propose a scheme for measuring parasitic resistance between the PSE and PD during detection.

Detection and Classification Considerations for PoDL

- Both PD voltage and current information need to be encoded in the class info, e.g.
 - $V_{PD} = \{5V, 12V, 48V\}$ and $I_{PD} = \{0.5A, 1A, 2A, 5A, 10A\}$ have been proposed.
- A means for detecting parasitic resistance between the PSE and PD during detection may also be required/desired.
- The detection and classification scheme should be easily extendable and straight forward to implement.
- Start-up latency requirement may present a significant time constraint.
 - An abbreviated detection scheme that just checks for open and short circuit conditions may be required.
 - Classification may be performed once or on demand with the subsequent PD info being stored in system NVM.

PoDL Network from PSE/PD Perspective



* - Optional reverse polarity blocking diode

- Decoupling network inductors L1-L4 value is a function of the PHY T_{droop} specification:


$$L \geq \frac{-50\text{ohms} \times t_{\text{droop}}}{\ln\left(1 - \frac{v_{\text{droop}}}{v_{\text{peak}}}\right)}$$

- PHY DC blocking capacitors C1-C4 are chosen to yield an adequately damped response:

$$C \geq -\zeta^2 \frac{4 \times t_{\text{droop}}}{50\text{ohms} \times \ln\left(1 - \frac{v_{\text{droop}}}{v_{\text{peak}}}\right)} \text{ where } \zeta \text{ is the desired damping ratio}$$

PoE Detection and Classification Scheme Recap

- The POE detection scheme looks for ~25kΩ signature resistance over a PD voltage chord > 1V in the range of 2.7V to 10.1V.



$$R_{\text{detect}} = \left\{ \frac{(V_2 - V_1)}{(I_2 - I_1)} \right\}_{\Omega}$$



- The subsequent classification scheme entails the PSE forcing a voltage between 14.5V and 20.5V while detecting the resulting current one or more times in order to determine the PD power requirement.

New Constraints on PoDL Detection and Class Scheme

- PoDL Detection and Class has significantly less voltage headroom to work with (<5V?) .
- Detect and Class may need to complete in <10ms for some applications.
- Parasitic resistance between the PSE and PD may need to be measured during detection prior to powering the PD load.

A New Approach to Detection and Classification for PoDL?


- The PSE may force current and sense one or more current limited voltages being shunt regulated by PD during detection and classification.
- Signature and class information may be encoded by PD shunt regulator voltage(s) (as opposed to PD current).



Time Invariant PoDL Detection and Classification Scenario

- A time-invariant PD always yields the same I-V plot on a curve tracer in response to an alternating I_{PSE} sweep.
 - The PD may exhibit hysteresis.
- The first or lowest voltage may encode the PD signature.
- Additional higher regulator voltages may be used to encode class information.
 - Voltage deltas may also be used to encode class information.
- Hysteresis may be used to encode additional information for the same PSE current.


Time Invariant PD Detect/Class I-V Plot



Time Variant PoDL Detection and Classification Scenario


- The PD's shunt regulated voltage may change in a non-repetitive way in response to an alternating PSE current about a predetermined threshold.
- The first voltage may encode the PD signature.
- Subsequent PD voltages may be used to encode class information.
 - Voltage deltas may also encode class information.
- The sequence may stop after a predetermined number of cycles, or the PSE may overdrive the PD in order to end the sequence.

Time Variant PD Detect/Class I-V Plot





Sensing Parasitic Resistance Between the PSE and PD

- Parasitic resistance between the PSE and PD may be sensed by varying the PSE current within a regulated voltage band and sensing the resulting change in V_{PSE} .
- The parasitic resistance information may be used to compensate the PSE voltage for cable drop as a function of the PD load current.



Settling Time Considerations

- PD regulator settling time is a function of capacitance downstream of the PSE and T_{droop} .
- Isolating large PD load capacitance from the PoDL network during detection and classification may be necessary for fast detection and classification.



Summary

- Both voltage and current information need to be encoded in the PD signature for PoDL.
- A new detection and classification scheme for PoDL was presented.
- PD load capacitance may need to be isolated from the PoDL network during detection and classification in order to minimize settling times.

