

IEEE 802.3 Ethernet Working Group
DRAFT Liaison Communication

Source: IEEE 802.3 Working Group¹

To: Frank Effenberger Rapporteur, ITU-T, SG15 Q2
feffenberger@huawei.com

Junichi Kani Associate Rapporteur, ITU-T, SG15 Q2
kani.junichi@lab.ntt.co.jp

CC: Konstantinos Karachalios Secretary, IEEE-SA Standards Board
Secretary, IEEE-SA Board of Governors
sasecretary@ieee.org

Paul Nikolich Chair, IEEE 802 LMSC
p.nikolich@ieee.org

Adam Healey Vice-chair, IEEE 802.3 Ethernet Working Group
adam.healey@broadcom.com

Pete Anslow Secretary, IEEE 802.3 Ethernet Working Group
panslow@ciena.com

Curtis Knittle Chair, IEEE P802.3ca Task Force
c.knittle@cablelabs.com

Steve Trowbridge Chairman, ITU-T Study Group 15
steve.trowbridge@nokia.com

From: David Law Chair, IEEE 802.3 Ethernet Working Group
dlaw@hpe.com

Subject: Liaison status of progress of IEEE P802.3ca as related to Wavelength selection,
Power Budget, and FEC

Approval: Agreed to at IEEE 802.3 Plenary Meeting, Rosemont, IL, 8th March, 2018

Dear Dr. Effenberger and Dr. Kani,

To support PON Convergence efforts and maintain an open communication channel between ITU-T SG15 Q2 and on-going IEEE P802.3ca Task Force efforts we are providing a status of progress from the March 2018 Rosemont, IL meeting.

The IEEE P802.3ca Task Force has approved the following elements associated with the standards effort:

¹ This document solely represents the views of the IEEE 802.3 Working Group, and does not necessarily represent a position of the IEEE, the IEEE Standards Association, or IEEE 802.

1. **Wavelength and Power Budget:**

- Downstream wavelength plan was accepted. Two wavelengths: 1358 +/- 2 nm and 1342 +/- 2 nm. 25G PON will use 1358 +/- 2 nm.
 - 25G PON OLT transmitter launch power: AVPmin = 4.8 dBm and ER min = 8 dB
 - 25G PON ONU receiver sensitivity was accepted: -25.7 dBm at BER= 1e-2 and ER=8 dB
 - Upstream wavelength plan was modified. UW0 1260-1280 nm, UW1 1290-1310 nm, UW2 1320 +/- 2 nm.
 - 25G PON ONU transmitter launch power: (AVP minus TDP) min = 4 dBm, ER min =5 dB
 - 25G PON OLT receiver sensitivity was accepted: -25.0 dBm at BER= 1e-2, ER=5 dB
2. **Forward Error Correction (FEC):** Task Force has agreed to use LDPC in both directions with optional precoding in the downstream.
3. **Task Force Draft 1.0:** The latest draft 1.0, a work in progress, is attached for your review. **[Please include boiler plate text on restricted distribution].**

Once again, thank you for your interest. We look forward to continued collaboration with the ITU-T Q2/15 team.

Sincerely,

David Law

Chair, IEEE 802.3 Ethernet Working Group