

C57.150™/D11

- 1 Overview
- 1.2 Purpose
- 2 Normative references
- 3 Definitions
- 4 Request for quotation and specification
- 5 Design considerations for transport
- 5.1 New transformers and reactors
- 5.2 Existing transformers and reactors
- 6 Transportation preparation
- 6.1 Main transformer or reactor tank
- 6.1.1 General
- 6.1.2 Gas filling, dry air supply
- 6.1.3 Impact recorders
- 6.1.4 Checkpoints
- 6.2 Transportation preparation—accessories
- 6.2.1 General
- 6.2.2 Packing the accessories
- 6.2.3 Material compliance
- 6.2.4 Dangerous materials
- 6.2.5 Proper transportation marks
- 6.2.6 Detailed packing lists
- 7 Planning for heavy-haul transportation
- 7.1 Heavy-haul situations
- 7.2 Identifying suitable heavy-hauler companies
- 7.3 Determinations of actual equipment transportation dimensions
- 7.4 Route inspections and verification of transportation route
- 7.5 Selection of proper heavy-haul equipment
- 7.6 Applicable safety and environmental requirements, regulations, and laws
- 7.7 Permits
- 7.8 Insurance coverage
- 8 Transport
- 8.1 Transportation information
- 8.1.1 Transportation information should include the following:
- 8.1.2 Equipment orientation
- 8.2 Transport terminology
- 8.2.1 Equipment shipped ex
- 8.2.2 Equipment shipped DAT, DAP, or DDP destination
- 8.2.3 International transport terms
- 8.3 Barge and ocean vessels
- 8.3.1 Transport of power equipment as marine cargo
- 8.3.2 Forces and motions to vessels when underway at sea
- 8.3.3 Cargo storage areas, compartments, and environment
- 8.3.4 Lifting provisions
- 8.3.5 Base footprint, surface loading, and bedding requirements
- 8.3.6 Securing/shoring
- 8.3.7 Assessment, planning, and surveyors
- 8.4 Rail
- 8.4.1 General
- 8.4.2 Positioning of rail car in train
- 8.4.3 Design and pre-clearance with railways
- 8.4.4 Loading, blocking, and bracing

8.4.5	Dimensional clearance and release for transport
8.5	Air cargo
8.6	Arrival at destination
9	Heavy-haul transportation
9.1	Condition of heavy-haul equipment
9.2	Inspection of equipment prior to receiving
9.3	Offloading the equipment onto heavy-haul transportation equipment
9.4	Securing the load
9.5	Transportation to the destination
10	Arrival (receipt) inspection
10.1	Preparation for inspection
10.2	Visual checks
10.2.1	Inspection of equipment externals, prior to unloading
10.3	Offloading considerations
10.3.1	General
10.3.2	Offloading using hydraulic jacks
10.3.3	Offloading using cranes or a gantry system
10.4	Up-righting of large shell-form transformers or reactors
10.5	Inspection and offloading of separately shipped parts and components accessories
10.5.1	Offloading accessories
10.5.2	Inspection
10.6	Internal inspection
10.7	Electrical tests
10.7.1	General
10.7.2	Frequency response analysis
10.7.2.1	FRA transportation configuration
10.7.2.2	Insulating liquid level and presence
10.7.2.3	De-energized and on-load tap changer position
10.7.2.4	Bushings and placement
10.7.3	Core insulation resistance (core ground)
10.7.4	Leakage reactance
10.7.5	Winding turns ratio
10.7.6	Insulation power factor
10.7.7	Winding insulation resistance
10.7.8	Other components
10.7.8.1	Bushings
10.7.8.2	Bushing current transformers (BCT)
10.8	Mechanical tests
10.8.1	Pressure tests
10.8.2	Dew point measurement

Annex A	Bibliography
---------	--------------

C57.93™-2007

- 1 **Scope**
- 2 **Normative references**
- 3 **Liquid-immersed power transformers rated 501 kVA to 10 MVA, or with primary windings less than 69 kV**
 - 3.1 **General**
 - 3.2 **Inspection and receipt**
 - 3.2.1 **Station-type configuration**
 - 3.2.2 **Pad-mount configuration**
 - 3.3 **Internal inspection**
 - 3.3.1 **General practices for internal inspection**
 - 3.3.2 **Atmospheric conditions**
 - 3.3.3 **Inspection**
 - 3.4 **Handling**
 - 3.4.1 **Pad-mount configuration**
 - 3.5 **Assembly**
 - 3.6 **Storage**
 - 3.7 **Tests**
 - 3.7.1 **Pad-mount configuration**
 - 3.7.2 **Hydrocarbon-based insulating oils (conventional and less flammable)**
 - 3.7.3 **Other insulating liquids**
 - 3.8 **Energization**
 - 3.8.1 **Connections**
 - 3.8.2 **Connecting to bushings**
 - 3.8.3 **Energization under cold conditions**
 - 3.9 **Maintenance**
 - 3.9.1 **Routine DGA testing**
 - 3.9.2 **External inspection**
- 4 **Liquid-immersed power transformers rated 10 MVA and above or with high-voltage windings 69 kV and above**
 - 4.1 **General**
 - 4.2 **Shipping**
 - 4.2.1 **General**
 - 4.2.2 **Shipping terminology - See C.3.**
 - 4.2.2.1 **Transformers shipped free on board factory**
 - 4.2.2.2 **Transformers shipped FOB destination**
 - 4.2.3 **Railroad shipments**
 - 4.2.3.1 **Routing**
 - 4.2.3.2 **Acceptance by carrier**
 - 4.2.3.3 **Rail cars**
 - 4.2.3.4 **Rail car loading standard**
 - 4.2.3.5 **Block and tie-down**
 - 4.2.3.6 **Impact recorders**
 - 4.2.3.7 **Personal escort, special freight team service**
 - 4.2.4 **Truck shipments**
 - 4.2.5 **Water shipment**
 - 4.3 **Inspection and receipt**
 - 4.3.1 **External, prior to unloading**
 - 4.3.2 **Internal, prior to unloading**
 - 4.4 **Internal inspection**
 - 4.4.1 **Atmospheric conditions**
 - 4.4.2 **Inspection**
 - 4.5 **Handling**
 - 4.5.1 **Complete transformer**

4.5.2	Lifting with slings
4.5.3	Raising with jacks
4.6	Anchorage
4.7	Assembly
4.7.1	General
4.7.2	Bushings
4.7.3	Heat exchangers and piping
4.7.4	Other accessories
4.8	Vacuum treatment
4.8.1	Preparation
4.8.2	Vacuum treatment
4.8.3	Vacuum leakage tests
4.8.3.1	Vacuum connection system leakage
4.8.3.2	Assembled unit vacuum leakage tests
4.8.3.3	Vacuum hold time and hot oil circulation
4.8.4	Processing dielectric liquid
4.8.5	Vacuum filling
4.9	Field drying of insulation
4.9.1	Method 1—Circulating hot oil
4.9.2	Method 2—High vacuum (with or without hot oil circulation)
4.9.3	Method 3—Hot air
4.9.4	Completion of drying
4.10	Reprocessing
4.10.1	Considerations for reprocessing
4.10.2	Methodology for reprocessing and absorption
4.11	Tests after the transformer has been assembled and filled with dielectric liquid
4.12	Energization
4.13	Maintenance
4.13.1	Maintenance intervals for transformers
4.13.1.1	Recently energized transformers
4.13.1.2	Maintenance—station inspection interval (at least monthly)
4.13.1.3	Maintenance—at least annually
4.13.1.4	Maintenance—one to three years, based on voltage and BIL
4.13.1.5	Maintenance—three to seven years, or as required by condition-based maintenance, based on voltage and BIL
4.13.2	Maintenance intervals for transformer load-tap-changing (LTC) equipment
4.13.2.1	Maintenance—station inspection interval
4.13.2.2	Maintenance—as established by manufacturer or trending
4.13.2.3	Maintenance—one to three years; based on voltage and BIL
4.13.2.4	Maintenance—three to seven years, based on voltage and BIL
4.13.2.5	Final “maintenance”—disposal
4.14	Storage guidelines
4.14.1	Storage of main transformer
4.14.1.1	Storage general guideline
4.14.1.2	Methods and duration of storage
4.14.1.2.1	Storage—less than 90 days
4.14.1.2.2	Storage—up to six months
4.14.1.2.3	Storage—more than six months
4.14.2	Storage of transformer accessories and components
Annex A	Bibliography
Annex B	Figures and table
Annex C	Field equipment for oil-filling EHV transformers and determination of insulation dryness
C.1	Recommended minimum equipment ratings (for new transformers)

- C.1.1 Oil-processing equipment (preferably an integrated trailer unit)**
- C.1.2 Vacuum pumps**
- C.1.3 Dry gas**
- C.1.4 Test equipment**
- C.2 Determination of insulation dryness**
 - C.2.1 Moisture determination of cellulose insulation**
 - C.2.1.1 Dew point measurement**
 - C.2.1.2 Cold weather dew point testing**
 - C.2.1.3 Cold trap technique**
 - C.2.2 Moisture determination of transformer oil**
- C.3 Shipping terminology**

