

# IEEE 1722a

# Assumptions

Dave Olsen

dave.olsen@harman.com

**Green Text = Agreed to at a Face 2 Face (was Blue or Red)**

**Black Text = Not Decided**

**Changes Marked with Red from last version**

# Subtype Assignment

- New subtypes
  - 0x02 AVTP Audio Format
  - 0x03 AVTP Video Format
  - 0x04 Control Streams (Automotive/TSCS)
  - 0x7a AVDECC Discovery
  - 0x7b AVDECC Enumeration and Control
  - 0x7c AVDECC Connection Management
  - 0x7d Media Clock Negotiation
- Divide the subtype table between C and D to clarify that these are different subtype domains

# Mac Address Assignment

- MCN needs MAC address (91:E0:F0:00:FF:01)
- 1722.1 has requested a block of 16k MAC addresses to be assigned by 1722a from the 1722 OUI (91:E0:F0:01:00:00 – 91:E0:F0:01:FF:FF)

# Changes to current standard

- Redefine gateway info to only be valid for 61883 formats
- Gateway info field to be replaced by a protocol specific field that can be used in new protocols
- GV bit to also be redefined to be available for use in new protocol types or reserved where not used
- Update reference to 802.1AS-2011
- Update other references???

# AVTP Audio Format

- Support PCM audio
  - Support more channels
  - Simpler data parsing
- Event Markers
- Link Protection field to indicate encryption
  - Encryption will be indicated by the new Version 1 security header

# AVTP Audio Format LPCM Format

- Timestamp in every packet
- Define a base required default format, a talker must support one of the formats, a listener must support both of the following:
  - 48k, 6 samples/packet, 32-bit sample size, 8 channels, interleaved
  - 44.1k, 6 samples/packet, 32-bit sample size, 8 channels
- We may want to split the defaults up by market

# AVTP Video

- Support new native AVTP formats
  - Support RAW sensor data (no one is claiming a desire for this, will be dropped if no further interest)
    - IIDC formats currently support this functionality.
- Support RTP Payload formats
  - Support MJPEG (RFC 2435)
  - Support MJPEG2000 (RFC 5372)
  - Support H.264 (RFC 6184)
- Event Markers
- Encryption is part of Version 1 Header
- HDCP is on for PES and indicated in the PES header
- SOF/EOF Markers used in RTP and other formats

# Media Clock Negotiation

- Frequency multipliers to match 1722.1
  - 1.001, 1/1.001, 24/25, 25/24
- Clock Quality field(s) to be added between priority1 and priority2
  - Media Clock variance should be determined by PTPDEV (16 bit field)
  - gptp\_clock\_period field related to gPTP interval typically 8ns or 40ns (8 bit field)
- Required Crystal GUID to be added for informational purposes to MCN Advertise packet



# Real Time Format Change (the HDMI problem)

- Include markers to indicate change
  - Prechange indication??
  - Format identifier??
  - Formats are prenegotiated
  - One bit could set to indicate a change is coming and then reset to indicate the change is here
- Required in AVTP audio/video formats
- Add bits to 61883 base formats
- Could this be used by the 802.1 multitalker problem??
- This feature relies on HDCP and so we should put this on hold until we solve the HDCP Problem

# Diagnostics

- Diagnostic Counter to be included with 1722a
  - List included in current draft

# 1722/1722a PICS

- 1722/1722a only (no PICS derived from IEC 61883 specific standards)
- Need PICS for AVTP audio/video
- Need PICS for MCN

# DTCP/HDCP

- Only support for HDCP IIA can possibly be included in this standard.
  - Everything else requires approval by DTLA
  - HDCP will be indicated in the PES
- 1722a will not work with the DTLA to get approval

# Control Streams

- Automotive base format
  - Flexray Protocol
  - CAN Protocol
  - LIN Protocol
- TSCS Protocol
- We will not be defining FlexRay synchronization

# Low Latency Security/Encryption

- Informative Annex
- MacSec – per link encryption
- 802.1X – per LAN authentication
- How do I secure a live performance?
  - Class A Stream latency
- Need a volunteer or this will be dropped

# Synchronization bits

- Need Synchronization Marker bits
- Currently M0 and M1
- Do we need more bits? Maybe 4 bits
- M0 used for format change
- M1 used to synchronize external events
- Can we add these same bits to the 61883 streaming formats?

# Version 1 Format

- New format to support security header
  - Packet signing
  - Encryption
  - See avtp\_dolsen\_koftinoff\_version\_1\_header\_v2.pdf
  - Make use of IEEE 1363a



## Other items?

- We have been contacted by IEC100 (IEC 61883 group) for a formal liaison
- New draft of 61883-6 that is coming. Do we want support it?

# Goals

- Next draft due Aug 1 2012
  - Update Automotive Control Streams – Dave
  - Update TSCS – Jeff
  - Header Version 1 draft – Dave/Jeff
    - Update all diagrams, including all in 1722
- Later draft
  - SDI Video Encapsulation
  - HDCP Annex
  - MCN State Machine
  - AVTP formats and MCN PICS