




Handling Multiple K-characters

Kevin Bross
15 April 2016

- ❑ Both 8b/10b and 64b/66b character encodings have special characters that have no equivalent un-encoded value
 - These special characters are called K-characters
- ❑ K-characters are used for special purposes to identify conditions independent of any normal data string
 - For example, CPRI uses K-characters to indicate the start of each hyperframe

- ❑ Structure Agnostic Mapper can only handle 0 or 1 K-characters per packet
 - This works fine for CPRI
 - Other protocols like OBSAI can have multiple K-characters within a given packet
- ❑ The “Structure Agnostic” mapper is not really agnostic to the protocols
 - It’s currently very CPRI-specific




- ❑ Provide support to handle multiple K-characters within a packet
 - Enhance current method to indicate position of K-character to allow chaining
- ❑ Payload expectation:
 - 1 or more words (16 bits) to indicate Kpos (position of K-character within packet)
 - 0xFF = no K-characters within packet
 - Jumbo packets could use 14 bits for position
 - Chaining bit: MSB clear (0) if another Kpos word immediately follows
 - Start of packetData field shifts out 2 bytes for each additional Kpos field inserted


Example Packets




0 or 1 K-characters:




2 K-characters:



3 K-characters:



- ❑ Structure-agnostic mapper is CPRI-specific today
 - Can only handle 0 or 1 K-characters
- ❑ Proposal: Use upper bit of Kpos field to indicate chaining of Kpos fields



- If upper bit is clear (0), another Kpos field immediately follows this Kpos field
- No impact to packet size (or format) if 0 or 1 K-characters in packetData