



DMTF Management Standards for Edge Virtual Bridging (EVB) and Network Port Profiles

Hemal Shah, Associate Technical Director, Broadcom Corporation
DMTF Platform Management Sub-Committee Chair
March, 2011



Agenda


- DMTF Overview
- IEEE/DMTF Areas of Collaboration
- DMTF Standards for EVB Management and Network Port Profiles
- VM Lifecycle Management
- Open Virtualization Format (OVF)
- Network Port Profiles
- CIM Profiles for Virtual Networking

Distributed Management Task Force (DMTF)



- Develops management standards for enterprise and Internet environments
- Formed in 1992
- More than 4,000 active participants
 - from nearly 200 organizations in over 40 countries
- 3 Major committees and 25+ Working Groups/Forums
 - Committees: Technical, Marketing, Interoperability...
- Over a dozen Alliance Partners
 - SNIA, OGF/GGF, NGN, TMF, TCG, OASIS, etc.
- Developed standards & initiatives
 - CIM, CIM-XML, SMBIOS, CDM, ASF, SMASH, DASH, WS-Management...

DMTF Technology Diagram




CIM – Common Information Model
WBEM – Web Based Enterprise Management
OVF – Open Virtualization Format
MOF – Managed Object Format
WS-Man – Web Services Based Management

DASH – Desktop and Mobile Architecture for System Hardware
SMASH – System Management Architecture for Server Hardware
SMI – Storage Management Initiative
CDM – Common Diagnostics Model
VMAN – Virtualization Management

DMTF Technical Committee Organization



<http://www.dmtf.org/about/working-groups>





Platform Management Sub-Committee Overview


- **Cloud Management Working Group (CMWG)**
 - Focuses on management interfaces between cloud service/consumer and cloud provider
- **Physical Platform Profiles (PPP) WG**
 - Defines platform independent, interoperable, industry standard management data models, profiles and registries for the aspects of managing the physical aspects of platforms
- **System Virtualization, Partitioning, and Clustering (SVPC) WG**
 - Defines platform independent, interoperable, industry standard management data models, profiles, formats and registries for the aspects of managing the virtualization aspects of platforms
- **Server, Desktop, and Mobile Working Group (SDMWG)**
 - Defines platform independent, interoperable, industry standard specifications for the management of server, desktop, and mobile platforms (owns DASH and SMASH wrapper specifications)
- **Platform Management Components Intercommunications (PMCI) WG**
 - Defines specifications for the “Inside the box” communication between components within the platform management subsystem
- **SMBIOS WG**
 - Defines SMBIOS specifications for low level platform asset information
- **Telco WG**
 - Defines specifications for the management of telecommunications systems, services, and applications

IEEE/DMTF Collaboration Areas




- **Network Port Profiles - SVPC WG**
 - Network Port Profile XML Schema
 - OVF Extensions for Network Port Profiles
- **Edge Virtual Bridge (EVB) Management - SVPC WG**
 - CIM Schema Enhancements for EVB
 - CIM Profiles for EVB Management
 - Virtual Ethernet Switch and Ethernet Port Resource Virtualization Profiles
- **Data Center Ethernet (DCE) Management – PPP WG**
 - CIM Schema Enhancements for DCE
 - Priority-Based Flow Control (PFC) and Enhanced Transmission Selection (ETS) Initially
 - CIM Profiles for DCE Management
 - Ethernet Port and Data Center Ethernet Port Profiles

DMTF Standards for EVB Management and Network Port Profiles



1. GOAL 1: Define CIM-based data models to allow Management of Network and Storage Networking on the Virtualization Platform
2. GOAL 2: Define OVF extensions in support of Network and Storage Networking deployment on the Virtualization Platform
3. GOAL 3: Define Port Profile XML Schema, for describing VSI Network attributes


VM Lifecycle Management




Open Virtualization Format (OVF)



- OVF
 - A distribution format for VMs
 - Supports single VM & multiple VM configs
 - Optimized for distribution & simple automation
 - Vendor and platform independent
- An OVF package consists of
 - One OVF descriptor with extension .ovf
 - zero or one OVF manifest (w/ extension .mf)
 - zero or one OVF certificate (w/ extension .cert)
 - zero or more disk image files
 - zero or more additional resource files
 - such as ISO images




An OVF Example



Network Port Profile



Life Cycle of Network Port Profile




Network Port Profile




Refers to a set of network attributes that can be applied to one or more virtual machines

Network Port Profile Use Case

- Network Infrastructure is not pre-provisioned
- Network switch accesses port profile DB during VM deployment
- Network Port profile info is in the OVF package
- VM Admin understands port profile metadata and schema
- VM admin/Manager applies port profile config during VM deployment
- At the deployment time, VM Admin/Manager does not access Port Profile DB



Network Port Profile and OVF



Network Port Profile Schema Proposal



```
<xs:schema xmlns:ppns="http://schemas.dmtf.org/svpc/portprofile/1"
  xmlns:xs="http://www.w3.org/2001/XMLSchema"
  xmlns:cim="http://schemas.dmtf.org/wbem/wscim/1/common"
  xmlns:xml="http://www.w3.org/XML/1998/namespace"
  xmlns:rasd="http://schemas.dmtf.org/wbem/wscim/1/cim-schema/2/CIM_ResourceAllocationSettingData"
  xmlns:epasd="http://schemas.dmtf.org/wbem/wscim/1/cim-schema/2/CIM_EthernetPortAllocationSettingData"
  xmlns:ns1="http://schemas.dmtf.org/svpc/portporfile/1"
  targetNamespace="http://schemas.dmtf.org/svpc/portporfile/1" elementFormDefault="qualified" attributeFormDefault="qualified">
  <xs:import namespace="http://www.w3.org/XML/1998/namespace" schemaLocation="http://www.w3.org/2001/xml.xsd"/>
  <xs:import namespace="http://schemas.dmtf.org/wbem/wscim/1/common"
    schemaLocation="http://schemas.dmtf.org/wbem/wscim/1/common.xsd"/>
  <xs:import namespace="http://schemas.dmtf.org/wbem/wscim/1/cim-schema/2/CIM_ResourceAllocationSettingData"
    schemaLocation="http://schemas.dmtf.org/wbem/wscim/1/cim-schema/2.22.0/CIM_ResourceAllocationSettingData.xsd"/>
  <xs:import namespace="http://schemas.dmtf.org/wbem/wscim/1/cim-schema/2/CIM_EthernetPortAllocationSettingData"
    schemaLocation="http://schemas.dmtf.org/wbem/wscim/1/cim-schema/2.27.0/CIM_EthernetPortAllocationSettingData.xsd"/>
  .....
  <xs:element name="PortProfile">
    <xs:annotation>
      <xs:documentation>Root element of Port Profile </xs:documentation>
    </xs:annotation>
    <xs:complexType>
      <xs:sequence>
        <xs:element name="Item" type="epasd:CIM_EthernetPortAllocationSettingData_Type" minOccurs="0" maxOccurs="unbounded"/>
        <xs:any namespace="##other" processContents="lax" minOccurs="0" maxOccurs="unbounded"/>
      </xs:sequence>
    </xs:complexType>
  </xs:element>
</xs:schema>
```

Network Port Profile Examples

Bandwidth Reservation

```
<?xml version="1.0" encoding="UTF-8"?>
<ppns:PortProfile ...>
    <epasd:NetworkPortProfileID>http://www.dmtf.org/portporfiles</epasd:NetworkPortProfileID>
    <epasd:NetworkPortProfileIDType>2</epasd:NetworkPortProfileIDType>
    <epasd:Address>00-16-8B-DB-00-5E</epasd:Address>
    <rasd:AllocationUnits>GigaBits per Second</rasd:AllocationUnits>
    <rasd:Reservation>1</rasd:Reservation>
</ppns:PortProfile>
```

Allowed MAC/VLAN Pairs

```
<?xml version="1.0" encoding="UTF-8"?>
<ppns:PortProfile ....>
    <epasd:NetworkPortProfileID>http://www.dmtf.org/portporfiles</epasd:NetworkPortProfileID>
    <epasd:NetworkPortProfileIDType>2</epasd:NetworkPortProfileIDType>
    <epasd:AllowedToTransmitMACAddresses>00-16-8B-DB-00-5E</epasd:AllowedToTransmitMACAddresses>
    <epasd:AllowedToTransmitMACAddresses>00-17-8B-DA-00-5E</epasd:AllowedToTransmitMACAddresses>
    <epasd:AllowedToTransmitVLANs> 5 </epasd:AllowedToTransmitVLANs>
    <epasd:AllowedToTransmitVLANs> 7 </epasd:AllowedToTransmitVLANs>
</ppns:PortProfile>
```

Note: MAC/VLAN Pairs are represented as indexed arrays.

Allowed Priorities


```
<?xml version="1.0" encoding="UTF-8"?>
<ppns:PortProfile....>
    <epasd:NetworkPortProfileID>http://www.dmtf.org/portporfiles</epasd:NetworkPortProfileID>
    <epasd:NetworkPortProfileIDType>2</epasd:NetworkPortProfileIDType>
    <epasd:AllowedPriorities>3</epasd:AllowedPriorities>
    <epasd:AllowedPriorities>5</epasd:AllowedPriorities>
</ppns:PortProfile>
```

Management Profiles for EVB/DCB Proposal




- Models Ethernet Port Resource Virtualization/Virtual Ethernet Switch
- Specifically, covers
 - Ethernet adapters (vNIC) – each adapter modeled as an Ethernet Port
 - Virtual Ethernet Switch and switch settings
 - Ethernet switch ports (vSwitch)
 - Connections between vNIC and vSwitch Ports
 - VLANs
 - Port characteristics, settings (MAC, speed, duplex..), statistics...
- Already Published CIM Profiles
 - DSP1014 Ethernet Port Profile
 - DSP1050 Ethernet Port Resource Virtualization Profile
 - DSP1097 Virtual Ethernet Switch Profile


Ethernet Port Profile Class Diagram




Ethernet Port Resource Virtualization Profile Class Diagram



Virtual Ethernet Switch Profile Class Diagram



EthernetPort Class



EthernetPortAllocationSettingData Class



ResourceAllocationSettingData	EthernetPortAllocationSettingData
ResourceType : uint16 {enum}	DesiredVLANEndpointMode: uint16 {enum}
ResourceType : string	OtherEndpointMode: string
ResourceSubType : string	PortCorrelationID: string {E}
PoolID : string	NetworkPortProfileID: string {E}
ConsumerVisibility : uint16 {enum}	NetworkPortProfileIDType: uint16{enum, E}
HostResource : string[]	AllowedPriorities: uint16[]{E}
AllocationUnits : string	ReceiveBandwidthLimit: uint64 {E}
VirtualQuantity : uint64	ReceiveBandwidthReservation: uint64 {E}
Reservation : uint64	DefaultPriority: uint16 {E}
Limit : uint64	PortVID: uint16 {E}
Weight : uint32	DefaultPortVID: uint16 {E}
AutomaticAllocation : boolean	Promiscuous: boolean {E}
AutomaticDeallocation : boolean	SourceMACFilteringEnabled: boolean {E}
Parent : string	AllowedToTransmitMACAddresses: string[] {E}
Connection : string[]	AllowedToReceiveMACAddresses: string[] {E}
Address : string	AllowedToTransmitVLANs: uint16[] {E}
MappingBehavior : uint16 {enum}	AllowedToReceiveVLANs: uint16[] {E}
AddressOnParent: string	OtherNetworkPortProfileIDTypeInfo: string {E}
VirtualQuantityUnits: string	



Useful Links

- CIM Profiles
 - DSP1014 Ethernet Port Profile
 - http://www.dmtf.org/sites/default/files/standards/documents/DSP1014_1.0.pdf
 - DSP1050 Ethernet Port Resource Virtualization Profile
 - http://www.dmtf.org/sites/default/files/standards/documents/DSP1050_1.0.0.pdf
 - DSP1097
 - http://www.dmtf.org/sites/default/files/standards/documents/DSP1097_1.0.0.pdf
- OVF
 - DSP0243 OVF 1.1 Specification
 - http://www.dmtf.org/sites/default/files/standards/documents/DSP0243_1.1.0.pdf
 - DSP8023 OVF 1.1 Envelope XSD
 - http://schemas.dmtf.org/ovf/envelope/1/dsp8023_1.1.xsd
 - DSP8027 OVF 1.1 Environment XSD
 - http://schemas.dmtf.org/ovf/environment/1/dsp8027_1.1.xsd
- White papers
 - DSP 2017 Open Virtualization Format White Paper 1.0.0
 - http://www.dmtf.org/sites/default/files/standards/documents/DSP2017_1.0.0.pdf
 - DSP 2025 Virtual Networking Management White Paper (Work-in-Progress)