

802.1Qbp – ECMP Editor’s Notes and Issues

Ben Mack-Crane
(ben.mackcrane@huawei.com)

What Seems Clear

- Unicast traffic ECMP load spreading
 - Flow ID calculated at edge and placed in frame (new tag format)
 - No need for standard edge hash function
 - Forwarding based on standard hash $f(\text{Flow ID}, \text{System ID})$ used to select from ECMP port map
- TTL to mitigate loops due to transient state or bugs
- OAM to test ECMP forwarding

Issues to Resolve

- Frame format (new tag)
 - See bp-mackcrane-tag-format-0511.ppt
 - Untagged option (i.e., no VID in tag)
- Standard forwarding hash function
- Method for selection from ECMP port list (how forwarding hash is used in next hop selection)
- Multicast load spreading
- OAM requirements
 - MEP per Flow ID or MEP cycling through Flow IDs?
 - Proactive or On Demand or both?

Clauses that need work for 802.1Qbp

- 1, 3, 4, 5: Overview, Definitions, Abbreviations, Conformance
- 6. Support of the MAC Service
 - Add primitive parameters
 - Add shim functionality related to new parameters (new tag format)
- 8. Principles of bridge operation
 - Modifications to FDB and forwarding process
- 9. Tagged frame format
- 12. Management
- 17. MIB
- 27. Shortest Path Bridging (SPB)
- 28. ISIS-SPB Link State Protocol
- Annex A. PICS
- TBD (depending on issue resolution and further study)
 - CFM clauses (18-22)
 - CN clauses (30-33)
 - SRP (35)