Project	IEEE 802.16 Broadband Wireless Access Working Group <http://ieee802.org/16>
Title	**Clarification on the Band AMC Operation**
Date Submitted	**2005-01-24**
Source(s)	Seungjoo Maeng, Jeongheon Kim, Jiho Jang, Jaeho Jeon, Jaehee Cho, Panyuh Joo sjmaeng@samsung.com Samsung Electronics Co., Ltd. Dong Suwon P.O.Box 105 416, Maetan-3dong, Yeongtong-gu, Suwon-city, Gyeonggi-do, Korea 442-600
Re:	
Abstract	Clarification on the Band AMC Operation
Purpose	Adopting of proposed method into P802.16d
Notice	This document has been prepared to assist IEEE 802.16. It is offered as a basis for discussion and is not binding on the contributing individual(s) or organization(s). The material in this document is subject to change in form and content after further study. The contributor(s) reserve(s) the right to add, amend or withdraw material contained herein.
Release	The contributor grants a free, irrevocable license to the IEEE to incorporate material contained in this contribution, and any modifications thereof, in the creation of an IEEE Standards publication; to copyright in the IEEE's name any IEEE Standards publication even though it may include portions of this contribution; and at the IEEE's sole discretion to permit others to reproduce in whole or in part the resulting IEEE Standards publication. The contributor also acknowledges and accepts that this contribution may be made public by IEEE 802.16.
Patent Policy and Procedures	The contributor is familiar with the IEEE 802.16 Patent Policy and Procedures (Version 1.0) <http://ieee802.org/16/ipr/patents/policy.html>, including the statement "IEEE standards may include the known use of patent(s), including patent applications, if there is technical justification in the opinion of the standards-developing committee and provided the IEEE receives assurance from the patent holder that it will license applicants under reasonable terms and conditions for the purpose of implementing the standard." Early disclosure to the Working Group of patent information that might be relevant to the standard is essential to reduce the possibility for delays in the development process and increase the likelihood that the draft publication will be approved for publication. Please notify the Chair <mailto:r.b.marks@ieee.org > as early as possible, in written or electronic form, of any patents (granted or under application) that may cover technology that is under consideration by or has been approved by IEEE 802.16. The Chair will disclose this notification via the IEEE 802.16 web site <http://ieee802.org/16/ipr/patents/notices>.

Clarification on the Band AMC Operation

Introduction

In section 6.3.17.4, diffential CINR report for Band AMC operation using FAST_FEEDBACK channel is described, but it is not in in section 8.4.5.4.10 in which FAST_FEEDBACK channel is described. So it is needed to add the corresponding sub-section in section 8.4.5.4.10.

Suggested change to the standard

[Adopt the following changes in section 6.3.17.4, page 270, line 37]
A CINR measurement is quantized into 32 levels and encoded into ~~5~~ four information bits.

[Adopt the following changes in section 6.3.17.4, page 270, line 50]
The REP-RSP (see 11.12 for the TLV encodings) includes the CINR measurements of ~~five~~ four best bands.

[Adopt the following changes in section 6.3.17.4, page 270, line 61]
The BS acknowledges the trigger by allocating Band AMC subchannels. From the next frame when the SS sent the REP-RSP, the SS starts reporting the differential of CINR ~~five~~ four selected bands (increment: 1 and decrement: 0 with a step of 1dB) on its CQICH.

[Add the following section after 8.4.5.4.10.3, page 544, line 65]
8.4.5.4.10.4 Band AMC differential CINR feedback
When the Band AMC operation is triggered, the SS shall report the differential of CINR for four selected bands (increment: 1 and decrement: 0 with a step of 1 dB) on its FAST_FEEDBACK channel.

[Adopt the following changes in section 11.12, page 700, line 52]

REP-REQ Channel Type request	Name	Type	Length	Value
…	…	…	…	…
Channel Type = 01	Band AMC Report	2.2	~~4~~ 5	First 12 bits for the band indicating bitmap and Next 25 bits for CINR reports (5 bits per each band)