Project	IEEE 802.16 Broadband Wireless Access Working Group < <u>http://ieee802.org/16</u> >
Title	Correction for P802.16f/D1
Date Submitted	2004-11-01
Source(s)	Sangho Park, Pyung-Su Park, Inkyu PaekVoice: +82-2-6266-5291 Fax: +82-2-6266-5309 pasang@hanaro.comHanaro Telecom 
Re:	Contribution to support comments on IEEE 802.16 Working Group Letter Ballot #16
Abstract	This contribution corrects problems in P802.16f/D1
Purpose	To correct the document IEEE P802.16f/D1
Notice	This document has been prepared to assist IEEE 802.16. It is offered as a basis for discussion and is not binding on the contributing individual(s) or organization(s). The material in this document is subject to change in form and content after further study. The contributor(s) reserve(s) the right to add, amend or withdraw material contained herein.
Release	The contributor grants a free, irrevocable license to the IEEE to incorporate material contained in this contribution, and any modifications thereof, in the creation of an IEEE Standards publication; to copyright in the IEEE's name any IEEE Standards publication even though it may include portions of this contribution; and at the IEEE's sole discretion to permit others to reproduce in whole or in part the resulting IEEE Standards publication. The contributor also acknowledges and accepts that this contribution may be made public by IEEE 802.16.
Patent Policy and Procedures	The contributor is familiar with the IEEE 802.16 Patent Policy and Procedures <http: 16="" ieee802.org="" ipr="" patents="" policy.html="">, including the statement "IEEE standards may include the known use of patent(s), including patent applications, provided the IEEE receives assurance from the patent holder or applicant with respect to patents essential for compliance with both mandatory and optional portions of the standard." Early disclosure to the Working Group of patent information that might be relevant to the standard is essential to reduce the possibility for delays in the development process and increase the likelihood that the draft publication will be approved for publication. Please notify the Chair <mailto:chair@wirelessman.org> as early as possible, in written or electronic form, if patented technology (or technology under patent application) might be incorporated into a draft standard being developed within the IEEE 802.16 Working Group. The Chair will disclose this notification via the IEEE 802.16 web site <http: 16="" ieee802.org="" ipr="" notices="" patents="">.</http:></mailto:chair@wirelessman.org></http:>

# Correction for P802.16f/D1

Sangho Park, Pyung-Su Park, Inkyu Paek Hanaro Telecom

## 1. Introduction

The document IEEE P802.16f/D1 contains several problems as follows.

- (1) In the base document (Std IEEE 802.16-2004), three management connections may be established at SS's network entry and are identified by their CID. In the overall document, "Basic SFID", "Primary SFID" and "Secondary SFID" are not mentioned. Therefore, it is required to clarify "basic SFID DL/UL" of Figure. 3 in P802.16f/D1.This document lists all found inconsistencies and proposes fixes.
- (2) In line 13 page 13, "wmanIfClassifierRuleTable" is missing 'cmn'.
- (3) In line 3 page 14, "wmanIfCryptoSuiteIndex" is missing 'cmn'.
- (4) In line 22 page 14, correct errors as listed in Figure 2.

# 2. Proposed changes

#### [Motify text in line 29 page 10 as follows]

For example, Basic SFID UL mapped to Basic CID UL for SSs A1, B1, and X1 uses profile 1. Service flow attribute profiles can be added or deleted dynamically to meet different QoS demands from subscribers.

### [Motify text in line 13 page 13 as follows]

wmanlfClassifierRuleTablewmanlfCmnClassifierRuleTable is indexed by service flow ID and contains runtime classifier

### [Motify text in line 3 page 14 as follows]

This table is doubly indexed by ifIndex and wmanlfCryptoSuiteIndexwmanlfCmnCryptoSuiteIndex and contains

#### [Motify text in line 22 page 14 as follows]

wmanlfDcdBurstProfileTablewmanlfOfdmDcdBurstProfileTable - Each entry in this table contains the parameters needed for the UCDDCD burst profile as defined in section 11, Table 360 of [3].