Project	**IEEE 802.16 Broadband Wireless Access Working Group <http://ieee802.org/16>**
Title	**Clarify the EAP based Authentication Procedure**
Date Submitted	**2006-03-01**
Source(s)	Cancan Huang chuang@ztesandiego.com Hong Chen Jeff Qian Mary Chion Ling Xu Sean Cai ZTE
Re:	Contribution on comments to P802.16g-D1
Abstract	In this contribution, we clarify the EAP based authentication procedure in Figure 477
Purpose	Adoption

Clarification on EAP Based Authentication Procedure Diagram

Cancan Huang, Hong Chen, Mary Chion, Jeff Qian, Ling Xu, Sean Cai

1. Introduction

In Section 14.2.5.1 (EAP based authentication procedures), Figure 477, it is confused to use bi-direction arrow line to show interaction between 802.16 Entity and NCMS. It is hard to tell sequence of the call flow. Based on EAP specification, the C_SM_REQ is sent from NCMS to 802.16 Entity. The 802.16 Entity will send C_SM_RSP in response to it. It is better to separate them, which will make the flow more accurate.

2. Proposed Solution

This contribution clarifies the primitive diagrams by separating the C_SM_REQ/RSP primitive into two unidirectional arrow line.

3. Detail Text Changes

[*Modify section 14.2.5.1, replace Figure 477with the following figures]*]

14.2.5.1 EAP based authentication procedure

Figure 477 ---- EAP based Authentication Procedure

Figure 477—EAP based Authentication Procedure