

Project	<b>IEEE 802.16 Broadband Wireless Access Working Group</b> < <a href="http://ieee802.org/16">http://ieee802.org/16</a> >	
Title	RS Handover	
Date Submitted	2007-01-16	
Source(s)	Hang Zhang, Peiyong Zhu, Mo-Han Fong, Wen Tong, David Steer, Gamini Senarath, Derek Yu, Mark Naden, G.Q. Wang  Nortel 3500 Carling Avenue Ottawa, Ontario K2H 8E9	Voice: +1 613 7631315 <a href="mailto:wentong@nortel.com">[mailto:wentong@nortel.com]</a>  <a href="mailto:pyzhu@nortel.com">[mailto:pyzhu@nortel.com]</a>
Re:	A response to a Call for Technical Proposal, <a href="http://wirelessman.org/relay/docs/80216j-06_034.pdf">http://wirelessman.org/relay/docs/80216j-06_034.pdf</a>	
Abstract	In this contribution, we propose the additional handover operations for two modes of moving RS.	
Purpose	To incorporate the proposed text into the P802.16j Baseline Document (IEEE 802.16j-06/026r1)	
Notice	This document has been prepared to assist IEEE 802.16. It is offered as a basis for discussion and is not binding on the contributing individual(s) or organization(s). The material in this document is subject to change in form and content after further study. The contributor(s) reserve(s) the right to add, amend or withdraw material contained herein.	
Release	The contributor grants a free, irrevocable license to the IEEE to incorporate material contained in this contribution, and any modifications thereof, in the creation of an IEEE Standards publication; to copyright in the IEEE's name any IEEE Standards publication even though it may include portions of this contribution; and at the IEEE's sole discretion to permit others to reproduce in whole or in part the resulting IEEE Standards publication. The contributor also acknowledges and accepts that this contribution may be made public by IEEE 802.16.	
Patent Policy and Procedures	The contributor is familiar with the IEEE 802.16 Patent Policy and Procedures < <a href="http://ieee802.org/16/ipr/patents/policy.html">http://ieee802.org/16/ipr/patents/policy.html</a> >, including the statement "IEEE standards may include the known use of patent(s), including patent applications, provided the IEEE receives assurance from the patent holder or applicant with respect to patents essential for compliance with both mandatory and optional portions of the standard." Early disclosure to the Working Group of patent information that might be relevant to the standard is essential to reduce the possibility for delays in the development process and increase the likelihood that the draft publication will be approved for publication. Please notify the Chair < <a href="mailto:chair@wirelessman.org">mailto:chair@wirelessman.org</a> > as early as possible, in written or electronic form, if patented technology (or technology under patent application) might be incorporated into a draft standard being developed within the IEEE 802.16 Working Group. The Chair will disclose this notification via the IEEE 802.16 web site < <a href="http://ieee802.org/16/ipr/patents/notices">http://ieee802.org/16/ipr/patents/notices</a> >.	

# Relay Station Handover

Hang Zhang, Peiying Zhu, Mo-Han Fong, Wen Tong, David Steer, Gamini Senarath, Derek Yu, Mark Naden,  
G.Q. Wang

*Nortel*

## 1. Introduction

In contribution [1], two modes of moving RS operation are proposed: moving RS (MRS) mode and moving BS (MBS) mode. The handover procedures of these two modes are different. In this contribution, we propose the handover operation for these two modes of moving RS.

## 2. Proposal

### 2.1 Moving RS mode

For a moving RS in MRS mode, the RS shall perform handover procedure as follows:

- Handover initiation
  - At a time when a moving RS decides to perform handover, the RS send MOB\_MSHO-REQ to the associated serving MR-BS.
  - The MR-BS shall reply with MOB\_BS\_RSP to the RS.
  - For the case where preamble index is reassigned to the moving RS, the MR-BS sends MOB\_BSHO\_REQ message to each of MS served by this moving RS to force a handover of the impacted MS.
  - All impacted MS(s) shall reply with MOB\_HO\_IND messages to MR-BS
  - The moving RS shall simply relay those messages on the link between the MR-BS and the RS
- Handover
  - When a moving RS switches to the target station, the RS shall perform other handover processes for itself per 6.3.22.2 defined for post-handover processes
  - For the case where preamble index is reassigned to the moving RS, all the attached MS(s) perform other handover processes per 6.3.22.2 defined for post-handover processes. RS relays those messages on the link between the target MR-BS and the RS. For the case where preamble index is not reassigned to the moving RS, CID update procedure may be carried out using REG-RSP messaging.
- Location update for idle mode MS(s)

- When a moving RS enters into a different paging Zone, the moving RS may perform the location update on-behalf of idle MS(s) it serves to inform the MR-BS (thus the paging controller) the association of the MSs and the moving RS to the new paging zone

## 2.2 Moving BS mode

For a moving RS in moving BS mode, the RS shall perform handover per 6.3.22.2. After handover of the RS finishes, the RS shall facilitate the handover of its attached MS(s).

- If the RS have entered into new subnet, all served MSs' IP addresses need to be re-established. The IP re-establishment processes of MS(s) are the same as defined in the current standard. The RS, however, can encapsulate the IP address re-establishment related signaling of MS(s) into a single message called RS\_mobile\_IP\_re\_est-REQ message. This message is sent to the target MR-BS over a transport connection of the RS. The MR-BS uses RS\_mobile\_IP\_re\_est-RSP to encapsulate the IP address re-establishment related messages of MS(s) and transmit this message over a DL transport connection of this moving RS. An alternative solution is to dedicate a specific transport connection between MR-BS and moving RS to be used for relaying MSs' IP address re-establishment related messages.
- When a moving RS enters into a different paging Zone, the moving RS may perform the location update on-behalf of idle MS served to inform the MR-BS (thus the paging controller) the association of the MSs and the moving RS to the new paging zone
- Other processes of post handover shown in Figure 130b are not required

## 3. Proposed text change

+++++Start Text +++++

### 3.1 RS handover

*[Insert a new section 6.3.22.2]*

#### 6.3.22.2 RS handover

Two moving modes are defined for a moving RS: moving RS mode and moving BS mode. The handover procedures for these two modes are described in this section.

##### 6.3.22.2.1. Moving RS mode

For a moving RS in MRS mode, the RS shall perform handover procedure for as follows:

- Handover initiation
  - At the time when a moving RS decides to perform handover, the RS sends MOB\_MSHO-REQ to the associated serving MR-BS.
  - The MR-BS shall reply with MOB\_BS\_RSP to the RS.

- For the case where preamble index is reassigned to the moving RS, the MR-BS sends MOB\_BSHO\_REQ message to each of MS served by this moving RS to force a handover of the impacted MS.
- All impacted MSs shall reply with MOB\_IND messages to MR-BS
- The moving RS shall simply relay those messages on the link between the target MR-BS and the RS
- Handover
  - When a moving RS switches to the target station, the RS shall perform other handover processes for itself per 6.3.22.2 defined for post-handover processes
  - For the case where preamble index is reassigned to the moving RS, all the attached MS(s) perform other handover processes per 6.3.22.2 defined for post-handover processes. RS relays those messages on the link between the target MR-BS and the RS. For the case where preamble index is not reassigned to the moving RS, CID update procedure may be carried out using REG-RSP messaging.
- Location update for idle mode MS(s)
  - If a moving RS enters into a new paging zone, the RS shall perform the location update on-behalf of MS(s) in idle mode to inform the MR-BS (thus the paging controller) the association of the MSs and the moving RS to the new paging zone, using RS\_mobile\_info\_update-REQ message. MR-BS shall send RS\_mobile\_info\_update-RSP message to confirm the location update.

#### 6.3.22.2.2 Moving BS mode

For a moving RS in moving BS mode, the RS shall perform handover per 6.3.22.2. After handover of the RS finishes, the RS shall facilitate the MS(s) handover

- If the RS have entered into new subnet, all served MSs' IP addresses need to be re-established. The IP re-establishment processes of MS(s) are the same as defined in the current standard. The RS, however, can encapsulate the IP address re-establishment related messages of MS(s) into a single message called RS\_mobile\_IP\_re\_est-REQ message. This message shall be sent to the target MR-BS over a transport connection of the RS. The MR-BS shall use RS\_mobile\_IP\_re\_est-RSP to encapsulate the IP address re-establishment related messages of MS(s) and transmit this message over a DL transport connection of this moving RS.
- If a moving RS enters into a new paging zone, the RS shall perform the location update on-behalf of MS(s) in idle mode to inform the MR-BS (thus the paging controller) the association of the MSs and the moving RS to the new paging zone, using RS\_mobile\_info\_update-REQ message. MR-BS shall send RS\_mobile\_info\_update-RSP message to confirm the location update.
- Other processes of post handover shown in Figure 130b are not required

### 3.2 Message format for IP address re-establishment of MS(s) served by a moving RS during handover

A new MAC management messages are introduced for the purpose of IP address re-establishment of MS(s) served by a moving RS in MBS mode during handover.

*[Modify the last row in Table 14 in page 46 as follows]*

Type	Message name	Message description	Connection
<del>62-255-67</del>	<u>RS_mobile_IP_re_est-REQ</u>	<u>Encapsulation of IP address establishment related messages of MSs (used by RS)</u>	<u>UL transport connection of a moving RS in moving BS mode</u>
68	<u>RS_mobile_IP_re_est-RSP</u>	<u>Encapsulation of IP address establishment related messages of MSs (used by MRBS)</u>	<u>DL transport connection of a moving RS in moving BS mode</u>
69	<u>RS_mobile_info_update-REQ</u>	<u>Report of mobiles's information (used by RS)</u>	<u>UL basic connection of a RS</u>
70	<u>RS_mobile_info_update-RSP</u>	<u>Confirmation of reception of report of mobiles's information (used by MRBS)</u>	<u>DL basic connection of a RS</u>
<del>71-255</del>		<u>Reserved</u>	

*[Add new sections 6.3.2.3.62 and 6.3.2.3.63 after section 6.3.2.3.61 in page 172]*

#### 6.3.2.3.62 Mobile IP address re-establishment request message

This message is used for a RS to consolidate multiple MS IP address establishment related messages for sending to a MR-BS when IP address re-establishments for MSs are required. The message format is shown in Table xxx

Table XXX. RS mobile IP re-est request (RS\_mobile\_IP\_re\_est-REQ) message format.

Syntax	Size	Notes
<u>RS_mobile_IP_re_est-REQ format {</u>		
<u>Management message type = 67</u>	<u>8 bits</u>	
<u>Number of messages</u>	<u>4 bits</u>	
<u>For (i = 0; Number of messages; i++) {</u>		
<u>Length</u>	<u>8 bits</u>	<u>Indicates the length in bytes of each message in the body part</u>
<u>}</u>		
<u>Messages</u>	<u>Variable</u>	<u>IP protocol messages</u>
<u>}</u>		

#### 6.3.2.3.63 Mobile IP address re-establishment response message

This message is used for a MRBS to consolidate multiple MS IP address establishment related messages for sending to a moving RS in moving BS mode as a response to RS mobile IP re-est-REQ message when IP address re-establishments for MSs are required. The message format is shown in Table xxx

Table XXX. RS mobile IP re-est response (RS\_mobile\_IP\_re-est-RSP) message format.

Syntax	Size	Notes
RS_mobile_IP_re-est-RSP format {		
Management message type = 68	8 bits	
Number of messages	4 bits	
For (i = 0; Number of messages; i++) {		
Length	8 bits	Indicates the length in bytes of each message in the body part
}		
Messages	Variable	IP protocol messages
}		

### 3.3 Location update for idle MS(s) served

[Add new sections 6.3.2.3.64 and 6.3.2.3.65]

#### 6.3.2.3.64 Mobile Information update request message

This message is used for a RS to report any mobile related information to MR-BS.

This message can be used for a moving RS to report MAC addresses of idle MSs when a moving RS enters a new paging zone. The purpose of this is for paging and DL traffic routing to a MS which is in idle mode and connected to a moving RS. The message format is shown in Table xxx

Table XXX. RS mobile info update request (RS\_mobile\_info-REQ) message format.

Syntax	Size	Notes
RS_mobile_info update request format {		
Management message type = 69	8 bits	
Info_type	4 bits	0000: Idle MS MAC address 0001-1111: reserved
Transaction ID	4 bits	
If (Info_type == 0000) {		
Number of MAC addresses	4	Indication of number of MAC addresses included
For (i = 0; Number of addresses; i++) {		
MAC address	48	Idle MS MAC address
}		
}		
}		

#### 6.3.2.3.65 Mobile Information update response message

This message is used for a MR-BS to confirm the reception of RS mobile info update request message sent by a RS. The message format is shown in Table xxx

Table XXX. RS mobile info update response (RS mobile info- RSP) message format.

Syntax	Size	Notes
<u>RS mobile info update response format {</u>		
<u>Management message type = 69</u>	<u>8 bits</u>	
<u>Info type</u>	<u>4 bits</u>	<u>0000: Idle MS MAC address</u> <u>0001-1111: reserved</u>
<u>Transetion ID</u>	<u>4 bits</u>	
<u>}</u>		
<u>}</u>		

++++++End Text++++++

### Reference

[1] IEEE 802.16j-07/087 “Moving Relay Station Operation”, Jan.8, 2007