

IEEE P802.3bt D1.2 4P PoE 5th Task Force review comments

CI 33 SC 33.1.4.1 P 199 L 14 # 1
Darshan, Yair Microsemi
Comment Type ER Comment Status D Cabling
Missing Type 4 in:
Type 2 and Type 3 operation requires a 10 °C reduction in the maximum:
SuggestedRemedy
Change from:
Type 2 and Type 3 operation requires a 10 °C reduction in the maximum:
To:
Type 2 Type 3 and Type 4 operation requires a 10 °C reduction in the maximum:
Proposed Response Response Status W
PROPOSED ACCEPT.
EZ

CI 33 SC 33.2.7.4 P 245 L 19 # 2
Darshan, Yair Microsemi
Comment Type E Comment Status D Icon
"single-signature PD shall meet ICon-2P as specified in Table 33-11 item 4a."
Typo: It is Icont-2P_unb and not Icont-2P
SuggestedRemedy
Change to:
single-signature PD shall meet ICon-2P-UNB as specified in Table 33-11 item 4a.
Proposed Response Response Status W
PROPOSED ACCEPT IN PRINCIPLE.
Change to:
single-signature PD shall meet ICon-2P-unb as specified in Table 33-11 item 4a.

CI 33 SC 33.2.7 P 240 L 42 # 3
Darshan, Yair Microsemi
Comment Type E Comment Status D PSE Power
Table 33-11 item 4a, additional information.
1. It is 33.2.7.4.1 and not 33.2.7.4a
2. The additional information do not cover all the information needed for item 4a. It is 33.2.7.4 and 33.2.7.4.1
SuggestedRemedy
Table 33-11 item 4a, additional information.
Replace See 33.2.7.4a with: See 33.2.7.4 and 33.2.7.4.1
Proposed Response Response Status W
PROPOSED ACCEPT.

CI 33 SC 33.2.7.4 P 245 L 23 # 4
Darshan, Yair Microsemi
Comment Type E Comment Status D Icon
"In addition to ICon-2P and ICon-2P-UNB as specified in Table 33-11, the..."
Typo: It is Icont and not Icont-2P
SuggestedRemedy
Change from:
"In addition to ICon-2P and ICon-2P-UNB as specified in Table 33-11, the..."
To:
"In addition to ICon and ICon-2P-UNB as specified in Table 33-11, the..."
Proposed Response Response Status W
PROPOSED ACCEPT IN PRINCIPLE.

CI 33 SC 33.2.7 P 243 L 45 # 5
Darshan, Yair Microsemi
Comment Type E Comment Status X Pres: Yair4
Editor Notes on Page 243 lines 44-47 and page 244 lines 1-21 to change per page 5 of darshan_04_0915.pdf due to addressing the issues in D1.1 and D1.2.
SuggestedRemedy
Editor Notes on Page 243 lines 44-47 and page 244 lines 1-21 to change per page 5 per darshan_04_0915.pdf.
Proposed Response Response Status W
Wait for presentation

IEEE P802.3bt D1.2 4P PoE 5th Task Force review comments

Cl 33 SC 33.3.7.3 P 272 L 8 # 6
 Darshan, Yair Microsemi
 Comment Type E Comment Status D Editorial
 Typo in "value requirements are specified in 33.2.7.6..."
 It is 33.3.7.6.
 SuggestedRemedy
 Change 33.2.7.6 to 33.3.7.6.
 Proposed Response Response Status W
 PROPOSED ACCEPT.
 EZ

Cl 33 SC 33.3.7.6 P 275 L 1622 # 7
 Darshan, Yair Microsemi
 Comment Type E Comment Status X Cport
 This text applies to different scenarios and for easy reading each scenario may need to
 start in new row.
 SuggestedRemedy
 Change the editing from:
 Type 1, Type 2, and single-signature Type 3 PDs with classes 0 to 4 shall meet the
 requirement for Cport as defined in Table 33.18 item 9. Type 3 dual-signature PDs with
 class 0 to 4 shall meet the requirement for Cport as defined in Table 33.18 item 9 for each
 pairset. For class 5 and 6 single-signature PDs, if CPort_min >=10uf, transient behavior
 has no further requirements. For dual-signature class 5 PDs, this recommendation applies
 to each pairset. For class 7 and 8 single signature PDs, if CPort_min >=20uf, transient
 behavior has no further requirements. See 33.2.7.2 (TBD) or the transient conditions
 To:
 Type 1, Type 2, and single-signature Type 3 PDs with classes 0 to 4 shall meet the
 requirement for Cport as defined in Table 33.18 item 9.
 Type 3 dual-signature PDs with class 0 to 4 shall meet the requirement for Cport as
 defined in Table 33.18 item 9 for each pairset.
 For class 5 and 6 single-signature PDs, if CPort_min >=10uf, transient behavior has no
 further requirements.
 For class 5 and 6 dual-signature PDs, if CPort_min >=10uf for each pairset, transient
 behavior has no further requirements.
 For class 7 and 8 single signature PDs, if CPort_min >=20uf, transient behavior has no
 further requirements.
 See 33.2.7.2 (TBD) or the transient conditions
 Proposed Response Response Status W
 Task Force to discuss.

Cl 33 SC 33.3.7.10 P 276 L 40 # 8
 Darshan, Yair Microsemi
 Comment Type ER Comment Status D Editorial
 The text:
 See Annex 33A for design guide lines for meeting the above requirements.

 It should be Annex 33A.5 and not Annex A.
 SuggestedRemedy
 Change from:
 See Annex 33A for design guide lines for meeting the above requirements.
 To:
 See Annex 33A.5 for design guide lines for meeting the above requirements.

Proposed Response Response Status W
 PROPOSED ACCEPT.
 EZ

Cl 33 SC 33.2.5.6 P 232 L 44 # 9
 Darshan, Yair Microsemi
 Comment Type ER Comment Status D Editorial
 marked as YD_001_PSEP2P for Reference)
 Addressing the text: "(see 33.3.5.3 and Annex 33B)"
 We agree last meeting that:
 1. The Auto Class Annex will be named Annex C and not Annex 33B.
 2. The Annex 33B was reserved for PSE PI P2P unbalanced requirements WHICH ARE
 NORMATIVE so they cannot be combined with Annex 33A.
 See related comment for fixing the incorrect implementation of Annex 33B in a comment
 marked as YD_002_PSEP2P.

SuggestedRemedy
 Change from (see 33.3.5.3 and Annex 33B)to (see 33.3.5.3 and Annex 33C)
 [See also YD_002_PSEP2P that addresses other correction need to be made due to
 incorrect implementation of darshan_06_0715.pdf in
[http://www.ieee802.org/3/bt/public/jul15/darshan_06_0715-REV008.docx.](http://www.ieee802.org/3/bt/public/jul15/darshan_06_0715-REV008.docx)]
 Proposed Response Response Status W
 PROPOSED ACCEPT IN PRINCIPLE.
 Change from (see 33.3.5.3 and Annex 33B) to (see 33.3.5.3 and Annex 33C)
 EZ

IEEE P802.3bt D1.2 4P PoE 5th Task Force review comments

CI 33 SC 33.2.7 P 243 L 45 # 10
 Darshan, Yair Microsemi

Comment Type ER Comment Status D

The following text contains error:
 "1. lcont-2P and lpeak-2P need to be addressed for Extended power..."
 It is lcont-2P_unb and not lcont-2P.

SuggestedRemedy

Change to:
 "1. lcont-2P_unb and lpeak-2P need to be addressed for Extended power..."

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

This is only an editor's note, but...

Change to:
 "1. lcon-2P_unb and lpeak-2P need to be addressed for Extended power..."

EZ

CI 33 SC 33.2.8 P 251 L 47 # 11
 Darshan, Yair Microsemi

Comment Type ER Comment Status D Editorial

We already agreed in last meeting that Annex B is a normative annex and is used for PSE PI P2Punb requirements.

Annex C was agreed to be used for Autoclass.
 (See also YD_002_PSE_P2P that addresses other correction need to be made due to incorrect implementation of darshan_06_0715.pdf in http://www.ieee802.org/3/bt/public/jul15/darshan_06_0715-REV008.docx.)

SuggestedRemedy

Change "See Annex 33B for more information on how..."
 To "See Annex 33C for more information on how..."

Proposed Response Response Status W

PROPOSED ACCEPT.

EZ

CI 33 SC 33.3.7 P 270 L 24 # 12
 Darshan, Yair Microsemi

Comment Type T Comment Status D PD Power

Table 33-18 item 7 for Type 3 and 4: The parameter name "peak operating power, class 5":
 It is true for all classes above class 5 and not just class 5.

SuggestedRemedy

Change parameter name in Table 33-18 item 7 for Type 3 and 4:
 From:
 peak operating power, class 5
 To:
 peak operating power, class 5 to 8.

Proposed Response Response Status W

PROPOSED ACCEPT.

EZ

CI 33 SC 33.2.7 P 240 L 39 # 13
 Darshan, Yair Microsemi

Comment Type T Comment Status D PSE Power

1.To update TBDs for lcont-2P_unb min in Table 33-11 item 4a for classes 5 and 7.
 2. To update class 8 value from 0.931A to 0.926A due to the change of Pclass PD from 71.3W to 71W.
 See details on page 2 of darshan_04_0915.pdf.

SuggestedRemedy

Replace TBDs in Table 33-11 item 4a, lcont-2P_unb minimum value column:
 Class 5: Replace TBD with 0.536A
 Class 7: Replace TBD with 0.778A
 Class 8: Change from 0.931A to 0.926A

Proposed Response Response Status W

PROPOSED ACCEPT.

IEEE P802.3bt D1.2 4P PoE 5th Task Force review comments

CI 33 SC 33.2.7 P 241 L 34 # 14
Darshan, Yair Microsemi

Comment Type T Comment Status X Pres: Yair6

1. To update TBDs for ILIM-2P min in Table 33-11 item 9 classes 5 and 7.
See derivation in darshan_06_0915.pdf.

SuggestedRemedy

Table 33-11 item 9, ILIM-2P minimum value column:
Class 5: Replace TBD in ILIM-2P min with 0.551A
Class 7: Replace TBD in ILIM-2P min with 0.829A

Proposed Response Response Status W

Wait for presentation.

CI 33 SC 33A.6 P 331 L 21 # 15
Darshan, Yair Microsemi

Comment Type T Comment Status X Pres: Yair4

Table 33A.1 in draft D1.2 (will be Table 33B-1 in D1.3 due to wrong implementation of darshan_06_0715.pdf in http://www.ieee802.org/3/bt/public/jul15/darshan_06_0715-REV008.docx.)

1. To update values per changes made in D1.1.
2. To replace TBDs with numbers
3. To add two additional columns to support extended power mode.

SuggestedRemedy

1. Update TBDs in page 331 lines 20-26 Table 33B-1 (was Table 33A-1 in D1.2).
PSE Class=5,Rload_min=0.739,Rload_max=0.1562
PSE Class=6,Rload_min=0.635.
PSE Class=7,Rload_min=0.577,Rload_max=1.094
PSE Class=8,Rload_min=0.533,Rload_max=0.979
2. Modify the table to include two additional columns for Extended Power mode.
See updated details in page 3 of darshan_04_0915.pdf

Proposed Response Response Status W

Wait for presentation

CI 33 SC 33.2.7.4.1 P 246 L 21 # 16
Darshan, Yair Microsemi

Comment Type T Comment Status X Pres: Yair4

To update equation 33-4b to include classes 5 and 7.
See details in page 1 of darshan_04_0915.pdf.

SuggestedRemedy

1. Implement updates per page 1 of darshan_04_0915.pdf.
2. Remove Editor Note in page 246 line 37

Proposed Response Response Status W

Wait for presentation

CI 33 SC 33.2.7 P 241 L 38 # 17
Darshan, Yair Microsemi

Comment Type T Comment Status X Pres: Yair6

To update ILIM-2P min in Table 33-11 item 9 classes 6 and 8.
It reduces currents by about 15% due margins reduction that can be left to designer decision.

Reason for update:

In order to reduce currents, we utilized the fact that Ppeak_PD is lower now and we dont force Icut_max/Icon-2P_unb= about 1.15 as in 802.3at.
See derivation in darshan_06_0915.pdf.

SuggestedRemedy

Table 33-11 item 9, ILIM-2P minimum value column:
Class 6: Change from 0.817A to 0.691A.
Class 8: Change from 1.162A to 0.990A.

Proposed Response Response Status W

Wait for presentation

CI 33 SC 33.2.7 P 241 L 20 # 18
Darshan, Yair Microsemi

Comment Type T Comment Status X Pres: Unbalance

Table 33-11 item 7.
We need to update Kicut3 and Kicut4 to include the constants for class 5 and 7 otherwise they will create errors resulted with Icont-2P_unb doesnt equal to Icut_min.
See details in Darshan_07_0915.pdf.

SuggestedRemedy

See details in Darshan_07_0915.pdf for updating Table 33-11 item 7.

Proposed Response Response Status W

Wait for presentation

IEEE P802.3bt D1.2 4P PoE 5th Task Force review comments

Cl 33 SC 33.1.4.1 P 199 L 5 # 19
 Darshan, Yair Microsemi

Comment Type T Comment Status X Cabling

This is my response to comment #4 in D1.1 per Maintenance Request #1271, on behalf of GEOFF THOMPSON, GRACASI S.A./LINEAR TECHNOLOGY.

I was asked to review it and submit my response.

Due to the fact that part of the requested is already implemented in clause 33.1.4, I will address only the comment part that addresses clause 33.1.4.1

SuggestedRemedy

Replace lines 5-12 in page 199 clause 33.1.4.1 from:

"Type 1 power levels may be transmitted over all specified premises cabling that meets the requirements

specified in Table 33-1. Type 2 operation requires Class D, or better, cabling as specified in ISO/

IEC 11801:1995, with the additional requirement that channel DC loop resistance shall be 25 .. or less.

These requirements are also met by Category 5e or better cable and components as specified in ANSI/TIA-

568-C.2; or Category 5 cable and components as specified in ANSI/TIA/EIA-568-A. Type 3 and Type 4

operation requires Class D or better cabling as specified in ISO/IEC 11801:2002. These requirements are

also met by Category 5e or better cable and components as specified in ANSI/TIA-568-C.2."

To:

The supply of power over the data connection is intended to operate with no additional requirements to the cabling that is normally installed for data usage. This is approximately true but may require some further attention. Power at Type 1 power levels may be transmitted over all specified premises cabling without further restrictions. Higher power levels may require heavier gauge conductors than are found in Class C/Category 3 cabling and (more uncommonly) in some lighter gauge Class D or better cable. The requirements for Type 2 are met by Category 5 or better cable and components as specified in ANSI/TIA/EIA-568-A."

Proposed Response Response Status W

Task Force to discuss.

Cl 33 SC 33.2.4.6 P 218 L 7 # 20
 Darshan, Yair Microsemi

Comment Type T Comment Status D Editorial

In Draft D1.2 Icont-2P became Icont in the list at:

"except for ICon-2P, ILIM-2P, TLIM-2P, and PType (see Table 33-11),".

SuggestedRemedy

Change from:

"except for ICon-2P, ILIM-2P, TLIM-2P, and PType (see Table 33-11),"

to:

"except for ICon, ILIM-2P, TLIM-2P, and PType (see Table 33-11),"

Proposed Response Response Status W

PROPOSED ACCEPT.

EZ

Cl 33 SC 33.2.5 P 227 L 39 # 21
 Darshan, Yair Microsemi

Comment Type T Comment Status D PSE Powering

Per the Editor Note we need to allow at POWER-UP or POWER_ON state to turn OFF and back to ON a sigle pairset.

SuggestedRemedy

1. Add the following text after line 39:

Type 3 and Type 4 PSE that successfully detected valid signature over each pairset and powered up a Single Signature PD, may turn off one of the pairsets and turn it on gain during POWER_UP or POWER_ON states.

2. Remove Editor Note in lines 39-40.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

OBE by comment 35.

IEEE P802.3bt D1.2 4P PoE 5th Task Force review comments

Cl 33 SC 33.2.7 P 240 L 21 # 22
 Darshan, Yair Microsemi

Comment Type T Comment Status D PSE Power

Table 33-11 item 1a, Vport_PSE_diff (PSE Vdiff).

Background:

We have shown that PSE Vdiff max for a single port is 0.2mV maximum calculated at worst case and the spec were set to 2mV.

After additional research on multi-port systems we have found that the PSE Vdiff may reach to 6-8mV due to cross regulation effect of ports using shared power leads.

Two solutions were analyzed:

a) To specify PSE Vdiff=2mV as is today for a single port and let system designer to figure out how to make sure that in multiport operation the spec will still be met.

This solution was rejected by few system vendors.

b) To specify PSE Vdiff=10mV while keeping system Vdiff=60mV as it was before which move some burden on PD to use 50mV maximum when diodes are used in the PD, instead of 58mV as it is today.

This solution looks better.

-It will keep the same maximum pair current.

-It will not affect PSE MPS solutions.

-It will add tolerable burden on PD by making sure that diode Vdiff is 50mV max and not 58mV.

- The total system E2EP2P_lunb stays the same

SuggestedRemedy

1. To change Table 33-11 item 1a from 2mV to 10mV.

2. To update all relevant PSE PI and PD PI numbers that will be affected by this change.

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 33 SC 33.2.7.6 P 248 L 18 # 23
 Darshan, Yair Microsemi

Comment Type T Comment Status D PSE Power

Referring to the text:

The ICUT-2P threshold may equal the IPeak-2P value determined by Equation (33-4).

When we changed Ppeak_PD/Pclass_PD ratio from 1.11 to 1.05 to reduce maximum ipeak current, it caused Ipeak-2P to be close to Icont-2P_unb which required tighter accuracy for setting Icut-2P threshold.

As a result, for allowing design flexibility and cost effective solutions we can allow Icut-2P threshold to be equal or higher that Ipeak-2P due to the fact that removing power due to crossing Icut-2P is not mandatory.

As a result we need to explicitly clarify and allow the following:

a) The ICUT-2P threshold may equal or greater (not just equal) the IPeak-2P value determined by Equation (33-4).

b) ICUT-2P threshold must be below ILIM_MIN (as usual).

c) The value of Icut_2P_max shall not exceed $1.15 \cdot I_{con-2P_unb}$

d) Any combinations of the above will not cause violating PSE maximum power allowed.

SuggestedRemedy

To change:

The ICUT-2P threshold may equal the IPeak-2P value determined by Equation (33-4).

To:

The ICUT-2P threshold may equal or greater than the IPeak-2P value determined by Equation (33-4). The Icut-2P threshold needs to be below ILIM_MIN as described by Figure 33-14.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

To change:

The ICUT-2P threshold may equal the IPeak-2P value determined by Equation (33-4).

To:

The ICUT-2P threshold shall be equal to or greater than the Ipeak-2P value determined by Equation (33-4). The Icut-2P threshold shall be below ILIM_MIN as described by Figure 33-14.

IEEE P802.3bt D1.2 4P PoE 5th Task Force review comments

Cl 33 SC 33.2.7.7. P 249 L 15 # 24
 Darshan, Yair Microsemi

Comment Type T Comment Status X Pres: Yair2

Figure 33-14.
 We need to capture Type 1 and Type 2 requirements and Type 3 and Type 4 requirements.
 See proposed solution in darshan_02_0915.pdf

SuggestedRemedy

To implement darshan_02_0915.pdf.

Proposed Response Response Status W

Wait for presentation

Cl 33 SC 33.2.7.7 P 248 L 33 # 25
 Darshan, Yair Microsemi

Comment Type T Comment Status D PSE Power

After line 33 which is the end of:
 "The maximum value of ILIM-2P is the PSE upperbound template described by Equation (33-6) and Figure 33-14."

We need to mention that ILIM-2P minimum in Table 33-11 item 9 include the effects of end to end pair to pair current/resistance unbalance.

SuggestedRemedy

1. Add after the above text:
 ILIM-2P minimum value in Table 33-11 item 9 for class 5 and above includes E2EP2PUnb effect.
2. Remove note #5 at the Editor Note section in page 244 line 13.

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 33 SC 33.2.7.5 P 247 L 14 # 26
 Darshan, Yair Microsemi

Comment Type T Comment Status D PSE Inrush

Addressing the text:
 For Type 1 PSE, measurement of minimum Inrush-2P requirement to be taken after 1 ms to allow startup transients. A Type 2 PSE that uses 1-Event Physical Layer classification, and requires the 1ms settling time, shall power up a class 4 PD as if it used 2Multiple-Event Physical Layer classification.

1. Measuring after 1msec to account for transients is true for:
 - a) all PSE Types and not just Type 1.
 - b) Not clear how the rest of the text addressing classification is related to the inrush requirements.

SuggestedRemedy

1. Change the first sentence from:
 For Type 1 PSE, measurement of minimum Inrush-2P requirement to be taken after 1 ms to allow startup transients.
 To:
 Measurement of minimum Inrush-2P requirement to be taken after 1 ms to allow startup transients.
2. Delete:
 A Type 2 PSE that uses 1-Event Physical Layer classification, and requires the 1ms settling time, shall power up a class 4 PD as if it used 2Multiple-Event Physical Layer classification. OR explain why we need it. As it is worded and combined with the first sentence, it is not clear the intent and the need.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

We need to extend this to all PSEs that use single event.

Task Force to discuss.

IEEE P802.3bt D1.2 4P PoE 5th Task Force review comments

Cl 33 SC 33.2.7.11a P 251 L 13 # 27
 Darshan, Yair Microsemi
 Comment Type T Comment Status D PSE Power
 The text:
 Type 4 PSEs shall not source more power than PType max as specified in Table 33-11 calculated with any sliding window with a width of 1 (TBD) second.

 For design flexibility we can allow 1sec window to 5sec which is much less than 60sec and get rid of the TBD
 SuggestedRemedy
 Replace TBD with 1 to 5 seconds.
 Proposed Response Response Status W
 PROPOSED ACCEPT.

Cl 33 SC 33A.5 P 330 L 12 # 28
 Darshan, Yair Microsemi
 Comment Type T Comment Status X Pres: YairB
 1. The constants in Annex 33A.5 needs to be replaced with numbers.
 2. In addition some of existing constants need to be slightly modified due to the changes made to D1.1.
 SuggestedRemedy
 Propose to implement darshan_08_0915.pdf
 Proposed Response Response Status W
 Wait for presentation

Cl 33 SC 33.3.7.3 P 271 L 41 # 29
 Darshan, Yair Microsemi
 Comment Type TR Comment Status D PD Inrush
 The objective of this comment is to restore some of the text used in IEEE802.3-2012 clause 33.3.7.3 in IEEE802.3bt clause 33.3.7.3 (same location) lines 39-41.
 The reason for text changes in 802.3bt was the concern that PD vendors will consume power above type 1 power while PD is still in POWER-UP mode which will cause unsuccessful startup.
 It will be shown that the new version in 802.3bt:
 1.Includes incorrect description of linrush process ending point while in 2012 version the text describing the ending point is correct.
 2.The concern was already resolved in existing text in two locations

The text in the PD spec in 802.3bt clause 33.3.7.3 page 271 lines 39-50 separated to 4 parts e.g. [Part A]:
 33.3.7.3 Input inrush current
 [Part A] Inrush current per pairset is drawn beginning with the application of input voltage at the pairset compliant with Vport_PD-2P requirements as defined in Table 33-18, [Part B] and ending before TInrush-2P min per Table 33-11.
 [Part C] After TInrush-2P min, the PD shall meet PClass_PD as specified in Table 33-18.

Part D] Type 2, Type 3 and Type 4 PDs with pse_power_leveltype state variable set to 2, 3 and 4 respectively prior to power-on shall behave like a Type 1 PD for at least Tdelay-2P min. Tdelay-2P for each pairset starts when VPD-2P crosses the PD power supply turn on voltage, VOn_PD. This delay is required so that the Type 2, Type3 and Type 4 PD does not enter a high power state before the PSE has had time to switch current limits on each pairset from lInrush-2P to lLIM-2P.

[Part A] is correct description of the starting point of linrush process in the PD.

[Part B] is incorrect description of the ending point of linrush process in the PD. The end point of inrush process depends only on PD physics and not anything else e.g. PSE linrush timer.

It is true that Inrush need to be ended before TInrush-2P min per Table 33-11 but it needs to be in separate sentence and not as part of the description of the end point of the Inrush process.

The end point of the inrush process can be only when Cport is get to steady state by having Cport to be charged to 99% of its final value.

The end point and the requirements for the linrush duration are described accurately in IEEE802.3-2012 version:

"and ending when CPort is charged to 99 % of its final value. This period should be less than TInrush min per Table 33-11."

[Part C] This part resolves the concern by requiring PD to meet PClass_PD as specified in Table 33-18 only after TInrush-2P min.

[Part D] This part also resolves the concern for Type 2 and above by waiting Tdelay before PD can consume more than Type 1 power.

Summary: The only problem with the current text of 802.3bt is the mixing between the

IEEE P802.3bt D1.2 4P PoE 5th Task Force review comments

Inrush end point process description and the requirement that the process will be ended within Tinrush minimum.

See detailed analysis in darshan_01_0915.pdf, titled: "Only PD affects PD POWERUP Tinrush max (Not the PSE Tinrush Timer).

SuggestedRemedy

1) Change lines 26-27 from:
 33.3.7.3 Input inrush current
 Inrush current per pairset is drawn beginning with the application of input voltage at the pairset compliant with Vport_PD-2P requirements as defined in Table 33-18, and ending before Tinrush-2P min per Table 33-11.
 After Tinrush-2P min, the PD shall meet PClass_PD as specified in Table 33-18.

To:
 Inrush current is drawn during the startup period beginning with the application of input voltage at the PI compliant with VPort_PD-2P requirements as defined in Table 33-18, and ending when CPort has reached a steady state and is charged to 99 % of its final value. This period shall be less than Tinrush min per Table 33-11.
 After Tinrush-2P min, the PD shall meet PClass_PD as specified in Table 33-18.

(2) To consider to add the following note after line 50 that address the concerns in details and supply design guide lines.
 Note: For successful startup, a PSE supplying linrush-2P minimum value and a PD not drawing more than Type 1 maximum DC current results in stable voltage ramping across the PD input capacitor which is important for successful POWER UP. In addition, Cport value and PD load current may be time dependent. As a result PD implementers need to ensure that for any combinations of Cport and Type 1 maximum DC current during POWERUP, the PD inrush period does not exceed 50msec and that higher PD load power is used only after Tdelay.

Proposed Response *Response Status* **W**

PROPOSED ACCEPT IN PRINCIPLE.

Accept changes in suggested remedy for (1).

Cl **33** *SC* **33.1.4** *P* **198** *L* **29** # **30**
 Darshan, Yair Microsemi

Comment Type **TR** *Comment Status* **D** *Cabling*

Table 33-1, Cable Type for Type 3 and 4 systems.
 If we agree that we want to work with cable instalations that were specified for Type 2 with Type 3 and 4 systems then we need to use Class D (ISO/IEC 11801:1995) for Type 3 and 4 as well.

SuggestedRemedy

1. Change Minimum Cabling Type for Type 3 and 4 to Class D (ISO/IEC 11801:2002) or

Cabling experts to explain the differences between Class D (ISO/IEC 11801:2002) and Class D (ISO/IEC 11801:1995) for group to decide.

Proposed Response *Response Status* **W**

PROPOSED ACCEPT IN PRINCIPLE.

OBE by comment 43

IEEE P802.3bt D1.2 4P PoE 5th Task Force review comments

Cl 33 SC 33A.6 P 330 L 21 # 31
 Darshan, Yair Microsemi

Comment Type TR Comment Status D Annex

Marked for reference as YD_002_PSEP2P)

In D1.1 we have approved darshan_06_0715.pdf in
http://www.ieee802.org/3/bt/public/jul15/darshan_06_0715-REV008.docx.
 It was requested specifically to use Annex B (and not Annex C and not Annex A) to the
 PSE PI material in 33.2.7.4.1 and 33.2.7.4.2 that links to a Normative Annex Named Annex
 B in the above link.
 Currently the editor named the original Annex B as Annex 33A.6 to Annex 33A.10 which is
 informative Annex and the intent was that this part will be separate NORMATIVE Annex B.
 In addition It is not clear that all parts of original Annex B that are now Annex 33A.6 to
 Annex 33A.10 are related to each other as in original Annex B and not independent parts
 We need to implement the relevant comment from D1.1 and others as approved.

Summary:

PSE PI Material from the above link is Normative Annex B.
 The Autoclass material is Annex C.

The following remedy is identical to adopt Annex B in the above approved document while
 correcting the relevant instances were Annex A, B and C are mentioned.

SuggestedRemedy

Make the following changes without editorial licensing to do otherwise:

1. In Annex 33A.6 page 330 line 21: Change title to: Annex 33B [Normative]PSE PI pair-to-pair resistance/current unbalance.
 - 1.1 In page 330 line 27: Change table Yuval_1 to Table 33B-1.
 - 1.2 In page 330 line 28: Change <> to Annex F.
 - 1.3 In page 330 line 51: Change Figure number from 33A-4 to 33B-1.
 - 1.4 In page 331 line 17: Change Table 33A-1 to Table 33B-1
2. In Annex 33A.7 page 331 line 35: Change title to: 33B.1 direct measurements of Rpse_max and Rpse_min
 - 2.1 in page 331 line 43: Change from 33A.8 and 33A.9 to 33B.2 and 33B.3
 - 2.1 in page 332 line 17: Change Figure number from 33A-5 to 33B-2.
3. in Annex 33A.8 page 332 line 21: Change title to: 33B.2 Effective Resistance Measurement Method by measurement of current unbalance under worst case pair-to-pair load conditions
 - 3.1 in page 332 line 41: Change Figure number from 33A-6 to 33B-3.
 - 3.2 in page 333 line 17: Change from 33A.9 to 33B.3
4. in Annex 33A.9 page 333 line 20: Change title to: 33B.3 Current Unbalance Measurement Method
 - 4.1 in page 333 line 22: change Table 33A-1 TO 33B-1
 - 4.2 in page 333 line 24: change Figure 33A-7 to 33B-4.

- 4.3 in page 333 line 41: change Figure 33A-7 to 33B-4.
5. in Annex 33A.10 page 334 line 9: Change title to: 33B.4 Channel resistance with less than 0.1 ohm

6: Add Annex F (informative) - Derivation of Rload_max and Rload_min.
 Editor Note (to be removed prior to publication): To consider the value of adding informative Annex F to present Rload_max and Rload_min equation derivation and values.

7: in Annex 33B page 335 line 2: Change to Annex C.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Make changes in suggested remedy with editorial liscense to combine with other accepted comments (fixing table and figure numbers, etc.).

Cl 33 SC 33.2.7.4.1 P 246 L 15 # 32
 Darshan, Yair Microsemi

Comment Type TR Comment Status D Editorial

See related comment YD_002_PSEP2P.

"For channels with common mode pair resistance lower than 0.1 ..., see guidelines in Annex 33A."

The relevant material in Annex 33A (from 33A.6 to 33A.10) is NORMATIVE and it was originally named Annex 33B. see seperate comment on Annex 33B ((MARKED FOR REFERENCE AS YD_002_PSEP2P) that was not implement correctly per the approved documents from July 2015)

Therefore:

1. the word guidelines not to be used.
2. Replace reference from Annex 33A to Annex 33B.

SuggestedRemedy

replace:

For channels with common mode pair resistance lower than 0.1 ..., see guidelines in Annex 33A."

With:

For channels with common mode pair resistance lower than 0.1 ..., see Annex 33B."

Proposed Response Response Status W

PROPOSED ACCEPT.

IEEE P802.3bt D1.2 4P PoE 5th Task Force review comments

Cl 33 SC 33.2.7.4 P 245 L 49 # 33
 Darshan, Yair Microsemi

Comment Type TR Comment Status X Pres: Yair 4

Equation 33-4a (the equation that describes K) need to be updated per class 5 and 7 and not just class 6 and 8 as it is now.
 It is in line with all updates made for PSE/PD P2P_Runb for better accuracy due to the fact that unbalance parameters are changed as function of current.

SuggestedRemedy

Implement the changes proposed in page 4 of darshan_04_09.pdf

Proposed Response Response Status W

Wait for presentation

Cl 33 SC 33.3.7.10 P 276 L 38 # 34
 Darshan, Yair Microsemi

Comment Type TR Comment Status D PD Power

Referring to the text:
 All Class 5 and higher PDs shall not exceed I_{con-2P-unb} (Table 33–11, item 4a) on either pairset when tested according to section 33.3.7.10.1.

1. PDs need to meet I_{con-2P-unb} for all classes above class 5 including for extended power mode.
2. In addition I_{peak-2P} need to be met for extended power mode as well. Meeting (1) ensures meeting (2) as regard to E2EP2PRunb effect.

SuggestedRemedy

1. Change from:
 All Class 5 and higher PDs shall not exceed I_{con-2P-unb} (Table 33–11, item 4a) on either pairset when tested according to section 33.3.7.10.1.

To:
 All Class 5 and higher PDs operating in non extended power mode or extended power mode, shall not exceed I_{con-2P-unb} (Table 33–11, item 4a) on either pairset when tested according to section 33.3.7.10.1.

2. After this text, to Add Editor Note:
 Editor Note: To update R_{min}/R_{max} and test setups for PD PI for meeting I_{cont-2P-unb} and I_{peak-2P} when PD is using extended power mode

Proposed Response Response Status W

PROPOSED REJECT.

Extended power is not mentioned anywhere in the standard. Also, the change does not add anything as all Class 5 and higher PDs includes those using extended power.

Cl 33 SC 33.2.5 P 227 L 37 # 35
 Darshan, Yair Microsemi

Comment Type TR Comment Status D PSE Powering

Addressing the text and the Editor Note following this text:
 In any operational state, the PSE shall not apply operating power to the PI a pairset until the PSE has successfully detected a valid signature over that pairset.

Editor's Note: The above sentence needs to be addressed as it forbids turning off and on a single pairset when connected to a SS class 0-4 PD.

We need to allow turning on and off a single pairset when connected to single signature PD for all classes.

SuggestedRemedy

1. To add the following text after line 38:
 Type 3 and Type 4 PSE that successfully detected valid signature over each pairset of a single signature PD, may turn off one of the pairsets and turn it on gain during POWER_UP or POWER_ON states.
2. If this comment accepted, to remove editor note in lines 38-40.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Remove editor's note.

The power on part is covered in section 33.2.7.1. The power up part should be addressed in the appropriate section.

IEEE P802.3bt D1.2 4P PoE 5th Task Force review comments

CI 33 SC 33.2.7.7 P 248 L 26 # 36
 Darshan, Yair Microsemi

Comment Type TR Comment Status X PSE Power

Referring to the text:
 When connected to a single signature PD, a Type 3 or Type 4 PSE should (TBD) remove power from both pairsets before the current exceeds the "PSE upperbound template" on either pairset.

 The above text meant to protect single signature classes 6 and up PDs from having all the current flowing over one pairset when the other pairset is about to cross the upperbound template of figure 33-14.

The TBD need to be replaced with text that reflects it.

SuggestedRemedy

Alternative 1:

Change from:

When connected to a single signature PD, a Type 3 or Type 4 PSE should (TBD) remove power from both pairsets before the current exceeds the "PSE upperbound template" on either pairset.

To:

When connected to above class 5 single signature PD, a Type 3 or Type 4 PSE should remove power from both pairsets before the current exceeds the "PSE upperbound template" on either pairset.

Alternative 2:

Remove the above text ("When connected to a single signature PD, a Type 3 or Type 4 PSE should (TBD) remove power from both pairsets before the current exceeds the "PSE upperbound template" on either pairset.")

Due to the fact that the text in lines 24-26 covers already what we want and shown here below for reference :

"A PSE may remove power from the PI if the PI current meets or exceeds the "PSE lowerbound template" in Figure 33-14. Power shall be removed from the a pairset PI of a PSE before the pairset PI current exceeds the "PSE upperbound template" in Figure 33-14."

So if the current over a pairset is about to cross the upperbound and as a result power was disconnected from that pair, the other pair will be overloaded and disconnected as well due its own protections.

Proposed Response Response Status W

Task Force to discuss.

CI 33 SC 33.2.7.7 P 249 L 43 # 37
 Darshan, Yair Microsemi

Comment Type TR Comment Status X Pres: Lennart2

In Equation 33-7 there is a TBD that can be replaced with parametric values. This part addresses the lowerbound template for the time point $t \geq T_{cut-2P}$ min. The value of this it has to be the value of 2P current without the effect of unbalance and up to $I_{cont-2P_unb}$ which is the maximum possible DC current over the pair including E2EP2P_{runb} effect.

In other words:

For Type 3 and 4 classes 5-8: The value is $0.5 * P_{class} / V_{port_PSE}$ to I_{con-2P_unb} .

SuggestedRemedy

1. Replace the entire row of the TBD in equation 33-7 to two separate rows:

Row #3: $0.5 * P_{class} / V_{port_PSE} - 2P$ to I_{con-2P_unb} for $t \geq T_{cut-2Pmin}$ and for classes 5-8 operating over four pairs.

Row #4: $0.5 * P_{class} / V_{port_PSE} - 2P$ for $t \geq T_{cut-2Pmin}$ and for classes 0-4 operating over two pairs.

2. Add after line 3 page 50:

I_{con-2P_unb} is specified in Table 33-11.

Proposed Response Response Status W

Wait for Lennart's presentations

CI 33 SC 33.3.1 P 255 L 43 # 38
 Darshan, Yair Microsemi

Comment Type TR Comment Status D Editorial

It is important to emphasis that PDs that are not implemented to be insensitive to polarity, are specifically not allowed by this standard. (We used this concept already in lines 47-48).

SuggestedRemedy

Add the following text after line 43 in page 255:

PDs that are not implemented to be insensitive to power supply polarity are specifically not allowed by this standard.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

OBE by comment 119.

EZ

IEEE P802.3bt D1.2 4P PoE 5th Task Force review comments

CI 33 SC 33.3.7.6 P 275 L 29 # 39
 Darshan, Yair Microsemi

Comment Type TR Comment Status X PD Power

There is some confusion in this text (lines 28-29):
 - A Type 1 PD input current shall not exceed the PD upperbound template (see Figure 33-18) after TLIM min (see Table 33-11 for a Type 1 PSE)

 The text refer to Figure 33-18 which specifies Tcut_min but talks about the current not to be exceed after Tlim_min so is it Tcut_min or Tlim_min?
 I believe that it should be Tcut_min both in the text and in Figure 33-18 due to the fact that It is related to Figure 33-18 that talks about not crossing Ppeak_PD which is the overload condition for 50msec.

SuggestedRemedy

I suggest changing from Tlim_min to Tcut_min in line 29 to sync with Figure 33-18.
 To be discussed by the group.

Proposed Response Response Status W

Task Force to discuss

CI 33 SC 33.2.7.4.2 P 246 L 41 # 40
 Darshan, Yair Microsemi

Comment Type TR Comment Status D Editorial

"See Annex 33A"

 The relevant material in Annex 33A (from 33A.6 to 33A.10) is NORMATIVE and it was originally named Annex 33B. see seperate comment on Annex 33B ((MARKED FOR REFERENCE AS YD_002_PSEP2P) that was not implement correctly per the approved documents from July 2015)
 Therefore:
 Aafter implementing YD_002_PSEP2P, change from Annex 33A to Annex 33B.

SuggestedRemedy

replace:
 See Annex 33A.

With:
 See Annex 33B.

Proposed Response Response Status W

PROPOSED ACCEPT.

EZ

CI 33 SC 33.3.7.3 P 90 L 43 # 41
 Darshan, Yair Microsemi

Comment Type TR Comment Status X Pres: Yair3

The following comment addresses linrush in Table 33-11 item 5a and PD Cport max to be supported by PSE linrush. Since both parameters are tied together, they are addressed at the same comment.
 See details in darshan_03_0915.pdf titled: Type 3 and 4 linrush for proposed solution that is a compromise for moving the standard forward.

SuggestedRemedy

See details in darshan_03_0915.pdf.

Proposed Response Response Status W

Wait for presentation.

CI 33 SC 33.2.7 P 243 L 45 # 42
 Darshan, Yair Microsemi

Comment Type ER Comment Status X Pres: Yair4

There are list of editor notes on page 243-244 that need to be updated per the progress made in D1.1 and the possible acceptance of comments in D1.2.
 See the proposed updates for Editor Notes in page 243-244 in darshan_04_0915.pdf page 5.

SuggestedRemedy

In case updates proposed by darshan_04_0915.pdf pages 1-4 will be accepted, to update Editor's Notes in page 243-244 per darshan_04_0915.pdf page 5.

Proposed Response Response Status W

Wait for presentation

IEEE P802.3bt D1.2 4P PoE 5th Task Force review comments

Cl 33 *SC* 33.1.4 *P* 198 *L* 26 # 43

Maguire, Valerie Siemon

Comment Type **ER** *Comment Status* **D** *Cabling*

Missing TIA reference in 4 locations in Table 33-1.

SuggestedRemedy

For Type 1, change,

"Class D recommended"

to,

"Class D or Category 5 recommended"

For Type 2, change,

"Class D (ISO/IEC 11801:1995)"

to,

"Class D (ISO/IEC 11801:1995) or Category 5 (ANSI/EIA/TIA-568-A:1995)"

For Type 3, change

"Class D (ISO/IEC 11801:2002)"

to,

"Class D (ISO/IEC 11801:2002) or Category 5e (ANSI/TIA-568-B.2:2001)"

For Type 4, change

"Class D (ISO/IEC 11801:2002)"

to,

"Class D (ISO/IEC 11801:2002) or Category 5e (ANSI/TIA-568-B.2:2001)"

Proposed Response *Response Status* **W**

PROPOSED ACCEPT.

See comment 30.

Cl 33 *SC* 33.1.1 *P* 196 *L* 6 # 44

Maguire, Valerie Siemon

Comment Type **T** *Comment Status* **D** *Cabling*

Missing TIA reference.

SuggestedRemedy

Change,

"Type 3 operation requires ISO/IEC 11801:2002 Class D or better cabling"

to,

"Type 3 operation requires ISO/IEC 11801:2002 Class D. ANSI/TIA-568-C.2 Category 5e, or better cabling"

Proposed Response *Response Status* **W**

PROPOSED ACCEPT.

EZ

Cl 33 *SC* 33.2.5.4 *P* 231 *L* 33 # 45

Bennett, Ken Sifos Technologies, In

Comment Type **E** *Comment Status* **D** *Editorial*

The word "tolerance" is referenced in the text: "but one or both of the offset tolerances are exceeded", however it has been removed from the table.

SuggestedRemedy

Change "offset tolerances" to "offsets"

Proposed Response *Response Status* **W**

PROPOSED ACCEPT.

EZ

IEEE P802.3bt D1.2 4P PoE 5th Task Force review comments

CI 33 SC 33.2.7 P 240 L 34 # 46
 Bennett, Ken Sifos Technologies, In

Comment Type E Comment Status D Editorial

Table 33-11 item 4, parameter column, states: "Continuous output current capability in POWER_ON state over both pairsets". In the info section, 33.2.7.4, it is referenced as the "total" current and has the information about the pairsets.

The parameter description would be clearer and simpler if it was referred to as the "Continuous total current" instead of using "over both pairsets".

SuggestedRemedy

Change to:
 "Continuous total output current capability in POWER_ON state."

Proposed Response Response Status W

PROPOSED ACCEPT.

EZ

CI 33 SC 33.2.7 P 240 L 39 # 47
 Bennett, Ken Sifos Technologies, In

Comment Type E Comment Status D Editorial

Item 4a in table 33-11 shows "E2ERunb" which doesn't match "E2EP2PRunb" used elsewhere. The suggested remedy makes them the same.

(Alternatively, given that it's defined, the symbol "E2EP2PRunb" could be simplified.)

SuggestedRemedy

Change entries in item 4a, table 33-11, from:
 "E2ERunb" to "E2EP2PRunb"

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

OBE by comment 210

EZ

CI 33 SC 33.3.4 P 262 L 6 # 48
 Bennett, Ken Sifos Technologies, In

Comment Type E Comment Status D LLDP

"LLDP variable PD 4P-ID" should be "LLDPDU variable.." or "TLV variable..".

SuggestedRemedy

Change "LLDP" to "TLV".

Proposed Response Response Status W

PROPOSED ACCEPT.

CI 33 SC 33.2.7.4 P 245 L 22 # 49
 Bennett, Ken Sifos Technologies, In

Comment Type T Comment Status D Icon

The statement:

"Icon-2P_unb is the maximum current the PSE is required to support..." should say:

"Icon-2P_unb is the minimum current the PSE is required to support..."

SuggestedRemedy

Change the word "maximum" to "minimum".

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

CI 33 SC 33.3.7 P 269 L 35 # 50
 Bennett, Ken Sifos Technologies, In

Comment Type T Comment Status X PD Classification

PClass is defined as a total port power and is described in Equation 33-3 using the PD Classification PClass_PD and the channel loss.

The descriptions for dual-signature PD's use PClass_PD per pairset, and different classes are allowed per pairset.

The suggestion is one possible approach to remedy this problem.

SuggestedRemedy

Create new dual signature parameters PClassDS_alta and PClassDS_altb, where PClass_PD = PClassDS_alta + PClassDS_altb. Add text in 33.3.7.2 stating that single-signature rules shall apply to each pairset in dual signature PDs.

Proposed Response Response Status W

Task Force to discuss.

IEEE P802.3bt D1.2 4P PoE 5th Task Force review comments

CI 33 SC 33.3.7 P 269 L 35 # 51
 Bennett, Ken Sifos Technologies, In

Comment Type TR Comment Status X PD Power

In item 4 of table 33-18 the PClass_PD parameter description has changed from "input average power" to "input available average power". The values for it are in the MAX column. It seems like the values for it should be in the MIN column, because it is a minimum "available" power under worst case conditions.

The pre-existing text in the item 4 info reference, 33.3.7.2, defines PClass_PD as the "maximum input power", which does not match either the pre-existing nor the modified PClass_PD parameter description in table 33-18.

There is an underlying problem, which is that PClass_PD, which is a power classification level, is shown as a Parameter in table 33-18, with a range within each class.

It would be much clearer to present this using the same method that's used in the PSE section for PClass, which specifies values for each class in a separate table (33-7), and uses "PClass" in the MIN/MAX columns of table 33-11.

The suggested remedy would not change the content or intent of the pre-existing information text in 33.3.7.2.

SuggestedRemedy

- 1) Incorporate PClass_PD levels into table 33-16a.
- 2) Change item 4 to a single row with the following items: Parameter="Input Average Power"; Symbol="Pport_PD"; and MAX="PClass_PD".
- 3) Adjust references as necessary

(See bennett_PClass_PD.pdf)

Proposed Response Response Status W
 Task Force to discuss

CI 33 SC 33.3.5.2.1 P 267 L 15 # 52
 Beia, Christian STMicroelectronics

Comment Type TR Comment Status D PD Classification

Table 33-17
 The PD long first class event spec introduces a big burden for PD timing accuracy, which can be relaxed if the PSE was able to better control the length of the long first class event. This should not add complexity to the PSE since its clock is typically more accurate than the PD one.

SuggestedRemedy

Change Table 33-17 item7, TLCF_PD max to 86.5
 Leave 75.5 as min

Proposed Response Response Status W
 PROPOSED ACCEPT IN PRINCIPLE.

OBE by 239

CI 33 SC 33.2.6.3 P 238 L 42 # 53
 Beia, Christian STMicroelectronics

Comment Type TR Comment Status D PSE Classification

Table 33-10
 The long first class Event timing for the PSE can be easily set to a tighter range with no impact on PSE complexity, since the accuracy of PSE clock already allows it. This is helpful for the PD timings which can be relaxed, since this is the more restrictive timing requirement for the PD.

SuggestedRemedy

Change Table 33-10 item 12 TLCF to 87.5 Min
 Leave 100 as Max

Proposed Response Response Status W
 PROPOSED ACCEPT IN PRINCIPLE.

See comment 240.

Make min 88. Max ?

IEEE P802.3bt D1.2 4P PoE 5th Task Force review comments

CI 33 SC 33.3.6 P 268 L 5 # 54
 Beia, Christian STMicroelectronics

Comment Type **TR** Comment Status **D** PD Classification

Table 33-17a
 The autotimer timing, as well as T_LCF_PD, introduces a big burden for PD timing accuracy, which can be relaxed if the PSE was able to better control the length of the first long finger.

SuggestedRemedy

Change Table 33-17 item7, TACS max to 86.5
 Leave 75.5 as min

Proposed Response Response Status **W**
 PROPOSED ACCEPT IN PRINCIPLE.

OBE by 239.

CI 33 SC 33.2.4.6 P 216 L 18 # 55
 Lukacs, Miklos Silicon Labs

Comment Type **TR** Comment Status **X** Definitions

This is the first place where the single and dual signature PD is mentioned, but these terms are not described.

SuggestedRemedy

Insert a chapter into section 33.1. describing the PD interface variants (single and dual signature)

Proposed Response Response Status **W**

We created definitions last time, they are in the definition section (1.4). Should we include a pointer here?

CI 33 SC 33.2.0.a P 200 L 49 # 56
 Lukacs, Miklos Silicon Labs

Comment Type **E** Comment Status **D** Editorial

There is a typo in this sentence: 1-Event Classification of differs between Types.

SuggestedRemedy

Change to: 1-Event Classification differs between Types.

Proposed Response Response Status **W**

PROPOSED ACCEPT.

EZ

CI 33 SC 33.2.6 P 236 L 15 # 57
 Yseboodt, Lennart Philips

Comment Type **E** Comment Status **D** Editorial

"In states CLASS_EV1, CLASS_EV2, and CLASS_EV3, the PSE shall measure I Class and classify the PD based on the observed current according to Table 33-9."

This line seems to be in a slightly larger font size.

SuggestedRemedy

Match fontsize with surrounding text.

Proposed Response Response Status **W**
 PROPOSED ACCEPT.

EZ

CI 33 SC 33.2.6.3 P 237 L 45 # 58
 Yseboodt, Lennart Philips

Comment Type **E** Comment Status **D** Editorial

"Type 3 and Type 4 PSEs may choose to implement an extension ..."

SuggestedRemedy

"Type 3 and Type 4 PSEs may implement an extension ..."

Proposed Response Response Status **W**
 PROPOSED ACCEPT.

EZ

CI 33 SC 33.2.0a P 200 L 49 # 59
 Yseboodt, Lennart Philips

Comment Type **E** Comment Status **D** Editorial

"1-Event Classification of differs between Types. Please refer to Table 33-10 items 11 and 12 for details."

SuggestedRemedy

"1-Event Classification differs between Types. Please refer to Table 33-10 items 11 and 12 for details."

Proposed Response Response Status **W**
 PROPOSED ACCEPT IN PRINCIPLE.

OBE by comment 186.

EZ

IEEE P802.3bt D1.2 4P PoE 5th Task Force review comments

Cl 33 SC 33.2.1 P 201 L 10 # 60
 Yseboodt, Lennart Philips
 Comment Type E Comment Status D Editorial
 Reference to "The location of Alternative A and Alternative B Endpoint PSEs and Midspan PSEs are illustrated in Figure 33-4, Figure 33-5, Figure 33-6, and Figure 33-7."
 SuggestedRemedy
 "The location of Alternative A and Alternative B Endpoint PSEs and Midspan PSEs are illustrated in Figure 33-4, Figure 33-5, Figure 33-5a, Figure 33-5b, Figure 33-6, Figure 33-7, Figure 33-7a, and Figure 33-7b."
 Proposed Response Response Status W
 PROPOSED ACCEPT.
 EZ

Cl 33 SC 33.2.4 P 209 L 35 # 61
 Yseboodt, Lennart Philips
 Comment Type E Comment Status D Editorial
 "Type 3 and Type 4 PSEs shall provide the behavior of the state diagrams shown in Figures (TBD)."
 SuggestedRemedy
 "Type 3 and Type 4 PSEs shall provide the behavior of the state diagrams shown in Figures 33-9a to Figure 33-9g."
 Proposed Response Response Status W
 PROPOSED ACCEPT.
 EZ

Cl 33 SC 33.2.4.1 P 210 L 5 # 62
 Yseboodt, Lennart Philips
 Comment Type E Comment Status D Editorial
 "If a PSE performs detection using Alternative B see 33.2.5.5."
 SuggestedRemedy
 "If a PSE performs detection using Alternative B see Section 33.2.5.5."
 Proposed Response Response Status W
 PROPOSED ACCEPT IN PRINCIPLE.
 OBE by comment 202.

Cl 33 SC 33.2.7.11 P 250 L 45 # 63
 Yseboodt, Lennart Philips
 Comment Type E Comment Status D Editorial
 "33.2.7.11 intra-pair current unbalance" Capitalization.
 SuggestedRemedy
 "33.2.7.11 Intra-pair current unbalance"
 Proposed Response Response Status W
 PROPOSED ACCEPT IN PRINCIPLE.
 OBE by 205
 EZ

Cl 33 SC 33.2.9.1.1 P 254 L 21 # 64
 Yseboodt, Lennart Philips
 Comment Type E Comment Status D Editorial
 original text: "Editors Note: Yair to review AC MPS for 4-pair."
 In July meeting we decided not supporting AC-MPS for Type 3/4.
 SuggestedRemedy
 Remove Editors note.
 Proposed Response Response Status W
 PROPOSED ACCEPT.
 EZ

IEEE P802.3bt D1.2 4P PoE 5th Task Force review comments

CI 33 SC 33.3.2 P 256 L 51 # 65
 Yseboodt, Lennart Philips

Comment Type E Comment Status D Editorial

"Type 3/DS and Type 4/DS PDs implement a minimum of Multiple-Event Physical Layer classification and Data Link Layer Classification (see 33.6). Type 3/DS PDs advertise a class signature of 1, 2, 3 or 4 on each pairset, while Type 4/DS PDs advertise a class signature of 5 on atleast one pairset."

Space missing 'atleast'.

SuggestedRemedy

Add space.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Space need in "atleast". Also add "," after "3" in "1, 2, 3 or 4".

EZ

CI 33 SC 33.3.3.3 P 259 L 6 # 66
 Yseboodt, Lennart Philips

Comment Type E Comment Status D PD State Diagram

In variable "pse_dll_power_level"
 "The PSE is delivering class x ..."

The variable indicates how much power the PSE has allocated by showing a number of class events (in combination with the shown class signature) or via DLL.
 The word 'delivering' is not correct.

SuggestedRemedy

Change (4x) 'is delivering' into 'has allocated'.

Proposed Response Response Status W

PROPOSED ACCEPT.

EZ

CI 33 SC 33.3.3.3 P 259 L 6 # 67
 Yseboodt, Lennart Philips

Comment Type E Comment Status D Editorial

In variable "pse_power_level"
 "The PSE is delivering the PD's requested power..."

The variable indicates how much power the PSE has allocated by showing a number of class events (in combination with the shown class signature).
 The word 'delivering' is not correct.

SuggestedRemedy

Change (4x) 'is delivering' into 'has allocated'.

Proposed Response Response Status W

PROPOSED ACCEPT.

EZ

CI 33 SC 33.3.4 P 262 L 13 # 68
 Yseboodt, Lennart Philips

Comment Type E Comment Status X PD Detection

"two voltage/current" can be read as 'or'

SuggestedRemedy

change to "two voltage and current"

Proposed Response Response Status W

PSEs don't measure both. They force one and measure the other. "and" can be misleading...

CI 33 SC 33.3.4 P 262 L 33 # 69
 Yseboodt, Lennart Philips

Comment Type E Comment Status D Editorial

"PD input connector" is not consistent with rest of document

SuggestedRemedy

change to "PD PI"

Proposed Response Response Status W

PROPOSED ACCEPT.

Does this change requirements? I don't think so.

IEEE P802.3bt D1.2 4P PoE 5th Task Force review comments

Cl 33 SC 33.3.4 P 263 L 1 # 70
 Yseboodt, Lennart Philips
 Comment Type E Comment Status D Editorial
 "PD input connector" is not consistent with rest of document
 SuggestedRemedy
 change to "PD PI"
 Proposed Response Response Status W
 PROPOSED ACCEPT.
 Does this change requirements? I don't think so.

Cl 33 SC 33.3.5.3 P 267 L 40 # 71
 Yseboodt, Lennart Philips
 Comment Type E Comment Status D Editorial
 "After power up, a PD implementing Autoclass shall draw its maximum power draw throughout..."
 2x draw.
 SuggestedRemedy
 "After power up, a PD implementing Autoclass shall draw its highest required power throughout..."
 Proposed Response Response Status W
 PROPOSED ACCEPT.
 EZ

Cl 33 SC 33.3.7.3 P 271 L 48 # 72
 Yseboodt, Lennart Philips
 Comment Type E Comment Status D Editorial
 "Type3" is missing space
 SuggestedRemedy
 "Type 3"
 Proposed Response Response Status W
 PROPOSED ACCEPT.
 EZ

Cl 33 SC 33.3.7.10.1 P 277 L 8 # 73
 Yseboodt, Lennart Philips
 Comment Type E Comment Status D PD Power
 Additional info is empty for Rpair(min) and Rpair(max).
 SuggestedRemedy
 Put "See Annex 33A.5" in both
 Proposed Response Response Status W
 PROPOSED ACCEPT.
 EZ

Cl 33 SC 33.3.8 P 278 L 18 # 74
 Yseboodt, Lennart Philips
 Comment Type E Comment Status D Editorial
 "of th MPS" is misspelled
 SuggestedRemedy
 change to: "of the MPS"
 Proposed Response Response Status W
 PROPOSED ACCEPT.
 EZ

Cl 33 SC 33.4.6 P 285 L 3 # 75
 Yseboodt, Lennart Philips
 Comment Type E Comment Status D Editorial
 no space between 'for' and bracket (two times)
 SuggestedRemedy
 Add space. De-italicize 'for'.
 Proposed Response Response Status W
 PROPOSED ACCEPT.
 EZ

IEEE P802.3bt D1.2 4P PoE 5th Task Force review comments

Cl 33 SC 33.4.9.1.1 P 288 L 47 # 76
 Yseboodt, Lennart Philips
 Comment Type E Comment Status D AES
 No dimension for NEXTconn parameter.
 SuggestedRemedy
 Replace "is the Near End Crosstalk loss" with "is the Near End Crosstalk loss in dB"
 Proposed Response Response Status W
 PROPOSED ACCEPT.
 EZ

Cl 33 SC 33.4.9.1.1 P 289 L 11 # 79
 Yseboodt, Lennart Philips
 Comment Type E Comment Status D AES
 No dimension
 SuggestedRemedy
 Replace "is the Near End Crosstalk loss" with "is the Near End Crosstalk loss in dB"
 Proposed Response Response Status W
 PROPOSED ACCEPT.
 EZ

Cl 33 SC 33.4.9.1.1 P 289 L 3 # 77
 Yseboodt, Lennart Philips
 Comment Type E Comment Status D Editorial
 no space between and before 'for' and bracket (two times)
 SuggestedRemedy
 Add space. De-italicize 'for'.
 Proposed Response Response Status W
 PROPOSED ACCEPT.
 EZ

Cl 33 SC 33.4.9.1.2 P 289 L 29 # 80
 Yseboodt, Lennart Philips
 Comment Type E Comment Status D AES
 Dimension is missing
 SuggestedRemedy
 Add "in dB" after insertion loss
 Proposed Response Response Status W
 PROPOSED ACCEPT.
 EZ

Cl 33 SC 33.4.9.1.1 P 289 L 3 # 78
 Yseboodt, Lennart Philips
 Comment Type E Comment Status D Editorial
 Straight brackets used, inconsistent with rest of document.
 SuggestedRemedy
 Change straight bracket to curly brackets and add dimension after brackets (dB).
 Proposed Response Response Status W
 PROPOSED ACCEPT.
 EZ

Cl 33 SC 33.4.9.1.2 P 289 L 40 # 81
 Yseboodt, Lennart Philips
 Comment Type E Comment Status D AES
 Dimension is missing
 SuggestedRemedy
 Add "in dB" after insertion loss
 Proposed Response Response Status W
 PROPOSED ACCEPT.
 EZ

IEEE P802.3bt D1.2 4P PoE 5th Task Force review comments

Cl 33 SC 33.6.3.4 P 302 L 52 # 82
 Yseboodt, Lennart Philips
 Comment Type E Comment Status D Editorial
 Lower border missing in "Table 33-23 Attribute to state diagram variable cross-reference"
 SuggestedRemedy
 Add lower border of table
 Proposed Response Response Status W
 PROPOSED ACCEPT.
 EZ

Cl 33 SC 33.A.4 P 329 L 27 # 83
 Yseboodt, Lennart Philips
 Comment Type E Comment Status D Editorial
 Four Pair is not consistent with rest of document
 SuggestedRemedy
 change Four Pair to 4-pair
 Proposed Response Response Status W
 PROPOSED ACCEPT.
 EZ

Cl 33 SC 33.A.6 P 330 L 27 # 84
 Yseboodt, Lennart Philips
 Comment Type E Comment Status D Editorial
 Table Yuval does not exist
 SuggestedRemedy
 Correct reference to table 33A-1.
 Proposed Response Response Status W
 PROPOSED ACCEPT.
 EZ

Cl 33 SC 33.A.6 P 330 L 28 # 85
 Yseboodt, Lennart Philips
 Comment Type E Comment Status D Editorial
 reference is missing instead <>
 SuggestedRemedy
 Yair, where does this refer to ?
 Proposed Response Response Status W
 Good question.

Cl 33 SC 33.A.6 P 330 L 34 # 86
 Yseboodt, Lennart Philips
 Comment Type E Comment Status D Editorial
 Equation 33B-1 is wrong
 SuggestedRemedy
 Equation 33A-4
 Proposed Response Response Status W
 PROPOSED ACCEPT.
 EZ

Cl 33 SC 33.A.6 P 331 L 4 # 87
 Yseboodt, Lennart Philips
 Comment Type E Comment Status D Annex
 There is suspicion that the addition needs to get priority. Otherwise the units are likely to add up as "ohms + dimensionless" rather than Ohms.
 Note sure due to missing description of Kpse.
 SuggestedRemedy
 Replace formula by
 $R_{pair_max} \leq R_{pair_min} * (U + K_{pse})$
 Yair, correct ?
 Proposed Response Response Status W
 PROPOSED ACCEPT.

IEEE P802.3bt D1.2 4P PoE 5th Task Force review comments

Cl 33 SC 33.A.6 P 331 L 12 # 88
 Yseboodt, Lennart Philips
 Comment Type E Comment Status D Editorial
 Kpse is not specified
 SuggestedRemedy
 Yair, please specify Kpse
 Proposed Response Response Status W
 PROPOSED ACCEPT.

Cl 33 SC 33.A.7 P 331 L 41 # 89
 Yseboodt, Lennart Philips
 Comment Type E Comment Status D Editorial
 Reference to 33-B2 is wrong.
 SuggestedRemedy
 Change reference to figure 33A-5.
 Proposed Response Response Status W
 PROPOSED ACCEPT.
 EZ

Cl 33 SC 33.A.10 P 334 L 9 # 90
 Yseboodt, Lennart Philips
 Comment Type E Comment Status D Editorial
 "33A.10Channel resistance" is missing space
 SuggestedRemedy
 add space
 Proposed Response Response Status W
 PROPOSED ACCEPT.
 EZ

Cl 33 SC 33.A.10 P 334 L 13 # 91
 Yseboodt, Lennart Philips
 Comment Type E Comment Status D Editorial
 missing spaces around <>
 SuggestedRemedy
 add spaces
 Proposed Response Response Status W
 PROPOSED ACCEPT.
 EZ

Cl 33 SC 33.2.5 P 227 L 38 # 92
 Yseboodt, Lennart Philips
 Comment Type ER Comment Status D PSE Powering
 "In any operational state, the PSE shall not apply operating power to the PI a pairset until the PSE has successfully detected a valid signature over that pairset."
 "Editor's Note: The above sentence needs to be addressed as it forbids turning off and on a single pairset when connected to a SS class 0-4 PD."
 This has been addressed by in 33.2.7.1:
 "A Type 3 or Type 4 PSE that is connected to a class 0-4 single-signature PD and is in the POWER_ON state may transition between 2-pair and 4-pair power at any time, including after the expiration of T pon."
 SuggestedRemedy
 Remove editors note.
 Possibly amend the sentence:
 "In any operational state, the PSE shall not apply operating power to the PI a pairset until the PSE has successfully detected a valid signature over that pairset. See 33.2.7.1 for transitions between 2-pair and 4-pair mode."
 Proposed Response Response Status W
 PROPOSED ACCEPT IN PRINCIPLE.
 OBE by comment 35.

IEEE P802.3bt D1.2 4P PoE 5th Task Force review comments

CI 33 SC 33.2.5 P 227 L 40 # 93
 Yseboodt, Lennart Philips
 Comment Type ER Comment Status D PSE Powering
 Topic: Class 0 / Type 3 removal
 "Editor's Note: The above sentence needs to be addressed as it forbids turning off and on a single pairset when connected to a SS class 0-4 PD."
 SuggestedRemedy
 "Editor's Note: The above sentence needs to be addressed as it forbids turning off and on a single pairset when connected to a SS class 1-4 PD."
 Proposed Response Response Status W
 PROPOSED ACCEPT IN PRINCIPLE.
 OBE by comment 35. (note removed)

CI 33 SC 33.2.7 P 240 L 35 # 94
 Yseboodt, Lennart Philips
 Comment Type ER Comment Status D Editorial
 Bulk comment.
 Table 33-11.
 1,2,3,4 as PSE Type is not consistent, All is better.
 SuggestedRemedy
 change 1,2,3,4 to All in:
 - page 240, item 4
 - page 241, item 5
 - page 242, item 13
 - page 243, item 20, 22, 23, 24
 Proposed Response Response Status W
 PROPOSED ACCEPT.
 EZ

CI 33 SC 33 P 0 L 0 # 95
 Yseboodt, Lennart Philips
 Comment Type ER Comment Status D Editorial
 "Class" and "class" are used inconsistently.
 We are capitalizing Type, it would make sense to do the same with Class.
 SuggestedRemedy
 Change all occurrences of 'class' to 'Class'.
 Proposed Response Response Status W
 PROPOSED ACCEPT.
 EZ

CI 33 SC 33.2.4.4 P 211 L 40 # 96
 Yseboodt, Lennart Philips
 Comment Type ER Comment Status D Editorial
 original text: "... Type 3 and Tyep 4 PSEs shall use this value...."
 Typo in type
 SuggestedRemedy
 "Type 3 and Type 4 PSEs shall use this value."
 Proposed Response Response Status W
 PROPOSED ACCEPT.
 EZ

CI 33 SC 33.2.4.6 P 218 L 5 # 97
 Yseboodt, Lennart Philips
 Comment Type ER Comment Status D Editorial
 "... for which the PSE shall select to meet the requirements of its Type or a less Type such that, Type PD <= PSE Type <= Type PSE."
 Can be more compact/clear + fix spelling mistake.
 SuggestedRemedy
 "... for which the PSE shall select to meet the requirements of any Type such that, Type_PD <= applied Type <= Type_PSE."
 Request to editor: the paragraph has so many strikeouts, readability is poor.
 Delete paragraph and insert a fresh one.
 Proposed Response Response Status W
 PROPOSED ACCEPT.

IEEE P802.3bt D1.2 4P PoE 5th Task Force review comments

CI 33 SC 33.2.5.2 P 229 L 50 # 98
Yseboodt, Lennart Philips

Comment Type E Comment Status D Editorial

'voltage/current' can be read as 'or', should be 'and'

SuggestedRemedy

Replace 'voltage/current' by 'voltage and current'

Proposed Response Response Status W

PROPOSED REJECT.

The PSE is only required to measure the voltage or current. The other one is supplied by the PSE.

CI 33 SC 33.2.6 P 234 L 40 # 99
Yseboodt, Lennart Philips

Comment Type E Comment Status D

Nitpick comment.

"Classes from 0 to 4", one can debate if this includes 4.

SuggestedRemedy

Revert to "0, 1, 2, 3, and 4" or use "from 0 up to and including 4".

Proposed Response Response Status W

PROPOSED ACCEPT.

Replace with: "from 0 up to and including 4".

EZ

CI 33 SC 33.2.6 P 235 L 8 # 100
Yseboodt, Lennart Philips

Comment Type E Comment Status D Editorial

"Editor's Note: Measurement method and PSE margin for Autoclass still need to be addressed."

SuggestedRemedy

This work is completed, editors note can be removed.

Proposed Response Response Status W

PROPOSED ACCEPT.

EZ

CI 33 SC 33.3.1 P 255 L 19 # 101
Yseboodt, Lennart Philips

Comment Type ER Comment Status D Editorial

"Type 1 and Type 2 PDs shall be capable of accepting power on either of two pairsets and may accept power on both pairsets. Type 3 and Type 4 PDs shall be capable of accepting power on either pairset and shall be capable of accepting power on both pairsets. The two conductor sets are named Mode A and Mode B."

'The two conductor sets' have not been called out at this point (due to changes in the previous text).

SuggestedRemedy

Replace by: "There are two conductor sets, named Mode A and Mode B, corresponding with the two pairsets."

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

OBE by 172

EZ

CI 33 SC 33.3.2 P 256 L 7 # 102
Yseboodt, Lennart Philips

Comment Type ER Comment Status D Editorial

MPS column uses different wording than matching PSE table 33-1a (page 200).

SuggestedRemedy

Change column header "Maintain Power Signature" to "Low MPS support"
Change values to "No, No, 5xYes".

Proposed Response Response Status W

PROPOSED ACCEPT.

EZ

IEEE P802.3bt D1.2 4P PoE 5th Task Force review comments

CI 33 SC 33.3.5 P 264 L 3 # 103
 Yseboodt, Lennart Philips
 Comment Type ER Comment Status D Editorial
 "The allowed PD classification configurations are shown in Table 33-15a."
 This line is redundant to line 1.
 SuggestedRemedy
 Remove sentence.
 Proposed Response Response Status W
 PROPOSED ACCEPT.
 EZ

CI 33 SC 33.3.5.1 P 265 L 7 # 104
 Yseboodt, Lennart Philips
 Comment Type ER Comment Status D PD Classification
 "Since 1-Event classification is a subset of Multiple-Event classification, Type 2, and Type 3 PDs operating with a maximum power draw corresponding to class 4 or higher, as well as Type 4 PDs respond to 1-Event classification with a Class 4 signature."
 Why list Type 4 separately ? Can be shorter.
 SuggestedRemedy
 "Since 1-Event classification is a subset of Multiple-Event classification, Type 2, Type 3, and Type 4 PDs operating with a maximum power draw corresponding to class 4 or higher respond to 1-Event classification with a Class 4 signature."
 Proposed Response Response Status W
 PROPOSED ACCEPT.

CI 33 SC 33.3.5.2 P 266 L 39 # 105
 Yseboodt, Lennart Philips
 Comment Type ER Comment Status D PD Classification
 "Dual-signature PDs may use different class signature per pairset."
 Better wording.
 SuggestedRemedy
 "Dual-signature PDs may use a different class signature on each pairset."
 Proposed Response Response Status W
 PROPOSED ACCEPT IN PRINCIPLE.
 OBE by 147.

CI 33 SC 33.3.7.1 P 270 L 1 # 106
 Yseboodt, Lennart Philips
 Comment Type ER Comment Status D PD Power
 Table 33-18.
 1,2,3,4 is not consistent, change to All (this is 8 times in table)
 SuggestedRemedy
 change to "All"
 - Item 5, Item 8, Item 9, Item 10, Item 11 (2x), Item 12, Item 13
 Proposed Response Response Status W
 PROPOSED ACCEPT.
 EZ

CI 33 SC 33A P 329 L 1 # 107
 Yseboodt, Lennart Philips
 Comment Type ER Comment Status D Editorial
 Change bars missing in this appendix.
 SuggestedRemedy
 Add change bars.
 Proposed Response Response Status W
 PROPOSED ACCEPT.
 EZ

CI 33 SC 33.2.7 P 240 L 38 # 108
 Yseboodt, Lennart Philips
 Comment Type ER Comment Status D Editorial
 Item 4a Parameter is "Pairset current due to E2ERunb within E2ERunb range for class x".
 Not intuitive.
 SuggestedRemedy
 Change Parameter for Item 4a to:
 "Pairset current capability in POWER_ON state, Class x"
 Proposed Response Response Status W
 PROPOSED ACCEPT IN PRINCIPLE.
 OBE by comment 210
 EZ

IEEE P802.3bt D1.2 4P PoE 5th Task Force review comments

Cl 33 SC 33.2.7 P 242 L 32 # 109
 Yseboodt, Lennart Philips
 Comment Type ER Comment Status D Editorial
 Table 33-11, Item 17, Ihold
 In Additional information: "Applies to highest current pair."
 SuggestedRemedy
 Replace (twice) by "Applies to pair with the highest current."
 Proposed Response Response Status W
 PROPOSED ACCEPT.
 EZ

Cl 33 SC 33.2.7 P 242 L 32 # 110
 Yseboodt, Lennart Philips
 Comment Type ER Comment Status D Editorial
 Table 33-11, Item 17b, Ihold
 Parameter is called "DC MPS current when total sum of both pairs with the same polarity is measured, connected to a single-signature PD"
 'total' adds no value to this lengthy description.
 SuggestedRemedy
 Replace by "DC MPS current when sum of both pairs with the same polarity is measured, connected to a single-signature PD"
 Proposed Response Response Status W
 PROPOSED ACCEPT.
 EZ

Cl 33 SC 33.2.7 P 243 L 28 # 111
 Yseboodt, Lennart Philips
 Comment Type ER Comment Status D Editorial
 Note 3 to Table 33-11 says:
 "3 Item 17b applies to PSEs that implement MPS detection by measuring sum of the pairset currents of the same polarity."
 'pairsets of the same polarity' does not make sense. This should be 'pairs'.
 SuggestedRemedy
 Replace by "3 Item 17b applies to PSEs that implement MPS detection by measuring the sum of the pair currents of the same polarity."
 Proposed Response Response Status W
 PROPOSED ACCEPT.
 EZ

Cl 33 SC 33.2.7.4.1 P 246 L 11 # 112
 Yseboodt, Lennart Philips
 Comment Type ER Comment Status D Icon
 "... the maximum pair current due to E2EP2PRunb, is not exceeding I con-2P-unb as defined in Table 33-11 during normal operating conditions."
 SuggestedRemedy
 "... the maximum pair current due to E2EP2PRunb, does not exceed I con-2P-unb as defined in Table 33-11 during normal operating conditions."
 Proposed Response Response Status W
 PROPOSED ACCEPT IN PRINCIPLE.
 OBE by 209.

Cl 33 SC 33.2.7.4.1 P 246 L 14 # 113
 Yseboodt, Lennart Philips
 Comment Type ER Comment Status D Icon
 "I con-2P-unb maximum is specified for total channel common mode pair resistance from 0.1 to 12.5."
 There is no I con-2P-unb maximum. Possible to use Rch rather than constant.
 SuggestedRemedy
 "I con-2P-unb is specified for total channel common mode pair resistance from 0.1 to Rch."
 Proposed Response Response Status W
 PROPOSED ACCEPT.

IEEE P802.3bt D1.2 4P PoE 5th Task Force review comments

CI 33 SC 33.2.4.6 P 218 L 5 # 114
 Yseboodt, Lennart Philips
 Comment Type T Comment Status D Types
 "... except for I Con-2P, I LIM-2P, T LIM-2P, and P Type (see Table 33-11), for which the PSE shall select to meet ..."
 Type 3/4 PSEs are (currently, D1.2) required to support "360uF" worth of inrush unconditionally when powering over 4P. We are likely to adopt that this will become
 - "180uF" for Type 3
 - "360uF" for Type 4
 It makes sense to give Type 4 PSEs (which may be restricted to lower classes) the option to support the lower inrush if they are powering (or are only capable of) lower Type PDs.
 SuggestedRemedy
 "... except for I Con-2P, I LIM-2P, Iinrush, Iinrush-2P, T LIM-2P, and P Type (see Table 33-11), for which the PSE shall select to meet ..."
 Proposed Response Response Status W
 PROPOSED ACCEPT IN PRINCIPLE.

CI 33 SC 33.2.4.7 P 223 L 13 # 115
 Yseboodt, Lennart Philips
 Comment Type T Comment Status X PSE State Diagram
 Autoclass missing from state diagrams, eg: "Figure 33-9c Type 3 and Type 4 PSE delivering power state diagram" and "Figure 33-9g Type 3 and Type 4 PSE classification state diagram".
 SuggestedRemedy
 Insert editors note: "Autoclass to be added to state machine".
 Proposed Response Response Status W
 Autoclass is an optional behavior. Do these go into the SD? I didn't think so...

CI 33 SC 33.2.6 P 232 L 12 # 116
 Yseboodt, Lennart Philips
 Comment Type T Comment Status X PSE classification
 Section 3.2.6 describes classification. Classification has become significantly more complicated compared to Type 2 classification:
 - single & dual signature
 - Autoclass
 - power demotion
 - long finger vs short finger
 The text alone + the state machine are sufficient to (eventually) figure out how it works, but providing a simple overview would help the reader.
 SuggestedRemedy
 See yseboodt_classification_overview_0915.pdf
 Proposed Response Response Status W
 Waiting for document

CI 33 SC 33.2.6.3 P 237 L 48 # 117
 Yseboodt, Lennart Philips
 Comment Type T Comment Status D Editorial
 original text: ""
 Annex 33B is still empty, what needs to go in there ?
 SuggestedRemedy
 Add editors note on text to be integrated into Annex 33B:
 "Annex 33B needs information on:
 - Explanation of the measurement method
 - Guideline for what PDs need to do for reliable measurement
 - Explain combination of L1 and LLDP Autoclass
 - Simplified margin calculation"
 Proposed Response Response Status W
 PROPOSED ACCEPT IN PRINCIPLE.
 Change 33B to 33C.
 Create/Add to Appendix 33C:
 ""Annex 33C needs information on:
 - Explanation of the measurement method
 - Guideline for what PDs need to do for reliable measurement
 - Explain combination of L1 and LLDP Autoclass
 - Simplified margin calculation"
 EZ

IEEE P802.3bt D1.2 4P PoE 5th Task Force review comments

Cl 33 SC 33.2.0a P 200 L 28 # 118
 Yseboodt, Lennart Philips

Comment Type T Comment Status D Types

In Table 33-1a we have a column "Number of Pairs used to deliver Power".
 What we really want here is to indicate if the PSE shall, may, or may not support 4P
 powering.
 The difference is in *support* versus *used*.

SuggestedRemedy

- Replace column title by "Support 4-pair power".
- Change content to "No, No, Allowed, Allowed, Yes, Yes"
- Remove note 4 as this clarification is then no longer needed.

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 33 SC 33.3.1 P 255 L 47 # 119
 Yseboodt, Lennart Philips

Comment Type T Comment Status D Editorial

"NOTE--PDs that implement only Mode A or Mode B are specifically not allowed by this
 standard."

SuggestedRemedy

Append to note: "PDs that are not implemented to be insensitive to polarity, are specifically
 not allowed by this standard."

Proposed Response Response Status W

PROPOSED ACCEPT.

EZ

Cl 33 SC 33.3.3.5 P 260 L 14 # 120
 Yseboodt, Lennart Philips

Comment Type T Comment Status X PD State Diagram

original text: ""
 "Figure 33-16 PD state diagram" does not yet include Autoclass partial
 finger support.

SuggestedRemedy

Insert editors note: "PD state diagram needs to be updated for Autoclass."

Proposed Response Response Status W

Do optional behaviors go in the State Diagram?

Cl 33 SC 33.3.4 P 261 L 50 # 121
 Yseboodt, Lennart Philips

Comment Type T Comment Status X PD Detection

"A Type 2 PD presents a non-valid detection signature when in a mark event state per
 Figure 33-16."
 Applies to any PD which supports Multiple event classification.
 Shall missing?

SuggestedRemedy

"A Type2, Type 3, or Type 4 PD shall present a non-valid detection signature when in a
 mark event state per Figure 33-16."

Proposed Response Response Status W

I don't believe there is a PICS associated with this line, but there should be...

any objection to adding a shall?

Cl 33 SC 33.3.5.3 P 267 L 35 # 122
 Yseboodt, Lennart Philips

Comment Type T Comment Status D PD Classification

"A PD implementing Autoclass shall not have class_sig_A of '0'.
 With the removal of Class 0 for Type 3/4, this 'shall' becomes redundant.

SuggestedRemedy

Remove sentence.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Remove "In addition," from beginning of next sentence.

EZ

IEEE P802.3bt D1.2 4P PoE 5th Task Force review comments

Cl 33 SC 33.3.5.3 P 267 L 40 # 123
 Yseboodt, Lennart Philips

Comment Type T Comment Status D PD Classification

"The PD shall not draw more power than the power consumed during the time from T AUTO_PD1 to T AUTO_PD2 (as defined in Table 33-17a) at any point until V Port_PD falls below V Reset_th."

This precludes re-negotiating through DLL.

SuggestedRemedy

"The PD shall not draw more power than the power consumed during the time from T AUTO_PD1 to T AUTO_PD2 (as defined in Table 33-17a) at any point until V Port_PD falls below V Reset_th, unless the PD successfully negotiates a higher power level through Data Link Layer classification as defined in section 33.6."

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

OBE by 148 (the exact same comment.)

Cl 33 SC 33.3.7.6 P 275 L 34 # 124
 Yseboodt, Lennart Philips

Comment Type T Comment Status D PD Power

"A Type 2 PD shall meet both of the following:
 a) The PD input current spike shall not exceed 2.5 A and shall settle below the PD upperbound template (see Figure 33-18) within 4 ms. During this test, the PD PI voltage is driven from 50 V to 52.5 V at greater than 3.5 V/ms, a source impedance of 1.5 , and a source that supports a current greater than 2.5 A.\

b) The PD shall not exceed the PD upperbound template beyond T LIM min under worst-case current draw under the following conditions. The input voltage source drives V PD from V Port_PSE min to 56 V at 2250 V/s, the source impedance is R Ch (see Table 33-1), and the voltage source limits the current to MDI I LIM per Equation (33-14)."

Does not support new Types.

SuggestedRemedy

"A Type 2, Type 3 or Type 4 PD shall meet both of the following:
 a) The PD input current spike shall not exceed 2.5 A ****per pairset**** and shall settle below the PD upperbound template (see Figure 33-18) within 4 ms. During this test, the PD PI voltage is driven from 50 V to 52.5 V at greater than 3.5 V/ms, a source impedance of 1.5 ohm ****divided by the number of pairsets****, and a source that supports a current greater than 2.5 A ****per pairset****.

b) The PD shall not exceed the PD upperbound template beyond T LIM min under worst-case current draw under the following conditions. The input voltage source drives V PD from V Port_PSE min to 56 V at 2250 V/s, the source impedance is R Ch **** per pairset**** (see Table 33-1), and the voltage source limits the current to MDI I LIM per Equation (33-14)."

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 33 SC 33.3.7.6 P 275 L 49 # 125
 Yseboodt, Lennart Philips

Comment Type T Comment Status D

Equation 33-14 has the constant 5.00 in without mentioning the dimension.
 Is that 5mA or 5 A ?

SuggestedRemedy

Add correct dimension to this equation.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

I believe that is mA

IEEE P802.3bt D1.2 4P PoE 5th Task Force review comments

CI 33 SC 33.3.8 P 279 L 23 # 126
 Yseboodt, Lennart Philips

Comment Type T Comment Status D PD MPS

In Table 33-19a under 'Conditions' the constructs
 - "If no long first class event"
 - "If long first class event (T_LCF)" a
 are used.

This can be replaced by using the PD variable 'short_mps' returned by the do_class_timing function.

SuggestedRemedy

Replace "If no long first class event" by "short_mps = FALSE"
 Replace "If long first class event (T_LCF)" by "short_mps = TRUE"

Proposed Response Response Status W

PROPOSED ACCEPT.

Is this reflected in state diagram.

CI 33 SC 33.2.7.7 P 248 L 27 # 127
 Yseboodt, Lennart Philips

Comment Type T Comment Status X PSE Power

"When connected to a single signature PD, a Type 3 or Type 4 PSE should (TBD) remove power from both pairsets before the current exceeds the "PSE upperbound template" on either pairset."

TF to discuss if we can lose the TBD.

SuggestedRemedy

Remove TBD.

Proposed Response Response Status W

Task Force to discuss.

CI 33 SC 33.2.8 P 251 L 36 # 128
 Yseboodt, Lennart Philips

Comment Type T Comment Status X PSE Power

"A PSE does not initiate power provision to a link if the PSE is unable to provide the maximum power level requested by the PD based on the PD's class." (As in 802.3at)

"A PSE shall not initiate power provision to a link if the PSE is unable to provide the maximum power level requested by the PD based on the PD's class." (As in 802.3af)

In .at the shall was changed to 'does not', which is no longer normative, but also not correct.

SuggestedRemedy

"A PSE shall not initiate power provision to a link if, based on the number of classification events produced by the PSE, the PD is unable to ascertain the available amount of power based on the PDs advertised class."

Proposed Response Response Status W

I don't understand the suggested remedy. How can the PSE know what the PD is able to ascertain or not?

This is handled in .3at by a Type 1 PSE classifying a class 4 PD as class 0 (or 3). We could handle it in a similar way or we can change this sentence to reflect power demotion.

CI 33 SC 33.2.4.7 P 226 L 1 # 129
 Yseboodt, Lennart Philips

Comment Type TR Comment Status X PSE State Diagram

This is part of the Type 3 and Type 4 state diagram, and as such the states CLASS_EV1 and 1-EVENT_CLASS do not apply and can be removed.

SuggestedRemedy

Remove mentioned states and incoming and outgoing arrows.
 See yseboodt_state_diagram_0915.pdf

Proposed Response Response Status W

Waiting for document.

IEEE P802.3bt D1.2 4P PoE 5th Task Force review comments

Cl 33 SC 33.2.6 P 232 L 31 # 130
 Yseboodt, Lennart Philips
 Comment Type **TR** Comment Status **D** PSE Classification
 "Based on the response of the PD, the minimum power level at the output of the PSE is P Class as shown in Equation (33-3)."
 This seems like an appropriate place to explain the Pclass nuance between SS and DS PDs.
 SuggestedRemedy
 "Based on the response of a single-signature PD, the minimum power level at the output of the PSE is P Class as shown in Equation (33-3). For dual-signature PDs P Class applies to each pairset independently."
 Proposed Response Response Status **W**
 PROPOSED ACCEPT.

Cl 33 SC 33.2.6 P 234 L 35 # 131
 Yseboodt, Lennart Philips
 Comment Type **TR** Comment Status **X** PSE Classification
 Topic: Type 4 classrange
 "A Type 3 PSE that will provide class 3 or lower power levels may opt to use 1-event Physical Layer classification."
 SuggestedRemedy
 "A Type 3 or Type 4 PSE that will provide class 3 or lower power levels may opt to use 1-event Physical Layer classification."
 Proposed Response Response Status **W**
 See comment 192.

Cl 33 SC 33.2.6 P 235 L 5 # 132
 Yseboodt, Lennart Philips
 Comment Type **TR** Comment Status **D** PSE Classification
 "When a dual-signature PD is detected, the PSE shall supply at least the requested power over a pairset per the class code detected over that pairset."
 Seems to force a PSE to delivered requested power, thereby breaking power demotion. Also mis-uses the word 'detection'.
 SuggestedRemedy
 "When connected to a dual-signature PD, the PSE shall treat the requested power over each pairset independently."
 Proposed Response Response Status **W**
 PROPOSED ACCEPT.

Cl 33 SC 33.2.6.2 P 236 L 52 # 133
 Yseboodt, Lennart Philips
 Comment Type **TR** Comment Status **D** PSE Classification
 "If the result of the first class event is any of Classes 0, 1, 2, or 3, a Type 3 or Type 4 PSE treats a single-signature PD as a Type 1 PD and shall omit the subsequent mark and class events and classify the PD according to the result of the first class event."
 The PSE should visit MARK_EV_LAST in this case.
 SuggestedRemedy
 "If the result of the first class event is any of Classes 0, 1, 2, or 3, a Type 3 or Type 4 PSE treats a single-signature PD as a Type 1 PD and shall skip all subsequent class events, transition directly to MARK_EV_LAST, and classify the PD according to the result of the first class event."
 Add editors note on page 226 below Figure 33-9g "TODO: add arrow from CLASS_EV1_LCF to MARK_EV_LAST".
 Proposed Response Response Status **W**
 PROPOSED ACCEPT IN PRINCIPLE.
 Change text as shown in suggested remedy.
 Update to Figure 33-9g to be presented.

Cl 33 SC 33.2.6.3 P 239 L 1 # 134
 Yseboodt, Lennart Philips
 Comment Type **TR** Comment Status **D** PSE Classification
 Autoclass Table 33-10a is missing values for T_auto_pse1(max) and T_auto_pse2(min).
 SuggestedRemedy
 Add to Table 33-10a:
 T_auto_pse1 max = 1.55
 T_auto_pse2 min = 3.1
 Proposed Response Response Status **W**
 PROPOSED ACCEPT IN PRINCIPLE.
 These numbers are WAY TOO tight. The accuracy required to get an timer to stop between 3.1 and 3.2 seconds is +/- 1.59 %
 Use:
 T_auto_pse1 max = 1.65
 T_auto_pse2 min = 2.8
 They both equat to 6.X% accuracies.

IEEE P802.3bt D1.2 4P PoE 5th Task Force review comments

Cl 33 SC 33.2.6.3 P 239 L 19 # 135
 Yseboodt, Lennart Philips
 Comment Type **TR** Comment Status **X** Pres: Autoclass
 An improved calculation for Autoclass margin is described in yseboodt_1_0915.pdf
 SuggestedRemedy
 See changes in yseboodt_1_0915.pdf
 Proposed Response Response Status **W**
 Wait for presentation.

Cl 33 SC 33.2.0a P 200 L 50 # 136
 Yseboodt, Lennart Philips
 Comment Type **TR** Comment Status **D** Types
 "Type 1 or 2 PDs may be powered using one pairset."
 Any PD may be powered over 2P, not just Type 1 or Type 2 PDs.
 SuggestedRemedy
 Remove sentence.
 Proposed Response Response Status **W**
 PROPOSED ACCEPT.

Cl 33 SC 33.2.3 P 209 L 20 # 137
 Yseboodt, Lennart Philips
 Comment Type **TR** Comment Status **D**
 "PSEs may choose the polarity choices associated with Alternative A or Alternative B listed in Table 33-2a corresponding with their Type."
 SuggestedRemedy
 Statement is too weak, 'shall' missing.
 "PSEs shall use permitted polarity configurations associated with Alternative A or Alternative B listed in Table 33-2a corresponding with their Type."
 Proposed Response Response Status **W**
 PROPOSED ACCEPT.
 EZ

Cl 33 SC 33.2.3 P 209 L 27 # 138
 Yseboodt, Lennart Philips
 Comment Type **TR** Comment Status **X** Types
 "Type 3 and Type 4 PSEs may operate simultaneously on both Alternatives."
 Conditions apply, this statement is not always true.
 SuggestedRemedy
 "Type 3 and Type 4 PSEs may operate simultaneously on both Alternatives, when the requirements of Section 33.2.5.6 are met."
 Proposed Response Response Status **W**
 See comment 184.

Cl 33 SC 33.2.4.4 P 214 L 52 # 139
 Yseboodt, Lennart Philips
 Comment Type **TR** Comment Status **X** Types
 Topic: Type 4 classrange
 "Type 3 and Type 4 PSEs shall issue no more class events than the class they are capable of supporting. For example, this would apply to a PSE that is oversubscribed and in power management mode or a Type 3 PSE that has a hardware limitation."
 Also applies to Type 4.
 SuggestedRemedy
 "Type 3 and Type 4 PSEs shall issue no more class events than the class they are capable of supporting. For example, this would apply to a PSE that is oversubscribed and in power management mode or a Type 3 or Type 4 PSE that has a hardware limitation."
 Proposed Response Response Status **W**
 Need outcome of comment 269.

Cl 33 SC 33.2.4.5 P 215 L 9 # 140
 Yseboodt, Lennart Philips
 Comment Type **TR** Comment Status **D** Editorial
 We need additional Autoclass signature timers (eg. Tacs Tab. 33-17a) in PSE and PD state machines to distinguish short and long first finger and for measurement time.
 SuggestedRemedy
 Insert editors note: "Timers to be added for Autoclass"
 Proposed Response Response Status **W**
 PROPOSED ACCEPT.
 EZ

IEEE P802.3bt D1.2 4P PoE 5th Task Force review comments

Cl 33 SC 33.2.4.6 P 216 L 29 # 141
 Yseboodt, Lennart Philips

Comment Type TR Comment Status X Editorial

"pd_requested_power: This variable indicates the power class requested by the PD. A Type 1 PSE that measures a Class 4 signature assigns that PD to Class 0. When a PD requests a higher class than a Type 3 or Type 4 PSE can support, the PSE shall assign the PD class 3, 4, or 6, whichever is the highest that it can support."

This exact same 'shall' statement is in 33.2.6.2, page 237, line 4-5.

SuggestedRemedy

Remove "When a PD requests a higher class than a Type 3 or Type 4 PSE can support, the PSE shall assign the PD class 3, 4, or 6, whichever is the highest that it can support."

Proposed Response Response Status W

Task Force to discuss.

The Type 1 requirement was also repeated here. This text mirrors that...

Cl 33 SC 33.2.9.1.2 P 254 L 27 # 142
 Yseboodt, Lennart Philips

Comment Type TR Comment Status D Editorial

The construction "the sum of I port-2P of both pairsets of the same polarity" is used 6 times in 33.2.9.1.2 'pairsets of the same polarity' does not make sense. This should be 'pairs'.

SuggestedRemedy

Replace by "the sum of I port-2P of both pairs of the same polarity" (6x)

Proposed Response Response Status W

PROPOSED ACCEPT.

EZ

Cl 33 SC 33.3.5 P 264 L 1 # 143
 Yseboodt, Lennart Philips

Comment Type TR Comment Status D Editorial

"A PD shall meet at least one of the allowable classification permutations listed in Table 33-8."
 Wrong Table reference.

SuggestedRemedy

Change to: "A PD shall meet at least one of the allowed classification configurations listed in Table 33-15a."

Proposed Response Response Status W

PROPOSED ACCEPT.

EZ

Cl 33 SC 33.3.5.1 P 265 L 6 # 144
 Yseboodt, Lennart Philips

Comment Type TR Comment Status D PD Classification

Topic: Class 0 / Type 3 removal
 "Type 3 PDs operating with a maximum power draw corresponding to class 0-3 respond to 1-Event classification by returning a Class signature 0, 1, 2, or 3 in accordance..."

Type 3 does not have class 0.

SuggestedRemedy

"Type 3 PDs operating with a maximum power draw corresponding to class 1-3 respond to 1-Event classification by returning a Class signature 1, 2, or 3 in accordance..."

Proposed Response Response Status W

PROPOSED ACCEPT.

EZ

IEEE P802.3bt D1.2 4P PoE 5th Task Force review comments

CI 33 SC 33.3.5.2 P 266 L 38 # 145
 Yseboodt, Lennart Philips
 Comment Type TR Comment Status D PD Classification
 Topic: Class 0 / Type 3 removal
 "Dual-signature PDs shall use only class 0 to 5 power level over each pairset."
 SuggestedRemedy
 "Dual-signature PDs shall use only class 1 to 5 power levels over each pairset."
 Proposed Response Response Status W
 PROPOSED ACCEPT IN PRINCIPLE.
 OBE by 147.

CI 33 SC 33.3.5.2 P 266 L 13 # 146
 Yseboodt, Lennart Philips
 Comment Type TR Comment Status D PD Classification
 Topic: Class 0 / Type 3 removal
 Table 33-16a lists Class 0 for Type 3 / Single-signature.
 SuggestedRemedy
 Remove row from table.
 Proposed Response Response Status W
 PROPOSED ACCEPT.
 EZ

CI 33 SC 33.3.5.2 P 266 L 38 # 147
 Yseboodt, Lennart Philips
 Comment Type TR Comment Status D PD Classification
 "Dual-signature PDs shall use only class 0 to 5 power level over each pairset. The class advertised over each pairset is the power requested by the PD over that pairset. Dual-signature PDs may use different classsignature per pairset. It is not recommended to use different class signatures with single load dual-signature PDs."

Remove Class 0 + Grammer improvement needed.
 SuggestedRemedy
 "Dual-signature PDs shall advertise a class signature of 1, 2, 3, 4 or 5 on each pairset. The class advertised on each pairset is the power requested by the PD on that pairset. Dual-signature PDs may advertise a different class signature on each pairset. It is not recommended to use different class signatures if the dual-signature PD powers a single electrical load."
 Proposed Response Response Status W
 PROPOSED ACCEPT.

CI 33 SC 33.3.5.3 P 267 L 40 # 148
 Yseboodt, Lennart Philips
 Comment Type TR Comment Status D PD Classification
 "The PD shall not draw more power than the power consumed during the time from T AUTO_PD1 to T AUTO_PD2 (as defined in Table 33-17a) at any point until V Port_PD falls below V Reset_th."
 This precludes re-negotiating through DLL.
 SuggestedRemedy
 "The PD shall not draw more power than the power consumed during the time from T AUTO_PD1 to T AUTO_PD2 (as defined in Table 33-17a) at any point until V Port_PD falls below V Reset_th, unless the PD successfully negotiates a higher power level through Data Link Layer classification as defined in section 33.6."
 Proposed Response Response Status W
 PROPOSED ACCEPT.

IEEE P802.3bt D1.2 4P PoE 5th Task Force review comments

Cl 33 SC 33.3.7.3 P 271 L 41 # 149
 Yseboodt, Lennart Philips
 Comment Type **TR** Comment Status **D** PD Power
 "After T Inrush-2P min, the PD shall meet P Class_PD as specified in Table 33-18."
 Disallows extended power.
 SuggestedRemedy
 "After T Inrush-2P min, Class 6 or Class 8 PDs shall meet Pclass at the PSE PI, all other
 PDs shall meet P Class_PD as specified in Table 33-18."
 Proposed Response Response Status **W**
 PROPOSED ACCEPT.

Cl 33 SC 33.3.7.6 P 275 L 17 # 150
 Yseboodt, Lennart Philips
 Comment Type **TR** Comment Status **D** PD Power
 Topic: Class 0 / Type 3 removal
 "Type 3 dual-signature PDs with class 0 to 4 shall..."
 SuggestedRemedy
 "Type 3 dual-signature PDs with class 1 to 4 shall..."
 Proposed Response Response Status **W**
 PROPOSED ACCEPT.
 EZ

Cl 79 SC 79.3.2.4.1 P 341 L 33 # 151
 Yseboodt, Lennart Philips
 Comment Type **TR** Comment Status **D** DLL
 "This field shall be set according to Table 79-4."
 Unfortunately the 'power type' field only supports Type 1/2 PDs and PSEs.
 How should a Type 3/4 device set this field ?
 SuggestedRemedy
 Replace by
 "This field shall be set according to Table 79-4.
 Type 3 or Type 4 PSEs shall set this field to the value corresponding with Type 2 PSEs.
 Type 3 or Type 4 PDs shall set this field to the value corresponding with Type 2 PDs."
 Proposed Response Response Status **W**
 PROPOSED ACCEPT.

Cl 33 SC 33.2.7 P 241 L 17 # 152
 Yseboodt, Lennart Philips
 Comment Type **TR** Comment Status **D** PSE Power
 Table 33-11, Item 7, Icut-2P.
 Icut-2p is the range in which the PSE may optionally cut power. The lowerbound was
 defined by Icon in 802.3-2012.
 The correct lowerbound now would be Icon-2P-unb. The calculation in D1.2 also results in
 Icon-2P-unb values.
 Issues:
 - Rather than a calculation, we can refer to Icon-2P-unb
 - In its current form it is defined per Type, which results in Icut-2P being smaller than Icon-
 2P-unb for Class 5 and 7
 - It is too high in 2P mode
 SuggestedRemedy
 Replace the 'min' value of Icut-2p for Type 3 and Type 4 by 'Icon-2P-unb'.
 Add editors note below Table 33-11 "Icut-2P min should be equal to the relevant section of
 the lowerbound template which is currently TBD. "
 Note: somewhat less broken, needs further work (does not work for dual-signature, have
 not fixed 2P mode)
 Proposed Response Response Status **W**
 PROPOSED ACCEPT IN PRINCIPLE.

This parameter should be fixed, but the min values you suggest are not correct. For
 example, if the PSE uses active current balancing, it could use the values listed currently.
 Task Force to Discuss

IEEE P802.3bt D1.2 4P PoE 5th Task Force review comments

Cl 33 SC 33.2.7.4 P 245 L 18 # 153
 Yseboodt, Lennart Philips

Comment Type TR Comment Status X Icon

"PSEs shall meet I Con as specified in Table 33-11. Type 3 and Type 4 PSEs when connected to a single-signature PD shall meet I Con-2P as specified in Table 33-11 item 4a."

Problems:
 - Does not address dual signature
 - I Con-2P no longer exists

SuggestedRemedy

"PSEs connected to a single-signature PD shall meet I Con and I Con-2P_unb as specified in Table 33-11.
 PSEs connected to a dual-signature PD shall meet I Con on each pairset as specified in Table 33-11."

(Note: this works, because Pclass is defined to be independent for dual-signature PDs.)
 (Note: we need to specify that I Con, in the context of dual-signature, refers to the pairset current (what used to be I Con-2P), see other comment).

Proposed Response Response Status W

Task force to discuss.

Do PSEs really need to meet I Con-2P_unb? Or do they only need to meet that if they don't control unbalance somehow?

Cl 33 SC 33.2.7.4 P 245 L 21 # 154
 Yseboodt, Lennart Philips

Comment Type TR Comment Status D Icon

"I Con is the total current of both pairs with the same polarity that a PSE has to support. I Con-2P_unb is the maximum current the PSE is required to support over one of the pairs of same polarity under E2EP2PRunb condition in the POWER_ON state."

Only applies to single-signature.
 Replace E2EP2PRunb by defined terminology.

SuggestedRemedy

"When connected to single-signature PDs, I Con is the total current of both pairs with the same polarity that a PSE has to support. I Con-2P_unb is the maximum current the PSE is required to support over one of the pairs of same polarity at maximum current unbalance condition in the POWER_ON state."

When connected to a dual-signature PD, I Con is the current of a pairset that a PSE has to support."

Note: by removing -2P, things fit better for single-signature, but now we have to shoehorn things for dual-signature.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

IEEE P802.3bt D1.2 4P PoE 5th Task Force review comments

Cl 33 SC 33.2.7.4 P 245 L 40 # 155
 Yseboodt, Lennart Philips

Comment Type TR Comment Status D Editorial

"K is the ratio between I Peak-2P due to system end to end pair-to-pair current unbalance effect..."

"K=0 for two pair systems (Type 1 and Type 2 systems). The value of K which is based on curve fit and is dimensionless, for a Type 3 and Type 4 system that operates as 4-pair system is given by Equation (33-4a)."

Main issue: K=0 also for dual-signature PDs.

SuggestedRemedy

Reword & fix:

Replace

"K=0 for two pair systems (Type 1 and Type 2 systems). The value of K which is based on curve fit and is dimensionless, for a Type 3 and Type 4 system that operates as 4-pair system is given by Equation (33-4a)."

By

"The value of K is based on a curve fit and is dimensionless. For Type 3 and Type 4 PSEs, operating in 4-pair mode and connected to single-signature PDs, the value of K is given by Equation 33-4a. In all other cases the value of K is 0."

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 33 SC 33.2.7.4.1 P 246 L 11 # 156
 Yseboodt, Lennart Philips

Comment Type TR Comment Status D Icon

"I con-2P-unb maximum is the average pair current due to E2EP2PRunb that is higher than I con-2P specified in Table 33-11."

There is no I con-2P-unb maximum. Icon-2P no longer exists.

SuggestedRemedy

"I con-2P-unb is the pairset current in case of maximum unbalance and will be higher than half of Icon."

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 33 SC 33.2.7.5 P 246 L 49 # 157
 Yseboodt, Lennart Philips

Comment Type TR Comment Status D PSE Inrush

"POWER_UP mode occurs on each pairset between the PSE's transition to the POWER_UP state on that pairset and either the expiration of T Inrush-2P or the conclusion of PD inrush currents on that pairset (see 33.3.7.3)."

For Type 3 and Type 4 PSEs, the conclusion of the PD inrush current is not cause to transition to POWER_ON.

SuggestedRemedy

"POWER_UP mode occurs on each pairset between the PSE's transition to the POWER_UP state on that pairset and either the expiration of T Inrush-2P or, for Type 1 and Type 2 PSEs that make use of legacy inrush, the conclusion of PD inrush currents on that pairset (see 33.3.7.3)."

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 33 SC 33.2.7.7 P 249 L 28 # 158
 Yseboodt, Lennart Philips

Comment Type TR Comment Status X Pres: Lennart2

In Figure 33-14, x axis, there is a marked time with value of 8.2ms. Followed by a marked time with value T_LIM-2P(min). For Type 4, T_LIM-2P(min)=6ms, which is less than 8.2ms.

SuggestedRemedy

See presentation yseboodt_2_0915.pdf on Figure 33-14 for replacement figures.

Proposed Response Response Status W

Wait for presentation.

IEEE P802.3bt D1.2 4P PoE 5th Task Force review comments

CI 33 SC 33.2.7.7 P 249 L 1 # 159
Yseboodt, Lennart Philips

Comment Type TR Comment Status X Pres: Lennart2

This Figure 33-14 now works on a per pairset basis, rather than a PI basis.
This has the effect to double all the constants in the Figure when the PSE operates in 4P mode.
The issue is with the 1.75A constant in the upperbound template.

In 802.3-2012 this was chosen as $100W / 57V = 1.75A$.
IEC 60950 lists a maximum I_{sc} for Class 2 power sources as $150W / V_{max} = 150W / 57V = 2.63A$ or 1.3A per pairset.

TF to discuss if we need to change 1.75A to 1.3A.

Note:
- Adopting 1.3A limit introduces a margin challenge for Class 7-8 PSEs
- Discussion with IEC experts still ongoing to see how to interpret this specification

SuggestedRemedy

See presentation yseboodt_2_0915.pdf on Figure 33-14 for replacement figures.

Proposed Response Response Status W

Wait for presentation.

CI 33 SC 33.2.7.7 P 249 L 1 # 160
Yseboodt, Lennart Philips

Comment Type TR Comment Status X Pres: Lennart2

Figure 33-14.
In contrast to 802.3-2012, the parameter $I_{lim}(min)$ went from being Type dependent to being Class dependent.
The reason is that we do not want Type 3/4 PSEs that are restricted to low power, to have to support comparatively enormous currents up to $I_{lim}(min)$ in the lowerbound template.

Fig 33-14 also uses $I_{lim}(min)$ in the upperbound template, for $t > T_{cut}(max)$.
The side effect is that that upperbound limit is no longer Type-constant, but moves with Class.

See comment #94 against D1.1:
"Comment is rejected because this is not necessary behavior and is a feature rather than a requirement. This allows PSEs to use a single current limit and not dynamically change it."

SuggestedRemedy

Solution is to have this section of the upperbound template defined by another parameter.
This could be any of: something new, $I_{lim}(max)$, $I_{cut}(max)$, ...

I am suggesting $I_{cut}(max)$ in the presentation.

See presentation yseboodt_2_0915.pdf on Figure 33-14 for replacement figures.

Proposed Response Response Status W

Wait for presentation.

CI 33 SC 33.2.7.7 P 249 L 1 # 161
Yseboodt, Lennart Philips

Comment Type TR Comment Status X Pres: Lennart2

Figure 33-14 still has a TBD. It is there because this is a very tricky to define value with our current set of parameters.

SuggestedRemedy

The lowerbound TBD is I_{con} - 'the current in the other pairset'.
It is probably helpful for the reader to also show the effect of unbalance in this Figure.

See presentation yseboodt_2_0915.pdf on Figure 33-14 for replacement figures.

Proposed Response Response Status W

Wait for presentation

IEEE P802.3bt D1.2 4P PoE 5th Task Force review comments

Cl 33 SC 33.4. P 281 L 37 # 162
 Zimmerman, George CME Consulting

Comment Type **TR** Comment Status **D** AES

Equation 33-16 ..."for a 100 Mb/s or greater PHY".
 While this is the spec for MDI impedance balance for 100BASE-T and 1000BASE-T, it is not consistent with the spec for 10GBASE-T in Clause 55.8.2.2.
 (it is unclear yet what the 2.5G/5G PHYs will be here)

SuggestedRemedy

Insert after line 43, (eqn 55-55 in 802.3bx d3p2)
 "Bal(f) >= 48 dB (1<=f<30 MHz)
 >= 44 - 19.2 log10(f/50) (30<= f < 500 MHz)
 for a 10GBASE-T PHY."

Proposed Response Response Status **W**
 PROPOSED ACCEPT.

Cl 33 SC 33.1.3 P 197 L 39 # 163
 Zimmerman, George CME Consulting

Comment Type **E** Comment Status **D** Editorial

External cross references 1.4.324,1.4.337, 1.4.256, 1.4.269 need to be marked as External (forest green)

SuggestedRemedy

See comment.

Proposed Response Response Status **W**
 PROPOSED ACCEPT.

EZ

Cl 33 SC 33.3.2 P 256 L 51 # 164
 Zimmerman, George CME Consulting

Comment Type **E** Comment Status **D** Editorial

missing space "atleast"

SuggestedRemedy

replace "atleast" with "at least"

Proposed Response Response Status **W**
 PROPOSED ACCEPT IN PRINCIPLE.

OBE by 65.

EZ

Cl 33 SC 33.3.5 P 263 L 43 # 165
 Zimmerman, George CME Consulting

Comment Type **E** Comment Status **D** Editorial

"The PD is classified based on power. The Physical Layer classification of the PD is the maximum power that the PD draws across all input voltages and operational modes."

The first statement is meaningless and needs clarification. The second sentence says all that needs to be said.

SuggestedRemedy

Delete "The PD is classified based on power."

Proposed Response Response Status **W**
 PROPOSED ACCEPT.

EZ

Cl 33 SC 33.3.7 P 268 L 29 # 166
 Zimmerman, George CME Consulting

Comment Type **E** Comment Status **D** Editorial

Somehow the editing instruction for Table 33-18 has gotten disassociated from the table...
 "Change Table 33-18 as follows:"

SuggestedRemedy

Wrestle with frame so the editing instruction stays with the table.

Proposed Response Response Status **W**
 PROPOSED ACCEPT.

EZ

IEEE P802.3bt D1.2 4P PoE 5th Task Force review comments

Cl 99 SC P1 L 24 # 167
 Zimmerman, George CME Consulting

Comment Type ER Comment Status D Front Matter

(to minimize comments, all related front matter stuff is here)
 Page 1 line 24: Need to fill in purpose of amendment from PAR,
 Page 1 line 25: status as "Task Force Review".
 Page 2, abstract and keywords.
 Page 3, line 36, this is 802.3bt-20XX
 Page 4 line 27, this is 802.3bt-20XX
 Page 4 line 28, include a brief summary of the changes, generally aligned with the PAR.

SuggestedRemedy

See comment

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 30 SC 30.1 P 30 L 1 # 168
 Zimmerman, George CME Consulting

Comment Type ER Comment Status D Editorial

No need to have all of clause 30 here. It appears only 30.9, 30.10, 30.12.2.1 and 30.12.3.1 relate to PoE, and only 30.12.2.1 and 30.12.3.1 are the only sections modified. For clarity, include 30.9 & 30.10, but really only the modified sections will be needed for WG ballot - 30.12.2.1 and 30.12.3.1.

SuggestedRemedy

Delete 30.1 through start of 30.9 (delete P30 L3 - 163 L 2)
 Delete 30.11 through 30.12.2.1.5 (delete P169 L28 - 177 L50)
 Delete 30.13 - 30. through end of clause 30 inclusion(delete P192 L7 - 194 L20)

Proposed Response Response Status W

PROPOSED ACCEPT.

EZ

Cl 33 SC 33.1.1 P 196 L 1 # 169
 Zimmerman, George CME Consulting

Comment Type ER Comment Status D Editorial

Previous editing instruction (P195 L 41) has clause 33.1.1 deleted - I assume this is correct. However P196 L1 and P196 L12 have edits to change the text in 33.1.1 items (c) & (d), which are now unnecessary.

SuggestedRemedy

Remove edits and editing instructions within 33.1.1, and show all of existing 33.1.1, including items c & d as it is in 802.3bxD3p2 (now 802.3-2015?) in strikeout.

Proposed Response Response Status W

PROPOSED ACCEPT.

EZ

Cl 33 SC 33.3.2 P 257 L 1 # 170
 Zimmerman, George CME Consulting

Comment Type ER Comment Status X Editorial

Most all of Section 33.3.2 appears to be informative - summarizing requirements and allowed type/classification/LLDP requirements where the normative requirements are elsewhere (if they aren't then the section is missing the 'shall' statements and any PICs). However, at the end of the section there are two requirements (PD5 (underpowered PDs) and PD6 (25.4.5 compliance) which seem misplaced. These make the informative nature of the new text unclear (hence why this isn't a maintenance request), and the informative text needs to be separated from the normative text

SuggestedRemedy

Add (informative) to the title of the section.
 (note the two normative requirements are moved elsewhere)

Proposed Response Response Status W

Task Force to discuss.

Are all of these informative? Are they all stated elsewhere?

IEEE P802.3bt D1.2 4P PoE 5th Task Force review comments

Cl 33 SC 33.3.7.6 P 275 L 54 # 171
 Zimmerman, George CME Consulting
 Comment Type ER Comment Status X PD Power
 "is the per pairset current limit at the MDI (MDI I_LIM)"
 the preceding text says this is MDI I_LIM-2P.
 SuggestedRemedy
 Either: remove the -2P notation for MDI I_LIM-2P (preferred)
 or change line 54 to read MDI I_LIM-2P
 Proposed Response Response Status W
 Task Force to discuss.
 Why are we repeating the parameter name in its definition?

Cl 33 SC 33.3.1 P 255 L 19 # 172
 Zimmerman, George CME Consulting
 Comment Type T Comment Status D Editorial
 "The two conductor sets are named Mode A and Mode B."
 we now call these "pairsets" - in fact, the two sentences immediately preceding this one
 use the term pairsets. Switching back to conductor sets is confusing and makes the
 reader think there is a difference where I think there should be none.
 SuggestedRemedy
 replace "conductor sets" with "pairsets" or clarify what is meant by the different term.
 Proposed Response Response Status W
 PROPOSED ACCEPT.
 EZ

Cl 33 SC 33.3.7.6 P 275 L 17 # 173
 Zimmerman, George CME Consulting
 Comment Type T Comment Status D PD Power
 "Type 1, Type 2, and single-signature Type 3 PDs with classes 0 to 4 shall meet the
 requirement for Cport as defined in Table 33-18 item 9. Type 3 dual-signature PDs with
 class 0 to 4 shall meet..."
 According to Table 33-13a, there are no class 0 Type 3 PDs. (the first sentence is OK
 because there are class 0 Type 1 PDs)
 SuggestedRemedy
 change "Type 3 dual-signature PDs with class 0 to 4" to "Type 3 dual-signature PDs with
 class 1 to 4"
 Proposed Response Response Status W
 PROPOSED ACCEPT IN PRINCIPLE.
 OBE by 150.
 EZ

Cl 33 SC 33.3.5.1 P 264 L 52 # 174
 Zimmerman, George CME Consulting
 Comment Type T Comment Status D PD Classification
 "Class 0 is the default for PDs".
 Now that we have Type 3 and Type 4, which are required to present at least 1-event
 classification class signatures, as described all over the place and summarized in Table 33-
 13a, Class 0 is NOT the default for PDs. Class 0 is the default that a PSE assumes. this
 clause specifies the PD. Class 0 appears to be only allowed for Type 1 PDs.
 This statement needs to be clarified.
 Additionally, Table 33-16a appears to allow class 0 for Type 3 PDs.
 Without a class sig, how is the PD a type 3?
 SuggestedRemedy
 Clarify the sentence as either applying only to Type 1 PDs or as applying to Type 1 and
 Type 3/SS PDs, and editor to search and align other references to class 0 Type 3 PDs in
 document (some of which I have commented on elsewhere).
 Proposed Response Response Status W
 PROPOSED ACCEPT IN PRINCIPLE.
 Change to: Class 0 is the default for Type 1 PDs."

IEEE P802.3bt D1.2 4P PoE 5th Task Force review comments

CI 33 SC 33.4.6 P 285 L 11 # 175
 Zimmerman, George CME Consulting

Comment Type T Comment Status D AES

DM noise for 10GBASE-T under 1 MHz is still to be defined. capping it at the 1MHz level should be more than sufficient to protect the system. Further, the 100BASE-T and 1000BASE-T DM noise is only specified down to 1MHz, so to be consistent, leave the spec as written.

SuggestedRemedy

Delete editor's note.

Proposed Response Response Status W

PROPOSED ACCEPT.

EZ

CI 33 SC 33.3.2 P 256 L 17 # 176
 Zimmerman, George CME Consulting

Comment Type TR Comment Status D Types

Table 33-13a is entitled "Permissible PD Types" as such, it should list the types, 1 row per type. There are two entries for "Type 3/SS", differentiated by their class, not their type. They differ in the physical layer class events and whether data link layer classification is required. These differences should just be noted in a single row since the PDs are of the same type, or, are they really a different type? (the first is preferable, since a PD really shouldn't change it's type, but might under some circumstances operate say as class 3, and others as class 4)

SuggestedRemedy

Either: a) Define Type 3/SS Class 1-3 and Type 3/SS Class 4-6 as separate types (i.e., rename them e.g., Type 3a/SS and Type 3b/SS) or, preferably b) merge the two rows showing the 2 class ranges under physical layer class and data link layer class.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

These rows could be combined if the class 1-3 row still uses multiple-event (I think it should). Then only a note would be needed for DLL support.

CI 33 SC 33.3.2 P 257 L 6 # 177
 Zimmerman, George CME Consulting

Comment Type TR Comment Status D Editorial

"Type 2, Type 3 and Type 4 PDs shall meet the requirements of 25.4.5 in the presence of (lunb / 2).", but the requirement of 25.4.5 specifically only applies to Type 2 devices. "A receiver in a Type 2 Endpoint PSE or Type 2 PD (see Clause 33) shall meet the requirements of 25.4.7. A transmitter in a Type 2 Endpoint PSE or Type 2 PD delivering or accepting more than 13.0W average power shall meet either the Open Circuit Inductance (OCL) requirement in 9.1.7 of TP-PMD, or meet the requirements of 25.4.5.1." Additionally, the requirement here requires ALL TType 2, 3 and 4 PDs whether or not they include 100BASE-TX, to meet the clause 25 requirement, which would make magnetics more expensive if, in the future, 100BASE-TX support were dropped. I believe the purpose of the requirement here is to add lunb to the clause 25 test, so, which might benefit from some descriptive text as to the purpose.

SuggestedRemedy

Insert after "PDs", "implementing 100BASE-TX (Clause 25) PHYs" Add a note after line 6 stating: "NOTE - For PDs implementing both Clause 25 and Clause 33, this adds the unbalance current to the requirements in Clause 25." Add Clause 25 to the 802.3bt amendment, and modify 25.4.5 to say "Type 2 or greater Endpoint PSE or Type 2 or greater PD" (2 places).

Proposed Response Response Status W

PROPOSED ACCEPT.

CI 33 SC 33.3.2 P 256 L 36 # 178
 Zimmerman, George CME Consulting

Comment Type TR Comment Status D Types

There are two major informative distinctions in the table, which are puzzling, but left out of the discussion. Without pointing these out, the reader is likely to think it a typographical error.
 1) Class 6 is not permitted for any Type 4 PDs
 2) Class 0 is not permitted for any PDs other than Type 1.

SuggestedRemedy

Insert: "Class 0 is not permitted for any PDs other than Type 1." on line 36, after the end of the sentence (same paragraph as Type 1 PDs).
 Insert: "Class 6 is not permitted for Type 4 PDs." as a new paragraph after line 52.

Proposed Response Response Status W

PROPOSED ACCEPT.

IEEE P802.3bt D1.2 4P PoE 5th Task Force review comments

Cl 33 SC 33.3.7.6 P 275 L 16 # 179
 Zimmerman, George CME Consulting

Comment Type TR Comment Status X Cport

"Type 1, Type 2, and single-signature Type 3 PDs with classes 0 to 4 shall meet the requirement for Cport as defined in Table 33-18 item 9. Type 3 dual-signature PDs with class 0 to 4 shall meet the requirement for Cport as defined in Table 33-18 item 9 for each pairset."

These belong as notes to Table 33-18 item 9, and not in the section called "PD behavior during transients" (yes, they relate to transients, but are not a specification of behavior"

SuggestedRemedy

Delete first 2 sentences of first paragraph of 33.3.7.6, and add them as either as Note 1 to item 9 of Table 33-18, OR, split Item 9 of Table 33-18 into 3 rows, one for Type 1, 2 and Type 3/SS PDs Class 0-4, and one for Type 3/DS PDs. (if Type 4 is to be added, it should be added in Table 33-18 and not 33.3.7.6 as well)

Proposed Response Response Status W

Task Force to discuss.

Could OBE 203.

Cl 33 SC 33.3.7.6 P 275 L 18 # 180
 Zimmerman, George CME Consulting

Comment Type TR Comment Status X Cport

Statements excluding PDs with CPort_min values greater than certain values are confusing, and do not appear to apply to any existing requirements, since the only requirements currently in the section are for Type 1 and Type 2.

"For class 5 and 6 single-signature PDs, if CPort_min >10uF, transient behavior has no further requirements. For dual-signature class 5 PDs, this recommendation applies to each pairset. For class 7 and 8 single signature PDs, if CPort_min >20uF, transient behavior has no further requirements. See 33.2.7.2 (TBD) or the transient conditions"

SuggestedRemedy

move statements to an editor's note, and explicitly state the requirements that these PDs are being excluded from, including what needs to be done to make those requirements (is it the referenced 'drop out' specification?)

Proposed Response Response Status W

Task Force to discuss

Cl 33 SC 33.3.5 P 264 L 36 # 181
 Zimmerman, George CME Consulting

Comment Type TR Comment Status D PD Classification

(Note 1 to Table 33-15a)
 "Any PD that is limited to class 0-3 power levels may omit DLL support." and P264 L43
 "Type 2, Type 3 and Type 4 PDs shall implement both Multiple-Event class signature (see 33.3.5.2) and Data Link Layer classification (see 33.6)."

Are in conflict. L43 would be read that any Type 3 Class 1-3 PD would have to implement DLL (which is also in conflict with table 33-13a's PD summary, which also says that Type 1-3 Type 3 PDs only have to do 1-Event class).

SuggestedRemedy

Change P264 L43 to read:
 "Type 2, Type 3 and Type 4 PDs at class 4 or greater power levels shall implement both Multiple-Event class signature (see 33.3.5.2) and Data Link Layer classification (see 33.6)."
 Add after the above sentence.
 "PD's of all Types at class 3 or lower power levels are not required to implement Multiple-Event class signature (see 33.3.5.2) and Data Link Layer classification (see 33.6)."

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 33 SC 33.3.5.2 P 266 L 23 # 182
 Zimmerman, George CME Consulting

Comment Type TR Comment Status D PD Classification

Table 33-16a shows no entries for dual signature class 0 PDs and text on line 38 indicates "Dual-signature PDs shall use only class 0 to 5 power level..."

Which is it? Table 33-13a suggests DS PDs don't have class 0

SuggestedRemedy

change "class 0 to 5" to "class 1 to 5"

Proposed Response Response Status W

PROPOSED ACCEPT.

OBE by 147.

IEEE P802.3bt D1.2 4P PoE 5th Task Force review comments

CI 33 SC 33.3.7.5 P 273 L 33 # 183
 Zimmerman, George CME Consulting

Comment Type TR Comment Status X PD Power

"When the input voltage at the PI is static and in the range of VPort_PD defined by Table 33-18, the transient current drawn by the PD shall not exceed 4.70 mA/us in either polarity. A dual-signature PD shall not exceed 4.70 mA/us in either polarity per pairset in the same conditions."

First, now that we have 4 pairs, this leaves the reader to have to assume whether for single signature PDs the 4.70 mA/us applies to the sum of the 2 pairsets or per pairset. In the below, I assume it is to the sum of the 2 pairsets.
 Second, it is worded awkwardly.

SuggestedRemedy

Change "When the input voltage at the PI is static and in the range of VPort_PD defined by Table 33-18, the transient current drawn by the PD shall not exceed 4.70 mA/us in either polarity. A dual-signature PD shall not exceed 4.70 mA/us in either polarity per pairset in the same conditions."
 to "When the input voltage at the PI is static and in the range of VPort_PD defined by Table 33-18, the transient current drawn by the PD shall not exceed 4.70 mA/us in either polarity. For a single-signature PD, this requirement applies to the sum of the current on both pairsets, for a dual-signature PD this requirement applies to the current on a per-pairset basis."

Proposed Response Response Status W

Task Force to discuss

CI 33 SC 33.2.3 P 209 L 27 # 184
 Johnson, Peter Sifos Technologies

Comment Type TR Comment Status D Types

"Type 3 and Type 4 PSEs may operate simultaneously on both Alternatives" reads like this is optional when it is not in many cases (Class 5 and above PSE's powering Type 3 and Type 4 PD's) as specified in Table 33-1a.

SuggestedRemedy

Change to:

Type 3 and Type 4 PSEs shall operate both Alternatives simultaneously when powering at Class 5 and above and may operate both Alternatives simultaneously when powering PDs capable of receiving power on both Alternatives.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

We need to be careful about our desire to put every requirement in every sentence. This sentence is obviously not as specific as later requirements, but the shalls in later requirements would override this may.

Task Force to discuss.

CI 33 SC 33.2.0a P 200 L 30 # 185
 Johnson, Peter Sifos Technologies

Comment Type E Comment Status D Types

Under the Table 33-1a heading "Number of Pairs use to deliver Power" are values "2-Pair Only", etc. Seems like these values need only be "2", "2 or 4", or "4" to be meaningful.

SuggestedRemedy

Change values to "2", "2 or 4", or "4". Furthermore, because footnote 4 uses the term "pairsets", and because pairset is now defined in Definitions, it might be even better to change column header to "Number of pairsets used to deliver power" and adjust the values to "1", "1 or 2", or "2".

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Possible OBE by comment 118.

IEEE P802.3bt D1.2 4P PoE 5th Task Force review comments

Cl 33 SC 33.2.0a P 200 L 49 # 186
 Johnson, Peter Sifos Technologies
 Comment Type E Comment Status D Editorial
 Footnote 3 to Table 33-1a has a typo - remove the "of" before "differs".
 SuggestedRemedy
 Remove the "of" before "differs" in footnote 3.
 Proposed Response Response Status W
 PROPOSED ACCEPT.
 EZ

Cl 33 SC 33.2.4.1 P 210 L 5 # 187
 Johnson, Peter Sifos Technologies
 Comment Type E Comment Status D Editorial
 Partially deleted sentence regarding Alt B backoff in presence of open circuit. Was this done as maintenance? (If not, it should have been a maintenance task.) Also, moving to the new clause 33.2.5.5 seems a bit out of place since the topic is clearly about back-off behavior.
 SuggestedRemedy
 Either delete the sentence in 33.2.4.1 entirely or re-locate 33.2.5.5 clause back to it's prior location.
 Proposed Response Response Status W
 PROPOSED ACCEPT IN PRINCIPLE.
 OBE by comment 202.

Cl 33 SC 33.2.6 P 232 L 44 # 188
 Johnson, Peter Sifos Technologies
 Comment Type E Comment Status D Editorial
 The paragraph concerning Autoclass seems off-topic in this exact location as it separates the Pclass equation from the associated paragraph starting on line 39.
 SuggestedRemedy
 Either move the Autoclass paragraph to after the Pclass equation or perhaps to after Table 33-7.
 Proposed Response Response Status W
 PROPOSED ACCEPT.
 Move paragraph to after equation 33-3.
 EZ

Cl 33 SC 33.2.0a P 200 L 50 # 189
 Johnson, Peter Sifos Technologies
 Comment Type T Comment Status D Types
 Footnote 4 should apply to ALL Type-3 PSE's that provide 4-pair powering including those in rows 3 and 4 of the table. Secondly, assuming that we are allowing for Type-3 PSE's that only power 2 pair (to Class 3/4 limit), then Section 33.2.5.6 (4-Pair ID) needs to specify 4-pair PSE's only. Finally, there is a caveat that a Type-3 or Type-4 PSE that is restricted to 1 or 2 event classification by power management will not be able to resolve if a PD is Type-2 versus Type-3 / 4.
 SuggestedRemedy
 Add footnote 4 to wherever "4-Pair" (or 2 pairsets) appears in the table.

Then modify 33.2.5.6 to start with "Type 3 and Type 4 PSEs that will deliver power on both pairsets shall determine...."
 Change 2nd line of footnote: "Type 1 PDs and Type 2 PDs that have been clearly identified as Type 1 or Type 2 may be powered using one pairset."
 Proposed Response Response Status W
 PROPOSED ACCEPT IN PRINCIPLE.
 AIP this part (possible obe by 118):
 Add footnote 4 to wherever "4-Pair" (or 2 pairsets) appears in the table.

 Accept this part:
 Then modify 33.2.5.6 to start with "Type 3 and Type 4 PSEs that will deliver power on both pairsets shall determine...."

.....
 Reject this part as unneeded (Any PD that presents a class signature in the valid range for a Type 1/2 PD may be 2-pair powered):
 Change 2nd line of footnote: "Type 1 PDs and Type 2 PDs that have been clearly identified as Type 1 or Type 2 may be powered using one pairset."

IEEE P802.3bt D1.2 4P PoE 5th Task Force review comments

Cl 33 SC 33.2.4.6 P 216 L 36 # 190
 Johnson, Peter Sifos Technologies

Comment Type T Comment Status D PSE State Diagram

The value descriptions, for example Class 5, do not account for Dual Signature classifications described in Table 33-16a.

SuggestedRemedy

Either update this to reflect Dual Signature classification processing or add editor's note that do_classification function must eventually take into account Dual Signature handling.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Add editor's note: "DS PD classification must be taken into account here."

Cl 33 SC 33.2.6 P 233 L 10 # 191
 Johnson, Peter Sifos Technologies

Comment Type T Comment Status X Editorial

In Table 33-7, the column header "Minimum supported power levels at output of PSE (Pclass)" is not accurate. Pclass is defined in equation 33-3. Text above refers to "over-margined values..." - that is a more accurate depiction of this column. Also, for Classes 4 - 7, phrases such as "30W or Ptype as defined in Table 33-11, whichever is lower" is unusual because as presented in Table 33-11, Ptype cannot be lower than 30W.

SuggestedRemedy

Change column header "Minimum PSE output power (Pclass) See NOTE 1" and modify NOTE 1 to "This is the minimum required power at the PSE PI calculated using minimum Vport_pse and maximum Rchan. Use equation 33-3 for other values of Vport_pse and Rchan. For maximum power available to PDs, see Table 33-18."

Utilize numeric values as is done for class 0-3, namely 30 Watts, 45 Watts, 60 Watts, 75 Watts, and 90 Watts.

Proposed Response Response Status W

Task Force to Discuss.

We cannot just leave numbers for classes 4 and above as a lower Type PSE cannot supply that amount of power and thus Ptype is the power required.

Cl 33 SC 33.2.6 P 234 L 35 # 192
 Johnson, Peter Sifos Technologies

Comment Type T Comment Status X PSE Classification

Footnote 1 to Table 33-8 says "A Type 3 PSE that will provide class 3 or lower power levels may opt to use 1-event Physical Layer classification". Is this really an option? Para. 33.2.6.2 mandates that a Type-3 or Type-4 PSE powering a Class 0 to 3 PD provides one-event classification with no mark events. Para. 33.3.2.4.4 (under Table 33-3) says Type-3 and Type-4 PSEs shall issue no more class events than the class they are capable of supporting..."

SuggestedRemedy

Replace "may opt to" with "is required to". (Any 'shall' here seems redundant with other paragraphs referenced above.)

Proposed Response Response Status W

Actually, do to the long first finger requirement, I think it would be better to make TYPE 3/4 PSEs do multiple-event class (even if its only one finger) so that they then go to mark and the PD "remembers" that it saw a long finger.

Task force to discuss.

Cl 33 SC 33.2.6 P 235 L 5 # 193
 Johnson, Peter Sifos Technologies

Comment Type T Comment Status D PSE Classification

Present text: "When a dual-signature PD is detected, the PSE shall supply at least the requested power over a pairset per the class code detected over that pairset". This statement, as written, demands that full requested power be provided to any dual-signature PD by any PSE detecting it. Not sure about the term "class code" - is that used anywhere else?

SuggestedRemedy

Revise this to:

A Type 3 or Type 4 PSE detecting a dual-signature PD shall not power any pairset with a classification exceeding the power available on that pairset at the PSE.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Possible OBE by 132

IEEE P802.3bt D1.2 4P PoE 5th Task Force review comments

CI 33 SC 33.2.6.2 P 236 L 27 # 194
 Johnson, Peter Sifos Technologies

Comment Type T Comment Status D PSE Classification

"PSEs that implement CLASS_EV1_LCF, when connected to single-signature PD's, shall transition directly from CLASS_EV1_LCF to MARK_EV_LAST if they implement only one class event."

First, why not say "Type 3 and Type 4 PSE's" ?

Second, the Figure 33-9g does not include this transition possibility. Figure 33-9g will need this transition if we want Type 3 and Type 4 PD's to "remember" that the PSE is Type 3 or Type 4.

Third, why is this limited to single signature PD's?

SuggestedRemedy

Figure 33-9g, the Classification State Diagram, probably needs a transition from CLASS_EV1_LCF to MARK_EV_LAST in place of transitioning to node "C".

(This could be an editor note now...)

Replace "PSEs that implement CLASS_EV1_LCF" with "Type 3 and Type 4 PSEs".

May need an editor note to review this phrase once all the details for Dual Signature classification are worked out.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Change text to "Type 3 and type 4 PSEs connected to single-signature PDs shall transition directly from..."

Update to Figure 33-9g to be presented.

CI 33 SC 33.2.6.2 P 237 L 10 # 195
 Johnson, Peter Sifos Technologies

Comment Type T Comment Status D PSE Classification

"...A Type 3 or Type 4 PSE connected to a dual-signature PD shall skip all subsequent class events and transition directly to MARK_EV_LAST if the class signature during CLASS_EV3 is 0, 1, 2, or 4."

This transition option is not currently available in Figure 33-9g, the classification state diagram. Only exit from CLASS_EV3 requires PD Class =4.

Also, if a PSE uses at least 3 events to resolve Type 1 Class 3 from Type 3 Class 3, then the only option is to move onto CLASS_EV4 after measuring Class 3 on the 3rd event. Is this a problem if the PSE will not support Class 5 on that pairset? (Would CLASS_EVAL just reject the power-up?)

SuggestedRemedy

Editor note indicating this deficiency in the state diagram Fig 33-9g.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Update to Figure 33-9g to be presented.

CI 33 SC 33.3.5.2 P 266 L 3 # 196
 Johnson, Peter Sifos Technologies

Comment Type T Comment Status D PD Classification

The terms "class_sig_A" and "class_sig_B" are just a problem waiting to happen in Table 33-16a and in the PD State Diagram (and associated variable definitions). Will get confused with classifying on Alt-A and Alt-B pairs when these really mean something else.

SuggestedRemedy

What about "search and replace" with "class_sig_A" with "class_sig_ev12" and "class_sig_B" with "class_sig_ev35" or something like this?

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

That is a fair point, but the suggestion may be even worse. Any other ideas?

IEEE P802.3bt D1.2 4P PoE 5th Task Force review comments

Cl 33 SC 33.3.5.2 P 266 L 26 # 197
 Johnson, Peter Sifos Technologies

Comment Type T Comment Status D PD Classification

In Table 33-16a, since class signatures are per-pairset in a Dual Signature PD, perhaps it would be beneficial to highlight this fact.

SuggestedRemedy
 Beneath Dual-Siganture under PD Type 3 and PD Type 4, add (per pairset)

Proposed Response Response Status W
 PROPOSED REJECT.

This idea is captured in the text below the table.

Cl 33 SC 33.2.7.4 P 245 L 22 # 198
 Dwelley, David Linear Technology

Comment Type E Comment Status D Icon

The E2EP2PRunb section of this sentence is awkward, and E2EP2PRunb is used before it is defined:

"Icon-2P_unb is the maximum current the PSE is required to support over one of the pairs of same polarity under E2EP2PRunb condition in the POWER_ON state."

SuggestedRemedy
 Replace with:

"Icon-2P_unb is the maximum current the PSE is required to support over any pair in the POWER_ON state when unbalance effects are included."

Proposed Response Response Status W
 PROPOSED ACCEPT IN PRINCIPLE.

Cl 33 SC 33.2.7.4.1 P 246 L 6 # 199
 Dwelley, David Linear Technology

Comment Type E Comment Status D Icon

The PSE_P2PRunb and E2EP2PRunb acronyms are unnecessarily complicated. The descriptions and analysis in 33.2.7.4.1 make the nature of the unbalance clear - the acronym doesn't need to carry all the details.

SuggestedRemedy
 Replace with PSEunb and E2Eunb throughout this section and in section 33A.6.

Proposed Response Response Status W
 PROPOSED ACCEPT.

Cl 33 SC 33.2.7.4 P 245 L 19 # 200
 Dwelley, David Linear Technology

Comment Type E Comment Status D Icon

Hierarchy of "shalls" is not as clear as it could be:
 "PSEs shall meet ICon as specified in Table 33-11. Type 3 and Type 4 PSEs when connected to a single signature PD shall meet ICon-2P as specified in Table 33-11 item 4a."

SuggestedRemedy
 Add an "also":
 "PSEs shall meet ICon as specified in Table 33-11. Type 3 and Type 4 PSEs when connected to a single signature PD shall also meet ICon-2P as specified in Table 33-11 item 4a."

Proposed Response Response Status W
 PROPOSED ACCEPT.

See comment 153

Cl 33 SC 33.2 P 200 L 34 # 201
 Dwelley, David Linear Technology

Comment Type E Comment Status D Editorial

We changed "2-Event" Classification to "Multiple-Event" Classification a while ago - now "1-Event" and "Multiple-Event" don't match well. "Single-Event" fits better.

I recognize that this is changing a long-standing parameter name, but I think the additional clarity this change would bring is worth it.

SuggestedRemedy
 Change "1-Event" to "Single-Event" throughout the document (first instance at p200 line 34).

Proposed Response Response Status W
 PROPOSED ACCEPT.

IEEE P802.3bt D1.2 4P PoE 5th Task Force review comments

CI 33 SC 33.2.4.1 P 210 L 5 # 202
Dwellely, David Linear Technology

Comment Type E Comment Status D Editorial

We were either too aggressive or not quite aggressive enough cutting text last time:
"If a PSE performs detection using Alternative B see 33.2.5.5."

SuggestedRemedy

Either restore the original sentence from D1.1, or kill this sentence entirely and add (see 33.2.5.5) to the end of the previous sentence.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

We removed the sentence in order to not have the same requirement in two places.

Change sentence to:

"If a PSE performs detection using
Alternative B see 33.2.5.5. for more information on detection backoff requirements."

CI 33 SC 33.3.7.6 P 275 L 16 # 203
Dwellely, David Linear Technology

Comment Type E Comment Status D Cport

New text needs improving:
"Type 1, Type 2, and single-signature Type 3 PDs with classes 0 to 4 shall meet the requirement for Cport as defined in Table 33–18 item 9. Type 3 dual-signature PDs with class 0 to 4 shall meet the requirement for Cport as defined in Table 33–18 item 9 for each pairset. For class 5 and 6 single-signature PDs, if CPort_min = 10μF, transient behavior has no further requirements. For dual-signature class 5 PDs, this recommendation applies to each pairset. For class 7 and 8 single signature PDs, if CPort_min = 20μF, transient behavior has no further requirements. See 33.2.7.2 (TBD) or the transient conditions"

SuggestedRemedy

Change to:
"A PD shall continue to operate normally in the presence of transients at the PSE PI as defined in 33.2.7.2. A single-signature PD shall include Cport >= Cport_min as defined in Table 33–18 item 9. A dual-signature PD shall meet this requirement for each pairset. For Class 0-4 PDs, no further considerations are required to maintain operation during PSE transients.

PDs with power draw greater than Class 4 may require extra capacitance to maintain operation during PSE transients. Class 5 and 6 single-signature PDs can typically meet the requirement with CPort_min = 10μF. Class 5 dual-signature PDs should include these Cport values at each pairset. Class 7 and 8 single signature PDs can typically meet this requirement with CPort_min = 20μF."

Proposed Response Response Status W

PROPOSED ACCEPT.

CI 33 SC 33.2.7 P 243 L 45 # 204
Dwellely, David Linear Technology

Comment Type E Comment Status D Editorial

"Icon" appears several places in the draft in Editor's notes and in 33A-9. It appears to be a typo - 33-11 defines the parameter as "Icon".

SuggestedRemedy

Replace "Icon" with "Icon" throughout: I count 8 instances, on pages 243, 244, and 334.

Proposed Response Response Status W

PROPOSED ACCEPT.

EZ

IEEE P802.3bt D1.2 4P PoE 5th Task Force review comments

Cl 33 SC 33.2.7.11 P 250 L 45 # 205
 Dwelley, David Linear Technology
 Comment Type E Comment Status D Editorial
 Missing capitalization: "intra-pair..."
 This typo also appears in the contents (p22 line 19) but I suspect it will fix itself.
 SuggestedRemedy
 Change to "Intra-pair..."
 Proposed Response Response Status W
 PROPOSED ACCEPT.
 EZ

Cl 33 SC 33.2.7 P 240 L 44 # 206
 Dwelley, David Linear Technology
 Comment Type ER Comment Status X Editorial
 Table 33-11, item 4a: The Icon-2p-unb label makes less sense than before because of the change made in the D1.1 comment cycle that changed Icon-2p to Icon. The -unb suffix made sense when there was a standalone Icon-2p parameter but not now.
 SuggestedRemedy
 Change Icon-2p-unb to Icon-2p throughout: I count 6 locations on pages 240, 245, 246, and 276, and two more with _unb on pages 198 and 245.
 Also change the existing Icon-2p to Icon on p245 line 23 to be consistent.
 Proposed Response Response Status W
 Task Force to Discuss (Yair...)

Cl 33 SC 33.2.7 P 240 L 34 # 207
 Dwelley, David Linear Technology
 Comment Type T Comment Status D Editorial
 Parameter isn't completely clear for the 2-pair case:
 "Continuous output current capability in POWER_ON state over both pairsets"
 SuggestedRemedy
 Change to:
 "Continuous output current capability in POWER_ON state over all powered pairsets"
 Proposed Response Response Status W
 PROPOSED ACCEPT IN PRINCIPLE.
 OBE by comment 46.
 EZ

Cl 33 SC 33.2.7.7 P 248 L 43 # 208
 Dwelley, David Linear Technology
 Comment Type T Comment Status D Editorial
 -2pmin and -2pmax suffices are missing a space/underscore in several locations. In each case (example here is Ilim-2pmin) it looks like a new parameter is being defined where that is not the intent
 SuggestedRemedy
 Change to -2p min or -2p_min (or max as appropriate), whichever the style guide likes better.
 I count 11 mins, 2 maxs on pages 248-250 and 275
 Proposed Response Response Status W
 PROPOSED ACCEPT IN PRINCIPLE.
 I believe a space is needed before the min or max.
 EZ

IEEE P802.3bt D1.2 4P PoE 5th Task Force review comments

Cl 33 SC 33.2.7.4.1 P 246 L 10 # 209
 Dwelley, David Linear Technology

Comment Type T Comment Status D Icon

Leftover Icon-2p reference and some awkward language:
 "The PSE_P2PRunb determined by RPair_max and RPair_min ensures that along with any other parts of the system - i.e. channel (cables and connectors) and the PD, the maximum pair current due to E2EP2PRunb, is not exceeding Icon-2P-unb as defined in Table 33-11 during normal operating conditions. Icon-2P-unb maximum is the average pair current due to E2EP2PRunb that is higher than Icon-2P specified in Table 33-11."

SuggestedRemedy

Fix first sentence:
 "The PSE_P2PRunb parameter is chosen to ensure that unbalance in other parts of the system (cables, connectors and PD) will not cause the maximum pair current to exceed Icon-2P-unb (as defined in Table 33-11) during normal operating conditions."

Strike the second sentence.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Suggested remedy for first sentence is good.

Still need definition of Icon-2p-unb (or whatever we choose to call it now).

Cl 33 SC 33.2.7 P 240 L 38 # 210
 Dwelley, David Linear Technology

Comment Type T Comment Status D Editorial

Table 33-11, item 4a

Parameter label is unwieldy:
 "Pairset current due to E2ERunb within E2ERunb range for class X"

33.2.7.4a (now 33.2.7.4.1 - this should also be fixed) contains enough information about unbalance to make this clear.

SuggestedRemedy

Replace with "Pairset current including unbalance for class X" (four places).

Correct Additional Information column to point to 33.2.7.4.1.

Proposed Response Response Status W

PROPOSED ACCEPT.

EZ

Cl 1 SC 1.4.415 P 97 L 8 # 211
 Dwelley, David Linear Technology

Comment Type TR Comment Status D Definitions

Page number is from 802.3bx D3.2

The Type 1 PD definition in Clause 1 is broken:
 "1.4.415 Type 1 PD: A PD that does not provide a Class 4 signature during Physical Layer classification (see IEEE 802.3, Clause 33)."

Type 1 PSE and Type 2 definitions appear to be OK.

SuggestedRemedy

Change to:
 "1.4.415 Type 1 PD: A PD that provides a Class 0, 1, 2 or 3 signature during Physical Layer classification (see IEEE 802.3, Clause 33)."

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

This definition needs to be updated, but the suggested remedy can also describe a Type 3 PD.

Change to:
 "1.4.415 Type 1 PD: A PD that provides a Class 0, 1, 2 or 3 signature during Physical Layer classification (see IEEE 802.3, Clause 33)."

IEEE P802.3bt D1.2 4P PoE 5th Task Force review comments

CI 1 SC 1.4 P97 L 17 # 212
 Dwelley, David Linear Technology

Comment Type TR Comment Status D Definitions

Page number is from 802.3bx D3.2

Definitions for Type 3 and Type 4 PDs and PSEs are missing.

SuggestedRemedy

Add definitions:

Type 3 PD: A PD that provides a Class 6 or lower signature during Physical Layer classification, understands multiple-Event classification, and is capable of Data Link Layer classification (see IEEE 802.3, Clause 33).

Type 3 PSE: A PSE that supports PD Types 1-3 and supports Low MPS.

Type 4 PD: A PD that provides a Class 7 or 8 signature during Physical Layer classification, understands multiple-Event classification, and is capable of Data Link Layer classification (see IEEE 802.3, Clause 33).

Type 4 PSE: A PSE that supports PD Types 1-4 and supports 4-pair power and Low MPS.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

These definitions aren't perfect, but should be included so people can comment on them.

Add definitions:

Type 3 PD: A PD that provides a Class 6 or lower signature during Physical Layer classification, implements multiple-Event classification, and is capable of Data Link Layer classification (see IEEE 802.3, Clause 33).

Type 3 PSE: A PSE that supports PD Types 1-3 and supports Low MPS.

Type 4 PD: A PD that provides a Class 7 or 8 signature during Physical Layer classification, implements multiple-Event classification, and is capable of Data Link Layer classification (see IEEE 802.3, Clause 33).

Type 4 PSE: A PSE that supports PD Types 1-4 and supports 4-pair power and Low MPS.

CI 1 SC 1.4.425 P97 L 40 # 213
 Dwelley, David Linear Technology

Comment Type TR Comment Status D Definitions

Page number is from 802.3bx D3.2

The Vpd and Vpse definitions in Clause 1 are 2-pair centric:

"1.4.425 VPD: The voltage at the PD PI measured between any conductor of one power pair and any conductor of the other power pair (see IEEE 802.3, Clause 33).

1.4.426 VPSE: The voltage at the PSE PI measured between any conductor of one power pair and any conductor of the other power pair (see IEEE 802.3, Clause 33)."

SuggestedRemedy

Adjust to support 4-pair operation:

"1.4.425 VPD: The voltage at the PD PI measured between any conductor of a positive power pair and any conductor of the matching negative power pair (see IEEE 802.3, Clause 33).

1.4.426 VPSE: The voltage at the PSE PI measured between any conductor of a positive power pair and any conductor of the matching negative power pair (see IEEE 802.3, Clause 33)."

Proposed Response Response Status W

PROPOSED ACCEPT.

Need to make sure these terms have not been changed to -2p.

CI 33 SC 33.2.5 P227 L 42 # 214
 Schindler, Fred Seen Simply

Comment Type TR Comment Status X PSE Detection

A previous comment filed indicated why changing link segment to link section changes requirements. This same concern exists for all of these changes.

SuggestedRemedy

The Task Force should discuss the implications of restoring IEEE 802.3-2012 values. When I review the specification I see link section and link segment values used interchangeably. The text in this section lines 42 and 43 are an example of this. The group should decide what is required and change all occurrences of these words to a consistent usage and technical implications.

Proposed Response Response Status W

Task Force to discuss.

IEEE P802.3bt D1.2 4P PoE 5th Task Force review comments

Cl 33 SC 33.6.3.2 P 299 L 16 # 215
 Schindler, Fred Seen Simply
 Comment Type **TR** Comment Status **X** Management
 It does not appear to be worthwhile providing class 6 and 7 if they are within 3% of eachother.
 SuggestedRemedy
 Have the Task Force discuss whether Class 7 PD power should be increased. Provide an Editor's note for the decision if the value changes so that participants provide corrections for the text for the next Draft.
 Proposed Response Response Status **W**
 class 6 is only that high because of extended power.
 Task force to discuss

Cl 79 SC 79.3.2.61.1 P 343 L 32 # 216
 Schindler, Fred Seen Simply
 Comment Type **TR** Comment Status **D** DLL
 Clarify what a PD places in a PSE field.
 SuggestedRemedy
 Add after line 32,
 "A TLV generated by a PD shall set the field to 00."
 Proposed Response Response Status **W**
 PROPOSED ACCEPT.

Cl 79 SC 79.3.2.6a.2 P 343 L 36 # 217
 Schindler, Fred Seen Simply
 Comment Type **TR** Comment Status **D** DLL
 Clarify what a PD places in a PSE field.
 SuggestedRemedy
 Add after line 36,
 "A TLV generated by a PD shall set the field to 0000."
 Proposed Response Response Status **W**
 PROPOSED ACCEPT.

Cl 33 SC 33.2.5.01 P 228 L 36 # 218
 Schindler, Fred Seen Simply
 Comment Type **E** Comment Status **D**
 The sentence,
 "The connection check shall be rerun if power up fails to meet the timing requirements or anytime power is removed from both pairsets at the same time after reaching the POWER_UP state." may be improved.
 SuggestedRemedy
 Replace the text with,
 "The connection check shall be rerun if power up fails to meet the timing requirements or when power is removed from both pairsets after reaching the POWER_UP state."
 Proposed Response Response Status **W**
 PROPOSED ACCEPT IN PRINCIPLE.

Replace with:
 "The connection check shall be rerun before applying power if power up fails to meet the timing requirements or anytime power is not present on at least one pairset after reaching the POWER_UP state."

Cl 33 SC 33.2.4.4 P 211 L 41 # 219
 Schindler, Fred Seen Simply
 Comment Type **ER** Comment Status **D** Editorial
 Fix typo "Tyep".
 SuggestedRemedy
 Use "Type".
 Proposed Response Response Status **W**
 PROPOSED ACCEPT IN PRINCIPLE.
 OBE by comment 96.

IEEE P802.3bt D1.2 4P PoE 5th Task Force review comments

CI 33 SC 33.2.5.0a P 228 L 14 # 220
 Schindler, Fred Seen Simply
 Comment Type ER Comment Status D Editorial
 The section repeats a requirement. Text,
 "The connection check shall be completed before classification is performed on any pairset." is not required because the same requirement is covered in line 5.
 SuggestedRemedy
 Strike the referenced text on line 14.
 Proposed Response Response Status W
 PROPOSED ACCEPT.
 EZ

CI 33 SC 33.2.7.6 P 248 L 26 # 221
 Schindler, Fred Seen Simply
 Comment Type ER Comment Status X PSE Power
 The existing text,
 " When connected to a single signature PD, a Type 3 or Type 4 PSE should (TBD) remove power from both pairsets before the current exceeds the "PSE upperbound template" on either pairset."
 provides unnecessary guidance. The prior sentence,
 "Power shall be removed from a pairset of a PSE before the pairset current exceeds the "PSE upperbound template" in Figure 33-14."
 provides requirement. On pages 239 to 240,
 "Power may be removed from both pairsets any time power is removed from one pairset.
 Editor's Note: All other instances of the above statement to be removed from draft. If commentators find any please comment against them." The first sentence called out in this comment is fits the concern expressed in the Editor's note.
 The requirement in this section prevents one or both of the pairsets from crossing the PSE upperbound template. Concerns about delays in turning off one pairset then a second pairset may not warranted because the device connected to the PSE is no longer considered a PD. Having the ability to control pairsets individually permits system providers to build systems capable of removing power from a fault while still providing power on a nonfaulting pairset.
 SuggestedRemedy
 Strike the sentence,
 " When connected to a single signature PD, a Type 3 or Type 4 PSE should (TBD) remove power from both pairsets before the current exceeds the "PSE upperbound template" on either pairset."
 Proposed Response Response Status W
 Task Force to discuss.

CI 33 SC 33.2.9.1.1 P 254 L 21 # 222
 Schindler, Fred Seen Simply
 Comment Type ER Comment Status D Editorial
 The following text is no longer required and should be removed,
 SuggestedRemedy
 Remove,
 "Editor's Note: Yair to review AC MPS for 4-pair."
 Proposed Response Response Status W
 PROPOSED ACCEPT IN PRINCIPLE.
 OBE by 64
 EZ

CI 33 SC 33.3.5.1 P 265 L 4 # 223
 Schindler, Fred Seen Simply
 Comment Type ER Comment Status D PD Classification
 The text,
 "PDs implementing a Multiple-Event class signature shall return Class 4 in accordance with the maximum power draw, PClass_PD, as specified in Table 33-18."
 may confuse the reader.
 SuggestedRemedy
 Replace the sentence with,
 PDs implementing a Multiple-Event class signature shall return Class 4 in accordance with the maximum power draw, PClass_PD, as specified in Table 33-18 and the responses specified in Table 33-16a."
 Proposed Response Response Status W
 PROPOSED ACCEPT.

IEEE P802.3bt D1.2 4P PoE 5th Task Force review comments

Cl 33 SC 33.2.4.6 P 218 L 1 # 224
 Schindler, Fred Seen Simply
 Comment Type ER Comment Status X Editorial
 Editor's note,
 "Editor's Note: "Mutual identification not complete" in above paragraph needs to be clear.
 Team to pay
 close attention to above paragraph during reviews."
 I do not understand why this note exists.
 SuggestedRemedy
 Briefly discuss if anyone has a concern with the reference section and remove the Editor's
 note if no concern remains. Otherwise add some specifics to the Editor's note.
 Proposed Response Response Status W
 Task force to discuss

Cl 33 SC 33.2.5 P 227 L 35 # 225
 Schindler, Fred Seen Simply
 Comment Type TR Comment Status D PSE Power
 The existing sentence,
 "In any operational state, the PSE shall not apply operating power to a pairset until the
 PSE has successfully detected a valid signature over that pairset."
 may be improved by permitting allowed specific system implementations.
 SuggestedRemedy
 Replace with,
 "In any operational state, the PSE shall not apply operating power to a pairset until the
 PSE has successfully detected a valid signature over that pairset. A PSE powering a
 single-signature PD with less than or equal to class 4 power levels may toggle between 2-
 pair and 4-pair power."
 Proposed Response Response Status W
 PROPOSED REJECT.
 This is not the place for the 2/4-pair power transition. Additionally, that sentence exists in
 the appropriate section.

Cl 33 SC 33.2.6 P 233 L 22 # 226
 Schindler, Fred Seen Simply
 Comment Type TR Comment Status D PSE Classification
 PSEs may indicate that they are not capable of providing more than class-4 power by
 ending classification after 2 or 3 events. Table 33-7 indicates 2 o 3 events but Table 33-3,
 omit 3 events, which is confusing.
 SuggestedRemedy
 Indicate that 3 events may be provided by Type-3 and Type-4 PSEs in Table 33-3 on page
 214.
 Proposed Response Response Status W
 PROPOSED REJECT.
 Class_num_events in Table 33-3 is a maximum. Table 33-7 is not the maximum, it is the
 number of events required for that power.

Cl 33 SC 33.2.7 P 239 L 25 # 227
 Schindler, Fred Seen Simply
 Comment Type TR Comment Status X PSE Power
 Legacy text,
 "PSE behavior conforms to the state diagrams in Figure 33-9,Figure 33-9 continued, and
 Figure 33-10.
 When the PSE provides power to the PI, it shall conform with Table 33-11."
 that states a requirement has been stricken from the spec.
 SuggestedRemedy
 Restore the text with the following TBD or replace with reference to the appropriate state
 diagrams.
 "PSE behavior conforms to the state diagrams in Figure 33-9,Figure 33-9 continued, Figure
 TBD, and Figure 33-10. When the PSE provides power to the PI, it shall conform with
 Table 33-11."
 Proposed Response Response Status W
 Task Force to discuss.

IEEE P802.3bt D1.2 4P PoE 5th Task Force review comments

CI 33 SC 33.1.4 P 198 L 8 # 228
 Schindler, Fred Seen Simply

Comment Type TR Comment Status X Cabling

Changes to the text, "A power system consists consisting of a single PSE, link segment, and a single PD, and the link section connecting them. " have changed legacy requirements.

1.4.241 link section: The portion of the link from the PSE to the PD.
 1.4.242 link segment: The point-to-point full-duplex medium connection between two and only two Medium Dependent Interfaces (MDIs).

We had a "link segment" that changed to "link section", which removes that requirement that a full-duplex medium be used.

SuggestedRemedy

The Task Force should discuss these implications. The preferred solution is to replace "link section" with "link segment".

Proposed Response Response Status W

Task Force to discuss.

CI 33 SC 33.3.1 P 255 L 51 # 229
 Schindler, Fred Seen Simply

Comment Type TR Comment Status X 57V

New PD Types will need to accept up to 57V on each pair set. Fix text, "The PD shall withstand any voltage from 0 V to 57 V at the PI indefinitely without permanent damage."

SuggestedRemedy

Replace the Draft text with,

Solution-1:

Type 1 and Type 2 PDs shall withstand any voltage from 0 V to 57 V at the powered pairset indefinitely without permanent damage. Type 3 and Type 4 PDs shall withstand any voltage from 0 V to 57 V on both pair sets indefinitely without permanent damage.

Solution-2:

Type 1 and Type 2 PDs shall withstand any voltage from 0 V to 57 V at the powered pairset indefinitely without permanent damage. Type 3 and Type 4 PDs shall withstand any voltage from 0 V to 57 V on both pair sets or between pairsets indefinitely without permanent damage.

Proposed Response Response Status W

Task Force to discuss.

IEEE P802.3bt D1.2 4P PoE 5th Task Force review comments

Cl 33 SC 33.2.7.11a P 251 L 3 # 230
Schindler, Fred Seen Simply

Comment Type TR Comment Status X Types

The added section and choices made related to Type power may confuse the market place. Previously we had Types that indicated abilities, one of which was maximum expected power. Type 3 and 4 introduce devices that no longer guaranty a specific power level. These choices require new terms to be used and explained.

Before we had a Type-X system that indicated cabling, connectors, power source, and power acceptance ability.

Now we have Type-X PSE that cannot provide full power to a Type-X PD and the system cabling infrastructure needs to meet the Type-X PSE needs. If I change the Type-X PSE to a PSE that supports the maximum class possible for Type-X the cabling infrastructure needs to be changed.

Using the suggested solution removes many corner-cases and footnotes, which makes the specification easier to understand.

SuggestedRemedy

The Task Force should discuss these implications and the need for so many variants of the same Type to determine how to proceed.

The preferred solution is to require a PSE of Type-X to provide Ptype(min) for that type.

Proposed Response Response Status W

Task Force to discuss.

Cl 33 SC 33.3.5 P 264 L 43 # 231
Schindler, Fred Seen Simply

Comment Type TR Comment Status D PD Classification

The footnote on Table 33-15a and text below the table may confuse the reader. If a PD already supports DLL then it should continue to support DLL whether is it consuming less than class-4 power or not.

SuggestedRemedy

Replace footnote 1 with,
"Any PD not capable of drawing more than class-3 power levels may omit DLL support."

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 33 SC 33.3.7.6 P 275 L 5 # 232
Schindler, Fred Seen Simply

Comment Type TR Comment Status X Pres: Fred1

New PD Types need to have their current demands constrained.

SuggestedRemedy

A presentation will be provided that cover why this section exists and why new PD Types should have the same constrains placed on them. Baseline text may also be proposed.

This section is based on work done in IEEE 802.3at see

http://www.ieee802.org/3/at/public/2007/05/avetteth_0507.pdf

http://www.ieee802.org/3/at/public/2007/03/schindler_1_0307.pdf

Proposed Response Response Status W

Wait for presentation

Cl 33 SC 33.5.1.1 P 293 L 8 # 233
Schindler, Fred Seen Simply

Comment Type TR Comment Status X Management

Changes in Table 33-21 are not correct and text is missing below the table.

SuggestedRemedy

On line 8 change table column one, "11.15.8" to "11.15.7".

On line 12 last table column add, "R/W".

After line 43 insert text,
33.5.1.1.x Force Power Test Mode Pairset Selection (11.7:6)
Bits 11.7:6 determine which PSE Alternative or Alternatives are enabled when Force Power Test Mode is enabled.

Proposed Response Response Status W

I don't understand the suggested remedy. Task Force to discuss.

IEEE P802.3bt D1.2 4P PoE 5th Task Force review comments

Cl 79 SC 79.3.2.4 P 341 L 2 # 234
Schindler, Fred Seen Simply

Comment Type TR Comment Status D DLL

The new sentence,
"A Type 3 or Type 4 device shall set the bits in power type to TBD."

Could be implementation specific but a preferred solution is provided below, which permits legacy Types to respond to new Types with the highest power levels possible.

SuggestedRemedy

Replace the referenced sentence with,
"A Type 3 or Type 4 device shall set the bits in power type to the highest Type the TLV generating device supports."

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 79 SC 79.3.2.6a P 342 L 52 # 235
Schindler, Fred Seen Simply

Comment Type TR Comment Status D DLL

Replace the Editor's note on line 52 with the requested text.

SuggestedRemedy

Replace the Editor's note on line 52 with,
"The PSE power status value field shall contain the PSE's bit-map of the PSE power pair, and PSE power class, defined in Table 79-6a and is reported for the device generating the TLV."

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 79 SC 79.3.2.6b P 343 L 40 # 236
Schindler, Fred Seen Simply

Comment Type TR Comment Status D DLL

Replace the Editor's note on line 40 with the requested text.

SuggestedRemedy

Replace the Editor's note on line 40 with,
"The System setup value field shall contain the device bit-map of the Power type, PD 4P-ID, and PD PI defined in Table 79-6b and is reported for the device generating the TLV."

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 33 SC 33.2.4.2 P 210 L 37 # 237
Schindler, Fred Seen Simply

Comment Type TR Comment Status D Editorial

In D1.0 comment 229 struckout text,
""both_alts_valid:A Type 3 or Type 4 PSE has detected a PD requesting power on both pair sets." This was not done for D1.1 or D1.2. The variable both_alts_valid was replaced by a do_detection state.

SuggestedRemedy

Replace text,
"Insert new variables both_alts_valid, PD_signature and PD_4pair_candidate as follows:"
With,
"Insert new variables PD_4pair_candidate as follows:"

Strike out text on lines 40 to 43,

"both_alts_valid

This variable is provided for Type 3 and Type 4 PSEs.
Values:False:do_detection does not yield "valid" on both pairsets.
True: do_detection yields "valid" on both pairsets."

Strike Editor's Note,

"Editor's Note: The above parameter (both_alts_valid) need to be refined by comments. These should be reviewed as connection check text is adopted."

Proposed Response Response Status W

PROPOSED ACCEPT.

This should have been done already.

EZ.

Cl 33 SC 33.3.5.3 P 268 L 5 # 238
Picard, Jean Texas Instruments

Comment Type TR Comment Status D PD Classification

The PD needs more margin for TACS to keep complexity down.

SuggestedRemedy

Increase the maximum value from 84.5 ms to 87.5 ms.

Proposed Response Response Status W

PROPOSED ACCEPT.

See comment 239.

IEEE P802.3bt D1.2 4P PoE 5th Task Force review comments

Cl 33 SC 33.3.5.2.1 P 267 L 15 # 239
 Picard, Jean Texas Instruments
 Comment Type **TR** Comment Status **D** PD Classification
 The PD needs more margin for TLCF_PD to keep complexity down.
 SuggestedRemedy
 Increase the maximum value from 84.5 ms to 87.5 ms.
 Proposed Response Response Status **W**
 PROPOSED ACCEPT.

Cl 33 SC 33.2.6.2 P 238 L 41 # 240
 Picard, Jean Texas Instruments
 Comment Type **TR** Comment Status **D** PSE Classification
 The PSE TLCF spec needs to readjusted to align with the PD proposed changes on TACS and TLCF_PD.
 SuggestedRemedy
 Change the TLCF range from 85-100 ms to 88-105 ms.
 Proposed Response Response Status **W**
 PROPOSED ACCEPT.
 See comments 53, 52, 54, 238, 239

Cl 33 SC 33.2.7 P 241 L 43 # 241
 Picard, Jean Texas Instruments
 Comment Type **TR** Comment Status **X** PSE Power
 there is too much margin for ILIM-2P
 SuggestedRemedy
 Reduce ILIM-2P class 8 to a value slightly below 1A
 Proposed Response Response Status **W**
 What is the reason behind this? Yair do you agree?

Cl 33 SC 33.2.7 P 241 L 38 # 242
 Picard, Jean Texas Instruments
 Comment Type **TR** Comment Status **X** PSE Power
 there is too much margin for ILIM-2P
 Table 33-11
 SuggestedRemedy
 Reduce ILIM-2P class 6 to a value slightly below 0.7A
 Proposed Response Response Status **W**
 What is the reason behind this? Yair do you agree?

Cl 33 SC 33.3.5 P 264 L 43 # 243
 Picard, Jean Texas Instruments
 Comment Type **TR** Comment Status **D** PD Classification
 The statement about Type 3 does not align with table 33-13 for class 1-3
 SuggestedRemedy
 Restate the sentence to Indicate that for class 1-3 SS, LLDP is optional
 Proposed Response Response Status **W**
 PROPOSED ACCEPT IN PRINCIPLE.
 OBE by comment 181

Cl 33 SC 33.3.5.3 P 267 L 37 # 244
 Picard, Jean Texas Instruments
 Comment Type **TR** Comment Status **D** PD Classification
 To indicate Autoclass, same requirement as indicated in table 33-16 needs to apply.
 SuggestedRemedy
 Replace with "a PD implementing Autoclass shall reduce its classification current at TACS (as defined in Table 33-17a), resulting in a classification signature of '0' (as shown in table 33-16 for type 3) for the remainder of CLASS_EV1."
 Proposed Response Response Status **W**
 PROPOSED ACCEPT.
 This means PDs need to draw at least 1mA during the TACS period so that the PI discharges.

IEEE P802.3bt D1.2 4P PoE 5th Task Force review comments

CI 33 SC 33.3.7.4 P 273 L 23 # 245
 Picard, Jean Texas Instruments

Comment Type TR Comment Status X PD Power

The peak power definition for class 6 and 8 is not consistent with statement of page 272 line 20 (referring to PSE Pclass).

SuggestedRemedy

Clarify how the peak power definition should be applied for class 6 and 8.

Proposed Response Response Status W

I don't understand the suggested remedy.

CI 33 SC 33.3.7 P 270 L 13 # 246
 Picard, Jean Texas Instruments

Comment Type TR Comment Status D PD Power

Ppeak_PD is not mentioned for class 6-8

SuggestedRemedy

Clarify how the peak power requirement should be applied for class 6 and 8 and define it accordingly for class 5 and 7, as well as for class 6 and 8.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

OBE by comment 12

CI 33 SC 33.2.4.1 P 210 L 5 # 247
 Picard, Jean Texas Instruments

Comment Type ER Comment Status D Editorial

Sentence seems imcomplete

SuggestedRemedy

Remove parentheses around "see 33.2.5.5"

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

OBE by comment 202.

CI 33 SC 33.3.7.10 P 276 L 37 # 248
 Picard, Jean Texas Instruments

Comment Type TR Comment Status X PD Power

ICON_2P max for class 5 and 6 may be too tight to pass the test described (using only 2.5m cable) due to diode mismatch (including temperature differences). To avoid later interoperability problems in the field related to diode selection.

SuggestedRemedy

If test conditions remain the same, need to verify and confirm if ICON-2P for class 6 allows sufficient margin. If not the case, increase its value accordingly.

Proposed Response Response Status W

What is the suggested remedy? Add editor's note?

CI 33 SC 33.2.4 P 209 L 36 # 249
 Dove, Daniel Dove Networking Solut

Comment Type ER Comment Status D Editorial

TBD No longer necessary

SuggestedRemedy

Strike"(TBD)" and replace with "33-9a through 33-9g and Figure 33-10."

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

We need to see if Figure 33-10 will apply to Type 3/4 or will we need to create a new one...

Partial OBE by comment 61.

EZ

CI 33 SC 33.2.4.4 P 209 L 44 # 250
 Dove, Daniel Dove Networking Solut

Comment Type ER Comment Status X Pres: SD

Additional Text required

SuggestedRemedy

Insert the following; "For Type 3 and Type 4 PSEs, the PI will consist of either an Alt-A pairset, an Alt-B pairset, or both Alt-A and Alt-B pairsets being controlled by pairset controllers. The pairset controller will utilize timers, variables and functions defined in this subclause as either a single controller, or as two controllers using local instances of each timer, variable and/or function."

Proposed Response Response Status W

Wait for presentation

IEEE P802.3bt D1.2 4P PoE 5th Task Force review comments

CI 33 SC 33.2.4.3 P 209 L 23 # 251
 Dove, Daniel Dove Networking Solut

Comment Type TR Comment Status X Pres: SD

Type 3 and Type 4 PSEs will use Pairset Controllers and this should be identified early in the constant descriptions.

SuggestedRemedy

Modify as follows; "The PSE and Pairset Control state diagrams use the following constants. For Type 3 and Type 4 PSEs, each pairset controller will maintain a local copy of each constant"

Proposed Response Response Status W

Wait for PSE State Diagram Presentations

CI 33 SC 33.2.4.4 P 209 L 36 # 253
 Dove, Daniel Dove Networking Solut

Comment Type TR Comment Status X Pres: SD

New variables to be added

SuggestedRemedy

Insert the following; "PS_Det_Fail_A This variable provides an indication from the Pairset A controller that a failure to detect has occurred. PS_Det_Fail_B This variable provides an indication from the Pairset B controller that a failure to detect has occurred.Values: True: The pairset controller has timed out when attempting detection.False: The pairset controller has not timed out when attempting detection."

Proposed Response Response Status W

Wait for presentation

CI 33 SC 33.2.4.4 P 209 L 49 # 254
 Dove, Daniel Dove Networking Solut

Comment Type TR Comment Status X Pres: SD

PD_4pair_candidate no longer required

SuggestedRemedy

Replace PD_4pair_Candidate with PD_Alt, replace the sentence "This variable is a function of the results of detection, connection_check and an additional 4PID method" with "This variable is a result of the function do_PD_Check." Under Values, delete the text for False and True, and insert the following; "A: The PD is a candidate for accepting power on Alt-A B: The PD is a candidate for accepting power on Alt-B Both: The PD is a candidate for accepting power on both Alt-A and Alt-B simultaneously"

Proposed Response Response Status W

wait for presentation

CI 33 SC 33.2.4.4 P 212 L 52 # 255
 Dove, Daniel Dove Networking Solut

Comment Type TR Comment Status X Pres: SD

Need to add variables to address pairset operation as independent for each pairset controller.

SuggestedRemedy

Add: mr_ps_enable:
 A control variable that selects Pairset operation and test functions. This variable is provided by a management interface that may be mapped to the PSE Control register PS Enable A, or PS Enable B bits (11.9 and 11.8 respectively), as described below, or other equivalent functions.
 Values: True - The pairset function is defined by PSE Control register bits 1:0
 False - The pairset function is disabled

Proposed Response Response Status W

Wait for presentation

CI 33 SC 33.2.4.4 P 213 L 4 # 256
 Dove, Daniel Dove Networking Solut

Comment Type TR Comment Status X Pres: SD

pi_powered should either be a local PS_Controller variable, or we need to have one for each pairset. For instance, one pairset may be unpowered, while the other is powered.

SuggestedRemedy

replace "PSE" with "pairset controller". I believe that this (replacing PSE with pairset controller) is going to be needed in multiple locations.

Proposed Response Response Status W

Wait for presentation

CI 33 SC 33.2.4.5 P 215 L 2 # 257
 Dove, Daniel Dove Networking Solut

Comment Type TR Comment Status X Pres: SD

We need to add tcc2det_timer into this subclause.

SuggestedRemedy

Add tcc2det_timer for state diagram to start, stop and/or identify when the timer is done.
 Defined as:
 Add tcc2det_timer for state diagram to start, stop and/or identify when the timer is done.
 Defined as:
 tcc2det_timer - A timer used to limit the duration from connection_check function being performed until detection function is started

Proposed Response Response Status W

Wait for Presentation.

IEEE P802.3bt D1.2 4P PoE 5th Task Force review comments

Cl 33 SC 33.2.4.6 P 217 L 10 # 258
 Dove, Daniel Dove Networking Solut

Comment Type TR Comment Status X Pres: SD

The values for the do_detection function don't align with my proposed pair-set control approach. Each detection is done by the pairset controller, thus only a single pairset is under consideration. This returns the function results to their original values.

SuggestedRemedy

delete Valid_A, Valid_B and Valid_AB references.

Proposed Response Response Status W

Wait for presentation.

Cl 33 SC 33.2.4.6 P 218 L 104 # 259
 Dove, Daniel Dove Networking Solut

Comment Type TR Comment Status X Pres: SD

Based on the latest proposal for the state diagram, we need to add a function called do_PD_check.

SuggestedRemedy

Insert the following; do_PD_check_
 This function initiates the PD_check in Section 33.2.5.0b. This function returns the following variable:
 PD_Alt: This variable indicates which pairsets are to be considered a candidate for accepting power from the PSE.
 Values:
 A - The PD is a candidate for receiving power on the Alt-A pairset.
 B - The PD is a candidate for receiving power on the Alt-B pairset.
 Both - The PD is a candidate for receiving power on both the Alt-A and Alt-B pairsets simultaneously.

Proposed Response Response Status W

Wait for presentation

Cl 33 SC 33.2.4.7 P 221 L 1 # 260
 Dove, Daniel Dove Networking Solut

Comment Type TR Comment Status X Pres: SD

The latest proposal for the Type 3 and Type 4 PSE State Diagram includes a higher-level hierarchical drawing, and an approach where each pairset is controlled independently for the case of a dual-signature PD, and/or a single pair-set controller (with both pairsets controlled by it).

SuggestedRemedy

Insert the attached state diagrams with appropriate color changes and removal of comments as shown in T3T4PSEStateDiagramV1.3a.pptx.

Proposed Response Response Status W

Wait for presentaiton

Cl 33 SC 33.2.5 P 227 L 39 # 261
 Dove, Daniel Dove Networking Solut

Comment Type TR Comment Status D PSE Powering

Regarding this Editor's Note: I believe that unless its imperative to support, having a SS Type 3 or Type 4 PD precludes powering off one pairset. The relevant issue is that the PSE State Diagram does not allow a single signature process to have different power states on the different pair-sets. Adding such would substantially increase complexity. Example; What state would a Type 3 PSE with single PS Control state machine, powering a single-signature PD be in if it removed power on one pairset while keeping power on the other?

SuggestedRemedy

Remove the Editor's note and leave text as is.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

OBE by comment 35.

IEEE P802.3bt D1.2 4P PoE 5th Task Force review comments

Cl 33 SC 33.2.5 P 228 L 5 # 262
 Dove, Daniel Dove Networking Solut

Comment Type ER Comment Status D Connection Check

The words "that will deliver" suggest that power WILL be delivered on both pairsets.

SuggestedRemedy

Replace "that will deliver" with "capable of delivering".

Proposed Response Response Status W

PROPOSED REJECT.

"that will deliver" is the intent of the sentence. If a type 3/4 PSE will only deliver power over 1 pairset, it does not need to do a connection check.

Cl 33 SC 33.2.5 P 232 L 2 # 263
 Dove, Daniel Dove Networking Solut

Comment Type TR Comment Status X Pres: SD

4PID has been deprecated (in my proposal) by PD_Check.

SuggestedRemedy

Replace "4PID" with "PD_Check" in all instances of text using search/replace, remove the TBD, delete "the detection state" and replace with "measurements on" and delete "mutual identification". Replace PD_4pair_candidate" with "PD_Alt".

Proposed Response Response Status W

Wait for presentation.

Cl 33 SC 33.2.7.1 P 244 L 43 # 264
 Dove, Daniel Dove Networking Solut

Comment Type TR Comment Status D PSE Power

If we are going to allow this, we need to address the stability issues and potential interoperability problems that may occur if a PSE suddenly removes power from one pairset, and also how to deal with applying power to that pairset without creating stability problems.

SuggestedRemedy

Remove the added text on lines 43 and 44.

Proposed Response Response Status W

PROPOSED REJECT.

Do you know of any stability or interoperability problems that may occur.

There are many systems that already do this...

Cl 33 SC 33.5.1.1 P 292 L 52 # 265
 Dove, Daniel Dove Networking Solut

Comment Type TR Comment Status X Management

We need bits in the PSE Control Register that control the state of each pairset independently from the overall PSE configuration. For instance, one pairset could be disabled while the other enabled or in forced-power mode.

SuggestedRemedy

Insert row for bit 11.9 PS Disable A
 Insert row for bit 11.8 PS Disable B

These bits identify whether the PSE Enable bits apply to the pairset A or B. If 0, the PSE Enable bits apply and default behavior is to follow the order of bits 1:0. If 1, the PSE Enable bits do not apply and the pairset is disabled. Note: I chose this polarity to keep consistent with existing implementations where those bits would naturally be zero yet pairset operation functions based upon the bits in values 1:0. Additional note: For Type 3 and Type 4 PSEs, one would expect the bits 1:0 to control both pairsets the same way when attached to a Type 3/4 SS PD This can be done by setting bits3:2 to '11' An alternative approach to this would be to define separate registers for PS_AltA and PS_AltB or identify them as local registers per pairset.

Proposed Response Response Status W

Task Force to discuss

Cl 00 SC 0 P 6 L 15 # 266
 Jones, Chad Cisco

Comment Type E Comment Status D Editorial

missing comment editor credit

SuggestedRemedy

add: David Abramson, IEEE P802.3bt DTE Power Via MDI over 4-Pair Task Force Comment Editor

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Awww, Thanks man.

EZ

IEEE P802.3bt D1.2 4P PoE 5th Task Force review comments

Cl 33 SC 33.1.4 P 198 L 9 # 267
 Jones, Chad Cisco
 Comment Type E Comment Status D Editorial
 Types are not introduced, they just magically appear
 SuggestedRemedy
 add a second sentence to the paragraph: "PSEs and PDs are categorized by Type." Then capitalize Type in the next sentence: "The power system is defined by the lowest Type..."
 Proposed Response Response Status W
 PROPOSED ACCEPT.
 EZ

Cl 33 SC 33.1.4 P 198 L 32 # 268
 Jones, Chad Cisco
 Comment Type T Comment Status X Cabling
 Table 33-1, last row, last column. We may need to adjust the cabling specs for Type 4 systems based on the regulations currently being drafted in the National Electric Code.
 SuggestedRemedy
 No change to suggest yet. Wanted a placeholder in the comment database to which to attach possible changes devised at the meeting.
 Proposed Response Response Status W
 Task Force to discuss

Cl 33 SC 33.2.0a P 200 L 45 # 269
 Jones, Chad Cisco
 Comment Type T Comment Status X Types
 Table 3301a. Comment #72 in D1.1 made some unintended changes that cause problems. The second column simply states "maximum class supported" and states Class 8. Join this with the information in Table 33-3 on page 214 that states Type 4 can have class_num_events, of 1,2,4,5 and this implies that we can make a Type 4 Class 0-3 system. The desire to bring the new features invented for 802.3bt to legacy systems is handled by allowing Type 3 systems class_num_events of 1,2,4. extending this to Type 4 causes a couple of problems:
 1. we now have two OPTIONS for new Class 0-3 systems and three total OPTIONS for Classes 0-3 systems. to quote Geoff: options bad, standards good.
 2. allowing a Type 4 Class 0-3 system implies that you can extend the 'improvements' made to T4 to these lower power systems; for instance, a single polarity PSE. We are already aware of some problems with legacy devices.
 The improvements for Type 4 are easily defended for a high power, engineered system but not so easily defended for the low power systems, (see MDI/MDIX addition required in AF to gain WG approval).

SuggestedRemedy
 Undo the changes made from comment #72 in D1.1. At a minimum, change Table 33-3 on page 214, line 39, Type 4 class_num_events from "1,2,4,5" to "5"
 Proposed Response Response Status W
 Task Force to discuss.

Cl 33 SC 33.2.4.1 P 210 L 5 # 270
 Jones, Chad Cisco
 Comment Type E Comment Status D Editorial
 "If a PSE performs detection using Alternative B (see 33.2.5.5)" This sentence looks lonely, and a lot of unnecessary text. Perhaps it's hard to see all this stuff without the version of the draft that doesn't show the change bars (I will request a clean version of the draft for D1.3 in addition to change bars).
 SuggestedRemedy
 add "(see 33.2.5.5)" to the end of the previous paragraph and delete this sentence.
 Proposed Response Response Status W
 PROPOSED ACCEPT IN PRINCIPLE.
 OBE by comment 202.

IEEE P802.3bt D1.2 4P PoE 5th Task Force review comments

CI 33 SC 33.3.1 P 255 L 51 # 271
Jones, Chad Cisco

Comment Type T Comment Status X 57V

Still looking for the proper wording for the understood implied specification: "The PD shall withstand any voltage from 0 V to 57 V at the PI indefinitely without permanent damage."

SuggestedRemedy

Type 1 and Type 2 PDs shall withstand any voltage from 0V to 57V at the PI indefinitely without permanent damage.

Type 3 and Type 4 PDs shall withstand any voltage or combination of voltages from 0V to 57V across any polarity combination of the Mode A pairset, the Mode B pairset, and both Mode A and Mode B pairsets (defined in Table 33-13) indefinitely without permanent damage.

These tests shall be run with the two conductors of each tested pair at the same voltage potential.

Proposed Response Response Status W

Task Force to discuss.

This language would cause problems for the "half active bridge" implementation that is commonly used.