

IEEE P802.3bt D1.7 4-Pair Power-over-Ethernet 10th Task Force review comments

Cl 00 SC 0 P L # 2
 Anslow, Pete Ciena

Comment Type ER Comment Status D Editorial

Not all changes in the draft have an associated editing instruction

SuggestedRemedy

Go through the draft making sure that all changes have an associated editing instruction. This includes at least 33A.5, Annex 33B, Annex 33C, Annex 33D, Annex 33E

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 00 SC 0 P L # 1
 Anslow, Pete Ciena

Comment Type ER Comment Status D Editorial

In general, for amended clauses, only the text of subclauses that are being changed are included.

Understanding that for Clause 33, the Task Force has decided to replace the whole Clause, this does not apply to other amended clauses.

SuggestedRemedy

In preparation for a request to proceed Working Group Ballot, go through the entire draft and for all amended clauses (except Clause 33) and remove all subclauses that are not being changed.

For Clause 25 this involves:

Leave heading for 25.4 but remove text

Remove heading and content for 25.4.1 through 25.4.4

Change editing instruction to: "Change text of 25.4.5 as follows:" (we do not use the term "section")

Remove heading and content for 25.4.5.1 through 25.4.6

Below heading for 25.4.7 add editing instruction: "Change text of 25.4.7 as follows:"

Remove heading and content for 25.4.5.1 through to the end of the clause.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Editor to follow suggested remedy, but I believe some of the sections are there because we believe changes will be made to them or that they are necessary for review. Any unchanged subsection to be removed before D2.0.

Cl 33 SC P L # 19
 Darshan, Yair Microsemi

Comment Type ER Comment Status D Editorial

For the next draft, it is preferred to show the new editorial marks (insertions and deletions) in addition to the changing bars. It helps to see the changes without the need to compare two documents.

SuggestedRemedy

For next Drafts: show the new editorial marks (insertions and deletions) in addition to the changing bars.

Proposed Response Response Status Z

REJECT.

This comment was WITHDRAWN by the commenter.

We are replacing the whole clause, so the editing marks do not get shown.

I believe what you are asking for would create a bunch of work for our editor.

TFTD

Cl 1 SC 1 P 1 L 1 # 201
 Yseboodt, Lennart Philips

Comment Type ER Comment Status X Editorial

Do you want me to reset the change bars in Clause 33 for D1.8 ?

SuggestedRemedy

Indicate YES/NO.

Proposed Response Response Status W

TFTD

IEEE P802.3bt D1.7 4-Pair Power-over-Ethernet 10th Task Force review comments

Cl 1 SC 1 P1 L1 # 202
Yseboodt, Lennart Philips

Comment Type ER Comment Status D Editorial

As we are preparing for D2.0 in July, we need to be getting rid of all Editor's Notes.

SuggestedRemedy

Remove all Editor's Notes that do not specifically say "remove prior to publication".

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

If anyone has an editor's note they would like to see remain in the document (other than those cited in the suggested remedy), please make a note of it and be ready to let me know when we get to this comment.

TFTD

Cl 30 SC 30.12.2.1.18a P37 L22 # 3
Anslow, Pete Ciena

Comment Type E Comment Status X Management

Adding 30.12.2.1.18a, 30.12.2.1.18b, 30.12.2.1.18c, 30.12.2.1.18d means that Table 30-7 should be modified with new rows.

Similarly for 30.12.3.1.18a, 30.12.3.1.18b, 30.12.3.1.18c, 30.12.3.1.18d

SuggestedRemedy

Show additions to Table 30-7 for new subclauses.

Proposed Response Response Status W

Where is Table 30-7. I don't see it in our draft.

TFTD

Cl 33 SC 33.1.3 P46 L1 # 135
Yseboodt, Lennart Philips

Comment Type E Comment Status D Editorial

"It should be noted that the cable references use "DC loop resistance," which... "

Wordy.

SuggestedRemedy

Less wordy:

"The cable references use "DC loop resistance," which... "

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 33 SC 33.1.3.2 P46 L30 # 136
Yseboodt, Lennart Philips

Comment Type E Comment Status D Editorial

"Within Clause 33 and its annexes, "channel", as defined in 1.4.134, refers to the electrical path on which the power signal passes, i.e., the link section."

'Power signal' seems strange.

SuggestedRemedy

"Within Clause 33 and its annexes, "channel", as defined in 1.4.134, refers to the electrical path on which the power is transferred, i.e., the link section."

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 33 SC 33.2.1 P47 L10 # 9
Bennett, Ken Sifos Technologies, In

Comment Type ER Comment Status D PSE Types

Table 33-2, 3rd column header states "Range of maximum Classes supported". The entries in the column are not ranges; they only show the maximum.

SuggestedRemedy

Change the column heading to: "Maximum Class Supported."

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

OBE by 137

We wanted to make sure that you could build a PSE that was not listed in that table such as a Type 3, class 3 PSE for example

IEEE P802.3bt D1.7 4-Pair Power-over-Ethernet 10th Task Force review comments

CI 33 SC 33.2.5 P 47 L 10 # 67
 Lukacs, Miklos Silicon Labs

Comment Type E Comment Status D PSE Types

It is hard to understand the column header of column 3 "Range of maximum classes supported."

SuggestedRemedy

Change it back to "Maximum Class Supported"

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

OBE by 137

We wanted to make sure that you could build a PSE that was not listed in that table such as a Type 3, class 3 PSE for example

CI 33 SC 33.2.1 P 47 L 10 # 66
 Lukacs, Miklos Silicon Labs

Comment Type E Comment Status D PSE Types

In the column header of table 33-2: the meaning of "Short MPS support" is not clear at this point in the document.

SuggestedRemedy

Add a note under table 33-2:

Note 1: TMPS min = 6ms, see table 33-17 line 23, clause 33.3.5.2 and table 33-29 for more details.

Proposed Response Response Status W

PROPOSED REJECT.

I believe we removed a note pointing to these sections from this header last time. None of the other columns headers have notes, and they don't need explanation. This table is only a summary of the allowed Types, the reader needs to read all the other sections to understand it.

CI 33 SC 33.1.3.2 P 47 L 12 # 137
 Yseboodt, Lennart Philips

Comment Type E Comment Status D PSE Types

Table 33-2. We made a change last time to show the "Range of maximum Classes supported".

But no ranges have been defined, only a maximum class.

SuggestedRemedy

Change 'Range of maximum Classes supported' data from:

"Class 3, Class 4, Class 4, Class 4, Class 6, Class 8" to:

"Class 3, Class 4, Class 4, Class 3 to 4, Class 3 to 6, Class 8"

Proposed Response Response Status W

PROPOSED ACCEPT.

CI 33 SC 33.2.2 P 47 L 31 # 138
 Yseboodt, Lennart Philips

Comment Type E Comment Status D Editorial

"Midspan PSE." period is inside quotes.

SuggestedRemedy

Change to "Midspan PSE".

Proposed Response Response Status W

PROPOSED ACCEPT.

CI 33 SC 33.2.5 P 56 L 7 # 218
 Yseboodt, Lennart Philips

Comment Type T Comment Status X Pres: Yseboodt11

Updates to the PSE State Diagram

SuggestedRemedy

Adopt yseboodt_11_0516_psestatedia.pdf

Proposed Response Response Status W

WFP

TFTD

IEEE P802.3bt D1.7 4-Pair Power-over-Ethernet 10th Task Force review comments

Cl 33 SC 33.2.5 P 56 L 13 # 83
Schindler, Fred Seen Simply, Broadco

Comment Type TR Comment Status X Pres: Schindler1

Variable parameter_type is used in legacy text to indicate the PSE type powering the system so that the electrical parameters (ILIM) may be set based on the PSE Type. The value of parameter_type is not a constant (p61, L53) and is determined by mutual identification of the PSE and PD. The function set_parameter_type is used to set the electrical values based on table values. New Types have these same parameters (ILIM) set based on class rather than Type. The Type 3 and 4 state diagrams (SDs) do not facilitate setting parameters based on class or Type. Comment D1.6 #278 turn the Type 3 and 4 parameter_type variable into a constant. The Type 3 and 4 SD do not use this name to perform a purpose.

New PSE Types are required to do physical classification so the facility to change electrical parameters is not required or included in the Type 3 and 4 SD. Remove the unnecessary use of parameter_type in new text. This comment may be covered in schindler_3bt_01_05_16.

SuggestedRemedy

Strike lines 40 to 45 on page 65.

Proposed Response Response Status W

WFP

TFTD

Cl 33 SC 33.2.5.1.1 P 57 L 1 # 140
Yseboodt, Lennart Philips

Comment Type E Comment Status X Pres: Yseboodt6

original text: "Editors Note (remove D2.0): Text is needed to introduce the specifics of the Type 3 and Type 4 state diagram. Specifically the structure and nomenclature (primary, secondary semi-independent state diagrams)."

SuggestedRemedy

Adopt yseboodt_06_0516_sdintro.pdf
Remove Note.

Proposed Response Response Status W

WFP

TFTD

Cl 33 SC 33.2.5.4 P 57 L 1 # 139
Yseboodt, Lennart Philips

Comment Type E Comment Status D Editorial

Values are written on same line after word "values:"
This is hard to read.

SuggestedRemedy

Move values to next line and use tabs, like we did for the Type 3+4 variable list.

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 33 SC 33.2.5.3 P 57 L 13 # 141
Yseboodt, Lennart Philips

Comment Type E Comment Status D Editorial

Type still has underline.

SuggestedRemedy

Remove underline.

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 33 SC 33.2.5.8 P 65 L 39 # 64
Lukacs, Miklos Silicon Labs

Comment Type E Comment Status X Pres: Lukacs

A timing diagram showing the cconnection check sequences would help in understanding the text and would make the intent more clear.

SuggestedRemedy

See timing diagrams presentation (Lukacs)

Proposed Response Response Status W

WFP

TFTD

IEEE P802.3bt D1.7 4-Pair Power-over-Ethernet 10th Task Force review comments

Cl 33 SC 33.2.5.8 P 65 L 40 # 219
 Yseboodt, Lennart Philips

Comment Type T Comment Status D PSE SD

original text: "parameter_type: Values:
 3: Type 3 PSE parameter values
 4: Type 4 PSE parameter values"

The legacy SD, uses PSE_TYPE for the purpose we are now using parameter_type in the new SD. We did this, because parameter_type is used in the DLL state machine. The link however between the DLL SM and the PSE SM needs to be properly looked at anyway and revised.

SuggestedRemedy

- Rename parameter_type to PSE_TYPE.
 "PSE_TYPE
 A constant indicating the Type of the PSE.
 Values:
 3: Type 3 PSE
 4: Type 4 PSE"

Proposed Response Response Status W
 PROPOSED ACCEPT.

Cl 33 SC 33.2.5.8 P 65 L 40 # 65
 Lukacs, Miklos Silicon Labs

Comment Type E Comment Status D PSE SD

constant named "parameter_type" is written in small caps, while the other constant "CC_DET_SEQ" is ALL CAPS

SuggestedRemedy

They should be written similarly, and preferably ALL CAPS:
 PARAMETER_TYPE

Proposed Response Response Status W
 PROPOSED ACCEPT IN PRINCIPLE.

OBE by 219

Cl 33 SC 33.2.5.12 P 66 L 18 # 142
 Yseboodt, Lennart Philips

Comment Type E Comment Status D Editorial

alt_pri_pwr and alt_sec_pwr do not follow our convention of putting _pri and _sec at the end of the variable name.

Same for tinrush_pri_timer and tinrush_sec_timer.

SuggestedRemedy

Rename alt_pri_pwr => alt_pwr_pri
 Rename alt_sec_pwr => alt_pwr_sec
 Rename tinrush_pri_timer => tinrush_timer_pri
 Rename tinrush_sec_timer => tinrush_timer_sec

Proposed Response Response Status W
 PROPOSED ACCEPT.

Cl 33 SC 33.2.5.9 P 66 L 39 # 70
 Picard, Jean Texas Instruments

Comment Type ER Comment Status D PSE SD

"A variable indicating if the PSE generates 3 class events to..."
 this is about primary alternate, it should be mentioned.

SuggestedRemedy

Replace with:
 "A variable indicating if the PSE generates 3 class events on the primary alternate to..."

Proposed Response Response Status W
 PROPOSED ACCEPT.

Cl 33 SC 33.2.5.9 P 66 L 39 # 102
 Stover, David Linear Technology

Comment Type E Comment Status D Editorial

"dual-signature" is hyphenated and not capitalized, per our convention. There are 4 locations where this convention is not followed.

SuggestedRemedy

Global search and replace "dual signature" with "dual-signature".

Proposed Response Response Status W
 PROPOSED ACCEPT.

IEEE P802.3bt D1.7 4-Pair Power-over-Ethernet 10th Task Force review comments

Cl 33 SC 33.2.5.9 P 66 L 46 # 69
 Picard, Jean Texas Instruments

Comment Type TR Comment Status D PSE SD

The class_4PID_mult_events_sec variable is missing from the list of variables although it is used in the SM

SuggestedRemedy

Add the following variable from "Picard_03_0316.pdf" page 1:

"class_4PID_mult_events_sec:

A variable indicating if the PSE generates 3 class events on the secondary alternate to determine if the dual signature PD is a candidate for 4-pair power.

TRUE: the PSE generates at least 3 class events to determine if the PD is a candidate for 4-pair power.

FALSE: the PSE does not need to generate 3 class events to determine if the PD is a candidate for 4-pair power."

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 33 SC 33.2.5.9 P 67 L 44 # 103
 Stover, David Linear Technology

Comment Type T Comment Status D PSE SD

The variable dll_4PID is redundant with pd_dll_power_type.

SuggestedRemedy

Remove dll_4PID. Replace logic in POWER_ON state as follows:

From: (dll_4PID + ((pd_req_pwr > 4) * (pse_avail_pwr > 4)) + (mr_pse_ss_mode = 1))

To: ((pd_dll_power_type > 2) + ((pd_req_pwr > 4) * (pse_avail_pwr > 4)) + (mr_pse_ss_mode = 1))

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 33 SC 33.2.5.9 P 68 L 10 # 43
 Johnson, Peter Sifos Technologies

Comment Type E Comment Status D PSE SD

The definitions for Iport-2P-pri and Iport-2P-sec each finish with (see 33.2.8.6), but there is no mention of these variables in 33.2.8.6.

SuggestedRemedy

Remove the references to 33.2.8.6

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 33 SC 33.2.5.9 P 68 L 12 # 220
 Yseboodt, Lennart Philips

Comment Type T Comment Status D Editorial

highest_2p is written with a small letter p.

SuggestedRemedy

Change to highest_2P.

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 33 SC 33.2.5.9 P 68 L 17 # 239
 Yseboodt, Lennart Philips

Comment Type TR Comment Status D PSE SD

"mps_sum

A variable indicating that the PSE uses the method consisting of measuring the sum of IPORT-2P of both pairsets to determine if the DC MPS component is present."

This does not highlight that mps_sum may only be TRUE in case of a single-signature PD.

SuggestedRemedy

"mps_sum

A variable indicating that the PSE uses the method consisting of measuring the sum of IPORT-2P of both pairsets to determine if the DC MPS component is present. mps_sum may only be set to TRUE when connected to a single-signature PD."

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 33 SC 33.2.5.9 P 69 L 11 # 143
 Yseboodt, Lennart Philips

Comment Type E Comment Status D PSE SD

Comment #262 / D1.6 attempted to fix this but was only partially adopted.

The description of variable mr_pse_enable duplicates bit assignments already listed in 33.5.1.

SuggestedRemedy

Remove all the "This value corresponds with..." sentences from mr_pse_enable.

Proposed Response Response Status W

PROPOSED ACCEPT.

IEEE P802.3bt D1.7 4-Pair Power-over-Ethernet 10th Task Force review comments

Cl 33 SC 33.2.5.9 P 70 L 18 # 144
 Yseboodt, Lennart Philips

Comment Type E Comment Status D PSE SD

pd_cls_4PID_pri:
 This variable indicates that 4PID has been established by confirming that both pairsets have a valid detection signature and that a device classified as a Type 3 or Type 4 PD.

Does not mention on which Alternative.

SuggestedRemedy

pd_cls_4PID_pri:
 This variable indicates that 4PID has been established on the Primary Alternative by confirming that both pairsets have a valid detection signature and that a device classified as a Type 3 or Type 4 PD.

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 33 SC 33.2.5.9 P 70 L 19 # 104
 Stover, David Linear Technology

Comment Type TR Comment Status X PSE SD

Definition of pd_cls_4PID_pri is inconsistent with assignment in PSE SD: "This variable indicates that 4PID has been established by confirming that both pairsets have a valid detection signature and that a device classified as a Type 3 or Type 4 PD."

SuggestedRemedy

Replace variable definition as follows: "This variable indicates that a device on the primary pairset classified as a Type 3 or Type 4 PD."

Proposed Response Response Status W

TFTD.

See 144

Cl 33 SC 33.2.5.9 P 70 L 25 # 173
 Yseboodt, Lennart Philips

Comment Type E Comment Status D PSE SD

pd_cls_4PID_sec:
 This variable indicates that 4PID has been established by confirming that both pairsets have a valid detection signature and that a device classified as a Type 3 or Type 4 PD.

Does not mention on which Alternative.

SuggestedRemedy

pd_cls_4PID_sec:
 This variable indicates that 4PID has been established on the Secondary Alternative by confirming that both pairsets have a valid detection signature and that a device classified as a Type 3 or Type 4 PD.

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 33 SC 33.2.5.9 P 70 L 25 # 105
 Stover, David Linear Technology

Comment Type TR Comment Status X PSE SD

Definition of pd_cls_4PID_sec is inconsistent with assignment in PSE SD: "This variable indicates that 4PID has been established by confirming that both pairsets have a valid detection signature and that a device classified as a Type 3 or Type 4 PD."

SuggestedRemedy

Replace variable definition as follows: "This variable indicates that a device on the secondary pairset classified as a Type 3 or Type 4 PD."

Proposed Response Response Status W

TFTD

See 173

IEEE P802.3bt D1.7 4-Pair Power-over-Ethernet 10th Task Force review comments

Cl 33 SC 33.2.5.9 P 70 L 39 # 221
 Yseboodt, Lennart Philips

Comment Type T Comment Status X PSE SD

original text: "Editors Note: Mutual identification will require a variable pd_power_type similar to pd_dll_power_type."

SuggestedRemedy

Remove Editors note and replace it by:

pd_power_type

A control variable output by the PSE power control state diagram (Figure 33-49) that indicates the Type of PD as advertised through Physical Link Layer classification.

Values:

- 1: PD is a Type 1 PD or a Type 3 PD (default)
- 2: PD is a Type 2 PD, a Type 3 PD, or a Type 4 PD
- 3: PD is a Type 3 PD
- 4: PD is a Type 4 PD

Proposed Response Response Status W

I don't understand this remedy. How does it fit in with Figure 33-49? Why have you made the choices you did with the meaning of each value?

TFTD

Cl 33 SC 33.2.5.9 P 70 L 48 # 174
 Yseboodt, Lennart Philips

Comment Type E Comment Status D PSE SD

Why use the negation "power_not_available"?
 In state diagram is written then (not power_not_available) and is double negation.

SuggestedRemedy

- Change to "power_available"
- Reverse False/True meaning
- add/remove "!" in the state diagram where it is used.

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 33 SC 33.2.5.9 P 73 L 32 # 106
 Stover, David Linear Technology

Comment Type T Comment Status D PSE SD

"Shall" statement potentially in conflict with optional PSE behavior.

SuggestedRemedy

Replace: "PSEs shall issue no more Class events than the Class they are capable of supporting."

With: "Type 3 and Type 4 PSEs shall issue no more Class events than the Class they are capable of supporting unless a class reset event clears the PD class and mark event counts."

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Replace: "PSEs shall issue no more Class events than the Class they are capable of supporting."

With: "Type 3 and Type 4 PSEs shall issue no more Class events than the Class they are capable of supporting between the last PD reset and a transition to POWER_UP"

TFTD. Should this be "between the last time VPSE was in the Vreset range and a transition to..."

Cl 33 SC 33.2.5.10 P 73 L 43 # 107
 Stover, David Linear Technology

Comment Type T Comment Status D PSE SD

tcc_timer is defined but never used in PSE SD. I believe we intentionally removed this from SD in review of D1.6.

SuggestedRemedy

Remove tcc_timer from list of Type 3 and Type 4 timers.

Proposed Response Response Status W

So, we removed it from the SD, but not the text. What is the intention moving forward? Do we need this timer or not?

TFTD

IEEE P802.3bt D1.7 4-Pair Power-over-Ethernet 10th Task Force review comments

Cl 33 SC 33.2.5.10 P 73 L 44 # 15
 Darshan, Yair Microsemi

Comment Type ER Comment Status X PSE SD

Missing link to Table 33-7 in the following text:
 "tcc_timer
 A timer used to monitor the duration of Connection Check."

SuggestedRemedy

Change from:
 "tcc_timer
 A timer used to monitor the duration of Connection Check."

To:
 "tcc_timer
 A timer used to monitor the duration of Connection Check. See Table 33-7."

Proposed Response Response Status W

See 107.

TFTD

Cl 33 SC 33.2.5.10 P 75 L 31 # 222
 Yseboodt, Lennart Philips

Comment Type T Comment Status D PSE SD

The Type 3/4 State diagram does not use or need a tpd timer, but it is defined in 33.2.5.10.

SuggestedRemedy

Remove tpd timer from 33.2.5.10

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 33 SC 33.2.5.11 P 75 L 50 # 61
 Lukacs, Miklos Silicon Labs

Comment Type E Comment Status D PSE SD

There is a typo here (if) and the text is not precise enough:
 "pd autoclass is set to True when a class signature if '0' is detected, otherwise it is set to False."

SuggestedRemedy

pd autoclass is set to True when a class signature of '0' is detected during the TACS window (no earlier than TACS min and no later than TACS max, as defined in Table 33-27), otherwise it is set to False.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

pd autoclass is set to True when a class signature of '0' is detected during the TACS window (see Table 33-27), otherwise it is set to False.

Also the variable name needs to include an "_". Change to "pd_autoclass"

Cl 33 SC 33.2.5.11. P 76 L 2 # 62
 Lukacs, Miklos Silicon Labs

Comment Type E Comment Status D PSE SD

mr pd autoclass refers to the signature seen during the first (long) class event, before the TACS window.

SuggestedRemedy

The PD classification signature seen before TACS min during the long first class event.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Change variable name to "mr_pd_autoclass_detected".

Do not implement suggest remedy.

The variable is referring to the signature during the window, not before it.

IEEE P802.3bt D1.7 4-Pair Power-over-Ethernet 10th Task Force review comments

Cl 33 SC 33.2.5.11 P76 L 10 # 63
 Lukacs, Miklos Silicon Labs
 Comment Type E Comment Status X Pres: Lukacs
 A timing diagram showing the classification part of Autoclass would help in understanding the text and would make the intent more clear.
 SuggestedRemedy
 See timing diagrams presentation (Lukacs)
 Proposed Response Response Status W
 WFP
 TFTD

Cl 33 SC 33.2.5.11 P76 L 17 # 108
 Stover, David Linear Technology
 Comment Type T Comment Status X PSE SD
 Propose we add an additional connection check result to express, for example, that the status of the link segment has changed during do_cxn_chk.
 SuggestedRemedy
 Add a result to sig_type: "Invalid: Neither open circuit, nor single-signature PD, nor dual-signature PD connection check signature has been found."
 Proposed Response Response Status W
 TFTD.

Cl 33 SC 33.2.5.12 P79 L 1 # 223
 Yseboodt, Lennart Philips
 Comment Type T Comment Status D PSE SD
 Entry arc into IDLE:
 pse_reset + error_condition * (mr_pse ...) can be ambiguous
 I have not found any mention of a defined order of operation. Convention is for AND to take precedence over OR, but this is not a universal truth.
 SuggestedRemedy
 Use brackets whenever ambiguity is possible.
 pse_reset + (error_condition * (mr_pse ...)).
 Proposed Response Response Status W
 PROPOSED ACCEPT IN PRINCIPLE.
 I don't believe your interpretation is correct.
 To get to idle, mr_pse_enable has to be true, so it should be ANDed with everything.
 Change to: (pse_reset + error_condition) * (mr_pse_enable = enable).
 Why do we have mr_pse_enable have enumerated choices (why isn't it True/False)?
 TFTD

Cl 33 SC 33.2.5.12 P79 L 35 # 71
 Picard, Jean Texas Instruments
 Comment Type TR Comment Status D PSE SD
 The IF(CC_DET_SEQ ≠ 2) statement is missing, seems to have been deleted from previous Draft.
 SuggestedRemedy
 Re-instate the IF(CC_DET_SEQ ≠ 2) statement. Refer to "Picard_02_0316.pdf" page 1
 Proposed Response Response Status W
 PROPOSED ACCEPT.
 The text shown to be inserted in Picard_02_... Replaced the text that was there rather than be inserted before it.

IEEE P802.3bt D1.7 4-Pair Power-over-Ethernet 10th Task Force review comments

Cl 33 SC 33.2.5.12 P 80 L 9 # 109
 Stover, David Linear Technology

Comment Type **TR** Comment Status **D** PSE SD

Transition logic in conflict: Out of DETECT_EVAL, PSE can be required to follow arcs "A" and "A1" simultaneously.

SuggestedRemedy

Replace: "(mr_pse_alternative != both) * (sig_pri = valid) + (det_temp = both_neither) * (sig_sec = valid)"

With: "(mr_pse_alternative != both) * (det_temp = only_one) * (sig_pri = valid) + (det_temp = both_neither) * (sig_sec = valid)"

Proposed Response Response Status **W**

TFTD, see 175.

Cl 33 SC 33.2.5.12 P 80 L 9 # 175
 Yseboodt, Lennart Philips

Comment Type **E** Comment Status **D** PSE SD

Figure 33-15, arc from DETECT_EVAL to A1
 (mr_pse_alternative [?] both) * (sig_pri = valid) + (det_temp = both_neither) * (sig_sec = valid)

Missing brackets.

SuggestedRemedy

((mr_pse_alternative [?] both) * (sig_pri = valid)) + ((det_temp = both_neither) * (sig_sec = valid))

Proposed Response Response Status **W**

TFTD, see 109.

Cl 33 SC 33.2.5.12 P 80 L 24 # 176
 Yseboodt, Lennart Philips

Comment Type **E** Comment Status **X**

Figure 33-15, arc from CXN_CHK_DETECT_EVAL to A:
 Brackets are not consistently used => what was the intent here ?

SuggestedRemedy

TFTD.

Proposed Response Response Status **W**

TFTD as requested.

Also see 109, 175

Cl 33 SC 33.2.5.12 P 80 L 30 # 179
 Yseboodt, Lennart Philips

Comment Type **E** Comment Status **X** PSE SD

Figure 33-15, arc from DETECT_EVAL to A:
 (...) + (mr_pse_alternative is not both) * (sig_pri is not valid)
 is ambiguous

SuggestedRemedy

use brackets... probably meant:
 (...) + ((mr_pse_alternative is not both) * (sig_pri is not valid))
 could also be
 (...) + (mr_pse_alternative is not both)) * (sig_pri is not valid)

Proposed Response Response Status **W**

TFTD

Cl 33 SC 33.2.5.12 P 80 L 30 # 178
 Yseboodt, Lennart Philips

Comment Type **E** Comment Status **D** PSE SD

Figure 33-15, arc from DETECT_EVAL to A:
 (noth_neither) is misspelled.

SuggestedRemedy

Change to both_neither.

Proposed Response Response Status **W**

PROPOSED ACCEPT.

Cl 33 SC 33.2.5.12 P 80 L 30 # 172
 Picard, Jean Texas Instruments

Comment Type **TR** Comment Status **D** PSE SD

2nd line of equation: sig ≠ valid should read sig_pri ≠ valid. Also "noth" should be "both"

SuggestedRemedy

Replace 2nd line with ((det_temp = only_one) * (sig_pri ≠ valid) + (det_temp = both_neither) * (sig_sec ≠ valid) +

Proposed Response Response Status **W**

PROPOSED ACCEPT IN PRINCIPLE.

OBE by 177, 178

IEEE P802.3bt D1.7 4-Pair Power-over-Ethernet 10th Task Force review comments

Cl 33 SC 33.2.5.12 P 80 L 30 # 177
 Yseboodt, Lennart Philips

Comment Type E Comment Status D PSE SD

Figure 33-15, arc from DETECT_EVAL to A:

```
(mr_pse_alternative = both) * ((det_temp = only_one) * (sig [?] valid) + (det_temp =
noth_neither) * (sig_sec [?] valid) + ((CC_DET_SEQ = 0) + (CC_DET_SEQ = 3) *
(det_temp = only_one) * tdet2det_timer_done)) + (mr_pse_alternative [?] both) * (sig_pri [?]
valid)
```

"sig" doesn't exist. sig_pri is meant ?

SuggestedRemedy

Change sig to sig_pri.

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 33 SC 33.2.5.12 P 81 L 8 # 110
 Stover, David Linear Technology

Comment Type T Comment Status X PSE SD

Conditional logic in SS state diagram (POWER_UP) may be simplified with no change to function.

SuggestedRemedy

Replace: "IF (mr_pse_alternative = both) * (mr_pse_ss_mode = 1) + ((pd_req_pwr > 4) * (pse_avail_pwr > 4)) THEN"
 With: "If (mr_pse_alternative = both) * (mr_pse_ss_mode = 1) + (pd_req_pwr > 4) THEN"

Proposed Response Response Status W

TFTD.

Is this true? This seems to imply that a PD assigned class 4 or less (due to demotion) must be powered up in 4-pair mode.

I think this breaks stuff...

See 73

Cl 33 SC 33.2.5.12 P 81 L 9 # 73
 Picard, Jean Texas Instruments

Comment Type ER Comment Status D PSE SD

A parenthesis is missing and another is at the wrong location.

SuggestedRemedy

Replace with this
 IF (mr_pse_alternative = both) * ((mr_pse_ss_mode = 1) + ((pd_req_pwr > 4) * (pse_avail_pwr > 4))) THEN

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 33 SC 33.2.5.12 P 81 L 18 # 74
 Picard, Jean Texas Instruments

Comment Type ER Comment Status D PSE SD

A parenthesis is missing

SuggestedRemedy

Insert a parenthesis between IF and "dll_4PID"

Proposed Response Response Status W

PROPOSED ACCEPT.

There is an unequal number of open and close parenthesis currently.

Cl 33 SC 33.2.5.12 P 81 L 20 # 111
 Stover, David Linear Technology

Comment Type T Comment Status X

Conditional logic in SS state diagram (POWER_ON) may be simplified with no change to function.

SuggestedRemedy

Replace: "IF dll_4PID + ((pd_req_pwr > 4) * (pse_avail_pwr < 4)) + (mr_pse_ss_mode = 1) THEN"
 With: "IF dll_4PID + (pd_req_pwr > 4) + (mr_pse_ss_mode = 1) THEN"

Proposed Response Response Status W

TFTD.

See response to 110.

IEEE P802.3bt D1.7 4-Pair Power-over-Ethernet 10th Task Force review comments

CI 33 SC 33.2.5.12 P 81 L 39 # 112
 Stover, David Linear Technology

Comment Type **TR** Comment Status **X** PSE SD

Transition logic from POWER_ON into POWER_DENIED is (power_not_available * !tmpdo_timer_done * etc);

Transition logic from POWER_ON into IDLE is (!power_not_available * tmpdo_timer_done * etc).

When power_not_available and tmpdo_timer_done are simultaneously TRUE, PSE state machine cannot transition to either IDLE or POWER_DENIED states.

SuggestedRemedy

Remove "!tmpdo_timer_done" from transition logic between POWER_ON and POWER_DENIED.

Proposed Response Response Status **W**

TFTD.

Don't we want the SD to transition to IDLE if tmpdo expires?

I believe the Type 1/2 SD has this same issue...

See 113, 114

CI 33 SC 33.2.5.12 P 83 L 32 # 113
 Stover, David Linear Technology

Comment Type **TR** Comment Status **X**

Transition logic from POWER_ON_PRI into POWER_DENIED_PRI is (power_not_available_pri * !tmpdo_timer_done_pri * etc). Transition logic from POWER_ON_PRI into IDLE_PRI is (!power_not_available_pri * tmpdo_timer_pri_done * etc). When power_not_available_pri and tmpdo_timer_pri_done are simultaneously TRUE, primary alt state machine cannot transition into either IDLE_PRI or POWER_DENIED_PRI states.

SuggestedRemedy

Remove "!tmpdo_timer_pri_done" from transition logic between POWER_ON_PRI and POWER_DENIED_PRI.

Proposed Response Response Status **W**

TFTD

See 112, 114

CI 33 SC 33.2.5.12 P 85 L 30 # 114
 Stover, David Linear Technology

Comment Type **TR** Comment Status **X**

Transition logic from POWER_ON_SEC into POWER_DENIED_SEC is (power_not_available_sec * !tmpdo_timer_done_sec * etc). Transition logic from POWER_ON_SEC into IDLE_SEC is (!power_not_available_sec * tmpdo_timer_sec_done * etc). When power_not_available_sec and tmpdo_timer_sec_done are simultaneously TRUE, secondary alt state machine cannot transition into either IDLE_SEC or POWER_DENIED_SEC states.

SuggestedRemedy

Remove "!tmpdo_timer_sec_done" from transition logic between POWER_ON_SEC and POWER_DENIED_SEC.

Proposed Response Response Status **W**

TFTD

See 112, 113

CI 33 SC 33.2.5.9 P 85 L 35 # 240
 Yseboodt, Lennart Philips

Comment Type **TR** Comment Status **X** Pres: Yseboodt7

We adopted a new MPS state diagram last cycle.

It works great for single-signature, but does not address dual-signature, which need independent MPS.

SuggestedRemedy

Adopt yseboodt_07_0516_dsmps.pdf

Proposed Response Response Status **W**

WFP

TFTD

IEEE P802.3bt D1.7 4-Pair Power-over-Ethernet 10th Task Force review comments

Cl 33 SC 33.2.5.12 P 86 L 1 # 115
 Stover, David Linear Technology

Comment Type T Comment Status X
 Per 33.2.7.2, the PSE shall return to the IDLE state in the event any measured IClass is equal to or greater than IClass_LIM. This is not reflected in the PSE SD.

SuggestedRemedy
 Add transition arcs to the appropriate idle state out of all CLASS_EV states as defined in 33.2.7.2, page 98, Line 25. Transition logic to read, "IClass >= IClass_LIM".

Proposed Response Response Status W
 TFTD

Does every little thing need to be in the state diagram? This was not in the Type 1/2 SD either, but it was a requirement for Type 2 PSEs.

Cl 33 SC 33.2.5.12 P 86 L 52 # 224
 Yseboodt, Lennart Philips

Comment Type T Comment Status D PSE SD
 Figure 33-19, arc from MARK_EV_LAST to C1 has no condition.

SuggestedRemedy
 Add condition: "tme2_timer_done".

Proposed Response Response Status W
 PROPOSED ACCEPT.

Cl 33 SC 33.2.5.12 P 86 L 53 # 180
 Yseboodt, Lennart Philips

Comment Type E Comment Status D Editorial
 C1 exit arrow not readable.

SuggestedRemedy
 Widen arrow to better fit text.

Proposed Response Response Status W
 PROPOSED ACCEPT.

Cl 33 SC 33.2.5.12 P 87 L 17 # 116
 Stover, David Linear Technology

Comment Type T Comment Status D PSE SD
 Transition logic from CLASS_EV2_PRI to MARK_EV_LAST_PRI redundantly performs a check for !class_4PID_mult_events_pri (was already checked out of CLASS_EV1_LCE_PRI).

SuggestedRemedy
 Strike the transition arc from CLASS_EV2_PRI to MARK_EV_LAST_PRI.

Proposed Response Response Status W
 PROPOSED REJECT.

I believe this is needed because we can get to class2 if the class sig is 4, right?

In addition, we can't strike the entire arc, it is checking for other things.

TFTD

Cl 33 SC 33.2.5.12 P 87 L 19 # 117
 Stover, David Linear Technology

Comment Type T Comment Status X PSE SD
 Transition logic from CLASS_EV2_PRI to MARK_EV2_PRI may be simplified.

SuggestedRemedy
 Change transition logic from CLASS_EV2_PRI to MARK_EV2_PRI as follows:
 "tcle2_timer_pri_done * (mr_pd_class_detected = temp_var_pri)"

Proposed Response Response Status W
 TFTD

See 116.

Cl 33 SC 33.2.5.12 P 87 L 36 # 118
 Stover, David Linear Technology

Comment Type ER Comment Status D PSE SD
 State CLASS_EV1_LCE_PRI should read CLASS_EV1_LCE_RESET_PRI as described in 33.2.7.2

SuggestedRemedy
 Change state name "CLASS_EV1_LCE_PRI" to "CLASS_EV1_LCE_RESET_PRI"

Proposed Response Response Status W
 PROPOSED ACCEPT.

IEEE P802.3bt D1.7 4-Pair Power-over-Ethernet 10th Task Force review comments

Cl 33 SC 33.2.5.12 P 87 L 40 # 79
 Picard, Jean Texas Instruments
 Comment Type ER Comment Status D PSE SD
 CLASS_EV1_LCE_PRI title is already used somewhere else
 SuggestedRemedy
 Replace with this
 CLASS_EV1_LCE_RESET_PRI. Refer to Picard_02_0316.pdf page 10
 Proposed Response Response Status W
 PROPOSED ACCEPT IN PRINCIPLE.
 OBE by 118.

Cl 33 SC 33.2.5.12 P 88 L 16 # 119
 Stover, David Linear Technology
 Comment Type T Comment Status D PSE SD
 Transition logic from CLASS_EV2_SEC to MARK_EV_LAST_SEC redundantly performs a check for !class_4PID_mult_events_sec (was already checked out of CLASS_EV1_LCE_SEC).
 SuggestedRemedy
 Strike the transition arc from CLASS_EV2_SEC to MARK_EV_LAST_SEC.
 Proposed Response Response Status W
 PROPOSED REJECT.
 TFTD
 See 115.

Cl 33 SC 33.2.5.12 P 88 L 18 # 120
 Stover, David Linear Technology
 Comment Type T Comment Status D PSE SD
 Transition logic from CLASS_EV2_SEC to MARK_EV2_SEC may be simplified.
 SuggestedRemedy
 Change transition logic from CLASS_EV2_SEC to MARK_EV2_SEC as follows:
 "tcle2_timer_pri_done * (mr_pd_class_detected = temp_var_sec)"
 Proposed Response Response Status W
 TFTD
 See 115, 116.

Cl 33 SC 33.2.5.12 P 88 L 35 # 121
 Stover, David Linear Technology
 Comment Type ER Comment Status D PSE SD
 State CLASS_EV1_LCE_SEC should read CLASS_EV1_LCE_RESET_SEC as described in 33.2.7.2
 SuggestedRemedy
 Change state name "CLASS_EV1_LCE_SEC" to "CLASS_EV1_LCE_RESET_SEC"
 Proposed Response Response Status W
 PROPOSED ACCEPT.

Cl 33 SC 33.2.5.12 P 88 L 40 # 80
 Picard, Jean Texas Instruments
 Comment Type ER Comment Status D PSE SD
 CLASS_EV1_LCE_SEC title is already used somewhere else
 SuggestedRemedy
 Replace with this
 CLASS_EV1_LCE_RESET_SEC. Refer to Picard_02_0316.pdf page 10
 Proposed Response Response Status W
 PROPOSED ACCEPT IN PRINCIPLE.
 OBE by 121.

Cl 33 SC 33.2.5.12 P 89 L 3 # 181
 Yseboodt, Lennart Philips
 Comment Type E Comment Status D PSE SD
 Figure 33-22, entry arcs into IDLE_MPS_*
 "higest_2p" is misspelled.
 SuggestedRemedy
 Change to "highest_2P"
 Proposed Response Response Status W
 PROPOSED ACCEPT.

IEEE P802.3bt D1.7 4-Pair Power-over-Ethernet 10th Task Force review comments

Cl 33 SC 33.2.5.12 P 89 L 14 # 78
 Picard, Jean Texas Instruments
 Comment Type ER Comment Status D PSE SD
 missing parentheses
 SuggestedRemedy
 Middle flowchart: (highest_2p = pri)
 Right flowchart: (highest_2p = sec)
 Proposed Response Response Status W
 PROPOSED ACCEPT.

Cl 33 SC 33.2.5.12 P 89 L 21 # 77
 Picard, Jean Texas Instruments
 Comment Type ER Comment Status D PSE SD
 "!" should NOT be there in the left column of Figure 33-22
 SuggestedRemedy
 Remove the "!" symbol to read "mr_mps_valid_sum"
 Proposed Response Response Status W
 PROPOSED ACCEPT.

Cl 33 SC 33.2.5.12 P 89 L 23 # 76
 Picard, Jean Texas Instruments
 Comment Type TR Comment Status X Pres: Yseboodt7
 PSE MPS monitor State Diagram for DS PD is missing
 SuggestedRemedy
 See yseboodt_07_0516_dsmps.pdf presentation
 Proposed Response Response Status W
 WFP
 TFTD

Cl 33 SC 33.2.5.12 P 89 L 23 # 75
 Picard, Jean Texas Instruments
 Comment Type TR Comment Status D PSE SD
 Figure 33-22 only shows the case of SS PD
 SuggestedRemedy
 Indicate in the description that this is applicable to SS PD
 Proposed Response Response Status W
 PROPOSED ACCEPT IN PRINCIPLE.

Change title of figure 33-22 to "Type 3 and Type 4 PSE MPS monitor state diagram for single-signature PDs"

Cl 33 SC 33.2.5.12 P 89 L 33 # 122
 Stover, David Linear Technology
 Comment Type T Comment Status X PSE SD
 When PSE is in the POWER_ON state, both alt_xxx_pwr and pwr_app_xxx are TRUE and the PSE inrush state diagram cycles through IDLE_INRUSH and MONITOR_INRUSH states, starting and stopping tinrush_xxx_timer indefinitely.
 SuggestedRemedy
 Replace transition logic from IDLE_INRUSH_PRI to MONITOR_INRUSH_PRI with "alt_pri_pwr * !pwr_app_pri".
 Replace transition logic from IDLE_INRUSH_SEC to MONITOR_INRUSH_SEC with "alt_sec_pwr * !pwr_app_sec".
 Proposed Response Response Status W
 TFTD
 Is this true. If so, the Type 1/2 SD has this same issue, right?

IEEE P802.3bt D1.7 4-Pair Power-over-Ethernet 10th Task Force review comments

Cl 33 SC 33.2.5.12 P 89 L 48 # 14
 Darshan, Yair Microsemi

Comment Type E Comment Status D PSE SD

In comment 202 from D.16 regarding overload.
 At the response, the comment editor wrote:
 "As of right now, we have multiple optional behaviors in the SD, how do we want to handle those cases?"
 This should be converted to editor note to be addressed by the group.
 The above was meant to increase PSE design flexibility.

SuggestedRemedy

Add the following Editor Note at the end of the SM clause:
 Editor Note: "We have multiple optional behaviors in the SD, how do we want to handle those cases?"

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Why don't we just make a decision during this meeting about how those will be handled.

TFTD

Cl 33 SC 33.2.6 P 90 L 5 # 33
 Darshan, Yair Microsemi

Comment Type TR Comment Status D PSE Detection

In the following text:
 "Also, a PSE may successfully detect a PD but then opt not to power the detected PD."

The following case is not covered:
 PSE may successfully detect and classify a PD but then opt not to power the detected PD.

To add text that PSE may detect and not continue and go to IDLE or detect and classify and not go to POWER_UP or detect and classify and POWER_UP and not continue to POWER_ON.

To find the location with the existing text and update it.

SuggestedRemedy

Change to:
 "Also, a PSE may successfully detect and classify a PD but then opt not to power the detected PD."

Proposed Response Response Status W

PROPOSED REJECT.

I believe that what you are asking for is already included (it detected a PD, but did not power it). Changing legacy text should be avoided if possible. I do not see any value to the new text and if anything it can be used to say that you must classify after a detection (which is not true).

Cl 33 SC 33.2.6 P 90 L 6 # 123
 Stover, David Linear Technology

Comment Type T Comment Status D PSE Detection

Allowable detection behavior is inconsistent between CC_DET_SEQ variants. Particularly, CC_DET_SEQ 3 is unique in that an invalid detection signature on alt_pri prevents PSE from investigating alt_sec.

SuggestedRemedy

Add the following text: "A Type 3 or Type 4 PSE detecting an invalid PD signature on either alternative may perform detection on the other alternative."

Proposed Response Response Status W

PROPOSED ACCEPT.

IEEE P802.3bt D1.7 4-Pair Power-over-Ethernet 10th Task Force review comments

CI 33 SC 33.2.6.1 P 90 L 15 # 182
 Yseboodt, Lennart Philips
 Comment Type E Comment Status D Editorial
 Vvalid(max) uses brackets, this is not convention
 SuggestedRemedy
 Change to Vvalid max.
 Proposed Response Response Status W
 PROPOSED ACCEPT.

CI 33 SC 33.2.6.1 P 90 L 39 # 124
 Stover, David Linear Technology
 Comment Type T Comment Status X Connection Check
 tcc_timer has been intentionally removed from PSE SD, but Tcc remains in Table 33-7.
 SuggestedRemedy
 Remove reference to Tcc on line 27, Table 33-7, and accompanying NOTE on Tcc min.
 Proposed Response Response Status W
 TFTD
 See 107

CI 33 SC 33.2.6.1 P 90 L 40 # 41
 Darshan, Yair Microsemi
 Comment Type TR Comment Status X Connection Check
 Table 33-7 item 3 and the note below.
 From the note it appears that before we will start connection check we need to wait until full mated MDI exists Tcc minimum. And then item 3 requires Tcc_min=200msec min from start to completion which can be interpreted that total Tcc_min is higher than 200msec. The requirement is not clear. The note doesn't explain the Tcc_min.
 SuggestedRemedy
 "NOTE-When a link segment is connected to an MDI, not all contacts are made simultaneously. Therefore, a minimum total time (Tcc_min) is required to complete connection check that includes the time required for full mated MDI and the time required to perform the connection check function."
 Proposed Response Response Status W
 TFTD
 See 124.

CI 33 SC 33.2.6.1 P 90 L 52 # 40
 Darshan, Yair Microsemi
 Comment Type TR Comment Status D Connection Check
 In the text:
 "If the voltage on either pairset rises above Vvalid max (defined in Table 33-8) during connection check, the PSE shall reset the PD by bringing the voltage at the PI below Voff max (defined in Table 33-17) for at least TReset (defined in Table 33-15) before performing classification."

We need to define the time in which we consider the voltage is above Vvalid to be imuned for noise.
 SuggestedRemedy
 Change to:
 "If the voltage on either pairset rises above Vvalid max (defined in Table 33-8) **for more than TBD msec** during connection check, the PSE shall reset the PD by bringing the voltage at the PI below Voff max (defined in Table 33-17) for at least TReset (defined in Table 33-15) before performing classification."

Proposed Response Response Status W
 PROPOSED REJECT.

PDs have no timing requirements that force them to filter out very small times of voltages crossing thresholds. Thus a PD can count a pulse above Vvalid max of 1ns as a class pulse (bad design, but allowed).

TFTD

CI 33 SC 33.2.6.1 P 90 L 52 # 203
 Yseboodt, Lennart Philips
 Comment Type ER Comment Status D Editorial
 "If the voltage on either pairset rises above Vvalid max (defined in Table 33-8) during connection check, the PSE shall reset the PD by bringing the voltage at the PI below Voff max (defined in Table 33-17) for at least TReset (defined in Table 33-15) before performing classification."
 This way of referring to Tables is used nowhere else in the Draft.
 SuggestedRemedy
 "If the voltage on either pairset rises above Vvalid max, as defined in Table 33-8, during connection check, the PSE shall reset the PD by bringing the voltage at the PI below Voff max, as defined in Table 33-17, for at least TReset, as defined in Table 33-15, before performing classification."
 Proposed Response Response Status W
 PROPOSED ACCEPT.

IEEE P802.3bt D1.7 4-Pair Power-over-Ethernet 10th Task Force review comments

Cl 33 SC 33.2.6.4 P 93 L 11 # 204
 Yseboodt, Lennart Philips

Comment Type ER Comment Status D Editorial

original text: "CAUTION
 In a multiport system, the implementer should maintain DC isolation through the termination circuitry to eliminate cross-port leakage currents."
 Format and position of this note is inconsistent with 802.3-2015.

SuggestedRemedy

Follow same style as 802.3-2015.

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 33 SC 33.2.6.7 P 93 L 51 # 183
 Yseboodt, Lennart Philips

Comment Type E Comment Status D Editorial

4PID in PSE section is named 4P-ID in PD section.
 Make this consistent.

SuggestedRemedy

Change "4P-ID" to "4PID" throughout the doc.

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 33 SC 33.2.7 P 94 L 32 # 84
 Schindler, Fred Seen Simply, Broadco

Comment Type TR Comment Status D PSE Class

Clause 33 is designed to permit understanding of the requirements of the network device after reading mainly the relevant PSE or PD subsections. To aid the reader in understanding of the PSE classification section add references to the PD section that provides details on classification event response interpretation.

SuggestedRemedy

Modify existing text,
 "The assigned Class is the results of the PDs requested Class and the number of class events produced by the PSE as shown in Table 33-11 and Table 33-12."

with,

"The assigned Class is the results of the PDs requested Class shown in Table 33-24 for single-signature PDs and Table 33-25 for dual-signature PDs, and the number of class events produced by the PSE as shown in Table 33-11 and Table 33-12."

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

I don't agree with your comment, I believe the extra references only add confusion to the sentence. However you did find a grammatical error...

Change "PDs" to "PD's"

Cl 33 SC 33.2.7 P 94 L 33 # 241
 Yseboodt, Lennart Philips

Comment Type TR Comment Status D PSE Class

"When a PD requests a higher Class than a Type 3 or Type 4 PSE can support, the PSE assigns the PD Class 3, 4, or 6, whichever is the highest that it can support."

Doesn't take dual-signature PDs into account.

SuggestedRemedy

"When a single-signature PD requests a higher Class than a Type 3 or Type 4 PSE can support, the PSE assigns the PD Class 3, 4, or 6, whichever is the highest that it can support. When a dual-signature PD requests a higher Class than a Type 3 or Type 4 PSE can support, the PSE assigns the PD Class 3 or 4, whichever is the highest that it can support."

Proposed Response Response Status W

PROPOSED ACCEPT.

IEEE P802.3bt D1.7 4-Pair Power-over-Ethernet 10th Task Force review comments

Cl 33 SC 33.2.7 P 95 L 25 # 225
 Yseboodt, Lennart Philips
 Comment Type T Comment Status D Autoclass
 "... with a maximum value defined in Table 33-11 of the corresponding PD Class and a minimum of 4.0 Watts."
 SuggestedRemedy
 Should be assigned Class to be completely clear.
 "... with a maximum value defined in Table 33-11 of the Class assigned to the PD and a minimum of 4.0 Watts."
 Proposed Response Response Status W
 PROPOSED ACCEPT.

Cl 33 SC 33.2.7 P 95 L 43 # 184
 Yseboodt, Lennart Philips
 Comment Type E Comment Status D Editorial
 Table 33-11, some ranges are very small, maybe better to make it explicit.
 SuggestedRemedy
 Change "2 to 3" into "2, 3".
 Proposed Response Response Status W
 PROPOSED ACCEPT.
 Consider "2 or 3" as it is the most meaningful in this table. If you agree, pull it out as a TFTD so we can change it, otherwise "2, 3" it is.

Cl 33 SC 33.2.7 P 96 L 1 # 125
 Stover, David Linear Technology
 Comment Type T Comment Status D PSE Class
 There is no indication in Table 33-12 that the PSE may, for example, issue 3 class events to a dual-signature PD for Type discovery, perform class reset, then issue a number of events consistent with PSE available power.
 SuggestedRemedy
 Add a note below Table 33-12: "Note: PSEs may issue additional class events to determine additional information about the PD and negotiate power allocation. See 33.2.7.2 for details." Reference this note in column header "Number of PSE class events".
 Proposed Response Response Status W
 PROPOSED ACCEPT IN PRINCIPLE.

Add a note below Table 33-12: "Note: PSEs may issue additional class events to determine additional information about the PD and negotiate power allocation. These PSEs will then reset the PD and reissue the correct number of class events. See 33.2.7.2 for details." Reference this note in column header "Number of PSE class events".

Cl 33 SC 33.2.7 P 96 L 2 # 185
 Yseboodt, Lennart Philips
 Comment Type E Comment Status D PSE Class
 Column "Assigned Class" is missing in Table 33-12.
 SuggestedRemedy
 Add this column, values: 1, 2, 3, 3, 4, 5.
 Proposed Response Response Status W
 PROPOSED ACCEPT.

Cl 33 SC 33.2.7 P 96 L 12 # 187
 Yseboodt, Lennart Philips
 Comment Type E Comment Status D Editorial
 Table 33-12, ranges are very small, maybe better to make it explicit.
 SuggestedRemedy
 Change "1 to 3" into "1, 2, 3".
 Do this for all ranges in this Table for the "Number of PSE class events" column.
 Proposed Response Response Status W
 PROPOSED ACCEPT.

See 184

IEEE P802.3bt D1.7 4-Pair Power-over-Ethernet 10th Task Force review comments

CI 33 SC 33.2.7 P 96 L 12 # 186
 Yseboodt, Lennart Philips
 Comment Type E Comment Status D Editorial
 Ranges are used with keyword "to" and not a dash.
 SuggestedRemedy
 Change "4-5" into "4 to 5".
 Proposed Response Response Status W
 PROPOSED ACCEPT.

CI 33 SC 33.2.7 P 96 L 13 # 242
 Yseboodt, Lennart Philips
 Comment Type TR Comment Status D Editorial
 Table 33-12 uses two dashes in the first column, rows 4 and 5.
 SuggestedRemedy
 Replace dash by the word 'to'.
 Proposed Response Response Status W
 PROPOSED ACCEPT.

CI 33 SC 33.2.7 P 96 L 17 # 126
 Stover, David Linear Technology
 Comment Type T Comment Status D PSE Class
 There is a note below Table 33-11, power classifications for single-signature PDs: "Data Link Layer classification takes precedence over Physical Layer classification." Table 33-12, power classification for dual-signature PDs, does not have such a note.
 SuggestedRemedy
 Add a note below Table 33-12: "Note: Data Link Layer classification takes precedence over Physical Layer classification."
 Proposed Response Response Status W
 PROPOSED ACCEPT.

CI 33 SC 33.2.7 P 96 L 29 # 226
 Yseboodt, Lennart Philips
 Comment Type T Comment Status D PSE Class
 We removed the PD equivalent of Table 33-13 in the PD section, because the text already covered that information. The same is true in the PSE section.
 We can get rid of the table.
 SuggestedRemedy
 Remove Table 33-13.

Change the text on page 97, line 4-12 as follows:
 "Subsequent to successful detection, all Type 2 PSEs ***shall*** perform classification using at least one of the following: Multiple-Event Physical Layer classification; Multiple-Event Physical Layer classification and Data Link Layer classification; or Single-Event Physical Layer classification and Data Link Layer classification.
 Subsequent to successful detection, all Type 3 and Type 4 PSEs ***shall*** perform classification using at least one of the following: Multiple-Event Physical Layer classification; or Multiple-Event Physical Layer classification and Data Link Layer classification. Both pairsets attached to a dual-signature PD shall be classified by Type 3 and Type 4 PSEs that will deliver 4-pair power."
 Proposed Response Response Status W
 PROPOSED ACCEPT.

CI 33 SC 33.2.7 P 97 L 16 # 127
 Stover, David Linear Technology
 Comment Type T Comment Status X PSE Class
 Unclear if PSE is allowed to investigate classification result on valid pairsets of a port outside behavior defined in PSE SD; behavior described in PSE SD addresses valid cases for powering a PD, does not address PSE simply investigating both pairsets of the link.
 SuggestedRemedy
 Add the following text: "A Type 3 or Type 4 PSE connected to a dual-signature PD may perform classification on any pairset presenting a valid detection signature prior to returning to the IDLE state."
 Proposed Response Response Status W
 TFTD
 See 33.

IEEE P802.3bt D1.7 4-Pair Power-over-Ethernet 10th Task Force review comments

CI 33 SC 33.2.7.1 P 97 L 32 # 243
 Yseboodt, Lennart Philips

Comment Type **TR** Comment Status **D** PSE Class

"All measurements of I Class shall be taken after the minimum relevant class event timing in Table 33-15."

We now have T_Class for this.

SuggestedRemedy

"All measurements of I Class shall be taken after T_Class, as defined in Table 33-15."

Proposed Response Response Status **W**

PROPOSED ACCEPT.

CI 33 SC 33.2.7.1 P 97 L 38 # 39
 Darshan, Yair Microsemi

Comment Type **TR** Comment Status **D** PSE Class

The requirement:

"If the measured IClass is within the range of IClass_LIM, a Type 1 PSE shall either return to the IDLE state or classify the PD as Class 0; a Type 2 PSE shall return to the IDLE state."

Is not covered by the state machine.

There are probably other requirements that are not covered by the state machine and have shall's.

Do we have rule that that force us to describe shall in SM?

I believe we don't. We can decide according to the cost effectiveness of it in regards to SM simplicity and readability.

SuggestedRemedy

Add the following Editor Note:

"Editor Note: To address in the state machine the case of what should Type 1 do if the measured IClass is within the range of IClass_LIM or use text only (preffered)."

Proposed Response Response Status **W**

PROPOSED REJECT.

We are not changing the Type 1/2 State Diagram unless you submit a maintenance request. I don't believe we should do this anyway. We don't have these requirements shown in the Type 1/2 SD, we shouldn't have to include them for the Type 3/4 SD either.

CI 33 SC 33.2.7.1 P 97 L 40 # 59
 Lukacs, Miklos Silicon Labs

Comment Type **T** Comment Status **X** Pres: Lukacs

A timing diagram showing the single event classification would help in understanding the text and would make the intent more clear.

SuggestedRemedy

See timing diagrams presentation (Lukacs)

Proposed Response Response Status **W**

WPF

TFTD

CI 33 SC 33.2.7.2 P 97 L 41 # 244
 Yseboodt, Lennart Philips

Comment Type **TR** Comment Status **X** Pres: Yseboodt8

The specification of Autoclass in the Multiple-event section can be improved.

SuggestedRemedy

Adopt yseboodt_08_0516_autoclass4.pdf

Proposed Response Response Status **W**

WFP

TFTD

CI 33 SC 33.2.7.2 P 97 L 41 # 128
 Stover, David Linear Technology

Comment Type **TR** Comment Status **X** Pres: Stover1

There are inconsistencies between Tpdcc, autoclass, and multiple-event classification.

SuggestedRemedy

See stover_01_0516.pdf

Proposed Response Response Status **W**

WFP

TFTD

IEEE P802.3bt D1.7 4-Pair Power-over-Ethernet 10th Task Force review comments

Cl 33 SC 33.2.7.2 P 97 L 48 # 205
 Yseboodt, Lennart Philips

Comment Type ER Comment Status D PSE Class

"PD classification signature measurements of I Class are specified in Table 33-11, Table 33-12 and Table 33-14."

Tables 33-11 and 33-12 are not relevant to the IClass to class signature mapping.

SuggestedRemedy

"PD classification signature measurements of I Class are specified in Table 33-14."

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 33 SC 33.2.7.2 P 98 L 4 # 129
 Stover, David Linear Technology

Comment Type T Comment Status D PSE Class

Requirements and allowances for 4PID, class, and mutual identification are unclear.

SuggestedRemedy

Replace sentence: "Type 3 and Type 4 PSEs may issue a class reset event to perform mutual identification."

With: "Type 3 and Type 4 PSEs may issue up to 3 class events to determine PD Class. Type 3 and Type 4 PSEs incapable of supporting negotiated PD Class may issue a class reset event to clear the class and mark event counts."

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

I believe we also need to define "class reset" somewhere. We use the term a lot, but is it defined anywhere?

TFTD

Cl 33 SC 33.2.5.12 P 98 L 4 # 27
 Darshan, Yair Microsemi

Comment Type TR Comment Status X PSE Class

We need to address the following use case (as an example):
 When Type 3 PSE with available power of Type 1 or Type 2 connected to single signature PD class 5 or above and we need to report to the host what is the actual PD class and yet to supply the correct number of fingers (1 in case of 15.4W) to indicate the available PSE power.
 For this purpose we need to allow class reset after 3 class event and issuing one class event.

SuggestedRemedy

1. To add the following text at page 98 line 4:
 "Type 3 and Type 4 PSEs may issue up to 3 class events to determine PD Class. Type 3 and Type 4 PSEs incapable of supporting PD Class may issue a class reset event to clear the class and mark event counts and may issue the lowest number of class events that is corresponding to the PSE available power."

2. No need to update PSE SM since it is optional feature similar to the text that "PSE can detect and not power" or PSE can use Type 4 class 7 current settings when operating Type 3 class 6 PDs or may other examples in the current spec including IEEE802.3-2012 version.

Proposed Response Response Status W

TFTD.

Better Text:

To add the following text at page 98 line 4:
 "Type 3 and Type 4 PSEs may issue up to 3 class events to determine the PD's requested Class. Type 3 and Type 4 PSEs incapable of supporting the assigned Class due to those class events may issue a class reset event to clear the class and mark event count and may issue the lowest number of class events that corresponds to the PSE available power."

IEEE P802.3bt D1.7 4-Pair Power-over-Ethernet 10th Task Force review comments

Cl 33 SC 33.2.7.2 P 98 L 25 # 206
 Yseboodt, Lennart Philips

Comment Type ER Comment Status D Editorial

On p.98, line 25 we have:
 "In the states CLASS_EV1, CLASS_EV1_LCE, CLASS_EV1_LCE_PRI, CLASS_EV1_LCE_SEC, CLASS_EV2, CLASS_EV2_PRI, CLASS_EV2_SEC, CLASS_EV3, CLASS_EV3_PRI, CLASS_EV3_SEC, CLASS_EV4, CLASS_EV4_PRI, CLASS_EV4_SEC, CLASS_EV5, CLASS_EV1_LCE_RESET_PRI, and CLASS_EV1_LCE_RESET_SEC, the PSE shall measure I Class after T Class and classify the PD based on the observed current."

Followed on p99, line 5:
 "All measurements of I Class shall be taken after T Class , as defined in Table 33-15. This measurement is referenced from the application of V Class min to ignore initial transients."

Long and tedious to read. Also, "classify the PD based on the observed current" is no longer really true.

SuggestedRemedy

Replace both by inserting on p98, line 25:
 "In all CLASS states except CLASS_EV1_AUTO, the PSE shall measure I Class after T Class. This measurement is referenced from the application of V Class min to ignore initial transients. "

Proposed Response Response Status W
 PROPOSED ACCEPT.

Cl 33 SC 33.2.7.2 P 98 L 38 # 207
 Yseboodt, Lennart Philips

Comment Type ER Comment Status D PSE Class

"When the Type 2 PSE is in the state MARK_EV2, the PSE shall provide to the PI or pairset V Mark . The timing specification shall be as defined by T ME2.

When the PSE is in the state MARK_EV_LAST, MARK_EV_LAST_PRI and MARK_EV_LAST_SEC, the PSE shall provide to the PI or pairset V Mark . The timing specification shall be as defined by T ME2."

Can be merged without changing meaning.

SuggestedRemedy

"When the PSE is in the state MARK_EV2, MARK_EV_LAST, MARK_EV_LAST_PRI and MARK_EV_LAST_SEC, the PSE shall provide to the PI or pairset V Mark . The timing specification shall be as defined by T ME2."

Proposed Response Response Status W
 PROPOSED ACCEPT IN PRINCIPLE.

However, MARK_EV2 is used in both the Type 1/2 SD and the Type 3/4 SD. The timing is not the same (TME2 for Type 2 and TME1 for Type 3/4).

Change text to:

"When a Type 2 PSE is in the state MARK_EV2, or a Type 3 or Type 4 PSE is in the states MARK_EV_LAST, MARK_EV_LAST_PRI or MARK_EV_LAST_SEC, the PSE shall provide to the PI or pairset V Mark . The timing specification shall be as defined by T ME2."

Cl 33 SC 33.2.7.2 P 99 L 1 # 130
 Stover, David Linear Technology

Comment Type TR Comment Status D PSE Class

"If any measured IClass is equal to or greater than IClass_LIM min, a Type 2, Type 3 or Type 4 PSE shall return to the IDLE state." Most importantly, this list is missing a serial comma. Failing that, SISM state machines experiencing class overcurrent should likely return to their resident IDLE_PRI/IDLE_SEC state, and not the global IDLE state.

SuggestedRemedy

"If any measured IClass is equal to or greater than IClass_LIM min, a Type 2 PSE shall return to the IDLE state. If any measured IClass is equal to or greater than IClass_LIM min, a Type 3 or Type 4 PSE shall return to the appropriate idle state."

Proposed Response Response Status W
 PROPOSED ACCEPT.

IEEE P802.3bt D1.7 4-Pair Power-over-Ethernet 10th Task Force review comments

Cl 33 SC 33.2.7.2 P 99 L 1 # 32
 Darshan, Yair Microsemi

Comment Type TR Comment Status D PSE Class

The following requirement is not described by the state machine.
 "If any measured IClass is equal to or greater than IClass_LIM min, a Type 2, Type 3 or Type 4 PSE shall return to the IDLE state. The PSE shall limit class event currents to IClass_LIM and shall limit mark event currents to IMark_LIM."

SuggestedRemedy

Add the following Editor Notes:
 "Editor Note: To address existing "shall" requirements that are not covered in the state machine."

"Editor Note: To address in the state machine the case of what should Type 2, 3 and 4 do if the measured IClass is within the range of IClass_LIM or use text only (preferred)."

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Partial OBE by 130.

I don't think we need to add editor's notes. Type 1/2 SD is not changing. Type 3/4 can be covered in text just like Type 1/2.

TFTD

Cl 33 SC 33.2.7.2 P 99 L 9 # 34
 Darshan, Yair Microsemi

Comment Type TR Comment Status D PSE Class

"The PSE shall complete Multiple-Event Physical Layer classification and transition to the POWER_ON state without allowing the voltage at the PI or pairset to go below VMark min, unless in the CLASS_RESET_PRI or CLASS_RESET_SEC states."

Missing POWER_UP state as well.

SuggestedRemedy

Change to:
 "The PSE shall complete Multiple-Event Physical Layer classification and transition to the POWER_UP and POWER_ON state without allowing the voltage at the PI or pairset to go below VMark min, unless in the CLASS_RESET_PRI or CLASS_RESET_SEC states."

Proposed Response Response Status W

PROPOSED REJECT.

If we transition to POWER_ON, that means we went through POWER_UP. So the requirement is already there.

Cl 33 SC 33.2.7.2 P 99 L 11 # 245
 Yseboodt, Lennart Philips

Comment Type TR Comment Status D PSE Class

"If the PSE returns to the IDLE state, it shall maintain the PI voltage at VClass for a period of at least TReset min before starting a new detection cycle."

- VClass should be VReset
- Also, that same requirement holds for PSEs that are in the CLASS_RESET states.

SuggestedRemedy

"If the PSE returns to the IDLE state, it shall maintain the PI voltage at VReset for a period of at least TReset min before starting a new detection cycle. If the PSE is in any of the CLASS_RESET states, it shall maintain the PI or pairset voltage at VReset for a period of at least TReset min."

- Remove the sentence on page 99, line 26 which says:
 "When the PSE is in the state CLASS_RESET_PRI or CLASS_RESET_SEC the PSE shall provide to the PI V Reset , subject to the T Reset timing specification."

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

List CLASS_RESET states explicitly as there are other states with RESET in the name and it may be confusing.

Cl 33 SC 33.2.7.2 P 99 L 20 # 217
 Yseboodt, Lennart Philips

Comment Type TR Comment Status D PSE Class

original text: "Classification events may appear on one or both pairsets."

True for single-signature, not for dual.
 Also problematic for Type 1 and Type 2 PSEs.

- The original intent of that sentence was to allow:
- "4-pair" class events for single-sig PDs
 - alternating class events between pairsets
 - other creative classification games

The sentences that deal with applying Vclass already say "to the PI or pairset", granting leave to do all of this.

SuggestedRemedy

We no longer need the quoted sentence. Remove it.

Proposed Response Response Status W

PROPOSED ACCEPT.

IEEE P802.3bt D1.7 4-Pair Power-over-Ethernet 10th Task Force review comments

Cl 33 SC 33.2.7.2 P 99 L 28 # 60
 Lukacs, Miklos Silicon Labs
 Comment Type T Comment Status X Pres: Lukacs
 A timing diagram showing the multiple event classification would help in understanding the text and would make the intent more clear.
 SuggestedRemedy
 See timing diagrams presentation (Lukacs)
 Proposed Response Response Status W
 WFP
 TFTD

Cl 33 SC 33.2.7.2 P 99 L 30 # 209
 Yseboodt, Lennart Philips
 Comment Type ER Comment Status D Editorial
 Itemcount is wrong in Table 33-15, item 6 is listed twice.
 SuggestedRemedy
 Fix.
 Proposed Response Response Status W
 PROPOSED ACCEPT.

Cl 33 SC 33.2.7.2 P 99 L 30 # 208
 Yseboodt, Lennart Philips
 Comment Type ER Comment Status D Editorial
 The item sorting in Table 33-15 has become confusing and seems arbitrary.
 SuggestedRemedy
 Sort Table 33-15 in the following way:
 Voltages: VClass, VMark, VReset
 Currents: IClass_LIM, IMark_LIM,
 Timing: TReset, TClass, TClass_LCE, Tpdc, TLCE, TCLE1, TCLE2, TCLE3,
 TME1, TME2
 Proposed Response Response Status W
 PROPOSED ACCEPT.

Cl 33 SC 33.2.7.2 P 99 L 50 # 16
 Darshan, Yair Microsemi
 Comment Type ER Comment Status D Editorial
 Table 33-15 item 6 and 7 use the same number (6).
 SuggestedRemedy
 To renumber Table 33-15 items.
 Proposed Response Response Status W
 PROPOSED ACCEPT IN PRINCIPLE.
 OBE by 209

Cl 33 SC 33.2.7.2 P 100 L 17 # 188
 Yseboodt, Lennart Philips
 Comment Type E Comment Status D Editorial
 Table 33-15, Item 10 and 11, say "See section 33.2.7.2".
 SuggestedRemedy
 Change to "See 33.2.7.2".
 Proposed Response Response Status W
 PROPOSED ACCEPT.

Cl 33 SC 33.2.7.3 P 101 L 10 # 210
 Yseboodt, Lennart Philips
 Comment Type ER Comment Status D Editorial
 "If the PSE implements Autoclass and the connected PD performs Autoclass, ...".
 Performs seems a weird word here.
 SuggestedRemedy
 "If the PSE supports Autoclass and the connected PD requests Autoclass during classification,.."
 Proposed Response Response Status W
 PROPOSED ACCEPT.

IEEE P802.3bt D1.7 4-Pair Power-over-Ethernet 10th Task Force review comments

Cl 33 SC 33.2.7.3 P 101 L 13 # 246
 Yseboodt, Lennart Philips

Comment Type **TR** Comment Status **D** Autoclass

"TAUTO_PSE1 and TAUTO_PSE2 timing is referenced from the transition of the POWER_UP or SET_PARAMETERS state to the POWER_ON state."

SET_PARAMETERS state no longer exists.

SuggestedRemedy

"TAUTO_PSE1 and TAUTO_PSE2 timing is referenced from the transition of the POWER_UP state to the POWER_ON state."

Proposed Response Response Status **W**

PROPOSED ACCEPT.

Cl 33 SC 33.2.7.3 P 101 L 33 # 189
 Yseboodt, Lennart Philips

Comment Type **E** Comment Status **D** Autoclass

Autoclass margin formula is not described but is defined in this section.

SuggestedRemedy

"P_ac_margin is the minimum amount of power the PSE must add to P_Autoclass in order to allocate enough power to cope with increases in channel resistance due to heating. P_ac_margin is defined in Equation (33-4)."

Proposed Response Response Status **W**

PROPOSED ACCEPT.

Cl 33 SC 33.2.7.3 P 101 L 43 # 190
 Yseboodt, Lennart Philips

Comment Type **E** Comment Status **D** Editorial

"PAutoclass in Watts" dimension should not be plural.

SuggestedRemedy

Change to "PAutoclass in Watt"

Proposed Response Response Status **W**

PROPOSED ACCEPT IN PRINCIPLE.

Editor to check on proper usage. This seems weird to me.

Cl 33 SC 33.2.8 P 101 L 51 # 131
 Stover, David Linear Technology

Comment Type **T** Comment Status **D** PSE Power

Guidance on how to handle dual-signature PDs with mismatched Class/Type combinations is unclear for some defined PSE implementations.

SuggestedRemedy

Insert the sentence "PSEs powering dual-signature PDs may enforce on both pairsets the values in Table 33-17 corresponding to the pairset of that PD identified as the highest PD Class."

Proposed Response Response Status **W**

PROPOSED ACCEPT IN PRINCIPLE.

Insert the sentence "PSEs powering dual-signature PDs may enforce the values in Table 33-17 corresponding to the pairset with the highest assigned class on both pairsets."

Cl 33 SC 33.2.8 P 102 L 32 # 4
 Beia, Christian STMicroelectronics

Comment Type **ER** Comment Status **D** PSE Power

Table 33-17, Item6 Icon-2P-unb is relevant to SS PD only.

SuggestedRemedy

Add "Single Signature PD" on each line of Item6, column Parameter, before the Class.

Proposed Response Response Status **W**

PROPOSED ACCEPT IN PRINCIPLE.

Change parameter description for Item 6 from "Pairset current including unbalance effect" to "Pairset current including unbalance effect when powering single-signature PDs"

IEEE P802.3bt D1.7 4-Pair Power-over-Ethernet 10th Task Force review comments

Cl 33 SC 33.2.8 P 102 L 49 # 29
 Darshan, Yair Microsemi

Comment Type TR Comment Status X Pres: Darshan1

1. Table 33-17 item 7 approved baseline additional information column was implemented incorrectly.
2. Some adjustment to linrush for dual-signature PD class 0-4 is required to address worst case operating conditions when PD using constant power sink that operates at minimum Von. Same applies to Table 33-28.
3. Some adjustments are required to clause 33.2.8.5.1 due to (2) + fixing PD type error.

SuggestedRemedy

See darshan_01_0516.pdf for proposed remedy.

Proposed Response Response Status W

WFP

TFTD

Cl 33 SC 33.2.8 P 103 L 30 # 35
 Darshan, Yair Microsemi

Comment Type TR Comment Status D PSE Power

Table 33-17 item 12 class 4 row, min value 0.684.
 The foot note 2 that was attached to the 0.684A for Type 3 and 4 was lost after updating this item.

SuggestedRemedy

Change "0.684A" to "0.684^2".
 Add the following text after Table 33-17:
 "^2 Unbalance at class 4 is not restricted. The ILIM-2P value is higher than the value for class 5 for Type 3 and 4 PSEs operating with 4-pairs."

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

TFTD

Was the wrong note deleted? Because note 1 doesn't seem to make sense anymore.

Should we delete note 1?

Change "0.684A" to "0.684^2".
 Add the following text after Table 33-17:
 "^2 Unbalance at Class 4 is not restricted. The ILIM-2P value is higher than the value for Class 5."

Cl 33 SC 33.3 P 103 L 30 # 85
 Schindler, Fred Seen Simply, Broadco

Comment Type TR Comment Status D PSE Power

Table 33-17, item 12, was edited to address D1.6 comment 254. However, the footnote referenced on the Class-4 row, Min. column is missing.

SuggestedRemedy

Add the missing footnote,
 "Unbalance at Class 4 is not restricted. The ILIM-2P value is higher than the value for Class 5."

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

OBE by 35.

Cl 33 SC 33.2.8 P 104 L 13 # 211
 Yseboodt, Lennart Philips

Comment Type ER Comment Status D Editorial

Additional info for Table 33-17, item 17, TRise is too long for this field causing vertical wastage.

SuggestedRemedy

- Add the following to 33.2.8.1
 "TRise is referenced from 10 % to 90 % of the voltage difference at the PI in POWER_ON state from the beginning of POWER_UP."
 - Replace additional information field by "See 33.2.8.1"

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 33 SC 33.2.8 P 105 L 32 # 23
 Darshan, Yair Microsemi

Comment Type T Comment Status D Editorial

Delete Editor Note #1. It was addressed in D1.7.

SuggestedRemedy

Delete Editor Note #1.

Proposed Response Response Status W

PROPOSED ACCEPT.

IEEE P802.3bt D1.7 4-Pair Power-over-Ethernet 10th Task Force review comments

Cl 33 SC 33.2.8 P 105 L 36 # 36
 Darshan, Yair Microsemi
 Comment Type **TR** Comment Status **X** Pres: Darshan4
 Editor Note #2. This item is important for the integrity and protection reliability of the PSE under unbalance condition.
 Due to lake of time, this subject was not resolved yet.
 To be discussed with the group how to continue with this item and yet meet our time table.
 SuggestedRemedy
 See darshan_04_0516.pdf for discussion details and possible remedy
 Proposed Response Response Status **W**
 WFP
 TFTD

Cl 33 SC 33.2.8 P 105 L 44 # 22
 Darshan, Yair Microsemi
 Comment Type **T** Comment Status **D** Editorial
 Delete Editor Note #3. It was addressed in D1.7.
 SuggestedRemedy
 Delete Editor Note #3. It was addressed in D1.7.
 Proposed Response Response Status **W**
 PROPOSED ACCEPT.

Cl 33 SC 33.2.8.1 P 106 L 1 # 191
 Yseboodt, Lennart Philips
 Comment Type **E** Comment Status **D** Editorial
 Class 1-4 is not allowed.
 SuggestedRemedy
 Change to: "Class 1 to 4"
 Proposed Response Response Status **W**
 PROPOSED ACCEPT.

Cl 33 SC 33.2.8.2 P 106 L 12 # 7
 Beia, Christian STMicroelectronics
 Comment Type **TR** Comment Status **D** PSE Power
 The resolution of comment 324 of Draft1.6 was only partially implemented, and some text is missing.
 SuggestedRemedy
 Replace :
 The minimum PD input capacitance CPort min or CPort-2P min defined in Table 33-28, allows a PD to operate for input voltage transients which cause VPD to drop as low as 0 V, lasting less than 30 μs.

With:
 The minimum PD input capacitance CPort min or CPort-2P min defined in Table 33-28, allows PDs of any Type to operate for input voltage transients which cause VPD to drop as low as 0V lasting less than 30μs as specified in 33.3.7.6.

Proposed Response Response Status **W**
 PROPOSED ACCEPT IN PRINCIPLE.

The "of any Type" is not needed.

Replace :

The minimum PD input capacitance Cport min or Cport-2P min defined in Table 33-28, allows a PD to operate for input voltage transients which cause VPD to drop as low as 0 V, lasting less than 30 μs.

With:

The minimum PD input capacitance Cport min or Cport-2P min defined in Table 33-28, allows PDs to operate for input voltage transients, which cause VPD to drop as low as 0V, lasting less than 30μs as specified in 33.3.7.6.

IEEE P802.3bt D1.7 4-Pair Power-over-Ethernet 10th Task Force review comments

Cl 33 SC 33.2.8.4 P 106 L 25 # 247
 Yseboodt, Lennart Philips
 Comment Type **TR** Comment Status **X** Pres: Yseboodt2
 There are several inconsistencies/errors identified in the PSE power section.
SuggestedRemedy
 Adopt yseboodt_02_0516_power.pdf
 Proposed Response Response Status **W**
 WFP
 TFTD

Cl 33 SC 33.2.8.4 P 106 L 27 # 50
 Johnson, Peter Sifos Technologies
 Comment Type **T** Comment Status **X** Pres: Johnson?
 This comment may be OBE by presentation.

One area where 33.2.8.4 is written for 4-Pair (Type 3/4) PSE's only:

The terms lport-2P and lport-2P-other are defined using terms from the Type 3/4 state diagram. These terms have no meaning for 2-Pair powering cases. lport-2P is then later used as vertical axis to current templates including those applicable to Type 1/2 PSEs.

lport is defined earlier with the Type 1 and Type 2 state machine in 33.2.5.4. that in turn references 33.2.8.6.

SuggestedRemedy

One remedy is to add a specificity to lport-2P definition:

lport-2P
 = lport for Type 1 and Type 2 PSE's
 = lport-2P-pri for the Primary Alternative of Type 3 and Type 4 PSEs
 = lport-2P-sec for the Secondary Alternative of Type 3 and Type 4 PSEs

lport-2P-other
 = lport-2P-sec for the Primary Alternative of Type 3 and Type 4 PSEs
 = lport-2P-pri for the Secondary Alternative of Type 3 and Type 4 PSEs

Proposed Response Response Status **W**
 WFP?
 TFTD

Cl 33 SC 33.2.8.4 P 106 L 28 # 17
 Darshan, Yair Microsemi
 Comment Type **ER** Comment Status **D** Editorial
 Comment #196 from D1.6 was not implemented correctly
 "lPort-2P and lPort-2P-other are the currents on the pairs with the same polarity of the two pairsets and are defined in Equation (33-5) **in and** Equation (33-6).
SuggestedRemedy
 Change to:
 "lPort-2P and lPort-2P-other are the currents on the pairs with the same polarity of the two pairsets and are defined in Equation (33-5) and in Equation (33-6)."
 Proposed Response Response Status **W**
 PROPOSED ACCEPT.

IEEE P802.3bt D1.7 4-Pair Power-over-Ethernet 10th Task Force review comments

Cl 33 SC 33.2.8.4 P 106 L 46 # 51
 Johnson, Peter Sifos Technologies

Comment Type T Comment Status X Pres: Johnson?

This comment may be OBE by presentation.

This comment may be OBE by presentation.

Equation 33-7 defines Icon-2P = Pclass / Vpse when in 2-pair mode. Table 33-17 (item 5) defines Icon = Pclass / Vport-PSE-2P. If we assume Vpse (defined in 1.4) is the really the same thing as Vport-PSE-2P (defined in Table 3-17), then Icon-2P is really the same as Icon.

Also, Pclass and Pclass-2P are really defined in EQ 33-2 and EQ 33-3 respectively, not Tables 33-11 and 33-12.

SuggestedRemedy

Change Equation 33-7 to:

Icon-2P
 = Icon when in 2-pair mode
 = min(.....) when 4-pair powering a single signature PD
 = Pclass-2P / Vpse when 4-pair powering a dual signature PD

where
 Pclass is defined in Equation 33-2
 Pclass-2P is defined in Equation 33-3

Proposed Response Response Status W

WFP?

TFTD

Cl 33 SC 33.2.8.4 P 107 L 7 # 52
 Johnson, Peter Sifos Technologies

Comment Type T Comment Status X Pres: Johnson?

This comment may be OBE by presentation.

Another area where 33.2.8.4 is written for 4-Pair (Type 3/4) PSE's only:

"A PSE is not required to support Icon-2P values greater than Icon-2P-unb. Icon is the total current of both pairs with the same polarity that a PSE supports. Icon-2P_unb is the maximum current the PSE supports over one of the pairs of the same polarity..."

SuggestedRemedy

Replace this text.

(New Paragraph)

"When a Type 3 or Type 4 PSE is powering 4 pairs, that PSE is not required to support Icon-2P values greater than Icon-2P-unb. Icon is the total current of both pairs with the same polarity that a PSE supports. Icon-2P_unb is the maximum current the PSE supports over one of the pairs of the same polarity..."

Proposed Response Response Status W

WFP?

TFTD

IEEE P802.3bt D1.7 4-Pair Power-over-Ethernet 10th Task Force review comments

Cl 33 SC 33.2.8.4 P 107 L 12 # 53
 Johnson, Peter Sifos Technologies

Comment Type T Comment Status X Pres: Johnson?

This comment may be OBE by presentation.

Another area where 33.2.8.4 is written for 4-Pair (Type 3/4) PSE's only:

"In addition to ICon, ICon-2P and ICon-2P-unb as specified in Table 33-17 and Equation (33-7), the PSE shall support the following AC current waveform parameters, while within the operating voltage range of VPort_PSE-2P:

I_{Peak}, I_{Peak-2P-unb}, and I_{Peak-2P} minimum for TCUT-2P minimum and 5 % duty cycle minimum, where"

SuggestedRemedy

This section needs some work. It probably should be re-written to individually address the three fundamental cases:

- 1) 2-Pair Powering:
Only need to define I_{peak-2P} using (Rchan) in quadratic
- 2) 4-Pair Powering Single Signature PD(where I_{peak-2P-unb} applies):
Define I_{peak}, I_{peak-2P}, I_{peak-2P_unb} using (Rchan/2) in the quadratic
- 3) 4-Pair Powering Dual Signature PD
Define I_{peak-2P} using (Rchan) and (P_{Peak_PD-2P}) in the quadratic

Proposed Response Response Status W

WFP?

TFTD

Cl 33 SC 33.2.8.4 P 107 L 33 # 54
 Johnson, Peter Sifos Technologies

Comment Type T Comment Status X Pres: Johnson?

This comment may be OBE by presentation.

There are 2 different equations for I_{peak-2P_unb}: EQ 33-9 and EQ 33-11.

EQ 33-9 describes I_{Peak-2P_unb} as a function of I_{peak} that is in turn a function of PSE port voltage and PD load.

EQ 33-11 describes I_{Peak-2P_unb} as a function of ILIM-2P, but ILIM-2P is not a function of PSE port voltage or PD load - it is a fixed value greater than ILIM-2P_min. Also, my sample calculation of I_{peak-2P_unb} for Class 6 (828mA) produces a figure well higher than ILIM-2P_min (702 mA) for Class 6.

Is EQ 33-11 indicating that ILIM-2P_min must be higher than what is in Table 33-17 ??????

SuggestedRemedy

Not sure what to do here.

One option is to just eliminate EQ 33-11. However, if it is adding information relevant to PSE behavior, we need to better capture that.

Proposed Response Response Status W

WFP?

TFTD

IEEE P802.3bt D1.7 4-Pair Power-over-Ethernet 10th Task Force review comments

Cl 33 SC 33.2.8.4 P 107 L 45 # 37
 Darshan, Yair Microsemi

Comment Type **TR** Comment Status **D** PSE Power

In 33.1.3 we have new definitions: Rchan and Rchan-2P.
 Equation 33-10 must use the Rchan-2P, so it is not required to use Rchan/2 while Rchan is not sufficiently specific and Rchan-2P is specific per 33.1.3.

SuggestedRemedy

1. Change from "Rchan/2" to "Rchan-2P" in Equation 33-10 in 4 locations.
2. Change "RChan is the channel DC loop resistance as defined in 33.1.3" To "RChan-2P is the channel DC loop resistance as defined in 33.1.3 per pairset.

Proposed Response Response Status **W**

PROPOSED ACCEPT.

Cl 33 SC 33.2.8.4.1 P 108 L 30 # 192
 Yseboodt, Lennart Philips

Comment Type **E** Comment Status **D** Editorial

"Type 3 and Type 4 PSEs operating over 4-pair are subject to unbalance requirements in this section."

SuggestedRemedy

"This section describes unbalance requirements for Type 3 and Type 4 PSEs that operate over 4-pair."

Proposed Response Response Status **W**

PROPOSED ACCEPT.

Cl 33 SC 33.2.8.4.1 P 108 L 39 # 193
 Yseboodt, Lennart Philips

Comment Type **E** Comment Status **D** Editorial

"Icon-2P-unb is specified for total channel common mode pair resistance from ..."

SuggestedRemedy

Change to:
 "Icon-2P-unb applies for the total channel common mode pair resistance ranging from ..."

Proposed Response Response Status **W**

PROPOSED ACCEPT.

Cl 33 SC 33.2.8.4.1 P 109 L 1 # 44
 Johnson, Peter Sifos Technologies

Comment Type **T** Comment Status **X** Unbalance

Rpse_max is defined as "the maximum PSE common mode effective resistance..." and Rpse_min is defined as "the minimum PSE common mode effective resistance".

This is slightly confusing and may infer that there are some maximum and minimum absolute values in some table somewhere.

SuggestedRemedy

Change to:

Rpse_min is the lowest possible effective resistance in the powered pairs of the same polarity.

For a given Rpse_min,

Rpse_max is the highest possible effective resistance in the powered pairs of the same polarity.

Proposed Response Response Status **W**

TFTD.

I don't think you can format it like that as the two parameters are inside a "where" that describes equation 33-13.

I also don't understand what we are really trying to say here.

Are we really trying to say that RPSE_min is the lower of the common mode effective resistance of the powered pairs of the same polarity? And RPSE_max is the maximum allowed common mode effective resistance in the powered pairs of the same polarity for a given RPSE_min?

IEEE P802.3bt D1.7 4-Pair Power-over-Ethernet 10th Task Force review comments

Cl 33 SC 33.2.8.5 P 109 L 10 # 194
 Yseboodt, Lennart Philips

Comment Type E Comment Status D Editorial

"POWER_UP mode occurs on each pairset between the PSE's transition to the POWER_UP state on that pairset and either the expiration of T Inrush-2P or, for Type 1 and Type 2 PSEs that make use of legacy powerup, the conclusion of PD inrush currents on that pairset (see 33.3.7.3 and legacy_powerup in 33.2.5.4)."

The term "POWER_UP mode" is only used 3 times in the doc, all in this section, and seems to be identical to the POWER_UP state. Is there a difference ?
 If not => replace by POWER_UP.

SuggestedRemedy

Change "POWER_UP mode" to "POWER_UP".
 Change 33.2.8.5 section title to "Output current during POWER_UP"

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 33 SC 33.2.8.5 P 109 L 16 # 81
 Picard, Jean Texas Instruments

Comment Type TR Comment Status D PSE Inrush

The following statement is incorrect in case where the PD is class 0-4, in which case a type 3 PSE is allowed to do inrush with only one 2P channel.

"Type 3 and Type 4 PSEs that apply power to both pairsets when connected to a single-signature PD shall reach the POWER_ON state on both pairsets within TInrush-2P max, starting with the first pairset transitioning into the POWER_UP state. The second pairset may transition to POWER_UP anytime within this time period."

SuggestedRemedy

Replace with this:

"Type 3 and Type 4 PSEs that have assigned Class 5 to 8 to a single-signature PD shall reach the POWER_ON state on both pairsets within TInrush-2P max, starting with the first pairset transitioning into the POWER_UP state, whereas the second pairset transitions to POWER_UP anytime within this time period."

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

TFTD

"Type 3 and Type 4 PSEs that have assigned Class 5 to 8 to a single-signature PD shall reach the POWER_ON state on both pairsets within TInrush-2P max, starting with the first pairset transitioning into the POWER_UP state, and where the second pairset transitions to POWER_UP anytime within this time period."

IEEE P802.3bt D1.7 4-Pair Power-over-Ethernet 10th Task Force review comments

Cl 33 SC 33.2.8.5 P 109 L 20 # 28
 Darshan, Yair Microsemi

Comment Type TR Comment Status X PSE Inrush

In the following text, it is not clear when the PSE is following the template:
 "The PSE shall limit Ilnrush-2P and Ilnrush during POWER_UP per the requirements of Table 33-17. The maximum inrush current sourced by the PSE per pairset shall not exceed the per pairset inrush template in Figure 33-26 and Equation (33-13)."
 in Figure 33-26 and Equation (33-13) some PD implementations start to show Ilnrush only after significant time (10-30msec) after the application of Vpd but still within Tinrush_min time duration but the template in figure 33-26 looks that it is relevant to Ilnrush appearance at t=0 only.

SuggestedRemedy

Change from:
 "The PSE shall limit Ilnrush-2P and Ilnrush during POWER_UP per the requirements of Table 33-17. The maximum inrush current sourced by the PSE per pairset shall not exceed the per pairset inrush template in Figure 33-26 and Equation (33-13)."

to:
 "The PSE shall limit Ilnrush-2P and Ilnrush during POWER_UP **state** per the requirements of Table 33-17. The maximum inrush current sourced by the PSE per pairset shall not exceed the per pairset inrush template in Figure 33-26 and Equation (33-13) **for the duration of POWER_UP state**."

Proposed Response Response Status W

TFTD

I am not sure how the suggested text makes your concern any clearer in the text.

Change to:
 "The PSE shall limit Ilnrush-2P and Ilnrush during POWER_UP per the requirements of Table 33-17. The maximum inrush current sourced by the PSE per pairset shall not exceed the per pairset inrush template in Figure 33-26 and Equation (33-13) for the duration of POWER_UP."

Cl 33 SC 33.2.8.5 P 110 L 9 # 195
 Yseboodt, Lennart Philips

Comment Type E Comment Status D Editorial

Equation 33-14 uses variable y1.
 Since there is neither a y0 or a y2, we can also rename it to 'i'.

SuggestedRemedy

Rename 'y1' to 'i' in Equation and variable list.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Rename it "Im". "i" seems like an index to something.

"Im" stands for I_{max} since this is what the variable represents.

IEEE P802.3bt D1.7 4-Pair Power-over-Ethernet 10th Task Force review comments

Cl 33 SC 33.2.8.5.1 P 110 L 32 # 212
Yseboodt, Lennart Philips

Comment Type ER Comment Status D PSE Inrush

"A Type 4 PSE, when connected to a single signature PD with assigned Class 7 or Class 8, may implement a minimum I Inrush lower than defined in Table 33-17, but not less than 0.4A respectively. When a Type 4 PSE is connected to a single-signature PD with assigned Class 7 or Class 8 and uses a lower I Inrush than which is defined in Table 33-17, it shall successfully power up a single-signature PD comprised of a parallel combination of 360 mF and a Class 2 load within T Inrush-2p min without startup oscillations during the POWER_UP period, when connected to the PD through a channel resistance of 0.1ohm to 12.5ohm per pairset."

First two sentences are very repetitive.

SuggestedRemedy

Shorter:

"A Type 4 PSE, when connected to a single signature PD with assigned Class 7 or Class 8, may implement a minimum I Inrush lower than defined in Table 33-17, but not less than 0.4A respectively. Such a PSE shall successfully power up a single-signature PD comprised of a parallel combination of 360 mF and a Class 2 load within T Inrush-2p min without startup oscillations during the POWER_UP period, when connected to the PD through a channel in the range of 0.1 ohm to Rch per pairset."

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

"A Type 4 PSE, when connected to a single signature PD with assigned Class 7 or Class 8, may implement a minimum I Inrush lower than defined in Table 33-17, but not less than 0.4A respectively. Such a PSE that implements a minimum I Inrush lower than defined in Table 33-17 shall successfully power up a single-signature PD comprised of a parallel combination of 360 mF and a Class 2 load within T Inrush-2p min without startup oscillations during the POWER_UP period, when connected to the PD through a channel in the range of 0.1 ohm to Rch per pairset."

Cl 33 SC 33.2.8.5.1 P 110 L 32 # 132
Stover, David Linear Technology

Comment Type E Comment Status D Editorial

"single-signature" is hyphenated and not capitalized, per our convention. There are 2 locations where this convention is not followed.

SuggestedRemedy

Global search and replace "single signature" with "single-signature".

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 33 SC 33.2.8.5.1 P 110 L 37 # 196
Yseboodt, Lennart Philips

Comment Type E Comment Status D Editorial

"during the POWER_UP period".

SuggestedRemedy

Shorter:

"... during POWER_UP ..."
Also on line 44

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 33 SC 33.2.8.5.1 P 110 L 39 # 213
Yseboodt, Lennart Philips

Comment Type ER Comment Status D Editorial

"A Type 4 PSE, when connected to a dual signature PD with assigned Class 5, may implement a minimum I Inrush and I Inrush-2P lower than defined in Table 33-17, but not less than 0.4A and 0.2A respectively. When a Type 4 PSE is connected to a dual-signature PD with assigned Class 5 and uses a lower I Inrush-2P than thosedefined in Table 33-17, it shall successfully power up a dual-signature PD comprised of a parallel combination of 110 mF and a Class 2 (TBD) load within T Inrush-2p min without startup oscillations during thePOWER_UP period, when connected to the PD through a channel resistance of 0.1ohm to 12.5ohm per pairset."

First two sentences are very repetitive.

SuggestedRemedy

Shorter:

"A Type 4 PSE, when connected to a dual signature PD with assigned Class 5, may implement a minimum I Inrush and I Inrush-2P lower than defined in Table 33-17, but not less than 0.4A and 0.2A respectively. Such a PSE shall successfully power up a dual-signature PD comprised of a parallel combination of 110 mF and a Class 2 (TBD) load within T Inrush-2p min without startup oscillations during the POWER_UP period, when connected to the PD through a channel resistance of 0.1ohm to Rch per pairset."

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

"A Type 4 PSE, when connected to a dual signature PD with assigned Class 5, may implement a minimum I Inrush and I Inrush-2P lower than defined in Table 33-17, but not less than 0.4A and 0.2A respectively. Such a PSE that implements a minimum I Inrush lower than defined in Table 33-17 shall successfully power up a dual-signature PD comprised of a parallel combination of 110 mF and a Class 2 (TBD) load within T Inrush-2p min without startup oscillations during the POWER_UP period, when connected to the PD through a channel resistance of 0.1ohm to Rch per pairset."

IEEE P802.3bt D1.7 4-Pair Power-over-Ethernet 10th Task Force review comments

Cl 33 SC 33.2.8.5.1 P 110 L 40 # 227
 Yseboodt, Lennart Philips

Comment Type T Comment Status D PSE Inrush

"When a Type 4 PSE is connected to a dual-signature PD with assigned Class 5 and uses a lower Inrush-2P than those defined in Table 33-17, it shall successfully power up a dual-signature PD comprised of a parallel combination of 110 uF and a Class 2 (TBD) load within TInrush-2p min without startup oscillations during the POWER_UP period, when connected to the PD through a channel resistance of 0.1ohm to 12.5ohm per pairset."

Unclear that this requirement applies per pairset.

SuggestedRemedy

Replace by:

"When a Type 4 PSE is connected to a dual-signature PD with assigned Class 5 and uses a lower Inrush-2P than those defined in Table 33-17, it shall successfully power up a dual-signature PD comprised of a parallel combination of 110 uF and a Class 2 (TBD) load ***on each pairset*** within TInrush-2p min without startup oscillations during the POWER_UP period, when connected to the PD through a channel resistance of 0.1ohm to 12.5ohm per pairset."

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 33 SC 33.2.8.6 P 110 L 48 # 45
 Johnson, Peter Sifos Technologies

Comment Type T Comment Status X PSE Power

Iport-2P is defined in two places, 33.2.8.4 and then again in 33.2.8.6. It should have only one definition, and given the present structure of the standard, that definition needs to be universal to all PSE types and powering modes. Both 33.2.8.4 and 33.2.8.6 infer a relationship between Iport-2P and Type 3/4 PSEs.

Suggestion is to broaden the Iport-2P definition in 33.2.8.4 - that is covered in a separate comment. Then move the Iport definition to 33.2.8.4 along side of the Iport-2P definition.

SuggestedRemedy

Modify 33.2.8.4:

Add first sentence:

"IPort is the total current supplied by the PSE to the PI."

Modify 33.2.8.6:

Revise:

"If IPort, the current supplied by the PSE to the PI, exceeds ICUT-2P for..."

to

"If IPort exceeds ICUT-2P for...."

Revise:

"If IPort-2P, the current supplied on a pairset by the PSE to the PI, exceeds ICUT-2P for longer..."

to

"If IPort-2P exceeds ICUT-2P for longer..."

Modify Iport definition in 33.2.5.4:

Revise:

"IPort Output current (see 33.2.8.6)."

to

"IPort Output current (see 33.2.8.4)."

Proposed Response Response Status W

TFTD

IEEE P802.3bt D1.7 4-Pair Power-over-Ethernet 10th Task Force review comments

Cl 33 SC 33.2.8.7 P 111 L 9 # 82
 Picard, Jean Texas Instruments

Comment Type TR Comment Status D PSE Power

There is an issue with allowing a Type 4 PSE to apply a 1.3A Upperbound template for as long as 4 seconds over 2P when powering a SS PD with Class 6 or lower or DS PD with class 4 or lower. That level of stress for so long can damage components that are not selected for this amount of energy, for example the data transformers of Mag Jacks.

SuggestedRemedy

Require Type 4 PSEs to apply the "Type 3 operating current template" when powering a Type 1-3 PD .

This means the following sentence:

"For Type 4 PSEs, Figure 33–29, Equation (33–17) and Equation (33–20) apply when connected to Type 4 PD, otherwise Figure 33–28, Equation (33–16) and Equation (33–19) apply. "

Proposed Response Response Status W

PROPOSED ACCEPT.

However, as we have dicussed before, the PD determines how much current is drawn. The PSE can't force 1.3A down the channel.

TFTD

Cl 33 SC 33.2.8.7 P 111 L 14 # 25
 Darshan, Yair Microsemi

Comment Type TR Comment Status X Pres: Darshan5

Referring to the text (see darshan_05_0516.pdf for details):

"**Part-1** Power shall be removed from a pairset PI of a PSE before the pairset PI current exceeds the "PSE upperbound template" in Figure 33-14, Figure 33-14a, and Figure 33-14b.

Part-2 When connected to a single signature PD, a Type 3 or Type 4 PSE should (TBD) remove power from both pairsets before the current exceeds the "PSE upperbound template" on either pairset."

Due to the fact that for single-signature PD:

- a)Each pairset is already protected by **part-1**.
- b)Shutting off both pairset doesn't add extra protection to the PD.
- c)Forcing the PSE to shut off both pairset in case of fault, kills PD applications that was designed to work at lower power in case of fault when 4-pairs is required for full power.

We don't need **Part-2** due to the fact that in single-signature PD if current over a pairset approaches the upper bound template, this pairset will be powered off, if the PD was not designed to handle lower power mode, the whole current will flow through the remaining pairset and it will be disconnected as well, so there is no need for the redundant text in **Part-2**.

SuggestedRemedy

Option 1:

Delete:

"When connected to a single signature PD, a Type 3 or Type 4 PSE should (TBD) remove power from both pairsets before the current exceeds the "PSE upperbound template"

Option 2: To address solution proposed by Chritian to be discussed by the group.

The solution may be described in darshan_05_0516.pdf if we get a consensus on the wording of it prior the meeting.

Proposed Response Response Status W

WFP

TFTD

IEEE P802.3bt D1.7 4-Pair Power-over-Ethernet 10th Task Force review comments

Cl 33 SC 33.2.8.7 P 111 L 14 # 228
 Yseboodt, Lennart Philips

Comment Type T Comment Status X Pres: Yseboodt4

"When connected to a single-signature PD, a Type 3 or Type 4 PSE should (TBD) remove power from both pairsets before the current exceeds the "PSE upperbound template" on either pairset."

SuggestedRemedy

See/adopt yseboodt_04_0516_pse4p.pdf

Proposed Response Response Status W

WFP

TFTD

Cl 33 SC 33.2.8.7 P 111 L 14 # 6
 Beia, Christian STMicroelectronics

Comment Type TR Comment Status X Pres: Yseboodt4

The following sentence,

When connected to a single-signature PD, a Type 3 or Type 4 PSE should (TBD) remove power from both pairsets before the current exceeds the "PSE upperbound template" on either pairset.

has several weak points:

- the (TBD) to be removed
- the "should" makes nobody happy: those who want the PSE to be able to go past a failure working on single pairset would ignore a recommendation, and those who want the power to be removed from both pairsets don't have the assurance it will be implemented.
- the timing requirements for power removal can increase PSE complexity.

The main goal here should be avoiding that a PD that failed to work over 4-pairs, when powered on 2-pairs would exceed the current originally intended to flow on one pairset, potentially overstressing the magnetics.

So, the requirement should allow the PSE to disconnect only one pairset only if the current of thesecond pairset is below one-half of the assigned power (i.e. the current that was originally supposed to flow in that pairset). It ensures that the PD is still keeping control of its own current, and no damage occurred.

See also Darshan_05

SuggestedRemedy

Replace:

When connected to a single-signature PD, a Type 3 or Type 4 PSE should (TBD) remove power from both pairsets before the current exceeds the "PSE upperbound template" on either pairset.

With:

When connected to a single-signature PD, a Type 3 or Type 4 PSE may remove power from one pairset and maintain power on the other pairset only if the PD power consumption is below one half of the assigned Pclass (0.5*Pclass).

Proposed Response Response Status W

WFP

TFTD

IEEE P802.3bt D1.7 4-Pair Power-over-Ethernet 10th Task Force review comments

Cl 33 SC 33.2.8.7 P 112 L 12 # 46
 Johnson, Peter Sifos Technologies
 Comment Type T Comment Status D PSE Power
 Figures 33-28 and 33-29 include an ILIM parameter on the right vertical axis. But there is no ILIM definition any more.
 Presumably, these should be removed.
 SuggestedRemedy
 Remove ILIM from Figures 33-28 and 33-29.
 Proposed Response Response Status W
 PROPOSED ACCEPT.
 TFTD

Cl 33 SC 33.2.8.7 P 112 L 48 # 47
 Johnson, Peter Sifos Technologies
 Comment Type E Comment Status D Editorial
 References to equations are all off by one.
 SuggestedRemedy
 Replace with:
 "...described by Equation (33-15), Equation (33-16), Equation (33-17)..."
 Proposed Response Response Status W
 PROPOSED ACCEPT.

Cl 33 SC 33.2.8.7 P 113 L 31 # 48
 Johnson, Peter Sifos Technologies
 Comment Type E Comment Status D Editorial
 The list of variables beneath Equations 33-15, 33-16, and 33-17 include 3 terms not used in those equations: PType max, VPSE, and lport-2P-other.
 SuggestedRemedy
 Remove these terms.
 Proposed Response Response Status W
 PROPOSED ACCEPT.

Cl 33 SC 33.2.8.7 P 114 L 16 # 49
 Johnson, Peter Sifos Technologies
 Comment Type TR Comment Status D PSE Power
 The list of variables beneath Equations 33-18, 33-19, 33-20 includes the term Icon-2P but it is 'Icon-2P min' that is used in the equations.
 The definition for Icon-2P is okay.
 SuggestedRemedy
 Replace Icon-2P with 'Icon-2P min'.
 Proposed Response Response Status W
 PROPOSED ACCEPT.

Cl 33 SC 33.2.8.7 P 114 L 22 # 197
 Yseboodt, Lennart Philips
 Comment Type E Comment Status D Editorial
 "A PSE in the POWER_ON state may remove power from a pairset without regard to T LIM when the pairset voltage no longer meets the V Port_PSE-2P specification."
 T LIM does not exist.
 SuggestedRemedy
 "A PSE in the POWER_ON state may remove power from a pairset without regard to T LIM-2P when the pairset voltage no longer meets the V Port_PSE-2P specification."
 Proposed Response Response Status W
 PROPOSED ACCEPT.

Cl 33 SC 33.2.8.13 P 115 L 37 # 198
 Yseboodt, Lennart Philips
 Comment Type E Comment Status D Editorial
 "Type 3 and Type 4 PSEs, when connected to a single-signature PD, both pairsets shall reach the POWER_ON state within T pon after detection on last pairset."
 Bad English.
 SuggestedRemedy
 "Type 3 and Type 4 PSEs, when connected to a single-signature PD, shall reach the POWER_ON state within T pon after completing detection on the last pairset."
 Proposed Response Response Status W
 PROPOSED ACCEPT.

IEEE P802.3bt D1.7 4-Pair Power-over-Ethernet 10th Task Force review comments

Cl 33 SC 33.2.10 P 116 L 14 # 214
 Yseboodt, Lennart Philips

Comment Type ER Comment Status D Editorial

"Figure 33-20 shows the PSE monitor state diagrams."
 Bad reference.

SuggestedRemedy

"Figure 33-14 shows the PSE monitor state diagrams for Type 1 and Type 2 PSEs. Figure 33-22 and Figure 22-23 show the PSE monitor state diagrams for Type 3 and Type 4 PSEs."

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

"Figure 33-14 shows the PSE monitor state diagrams for Type 1 and Type 2 PSEs. Figure 33-22 and Figure 33-23 show the PSE monitor state diagrams for Type 3 and Type 4 PSEs."

Cl 33 SC 33.2.10.1.1 P 117 L 25 # 199
 Yseboodt, Lennart Philips

Comment Type E Comment Status D Editorial

Table 33-18 is formatted differently from every other Table in the doc.

SuggestedRemedy

- Remove 'bold' from subtable headers (eg. "AC signal parameters")
- Fix item numbering to be numerical (1, 2, 3, ...)

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 33 SC 33.2.10.1.2 P 118 L 26 # 248
 Yseboodt, Lennart Philips

Comment Type TR Comment Status D PSE MPS

"A PSE, depending on the connected Type of PD, shall use the applicable I Hold min, I Hold max, T MPS and T MPDO values as defined in Table 33-17."

Needs to mention I_Hold-2P.

SuggestedRemedy

"A PSE, depending on the connected Type of PD and whether it is a single-, or dual-signature PD, shall use the applicable I Hold, I Hold-2P , T MPS and T MPDO values as defined in Table 33-17."

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

"A PSE, depending on the connected Type of PD and whether it is a single-signature or dual-signature PD, shall use the applicable I Hold, I Hold-2P , T MPS and T MPDO values as defined in Table 33-17."

IEEE P802.3bt D1.7 4-Pair Power-over-Ethernet 10th Task Force review comments

Cl 33 SC 33.2.10.1.2 P 118 L 30 # 55
 Johnson, Peter Sifos Technologies

Comment Type T Comment Status D PSE MPS

It seems that this section is not accounting for a Type 3 PSE that powers 2-pair (Class 1-3). The rules for Type 3 and Type 4 PSEs are written for 4-Pair powering of single signature and dual signature PDs.

SuggestedRemedy

Revise:
 "A Type 1 and Type 2 PSE:" to
 "A PSE powering with 2 pairs:"

Revise:
 "A Type 3 or Type 4 PSE, when connected to a single-signature PD:" to
 "A PSE powering a single signature PD with 4 pairs:"

Revise:
 "A Type 3 or Type 4 PSE, when connected to a dual-signature PD:" to
 "A PSE powering a dual signature PD with 4 pairs:"

Proposed Response Response Status W
 PROPOSED ACCEPT IN PRINCIPLE.

DS PD rules should not change based on number of powered pairsets (DS PDs have their own unique rules per pairset). Also, I suggest keeping the Types listed to make it easier to a reader to understand

Revise:
 "A Type 1 and Type 2 PSE:" to
 "A Type 1, Type 2, or Type 3 PSE powering a single-signature PD with 2 pairs:"

Revise:
 "A Type 3 or Type 4 PSE, when connected to a single-signature PD:" to
 "A Type 3 or Type 4 PSE powering a single signature PD with 4 pairs:"

Revise:
 "A Type 3 or Type 4 PSE, when connected to a dual-signature PD:" to
 "A Type 3 or Type 4 PSE powering a dual signature PD:"

Cl 33 SC 33.2.10.1.2 P 118 L 32 # 200
 Yseboodt, Lennart Philips

Comment Type E Comment Status D PSE MPS

The DC MPS Type 1 and Type 2 requirements (the dashed list), still say "the applicable" in the first 3 items (line 32, 34 and 36/37).

This is already stated above and is not needed here.

SuggestedRemedy

Remove "the applicable" three times.

Proposed Response Response Status W
 PROPOSED ACCEPT.

Cl 33 SC 33.2.10.1.2 P 118 L 40 # 229
 Yseboodt, Lennart Philips

Comment Type T Comment Status D PSE MPS

"A Type 1 and Type 2 PSE: - shall not remove power from the PI when I Port is greater than or equal to I Hold-2P max continuously for at least T MPS every T MPS + T MPDO , as defined in Table 33-17."

This final shall is inconsistently worded compared to the "do not remove power" shalls for Type 3 and Type 4.

See: hstewart_01_0116_DC_MPS_Template_v8.pdf for what the intent was.

SuggestedRemedy

Replace by:
 "- shall not remove power from the PI when DC MPS has been present within the T_MPS + TMPDO window."

Proposed Response Response Status W
 PROPOSED ACCEPT.

IEEE P802.3bt D1.7 4-Pair Power-over-Ethernet 10th Task Force review comments

CI 33 SC 33.2.10.1.2 P 118 L 40 # 230
 Yseboodt, Lennart Philips

Comment Type T Comment Status D PSE MPS

"A Type 1 and Type 2 PSE: - shall not remove power from the PI when I Port is greater than or equal to I Hold-2P max continuously for at least T MPS every T MPS + T MPDO , as defined in Table 33-17."

"A Type 3 or Type 4 PSE, when connected to a single-signature PD: -shall not remove power from the PI when DC MPS has been present within the T MPS + T MPDO window. This allows a PD to minimize its power consumption."

"A Type 3 or Type 4 PSE, when connected to a dual-signature PD: -- shall not remove power from a pairset when DC MPS has been present on both pairsets every T MPS + T MPDO ."

These shalls are essentially meaningless. PSEs may remove power for any reason. The PSE shall remove power in the case of overcurrent, or Vport-2P being out of spec.

This is to protect against bad MPS implementations that remove power when they shouldn't.

SuggestedRemedy

Add a condition 'unless there is a non-MPS related reason to do so':

"A Type 1 and Type 2 PSE: - shall not remove power from the PI, unless there is a non-MPS related reason to do so, when I Port is greater than or equal to I Hold-2P max continuously for at least T MPS every T MPS + T MPDO , as defined in Table 33-17."
 (Note: merge the above with the other comment that touches this if adopted).

"A Type 3 or Type 4 PSE, when connected to a single-signature PD: -shall not remove power from the PI, unless there is a non-MPS related reason to do so, when DC MPS has been present within the T MPS + T MPDO window. This allows a PD to minimize its power consumption."

"A Type 3 or Type 4 PSE, when connected to a dual-signature PD: -- shall not remove power from a pairset, unless there is a non-MPS related reason to do so, when DC MPS has been present on both pairsets every T MPS + T MPDO ."

Proposed Response Response Status W
 PROPOSED ACCEPT IN PRINCIPLE.

I understand the idea, but the wording is terrible. Also, .3at did not include this language, do we need to?

How about, "...shall not remove power for due to MPS absense when..."

TFTD

CI 33 SC 33.2.10.1.2 P 118 L 52 # 249
 Yseboodt, Lennart Philips

Comment Type TR Comment Status X PSE MPS

For Type 3 and 4 PSEs, connected to a single-signature PD, there are 2 'shall's' and a 'may' that determine if DC MPS component is either PRESENT, ABSENT or PRESENT OR ABSENT. These requirements should not overlap, ie, only one of those 3 conditions can be true at the same time.

The 'may' statement overlaps with the two shalls for certain combinations of current. For example, if the Iport-2P currents are 1mA and 6mA respectively, the first 'shall' says MPS is PRESENT.

The may statement however is also True, indicating that MPS may be PRESENT OR ABSENT.

To avoid overlap, the two shall statements need to be made more narrow.

SuggestedRemedy

The 'or' in the first two shall statements for "A Type 3 or Type 4 PSE, when connected to a single-signature PD" needs to become and 'and':
 - change "or" to "and" on page 118, line 46
 - change "or" to "and" on page 118, line 49

Proposed Response Response Status W
 TFTD

I don't like this remedy as it implies that the PSE must check both the sum and individual pairset currents.

CI 33 SC 33.2.10.1.2 P 119 L 19 # 231
 Yseboodt, Lennart Philips

Comment Type T Comment Status D PSE MPS

"A Type 3 or Type 4 PSE, when connected to a dual-signature PD: -may maintain power on a pairset if DC MPS has been present on that pairset every T MPS + T MPDO."

Is inconsistent in describing the timing requirements.

SuggestedRemedy

"-may maintain power on a pairset _when_ DC MPS has been present on that pairset _within_ the T MPS + T MPDO _window_."

Proposed Response Response Status W
 PROPOSED ACCEPT.

IEEE P802.3bt D1.7 4-Pair Power-over-Ethernet 10th Task Force review comments

Cl 33 SC 33.2.10.1.2 P 119 L 22 # 26
 Darshan, Yair Microsemi

Comment Type TR Comment Status X PSE MPS

False disconnect or false maintain power as a result of Short MPS under PSE transient need to be addressed.

We need to allow PSE system to decide what to do in this case when a PSE dv of up to 2V for a dt of 0.8ms to 20ms which result with distored of the short MPS pulse for at least one cycle of MPS+TMPDO for a specific time window.

SuggestedRemedy

Add the following text to the end of section 33.2.10.1.2:

Option 1:

Type 3 and Type 4 PSE when supporting short MPS may fail to detect presence or absence of a short MPS pulse as a result of PSE dv/dt that may cancel or distorted or add MPS pulse. Type 3 and Type 4 PSE when supporting short MPS during PSE dv/dt for PSE voltage change dv of up to 2V and time duration dt of 0.8msec to 10msec for a sliding time window of 3 sec (TBD) may maintain the power or disconnect the power when presence or absence of short MPS pulse is not possible under the above conditions.

Option 2:

A PSE may ignore the current MPS status of a short MPS pulse once every 3 seconds, which permits PSEs to deal with seldom occurring transients that may distort the MPS signal.

Proposed Response Response Status W

TFTD

I do not like either option. Option 1 says "up to 2V" which means that a PSE can always ignore the MPS status and say that there was a 1nV transient. Option 2 seems way to often. To let the PSE ignore a missed MPS pulse every 3 seconds seems to make it just a matter of time before something is unplugged and something new is plugged in and the PSE toasts some poor NIC.

Cl 33 SC 33.3.1 P 119 L 41 # 145
 Yseboodt, Lennart Philips

Comment Type E Comment Status D Editorial

"Type 3 and Type 4 PDs shall be capable of accepting power on either pairset and shall be capable of accepting power on both pairsets."

SuggestedRemedy

Shorter:

"Type 3 and Type 4 PDs shall be capable of accepting power on either pairset and both pairsets."

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 33 SC 33.3.2 P 120 L 31 # 146
 Yseboodt, Lennart Philips

Comment Type E Comment Status D Editorial

Table 33-20, column "Other optional capabilities"
 The word "other" in the header is obsolete.

SuggestedRemedy

Remove "other" in header.

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 33 SC 33.3.3 P 121 L 13 # 232
 Yseboodt, Lennart Philips

Comment Type T Comment Status X Pres: Yseboodt12

Updates to the PD State Diagram

SuggestedRemedy

Adopt yseboodt_12_0516_pdstatedia.pdf

Proposed Response Response Status W

WFP

TFTD

Cl 33 SC 33.3.3.5 P 124 L 1 # 147
 Yseboodt, Lennart Philips

Comment Type E Comment Status X Pres: Yseboodt05

The PD legacy state machine has the issue that it is incapable of leaving the IDLE state.

SuggestedRemedy

See yseboodt_05_0516_pdsmllegacy.pdf

Proposed Response Response Status W

WFP

TFTD

IEEE P802.3bt D1.7 4-Pair Power-over-Ethernet 10th Task Force review comments

Cl 33 SC 33.3.3.5 P 124 L 3 # 86
 Schindler, Fred Seen Simply, Broadco
 Comment Type **TR** Comment Status **D** Editorial
 The remedy to D1.6, comment 248 may not be completely implemented. I believe the request should apply to legacy state diagrams.
 SuggestedRemedy
 Implement the accepted solution,
 "Replace all square brackets with parenthesis in state diagrams."
 Proposed Response Response Status **W**
 TFTD
 We have decided to leave the existing Type 1/2 state machine alone (except for maintenance requests). Does this include formatting?

Cl 33 SC 33.2.3.8 P 127 L 38 # 87
 Schindler, Fred Seen Simply, Broadco
 Comment Type **TR** Comment Status **D** PD SD
 Existing sentence, "tpowerdly_timer
 A timer used to prevent Type 2 and Type 3 PDs from drawing more than Type 1 power and Type 4 PDs from drawing more than Class 2 power during the PSE's inrush period; see Tdelay-2P in Table 33-28." Incorrectly covers Type 2 PDs in the Type 3 and 4 section. Type 2 PDs are covered by legacy text on p123.
 SuggestedRemedy
 Replace the sentence with, "tpowerdly_timer
 A timer used to prevent Type 3 PDs from drawing more than Type 1 power and Type 4 PDs from drawing more than Class 2 power during the PSE's inrush period; see Tdelay-2P in Table 33-28."
 Proposed Response Response Status **W**
 PROPOSED ACCEPT.

Cl 33 SC 33.3.3.10 P 129 L 8 # 42
 Darshan, Yair Microsemi
 Comment Type **TR** Comment Status **X** Pres: Darshan7
 It is not clear that the state machine permits Tdelay also for Type 1.
 Technically there is no need for it since Type 1 current always < PSE Inrush_min however to simplify future PD chip designs we need to allow same behavior for all PD types regarding delaying the load current consumption by Tdelay.
 SuggestedRemedy
 See darshan_07_0516.pdf for proposed remedy.
 Proposed Response Response Status **W**
 WFP
 TFTD
 However, I see no need for this because the Tpowerdly timer is meant to make all PDs act like Type 1, which Type 1 PDs already do...

Cl 33 SC 33.3.3.10 P 129 L 41 # 18
 Darshan, Yair Microsemi
 Comment Type **ER** Comment Status **D** PD SD
 Title of figure 33-33 need to be 33-2
 SuggestedRemedy
 Change fig number to 33-2
 Proposed Response Response Status **W**
 PROPOSED ACCEPT IN PRINCIPLE.
 Change figure number to "33-32" as its "continued"
 Replace "The PD shall provide the behavior of the state diagram shown in Figure 33-32."
 With: "Type 1 and Type 2 PDs shall provide the behavior of the state diagram shown in Figure 33-31. Single-signature Type 3 and Type 4 PDs shall provide the behavior of the state diagram shown in Figure 33-32. Dual-signature Type 3 and Type 4 PDs shall provide the behavior of the state diagram shown in Figure 33-33."
 Change all figure numbering after 33-32 to match.

IEEE P802.3bt D1.7 4-Pair Power-over-Ethernet 10th Task Force review comments

Cl 33 SC 33.3.3.11 P 130 L 3 # 38
 Darshan, Yair Microsemi
 Comment Type **TR** Comment Status **X** Pres: Darshan6
 To add dual sig PD state machine.
 SuggestedRemedy
 See proposal for dual-signature state machine in darshan_06_0516.pdf
 Proposed Response Response Status **W**
 WFP
 TFTD

Cl 33 SC 33.3.4 P 131 L 1 # 250
 Yseboodt, Lennart Philips
 Comment Type **TR** Comment Status **X** Pres: Yseboodt3
 A PD is either a single-, or a dual-signature device. The determination of single/dual impacts nearly every requirement.
 Yet the PD section offers zero guidance or requirements on what a PD needs to meet to be guaranteed to be correctly identified by connection check.
 SuggestedRemedy
 Adopt yseboodt_03_0516_pdsig.pdf
 Proposed Response Response Status **W**
 WFP
 TFTD

Cl 33 SC 33.3.4 P 131 L 9 # 251
 Yseboodt, Lennart Philips
 Comment Type **TR** Comment Status **D** PD Detection
 "A Type 2 PD presents a non-valid detection signature when in a mark event state per Figure 33-32."
 SuggestedRemedy
 Change to:
 "A Type 2, Type 3 or Type 4 PD ..."
 Proposed Response Response Status **W**
 PROPOSED ACCEPT IN PRINCIPLE.
 We have different PD SDs.
 Change to: "A Type 2, Type 3, or Type 4 PD presents a non-valid detection signature when in a mark event state per Figure 33-31, Figure 33-32, and Figure 33-33.

Cl 33 SC 33.3.4 P 131 L 9 # 88
 Schindler, Fred Seen Simply, Broadco
 Comment Type **TR** Comment Status **D** PD Detection
 Existing sentence, "A Type 2 PD presents a non-valid detection signature when in a mark event state per Figure 33-32." should apply to all PDs that respond to multievent classification. Note that the reference figure is incorrect and on reference is missing.
 SuggestedRemedy
 Replace the sentence with, "A Type 2, 3 and 4 PDs presents a non-valid detection signature when in a mark event state per Figure 33-31and Figure 33-33."
 Proposed Response Response Status **W**
 PROPOSED ACCEPT IN PRINCIPLE.
 OBE by 251

Cl 33 SC 33.3.4 P 132 L 3 # 89
 Schindler, Fred Seen Simply, Broadco
 Comment Type **TR** Comment Status **D** Editorial
 Tables 33-21 and 33-22 do not use the same style as other tables.
 SuggestedRemedy
 Recommend Table 33-26 be used as a guide to add missing columns, Item, and Symbol. Column Unit should also be relocated to match style. Provide editor with license to fill in other columns. Thank the Editor for exception this. This is related to comment marked COMMENT-1.
 Proposed Response Response Status **W**
 PROPOSED REJECT.
 Why is this a technical comment?
 If none of the parameters from these tables are referenced by name in the draft, why do they need Item numbers and symbols?
 TFTD

IEEE P802.3bt D1.7 4-Pair Power-over-Ethernet 10th Task Force review comments

Cl 33 SC 33.3.4 P 132 L 5 # 91
 Schindler, Fred Seen Simply, Broadco
 Comment Type **TR** Comment Status **D** Editorial
 Related to a comment marked COMMENT-1. Tables 33-21 and 33-22 use Rdetect as a Symbol (indirectly) as a reference for different conditions.
 SuggestedRemedy
 Replace the Rdetect in Table 33-22 with Rdetect_invlaid.
 Proposed Response Response Status **W**
 PROPOSED ACCEPT.

Cl 33 SC 33.3.4 P 132 L 11 # 148
 Yseboodt, Lennart Philips
 Comment Type **E** Comment Status **D** Editorial
 Table 33-21, column widths are too narrow.
 SuggestedRemedy
 Format properly.
 Proposed Response Response Status **W**
 PROPOSED ACCEPT.

Cl 33 SC 33.3.4 P 132 L 12 # 90
 Schindler, Fred Seen Simply, Broadco
 Comment Type **TR** Comment Status **D** Editorial
 Fix the last two rows of Table 33-21 so that Min and Max columns are wide enough to accommodate the numbers within each cell.
 SuggestedRemedy
 See comment for the solution.
 Proposed Response Response Status **W**
 PROPOSED ACCEPT IN PRINCIPLE.
 OBE by 148

Cl 33 SC 33.3.5 P 133 L 22 # 149
 Yseboodt, Lennart Philips
 Comment Type **E** Comment Status **D** Editorial
 "Type 1 PDs and Class 1 to 3 Type 3 PDs" is hard to read.
 SuggestedRemedy
 Change to:
 "Type 1 PDs and Type 3 Class 1 to 3 PDs"
 Proposed Response Response Status **W**
 PROPOSED ACCEPT.

Cl 33 SC 33.3.5.1 P 133 L 23 # 150
 Yseboodt, Lennart Philips
 Comment Type **E** Comment Status **D** Editorial
 "Type 2 PDs, Class 4 to 6 Type 3 PDs, Type 4 PDs, and dual-signature PDs shall provide DLL classification."
 Better to mention Type first, then Class.
 SuggestedRemedy
 "Type 2 PDs, Type 3 Class 4 to 6 PDs, Type 4 PDs, and dual-signature PDs shall provide DLL classification."
 Proposed Response Response Status **W**
 PROPOSED ACCEPT.

Cl 33 SC 33.3.5.1 P 133 L 41 # 151
 Yseboodt, Lennart Philips
 Comment Type **E** Comment Status **D** Editorial
 "Type 2, Type 3, and Type 4 PDs operating with a maximum power draw corresponding to Class 4 or higher, respond to Single-Event classification with a Class 4 signature."
 Class 4 signature == class signature `4`.
 SuggestedRemedy
 "Type 2, Type 3, and Type 4 PDs operating with a maximum power draw corresponding to Class 4 or higher, respond to Single-Event classification with class signature `4`."
 Proposed Response Response Status **W**
 PROPOSED ACCEPT.

IEEE P802.3bt D1.7 4-Pair Power-over-Ethernet 10th Task Force review comments

Cl 33 SC 33.3.5.3 P 136 L 44 # 152
 Yseboodt, Lennart Philips
 Comment Type E Comment Status D Editorial
 "VPD rises above VPort_PD min" in column "Additional information" had larger font size (2x)
 SuggestedRemedy
 Change font size.
 Proposed Response Response Status W
 PROPOSED ACCEPT.

Cl 33 SC 33.3.7.1 P 140 L 4 # 153
 Yseboodt, Lennart Philips
 Comment Type E Comment Status D Editorial
 "Note, VPD = VPSE - (R Chan x I Port-2P)" VPD has smaller font size than the rest of equation.
 SuggestedRemedy
 Change to correct font size.
 Proposed Response Response Status W
 PROPOSED ACCEPT.

Cl 33 SC 33.3.6 P 137 L 1 # 233
 Yseboodt, Lennart Philips
 Comment Type T Comment Status D PD Power
 "The default value of pse_power_level is 3. After a successful Multiple-Event Physical Layer classification has completed the pse_power_level is set to either 3, 4, 6, or 8. After a successful Data Link Layer classification has completed, the pse_power_level is set to either 1, 2, 3 or 4."
 Obviously impossible.
 SuggestedRemedy
 Change last sentence to:
 "After a successful Data Link Layer classification has completed, the pse_power_level is set to either 3, 4, 6 or 8."
 Proposed Response Response Status W
 PROPOSED ACCEPT.

Cl 33 SC 33.3.7.2.1 P 140 L 36 # 11
 Bennett, Ken Sifos Technologies, In
 Comment Type TR Comment Status X PD Power
 Until recently, Pport_PD only existed in 33.3.7.2.1. Pport_PD and Pport_PD_2P are now symbols for the input average power in Table 33-28 and in 33.3.7.2.
 The definitions of the Pport_PD and Pport_PD_2P variables in Section 33.3.7.2.1 are in conflict with the average power variables in the PClass_PD specification. They use a static (fixed) Vport_PD_2P value which is incorrect; The PD input Voltage changes dynamically with power variations in the PD (due to channel resistance).
 Section 33.3.7.2.1 also doesn't seem to make sense. It is a subsection of 33.3.7.2-Input Average Power, and is entitled:
 "System Stability Test Conditions During Start-up and Steady State."
 The content states Pport_PD and Pport_PD_2P "shall be defined by" ..., and that's it. There IS no test condition mentioned. Pport_PD isn't even used anywhere else in the existing (.at) standard.
 Section 33.3.7.2.1 should be deleted. Alternatively, different symbols should be used for average power in table 33-28.
 SuggestedRemedy
 Delete section 33.3.7.2.1.
 OR
 Change Pport_PD and Pport_PD_2P in table 33-28 to Pavg_PD and Pavg_PD_2P.
 Proposed Response Response Status W
 TFTD
 Does this affect anything I am not seeing?

Cl 33 SC 33.3.7 P 138 L 29 # 234
 Yseboodt, Lennart Philips
 Comment Type T Comment Status D Editorial
 Table 33-28, item 8 and 9 say "single-signature PD only" and "dual-signature PD only"
 SuggestedRemedy
 Remove the word 'only'.
 Proposed Response Response Status W
 PROPOSED ACCEPT.

IEEE P802.3bt D1.7 4-Pair Power-over-Ethernet 10th Task Force review comments

Cl 33 SC 33.3.7.2.1 P 140 L 50 # 154
 Yseboodt, Lennart Philips
 Comment Type E Comment Status D Editorial
 PPort_PD-2P in equation 33-24 font size is larger than e.g. equation 33-23.
 SuggestedRemedy
 Change to correct font size. [Note to self: all Eqs must be medium-size].
 Proposed Response Response Status W
 PROPOSED ACCEPT.

Cl 33 SC 33.3.7.3 P 141 L 7 # 133
 Stover, David Linear Technology
 Comment Type TR Comment Status X Pres: Stover2
 PD input inrush current requirements are inconsistent with other sections of the text.
 SuggestedRemedy
 See stover_02_0516.pdf
 Proposed Response Response Status W
 WFP
 TFTD

Cl 33 SC 33.3.7.3 P 141 L 7 # 215
 Yseboodt, Lennart Philips
 Comment Type ER Comment Status X Pres: Yseboodt10
 The PD inrush section is particularly troublesome. How many times have we tweaked this text. It doesn't seem to improve.
 SuggestedRemedy
 Completely new text, adopt yseboodt_10_0516_pdinrush.pdf
 Proposed Response Response Status W
 WFP
 TFTD

Cl 33 SC 33.3.7.3 P 141 L 8 # 68
 Picard, Jean Texas Instruments
 Comment Type TR Comment Status D PD Inrush
 PD inrush section needs to be cleaned up to remove contradicting sentences and make the spec simpler and clearer.
 SuggestedRemedy
 See yseboodt_10_0516_pdinrush.pdf
 Proposed Response Response Status W
 PROPOSED ACCEPT IN PRINCIPLE.
 OBE by outcome of 215.

Cl 33 SC 33.3.7.3 P 141 L 16 # 30
 Darshan, Yair Microsemi
 Comment Type TR Comment Status X Pres: Darshan2
 Addressing comments # 179 and others related to this clause as elaborated below from D1.6:
 The following proposed modifications are addressing the following questions:
 1.Does PDs that are internally limiting their inrush current are required to end Inrush period within TInrush-2P min per Table 33-17?
 2.How we prevent that PD internal load during linrush period is less than Inrush current setting value to ensure successful POWER_UP?
 3.Adding a note that explains why the PD PI current is not equal to the DC load current during POWER UP.
 4.Adding text that addresses the new 110uF value for dual-signature class 1-4.
 SuggestedRemedy
 See darshan_02_0516.pdf for proposed remedy.
 Proposed Response Response Status W
 WFP
 TFTD

IEEE P802.3bt D1.7 4-Pair Power-over-Ethernet 10th Task Force review comments

Cl 33 SC 33.3.7.3 P 141 L 22 # 155
 Yseboodt, Lennart Philips

Comment Type E Comment Status D Editorial

"T delay-2P for each pairset starts when V PD crosses the PD power supply turn on voltage, V On_PD."
 V PD has smaller font size than V On_PD.

SuggestedRemedy

Change to correct font size

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 33 SC 33.3.7.3 P 141 L 23 # 156
 Yseboodt, Lennart Philips

Comment Type E Comment Status D Editorial

"This delay is required so that the Type 2, Type 3 and Type 4 PD does not enter ...".
 Use "or" instead of "and".

SuggestedRemedy

"This delay is required so that the Type 2, Type 3 or Type 4 PD does not enter ...".

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 33 SC 33.3.7.3 P 141 L 35 # 92
 Schindler, Fred Seen Simply, Broadco

Comment Type TR Comment Status D Editorial

Text previously corrected was changed back to the same undesirable form. It is incorrect to state that a thing has human properties, liking seeing.

SuggestedRemedy

Existing text:

CPort in Table 33–28 is the total PD input capacitance during the POWER_UP and POWER_ON states that a PSE sees as load when operating one or both pairsets, when connected to a single-signature PD. CPort-2P in Table 33–28 is the PD input capacitance during the POWER_UP and POWER_ON states that a PSE sees as load on each pairset independently, when connected to a dual-signature PD.

Corrected:

A PSE is connected to CPort in Table 33–28 during POWER_UP and POWER_ON states, when connected to a single-signature PD. A PSE is connected to CPort-2P in Table 33–28, on each pairset, during POWER_UP and POWER_ON states, when connected to a dual-signature PD.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

While factually correct, the new text doesn't actually provide any clarity on what Cport and Cport-2P are...

TFTD, new text is welcome.

IEEE P802.3bt D1.7 4-Pair Power-over-Ethernet 10th Task Force review comments

Cl 33 SC 33.3.7.4 P 141 L 49 # 56
 Johnson, Peter Sifos Technologies

Comment Type T Comment Status X Pres: Johnson1

This comment is a recommendation to separate concepts of extended power to class 6 and class 8 PDs and associated requirements to meet *PSE* output power rather than *PD* input power requirements from other more general and more widely applicable PD requirements. We also need to better qualify the cases where Class 6 and Class 8 PDs are not subject to Pclass_PD and Ppeak_PD limits.

Rationale is that extended power will be applicable only in specialized systems that are engineered to allow certain PD's to operate above Pclass_PD and interoperate with standard compliant PSE's.

SuggestedRemedy

Create new sub-sections 33.7.2.1 and 33.3.7.4.1.

Re-locate Class 6 / Class 8 extended power text, formulas, and current templates into those respective sections.

I will separately provide a document (baseline text) showing what this would look like in johnson_01_0516_Extended_Pwr_baseline_v1.docx.

Proposed Response Response Status W

WFP

TFTD

Cl 33 SC 33.3.7.3 P 142 L 2 # 8
 Bennett, Ken Sifos Technologies, In

Comment Type E Comment Status D Editorial

Figure 33-37 is an Inrush section figure, but it appears within the Ppeak_PD section

SuggestedRemedy

Place the figure within the Inrush section

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

I have a feeling there isn't room on the previous page so frame has moved it to the next. Editor to make sure figure is properly placed in Frame.

Cl 33 SC 33.3.7.3 P 142 L 2 # 93
 Schindler, Fred Seen Simply, Broadco

Comment Type TR Comment Status D PSE Inrush

It is incorrect to state that a thing has human properties, liking seeing.

SuggestedRemedy

Figure 33-27 text uses "PSE sees". Replace with, "PSE load capacitance is".

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Again, while factually correct the new text doesn't distinguish between what is seen on a pairset vs seen at the PI, which is the entire point of the figure.

Better text is welcome.

TFTD.

Cl 33 SC 33.3.7.4 P 142 L 22 # 12
 Bennett, Ken Sifos Technologies, In

Comment Type TR Comment Status D PD Power

The statement below, which is in the Peak Power section, "allows" an RMS current. Its limit in equation 33-26 is based upon average power and a fixed voltage, which is inconsistent with Ppeak_PD. It's not clear that the "Allowed" RMS current still must meet the Ppeak_PD requirement.

Existing text:

"Ripple current content (IPort_ac) superimposed on the DC current level (IPort_dc) "IS ALLOWED" if the total input power is less than or equal to PClass_PD max, or PClass at the PSE PI for Class 6 and Class 8 PDs."

SuggestedRemedy

Insert the quoted text as shown:

Ripple current content (IPort_ac) superimposed on the DC current level (IPort_dc) is allowed if "Ppeak_PD requirements are met" and the total input power is less than or equal to PClass_PD max, or PClass at the PSE PI for Class 6 and Class 8 PDs.

Proposed Response Response Status W

PROPOSED ACCEPT.

IEEE P802.3bt D1.7 4-Pair Power-over-Ethernet 10th Task Force review comments

Cl 33 SC 33.3.7.4 P 142 L 27 # 10
 Bennett, Ken Sifos Technologies, In

Comment Type ER Comment Status D PD Power

"Iport" is defined as the RMS current in this section.

The symbol "Iport" is now used extensively in the standard in ways that are not consistent with an RMS Current definition. (Including instantaneous values, limits, time-limited, etc.)

The RMS Current definition should be apparent in the symbol to distinguish it from other instances of Iport.

SuggestedRemedy

In section 33.3.7.4,

Change Iport to IportRMS and change Iportmax to IportRMSmax

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 33 SC 33.3.7.4 P 142 L 35 # 57
 Johnson, Peter Sifos Technologies

Comment Type T Comment Status D PD Power

This comment may be OBE by another comment I'm submitting for 33.3.7.4.

Certain phrases are written as if all Class 6 and Class 8 PDs will benefit from extended power. This is contradictory with 33.3.7.2 and needs to be corrected.

Examples:

Line 35

"The maximum IPort value for all PDs except those in Class 6 or Class 8..."

Line 47

"The maximum IPort value for all PDs in Class 6 or Class 8, over the operating VPort_..."

SuggestedRemedy

Revise these phrases.

Line 35

"The maximum IPort value for PDs that operate across all possible channels, over the operating VPort_PD-2P range..."

Line 47

"The maximum IPort value for Class 6 or Class 8 PDs that are aware of actual channel DC resistance, over the operating VPort_PD-2P range..."

Proposed Response Response Status W

PROPOSED REJECT.

I don't see a remedy, just a comment telling me which text is wrong.

IEEE P802.3bt D1.7 4-Pair Power-over-Ethernet 10th Task Force review comments

CI 33 SC 33.3.7.4 P 143 L 6 # 58
 Johnson, Peter Sifos Technologies

Comment Type ER Comment Status D PD Power

The final sentence in this section is *really* hard to comprehend:

"....These equations may be used to calculate PPeak_PD or PPeak_PD-2P for Data Link Layer classification and for Autoclass by substituting PClass_PD with PDMaxPowerValue and PAutoclass_PD respectively."

SuggestedRemedy

Make it easier to understand:

"....These equations may be used to calculate PPeak_PD and PPeak_PD-2P from PClass_PD and PClass_PD-2P respectively, or from PDMaxPowerValue utilized in Data Link Layer classification, or from PAutoclass_PD utilized in Autoclass."

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

"....These equations may be used to calculate Ppeak_PD or Ppeak_PD-2P for Data Link Layer classification by substituting Pclass_PD with PDMaxPowerValue and for Autoclass by substituting Pclass_PD with Pautoclass_PD."

CI 33 SC 33.3.7.5 P 143 L 46 # 157
 Yseboodt, Lennart Philips

Comment Type E Comment Status D Editorial

"NOTE--PDs are required to meet Equation (33-2) which results in a slightly lower power and current than results from Figure 33-38, Figure 33-39, Equation (33-27) , Equation (33-28) and Equation (33-29) ." Font size fluctuates in Note.

SuggestedRemedy

Make font size consistent.

Proposed Response Response Status W

PROPOSED ACCEPT.

CI 33 SC 33.3.7.6 P 145 L 11 # 235
 Yseboodt, Lennart Philips

Comment Type T Comment Status X Pres: Yseboodt9

The PD transients section contains many duplicate requirement text blocks which can be merged and the differences captured in a Table.
 We love Tables.

SuggestedRemedy

Adopt yseboodt_09_0516_pdtransient.pdf

Proposed Response Response Status W

WFP

TFTD

If only Tables felt the same way about you...

CI 33 SC 33.3.7.6 P 145 L 23 # 158
 Yseboodt, Lennart Philips

Comment Type E Comment Status D Editorial

"A single-signature Type 4 PD with peak power draw that does not exceed P Class PD max and has an input capacitance of 360mF or less requires no special considerations with regards to transients at the PD PI."

"P Class PD" has no underline between "P Class" and "PD".

SuggestedRemedy

Add underline.

Proposed Response Response Status W

PROPOSED ACCEPT.

CI 33 SC 33.3.7.6 P 145 L 25 # 31
 Darshan, Yair Microsemi

Comment Type TR Comment Status X Pres: Darshan3

We need to address the fact that we change dual-signature class 1-4 PD capacitance value from 180uF to 110uF

SuggestedRemedy

See proposed remedy in darshan_03_0516.pdf

Proposed Response Response Status W

WFP

TFTD

IEEE P802.3bt D1.7 4-Pair Power-over-Ethernet 10th Task Force review comments

Cl 33 SC 33.3.7.6 P 145 L 30 # 24
 Darshan, Yair Microsemi

Comment Type T Comment Status D Editorial

Per comment #193 in D1.6 according to approved remedy DARSHAN_06_0316.PDF the "a)" should be deleted in the following text:

"a) A Type 1 PD input current shall not exceed the PD upperbound template (see Figure 33-38) after TLIM min (see Table 33-17 for a Type 1 PSE) when the following...."

SuggestedRemedy

Change to:

1. "A Type 1 PD input current shall not exceed the PD upperbound template (see Figure 33-38) after TLIM min (see Table 33-17 for a Type 1 PSE) when the following...."
2. Align the paragraph to the next paragraph starting with "A Type 2 or single-signature Type 3 PD...."

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Editor to follow IEEE style guide (are a's allowed if no b is present?).

Cl 33 SC 33.3.7.6 P 145 L 31 # 159
 Yseboodt, Lennart Philips

Comment Type E Comment Status D Editorial

"A Type 1 PD input current shall not exceed the PD upperbound template (see Figure 33-38) after T LIM min (see Table 33-17 for a Type 1 PSE) when the following input voltage is applied."

"T LIM" does not exist anymore.

SuggestedRemedy

Change to "T LIM-2P"

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 33 SC 33.3.7.6 P 145 L 40 # 95
 Schindler, Fred Seen Simply, Broadco

Comment Type T Comment Status D Freddy

Related to a comment marked COMMENT-1.

SuggestedRemedy

Proposed Response Response Status Z

REJECT.

This comment was WITHDRAWN by the commenter.

No Comment let alone a remedy.

IEEE P802.3bt D1.7 4-Pair Power-over-Ethernet 10th Task Force review comments

CI 33 SC 33.3.7.6 P 145 L 42 # 94
 Schindler, Fred Seen Simply, Broadco

Comment Type TR Comment Status X PD Power

Presentation, schindler_1_0915, provides an over view of this section and the details used to add new Types to this section. This section was created to prevent a PSE disconnecting a PD by providing requirements for PDs being subject to PSE transients. Legacy devices used associated Type with a class, and the PSE Type determined ILIM and TLIM limits that the PD need to remain below. New Types support legacy classes using different ILIM and TLIM values. It would be better to base operational requirements of ILIM and TLIM based on assigned PD class.

However, since D1.2, when the requirements we first created, the values of ILIM have changed. Type-3 ILIM moved down from 817 mA to 702 mA. Type-4 moved down from 1.162 A to 0.990 A. A rerun of the SPICE simulation for the Type-3 Extended PD using a 2,250V ramp shows the time to reach a point where the system current is below its limit has increased from 3.5 ms to 8 ms, which is acceptable. A rerun of the SPICE simulation for the Type-4 PD using a 2,250V ramp shows the time to reach a point where the system current is below its limit has increased from 1.7 ms to 5.7 ms, which is acceptable. A rerun of the SPICE simulation for the Type-4 Extended PD using a 2,250V ramp shows the time to reach a point where the system current is below its limit has increased from 4.1 ms to a value that exceeds significantly TLIM, which is NOT acceptable.

SuggestedRemedy

Replace text on line 42 on page 145, line 1 on page 146, line 12 on page 146, line 24 on page 146, and line 36 on page 146. "The PD shall not exceed the PD upperbound template beyond TLIM-2P min under worst-case current draw under the following conditions.", with

"The PD shall not exceed the PD upperbound template beyond TLIM-2P min and under worst-case current draw for the assigned PD class under the following conditions."

TFT discuss how to deal with the problem with Type-4 Extended power compliance. This could be called out as a concern that these PDs need to deal with by lowering PD bulk capacitance (~240uF appears to work). Recommend that the following sentence be added on page 145 line 24 before the sentence that starts with "A dual-signature..." with, "Type-4 single-signature PDs that consume more than class-8 PClass_PD, see 33.3.7.2, shall meet these requirements for the PD bulk capacitance utilized.

Delete the Editor's note at the start of this section.

Proposed Response Response Status W

TFTD as requested.

CI 33 SC 33.3.7.9 P 147 L 16 # 160
 Yseboodt, Lennart Philips

Comment Type E Comment Status D Editorial

"When V Port_PD -2P max is applied across the PI at either polarity specified on the conductors for Mode A according to Table 33-19, the voltage measured across the PI for Mode B with a 100 kOhm load resistor connected shall not exceed V bfd max as specified in Table 33-28. When V Port_PD-2P max is applied across the PI at either polarity specified on the conductors for Mode B according to Table 33-19, the voltage measured across the PI for Mode A with a 100 kohm load resistor connected shall not exceed V bfd max."

These two lines can be merged.

SuggestedRemedy

"When V Port_PD -2P max is applied across the PI at either polarity specified on the conductors of either Mode A or Mode B according to Table 33-19, the voltage measured across the PI for the other Mode with a 100 kOhm load resistor connected shall not exceed V bfd max as specified in Table 33-28."

Proposed Response Response Status W

PROPOSED ACCEPT.

CI 33 SC 33.3.7.10 P 147 L 25 # 161
 Yseboodt, Lennart Philips

Comment Type E Comment Status D Editorial

Section title "33.3.7.10 PD PI pair-to-pair resistance and current unbalance"

SuggestedRemedy

More apt title: "PD pair-to-pair current unbalance"

Proposed Response Response Status W

PROPOSED ACCEPT.

IEEE P802.3bt D1.7 4-Pair Power-over-Ethernet 10th Task Force review comments

Cl 33 SC 33.3.7.10 P 147 L 26 # 13
 Bennett, Ken Sifos Technologies, In

Comment Type TR Comment Status X Pres: Bennet1

The first two paragraphs are ambiguous. It's not clear whether the ICon_2P_unb, ICon_2P requirements must be met for a single set of RSource and Vport_PSE values that fall within the ranges mentioned, or if ICon_2P_unb, ICon_2P must be met over the full Rsource and Vport_PSE_2P ranges.

The requirements for ICon apply to the full Rsource and Vport ranges, which correspond to compliant ranges of PSE and Channel characteristics. (PDs can fail ICon_unb at short or long channels, and at any length for extended power.)

SuggestedRemedy

See bennett_1_0516.pdf

Proposed Response Response Status W

WFP

TFTD

Cl 33 SC 33.3.7.10 P 148 L 1 # 162
 Yseboodt, Lennart Philips

Comment Type E Comment Status D Editorial

Figure 33-40 has unclear title

SuggestedRemedy

New title "PD PI pair-to-pair current unbalance test setup"

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 33 SC 33.3.8 P 148 L 26 # 163
 Yseboodt, Lennart Philips

Comment Type E Comment Status D Editorial

"A PD that does not maintain the MPS components mentioned above may have its power removed within the limits of T MPDO as specified in Table 33-17."

"mentioned above" is a historic positional reference that no longer makes sense.

SuggestedRemedy

Remove "mentioned above".

Change to:

"A PD that does not maintain the MPS components may have its power removed within the limits of T MPDO as specified in Table 33-17."

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 33 SC 33.3.8 P 148 L 41 # 164
 Yseboodt, Lennart Philips

Comment Type E Comment Status D Editorial

"Type 3 and Type 4 PDs that detect a long first class event in the range of T LCE_PD may reduce T MPS_PD in order to draw a lower standby MPS power."

Does not say where to find T LCE_PD.

SuggestedRemedy

"Type 3 and Type 4 PDs that detect a long first class event in the range of T LCE_PD, as defined in Table 33-26, may reduce T MPS_PD in order to draw a lower standby MPS power."

Proposed Response Response Status W

PROPOSED ACCEPT.

IEEE P802.3bt D1.7 4-Pair Power-over-Ethernet 10th Task Force review comments

Cl 33 SC 33.3.8 P 149 L 29 # 252
 Yseboodt, Lennart Philips

Comment Type TR Comment Status D PD MPS

"NOTE--PDs may not be able to meet the IPort_MPS specification in Table 33-29 during the maximum allowed port voltage droop (VPort_PSE max to VPort_PSE min with series resistance RCh). Such a PD should increase its IPort min or make other such provisions to meet the Maintain Power Signature."

We also need to mention IPort-MPS-2P for dual-signature PDs.

SuggestedRemedy

"NOTE--PDs may not be able to meet the IPort_MPS or Iport_MPS-2P specification in Table 33-29 during the maximum allowed port voltage droop (VPort_PSE max to VPort_PSE min with series resistance RCh). Such a PD should increase its IPort min or make other such provisions to meet the Maintain Power Signature."

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Implement suggested remedy but change Vport_PSE to Vport_PSE-2P.

Cl 33 SC 33.4.1.1.2 P 151 L 11 # 5
 Beia, Christian STMicroelectronics

Comment Type TR Comment Status D AES

In order to successfully detect DS PDs with a common ground, PSEs that support 4-pair operation have to switch the more negative conductor at least. This is already specified for Environment A PSEs, but not for Environment B.

SuggestedRemedy

Add after the second paragraph of 33.4.1.1.2 the following sentence:

An Environment B PSE that supports 4-pair power shall switch the more negative conductor. It is allowable to switch both conductors

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 33 SC 33.4.2 P 151 L 26 # 253
 Yseboodt, Lennart Philips

Comment Type TR Comment Status X AES

"The PSE PI shall withstand without damage the application of short circuits of any wire to any other wire within the cable for an indefinite period of time. The magnitude of the current through such a short circuit shall not exceed I LIM max as defined in Table 33-17."

No longer correct for the new Types.

SuggestedRemedy

Replace second sentence by:

"The magnitude of the current through such a short circuit:

- shall not exceed I LIM-2P max, as defined in Table 33-17, for Type 1 and Type 2 PSEs
- shall not exceed 0.85A for Type 3 PSEs
- shall not exceed I_LPS for Type 4 PSEs"

Proposed Response Response Status W

TFTD

You are taking a statement that referenced I LIM max (which is the upperbound template) and replacing it with fixed numbers for Type 3 and Type 4. How does that work? Shouldn't all types just reference the upperbound template?

Cl 33 SC 33.4.2 P 151 L 28 # 96
 Schindler, Fred Seen Simply, Broadco

Comment Type TR Comment Status X AES

The concerns of D1.6 comments 272 remain unaddressed.

The Fault tolerance section covers cases where a PSE is subjected to faults like link section conductor shorts. This section should contain similar requirements for new PDs so that they continue operating after a link segment conductor open fault has been removed.

SuggestedRemedy

Add the following text before the third paragraph of the called out section.

"Type-3 and Type-4 PDs shall withstand one or more conductor open failures within the link section without damage when powered by any PSE."

Proposed Response Response Status W

TFTD

IEEE P802.3bt D1.7 4-Pair Power-over-Ethernet 10th Task Force review comments

Cl 33 SC 33.4.9.1.5 P 161 L 26 # 236
 Yseboodt, Lennart Philips

Comment Type T Comment Status X AES

Both sections are new text.

33.4.9.1.5 Maximum link delay says "The propagation delay contribution of the Midspan PSE device shall not exceed 2.5 ns from 1 MHz to the highest referenced frequency."

33.4.9.1.6 Maximum link delay skew says "The propagation delay contribution of the Midspan PSE device shall not exceed 1.25 ns from 1 MHz to the highest referenced frequency."

The requirement is the same, with different value, and it seems that 33.4.9.1.6 should say something on skew ?

SuggestedRemedy

TFTD
 Is this correct ?

Proposed Response Response Status W
 TFTD as requested

Cl 33 SC 33.4.9.2 P 162 L 30 # 20
 Darshan, Yair Microsemi

Comment Type ER Comment Status D Editorial

The Editor Note is not required anymore. All the necessary parameters were defined.

SuggestedRemedy

Delete Editor Note.

Proposed Response Response Status W
 PROPOSED ACCEPT.

Cl 33 SC 33.6.2 P 169 L 6 # 165
 Yseboodt, Lennart Philips

Comment Type E Comment Status D Editorial

"Type 2, 3, and 4 PSEs shall send an LLDPDU containing..."

PSEs contains underline.

SuggestedRemedy

Remove underline.

Proposed Response Response Status W
 PROPOSED ACCEPT.

Cl 33 SC 33.6.3.2 P 169 L 44 # 166
 Yseboodt, Lennart Philips

Comment Type E Comment Status X Pres: Yseboodt1

LLDP can support extended power in a better way.

SuggestedRemedy

Adopt yseboodt_01_0516_lldpxt.pdf

Proposed Response Response Status W
 WFP

TFTD

Cl 33 SC 33.6.3.2 P 170 L 33 # 134
 Tremblay, David Hewlett Packard Enter

Comment Type ER Comment Status D Editorial

Inconsistent spelling of PD_DLLMAX_VALUE on line 170:

Variables PD_DLL_MAX_VALUE, PD_INITIAL_VALUE, and PSE_INITIAL_VALUE, are quantized to fit the available resolution.

SuggestedRemedy

Change PD_DLL_MAX_VALUE to PD_DLLMAX_VALUE

Proposed Response Response Status W
 PROPOSED ACCEPT.

Cl 33 SC 33.6.3.3 P 172 L 35 # 97
 Schindler, Fred Seen Simply, Broadco

Comment Type ER Comment Status D Editorial

Editor's notes use comment number references without reference to which draft was commented on.

SuggestedRemedy

From now on, please reference using style D1.6 #48, where this example references Draft 1.6 comment #48.

Proposed Response Response Status W
 PROPOSED ACCEPT.

Editor to note.

IEEE P802.3bt D1.7 4-Pair Power-over-Ethernet 10th Task Force review comments

Cl 33 SC 33.6.3.5 P 175 L 9 # 98
Schindler, Fred Seen Simply, Broadco

Comment Type **TR** Comment Status **X** Pres: Schindler1

The San Antonio 2014 meeting presentation, Mutual_ID_PD_updated, change variable pse_dll_power_type to pse_dll_power_level and added variable pse_power_level for Type 3 and 4 state diagrams. This was probably done because Type no longer indicates the power being provided.

Unfortunately, this change:

1. Broke legacy DLL power control.
2. Broke DLL classification for new Types.

LLDP and the SD on p175 work together to provide LLDP field values. To reported PSE Type and not class, we need access to variable that reports Type.

SuggestedRemedy

This comment may be covered in schindler_3bt_01_05_16.

Proposed Response Response Status **W**

WFP

TFTD

Cl 33 SC 33.6.4.1 P 176 L 31 # 99
Schindler, Fred Seen Simply, Broadco

Comment Type **TR** Comment Status **D** DLL

It is incorrect to state that a thing has human properties, liking seeing.

SuggestedRemedy

Existing text:

If the PSE sees a change to the previously stored MirroredPDRRequestedPowerValue, it recognizes a request by the PD to change its power allocation.

Corrected:

If the PSE previously stored MirroredPDRRequestedPowerValue changes, a request by the PD to change its power allocation is recognizes.

Proposed Response Response Status **W**

PROPOSED ACCEPT IN PRINCIPLE.

If the PSE previously stored MirroredPDRRequestedPowerValue changes, a request by the PD to change its power allocation is recognized.

Cl 33 SC 33.6.4.1 P 176 L 44 # 100
Schindler, Fred Seen Simply, Broadco

Comment Type **TR** Comment Status **D** DLL

It is incorrect to state that a thing has human properties, liking seeing.

SuggestedRemedy

Existing text:

If the PD sees a change to the previously stored MirroredPSEAllocatedPowerValue or local_system_change is asserted by the PD so as to change its power allocation, it enters the PD POWER REVIEW state.

Corrected:

If the PD previously stored MirroredPSEAllocatedPowerValue is changed or local_system_change is asserted by the PD so as to change its power allocation, it enters the PD POWER REVIEW state.

Proposed Response Response Status **W**

PROPOSED ACCEPT IN PRINCIPLE.

If the PD previously stored MirroredPSEAllocatedPowerValue is changed or local_system_change is asserted by the PD so as to change its power allocation, the PD enters the PD POWER REVIEW state.

Cl 79 SC 79.3.2 P 203 L 27 # 101
Schindler, Fred Seen Simply, Broadco

Comment Type **TR** Comment Status **X** Pres: Schindler2

Accepted draft 1.4 comments broke extended power operation using LLDP and DLL. An ad hoc meeting reviewed these concerns during D1.5 review cycle and a very busy person was not able to complete a solution for the D1.6 review cycle.

SuggestedRemedy

A solution should appear in schindler_3bt_02_05_16 or other related presentation for this review cycle.

Proposed Response Response Status **W**

WFP

TFTD

IEEE P802.3bt D1.7 4-Pair Power-over-Ethernet 10th Task Force review comments

Cl 79 SC 79.3.2 P 203 L 29 # 167
 Yseboodt, Lennart Philips

Comment Type E Comment Status D Editorial

"These entities allow devices to draw/supply power over the sample generic cabling as used for data transmission."

'sample' should be 'same' ?

SuggestedRemedy

"These entities allow devices to draw/supply power over the same generic cabling as used for data transmission."

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 79 SC 79.3.2 P 203 L 36 # 168
 Yseboodt, Lennart Philips

Comment Type E Comment Status D Editorial

Figure 79-3 uses a different font than 79-2.

SuggestedRemedy

Change font and drawing style to match 79-2.

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 79 SC 79.3.2 P 203 L 53 # 169
 Yseboodt, Lennart Philips

Comment Type E Comment Status D Editorial

The second paragraph of 79.3.2 explains that Figure 79-3 is a revision of the original TLV defined in 802.1AG-2009 Annex F.3.

We have now further revised this TLV with new capabilities.

SuggestedRemedy

Add the following after page 204, line 7:

"The TLV in Figure 79-3 has been further revised to support additional capabilities offered by Type 3 and Type 4 PSEs and PDs as defined in Clause 33. Type 3 and Type 4 PSEs and PDs may use these additional fields."

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 79 SC 79.3.2.6 P 206 L 49 # 170
 Yseboodt, Lennart Philips

Comment Type E Comment Status D Editorial

The Editing instruction is missing the word 'Insert'.
 (At one point something removed all the words "insert" from the draft it seems).

SuggestedRemedy

Add 'Insert' before 'sections'.

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 79 SC 79.3.2.6a.2 P 207 L 37 # 237
 Yseboodt, Lennart Philips

Comment Type T Comment Status D LLDP

The PSE power class field is described as:
 "The power class field shall contain an integer value for PSE Classes defined by 33.2.6. A TLV generated by a PD shall set the field to 0000."

This doesn't say if it should be assigned or requested Class. Assigned Class seems logical.

SuggestedRemedy

- Remove the underline and strikethrough
- Change to read:

"The power class field shall contain an integer value for the assigned Class by the PSE as defined in 33.2.6. A TLV generated by a PD shall have the field set to 0000."

Proposed Response Response Status W

PROPOSED ACCEPT.

IEEE P802.3bt D1.7 4-Pair Power-over-Ethernet 10th Task Force review comments

CI 79 SC 79.3.2.6b.3 P 208 L 31 # 238
 Yseboodt, Lennart Philips

Comment Type T Comment Status X LLDP

In Table 79-6b and section 79.3.2.6b.3 the "PD PI" bit is described. Given the recent evolutions we made in defining single and dual signature PDs, this bit no longer serves any purpose. It can however be repurposed to make LLDP support dual-signature PDs in a proper way.

SuggestedRemedy

- Rename "PD PI" to "PD Mode selection"
- Change value of item 2 in Table 79-6b to read:
 "1 = PD requested power applies to Mode A pairset
 0 = PD requested power applies to Mode B pairset"
- Change text in 79.3.2.6b.3 to read:
 "This field shall be set according to Table 79-6b to select the Mode for which the PD is requesting power when the power type is PD. This field shall be set to 0 when the power type is PSE."

Proposed Response Response Status W

TFTD

I would like those group members interested in LLDP to review this change as it seems substantial.

CI 79 SC 79.3.7.1 P 211 L 23 # 171
 Yseboodt, Lennart Philips

Comment Type E Comment Status D LLDP

In Table 79-6f on PD measurements, Item 92:91 it refers to "Pairset Alternative A" and "B".

SuggestedRemedy

Since this is the PD, it should be "Pairset Mode A" and likewise for B.

Proposed Response Response Status W

PROPOSED ACCEPT.

CI 33 SC 33.3.7 P 231 L 52 # 216
 Yseboodt, Lennart Philips

Comment Type ER Comment Status X Annex 33B

"Selected resistance values for RPSE_max and RPSE_min which provide adequate verification to Equation (33-13) or control ICon-2P_unb value are dependent upon PSE circuit implementation and as such are left to the designer."

PARSE_ERROR.

SuggestedRemedy

I don't know where to begin. What does this mean ?

Proposed Response Response Status W

Yair?

TFTD

CI 33 SC Annex B P 232 L 28 # 21
 Darshan, Yair Microsemi

Comment Type T Comment Status D Annex 33B

In the text:
 "Verification of ICon-2P_unb in step 6 and 7 confirms PSE RPSE_max and RPSE_min are in conformance to this specification."

replace "PSE" with "that"

SuggestedRemedy

Change to:
 "Verification of ICon-2P_unb in step 6 and 7 confirms that RPSE_max and RPSE_min are in conformance to this specification."

Proposed Response Response Status W

PROPOSED ACCEPT.

IEEE P802.3bt D1.7 4-Pair Power-over-Ethernet 10th Task Force review comments

Cl 33 SC 33B P 232 L 34 # 254
Yseboodt, Lennart Philips

Comment Type TR Comment Status D Annex 33B

"I Con_2P_unb max and Equation (33-13) are specified for total channel common mode pair resistance from 0.1 O to 12.5 O and worst case unbalance contribution by a PD."

ICon-2P-unb is a minimum.

SuggestedRemedy

"I Con-2P-unb and Equation (33-13) are specified for total channel common mode pair resistance from 0.1 O to 12.5 O and worst case unbalance contribution by a PD."

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 33 SC 33B P 232 L 36 # 172
Yseboodt, Lennart Philips

Comment Type E Comment Status D Annex 33B

"When the PSE is tested for channel common mode resistance less than 0.1 O, i.e. $0 < R_{ch_x} < 0.1 O$, the PSE shall be tested with $(R_{load_min} - R_{ch_x})$ and $(R_{load_max} - R_{ch_x})$ to meet I Con-2P-unb requirements and R PSE_min and R PSE_max conformance to Equation (33-13)."

Rch is the maximum channel resistance. Rchan is the actual channel resistance.
Rch_x is simply confusing.

SuggestedRemedy

Replace Rch_x by Rchan.

Proposed Response Response Status W

PROPOSED ACCEPT.