

IEEE P802.3bt D1.1 4-Pair Power over Ethernet 4th Task Force review comments

Cl 33 SC 33.8.2.1 P 134 L 20 # 1 [REDACTED]
 Jones, Chad Cisco
 Comment Type E Comment Status A Editorial
 "Contact point for enquiries about the PICS" - an approved maintenance comment changes enquiries to inquiries
 SuggestedRemedy
 change enquiries to inquiries
 Response Response Status C
 ACCEPT.
 EZ

Cl 79 SC 79.5.2.1 P 172 L 20 # 2 [REDACTED]
 Jones, Chad Cisco
 Comment Type E Comment Status A Editorial
 "Contact point for enquiries about the PICS" - an approved maintenance comment changes enquiries to inquiries
 SuggestedRemedy
 change enquiries to inquiries
 Response Response Status C
 ACCEPT.
 EZ

Cl 33 SC 33.2.5.3 P 55 L 52 # 3 [REDACTED]
 Jones, Chad Cisco
 Comment Type E Comment Status A Editorial
 There were complaints about this text in Manchester, trying to make it better: "In the presence of an offset voltage up to Vos max and an offset current up to los max as specified in Table 33–5, a PSE shall accept as a valid PD detection signature a pair set within a link section with both of the following characteristics:
 a) Signature resistance Rgood, and
 b) Parallel signature capacitance Cgood."
 SuggestedRemedy
 note to comment editor: this is NOT an 'easy' bucket comment.
 A pair set within a link section with the following characteristics:
 a) Signature resistance Rgood
 b) Parallel signature capacitance Cgood
 c) in the presence of an offset voltage up to Vos max, as specified in Table 33–5
 d) in the presence of an offset current up to los max, as specified in Table 33–5 shall be accepted as a valid PD detection signature by a PSE.
 Response Response Status C
 ACCEPT IN PRINCIPLE.
 Replace sentence with:
 "A pairset with all of the characteristics specified in Table 33–5 shall be accepted as a valid PD detection signature by a PSE."
 Remove "tolerance" from items 3 and 4 in Table 33-5.

IEEE P802.3bt D1.1 4-Pair Power over Ethernet 4th Task Force review comments

CI 33 SC 33.1.4 P 22 L 6 # 4
 Jones, Chad Cisco

Comment Type T Comment Status X Cabling

Maintenance Request #1271, on behalf of GEOFF THOMPSON, GRACASI S.A./LINEAR TECHNOLOGY

Move as much of the cabling specification to cabling documents as possible. (This RR was entered as a tracking mechanism for Thompson Comment #59 against P802.3REVbx/D2.0 during initial WG ballot. Resolution of this comment was given over to P802.3bt as they will have CI 33 open.)

SuggestedRemedy

See attached sheet for proposed new text.
 (http://www.ieee802.org/3/maint/requests/maint_1271.pdf, page 2)
 A number of these changes have already been adopted. The two remaining changes are:
 Replacing the first sentence in 33.1.4 with:
 "A power system, consists of a single PSE, a single PD and the link section connecting them. A power system is characterized as Type 1 or Type 2 by lowest type number of the PSE or PD in the system, see Table 33-1."
 and replacing the first paragraph of 33.1.4.1 with (as well as changing the title of the subclause to "Cabling requirements"):
 "The supply of power over the data connection is intended to operate with no additional requirements to the cabling that is normally installed for data usage. This is approximately true but may require some further attention. Power at Type 1 power levels may be transmitted over all specified premises cabling without further restrictions. Higher power levels may require heavier gauge conductors than are found in Class C/Category 3 cabling and (more uncommonly) in some lighter gauge Class D or better cable. The requirements for Type 2 are met by Category 5 or better cable and components as specified in ANSI/TIA/EIA-568-A."

Proposed Response Response Status W

Waiting for Yair to review.

Yair to review by September, or these changes will be accepted.

To be held open.

CI 33 SC 33.3.1 P 80 L 47 # 5
 Jones, Chad Cisco

Comment Type T Comment Status X Pres: PD PI

Maintenance Request #1274 on behalf of George Zimmerman, CME Consulting/LTC

Text in the existing standard is ambiguous and is inconsistent with terminations and usage commonly found in Ethernet equipment. The intent is to require PDs to be able to withstand application of common-mode PoE voltage. Application of 57V DC voltages in across the pins corresponding to the two pairs twisted differentially to form a balanced pair of the link segment would run a DC current across the transformer windings commonly found in BASE-T Ethernet equipment and burn them out.

SuggestedRemedy

Change: The PD shall withstand any voltage from 0 V to 57 V at the PI indefinitely without permanent damage.
 To: The PD shall withstand any common-mode voltage from 0 V to 57 V applied to any two sets of two pins at the PI indefinitely without permanent damage. The two pins in each set shall correspond to the balanced twisted wire pairs of the connected link segment.

Proposed Response Response Status W

Waiting for Presentation

See comment 189, 145

CI 33 SC 33.2.7 P 66 L 52 # 6
 Abramson, David Texas Instruments

Comment Type TR Comment Status A

This comment applies to Table 33-11, item 4.

The Icon-2p value is not correct for Type 3/4 PSEs when operating over 4-pair, class 0-4. Class 0-4 PDs have no unbalance requirement and can draw their entire current over one pairset. This is not represented in item 4.

SuggestedRemedy

remove "2-pair mode" from middle row of item 4 so that it applies to both 2-pair and 4-pair mode.

Add "Class 5-8 only. See 33.2.7.4." to additional information row for bottom row of item 4.

Response Response Status C

ACCEPT IN PRINCIPLE.

OBE by comment 113.

IEEE P802.3bt D1.1 4-Pair Power over Ethernet 4th Task Force review comments

Cl 33 SC 33.2.4.6 P 41 L 23 # 7
 Abramson, David Texas Instruments

Comment Type TR Comment Status A PSE SD

This comment applies to the "invalid" entry for the variable "PD_Signature" in the do_connection_check function.

The entry "invalid" and its definition are misleading. If a PSE does connection check with an open circuit on one pairset and something plugged in on the other pairset, it should return "Dual".

Furthermore, the connection check does not do detection, no conclusions as to whether a PD is valid or invalid (or open) should be made here, it is part of detection.

SuggestedRemedy

Remove "Invalid" option for PD_Signature variable.
 Rename PD_Signature to Signature_Type.

Response Response Status C

ACCEPT IN PRINCIPLE.

Delete Invalid.

Change the definition of Open_Circuit to: Open_Circuit: An open circuit has been detected on both pairsets.

Change name of variable to "Signature_Type".

Cl 33 SC 33.2.5 P 52 L 45 # 8
 Abramson, David Texas Instruments

Comment Type TR Comment Status A PSE Power

The line:

"In any operational state, the PSE shall not apply operating power to a pair set until the PSE has successfully detected a valid signature over that pair set."

forbids turning a pairset off and back on in order to check disconnect. This behavior has consensus as something we want to allow.

SuggestedRemedy

As this is a new topic, I would like to prepare a presentation for September.

For now, add:

"Editor's note (to be removed before D2.0): This sentence needs to be addressed as it forbids turning off and on a single pairset when connected to a SS class 0-4 PD."

Response Response Status C

ACCEPT.

Cl 33 SC 33.3.8 P 102 L 36 # 9
 Bennett, Ken Sifos Technologies, In

Comment Type TR Comment Status A Pres: MPS

Item 1 in table 33-19, PD Maintain Power Signature, specifies an input resistance of 26.3k-Ohm max. The new DC MPS could enable average DC currents as low as 250uA, however the resistance requirement of 26.3k max. requires average currents on the scale of 2mA.

The 26.3k resistance requirement should be removed for Type 3 and 4 PD's so that the efficiency provided by the new DC MPS rules can be fully realized.

SuggestedRemedy

In the additional information of item 1 table 33-19, add the following:
 Type 1 and Type 2 Only

Response Response Status C

ACCEPT IN PRINCIPLE.

OBE by comment 243.

Waiting for presentation.

IEEE P802.3bt D1.1 4-Pair Power over Ethernet 4th Task Force review comments

Cl 33 SC 0 P 0 L 0 # 10
 Yseboodt, Lennart Philips
 Comment Type E Comment Status A Editorial
 There are still lingering occurrences or "pair to pair" or other variants which need changing to "pair-to-pair".
 SuggestedRemedy
 Replace on
 - page 100, line 50
 - page 101, line 5
 - page 105, line 12
 Response Response Status C
 ACCEPT.
 EZ

Cl 33 SC 33.1.1 P 20 L 5 # 11
 Yseboodt, Lennart Philips
 Comment Type E Comment Status A Editorial
 "Type 1 operation adds no significant requirements to the cabling. Type 2 operation requires ISO/IEC 11801:1995 Class D or better cabling, and Type 3 operation requires ISO/IEC 11801:2002 Class D or better cabling, and a derating of the cabling maximum ambient operating temperature."
 It is not clear if the derating refers to both Type 2 and Type 3, or only to Type 3.
 SuggestedRemedy
 "Type 1 operation adds no significant requirements to the cabling. Type 2 operation requires ISO/IEC 11801:1995 Class D or better cabling, and Type 3 operation requires ISO/IEC 11801:2002 Class D or better cabling, both require a derating of the cabling maximum ambient operating temperature."
 Response Response Status C
 ACCEPT IN PRINCIPLE.
 OBE by comment # 159.
 EZ

Cl 33 SC 33.1.4 P 22 L 17 # 12
 Yseboodt, Lennart Philips
 Comment Type E Comment Status A Editorial
 Table 33-1 caption "System Power parameters Vs System Type" "System Power parameters Vs System Type"
 Inconsistent capitalization.
 SuggestedRemedy
 "System power parameters vs system Type"
 Response Response Status C
 ACCEPT.
 EZ

Cl 33 SC 33.1.4 P 22 L 21 # 13
 Yseboodt, Lennart Philips
 Comment Type E Comment Status A Editorial
 icable, A is not bold
 SuggestedRemedy
 icable, A in bold text
 Response Response Status C
 ACCEPT.
 EZ

Cl 33 SC 33.1.4.1 P 23 L 15 # 14
 Yseboodt, Lennart Philips
 Comment Type E Comment Status A Editorial
 "with the additional requirement that channel DC loop resistance shall be 25ohm or less."
 no space between 25Ohm
 SuggestedRemedy
 25 Ohm (add space)
 Response Response Status C
 ACCEPT.
 EZ

IEEE P802.3bt D1.1 4-Pair Power over Ethernet 4th Task Force review comments

CI 33 SC 33.2.4.4 P 39 L 5 # 15
 Yseboodt, Lennart Philips
 Comment Type E Comment Status A Editorial
 Table 33-3 has now become very long and narrow.
 SuggestedRemedy
 Table can be compacted now that DLL permutations are out. See yseboodt_Table_33_3.pdf
 Response Response Status C
 ACCEPT.

CI 33 SC 33.2.4.6 P 42 L 37 # 16
 Yseboodt, Lennart Philips
 Comment Type E Comment Status A Editorial
 "... set to values corresponding to either a Type 1 Type 2, Type 3 or Type 4 PSE. This function returns the following variable:"
 comma is missing as well as the Harvard comma.
 SuggestedRemedy
 "... set to values corresponding to either a Type 1, Type 2, Type 3, or Type 4 PSE. This function returns the following variable:"
 Response Response Status C
 ACCEPT.
 EZ

CI 33 SC 33.2.7 P 67 L 53 # 17
 Yseboodt, Lennart Philips
 Comment Type E Comment Status A Editorial
 Bottom line of Table 33-11 is not bold everywhere
 SuggestedRemedy
 Make line bold.
 Response Response Status C
 ACCEPT.
 EZ

CI 33 SC 33.2.7 P 68 L 45 # 18
 Yseboodt, Lennart Philips
 Comment Type E Comment Status A Editorial
 Table 33-11, item 17b, additional information, Pclass 'class' not in subscript and no capital C.
 SuggestedRemedy
 Replace by P_Class.
 Response Response Status C
 ACCEPT.

EZ
 CI 33 SC 33.2.7.4a P 72 L 7 # 19
 Yseboodt, Lennart Philips
 Comment Type E Comment Status A Editorial
 Stutter in the section title.
 "PSE PI Pair-to-Ppair-to-pairair resistance and current unbalance"
 SuggestedRemedy
 "PSE PI Pair to Pair resistance and current unbalance."
 Response Response Status C
 ACCEPT IN PRINCIPLE.
 OBE by comment #232.
 EZ

CI 33 SC 33.2.7.4a P 72 L 9 # 20
 Yseboodt, Lennart Philips
 Comment Type E Comment Status A Editorial
 "Type 3 and Type 4 PSEs operating over 4-pair are subject to..."
 4-pair is not used in rest of document
 SuggestedRemedy
 use four-pair
 Response Response Status C
 ACCEPT.
 EZ

IEEE P802.3bt D1.1 4-Pair Power over Ethernet 4th Task Force review comments

Cl 33 SC 33.2.7.4a P 72 L 10 # 21
 Yseboodt, Lennart Philips
 Comment Type E Comment Status A Editorial
 "The contribution of PSE PI pair to pair effective resistance unbalance(PSE_P2PRunb) to the whole effective..."
 Missing space between unbalance and (
 SuggestedRemedy
 Replace by
 "The contribution of PSE PI pair to pair effective resistance unbalance (PSE_P2PRunb) to the whole effective..."
 Response Response Status C
 ACCEPT.
 EZ

Cl 33 SC 33.2.7.4a P 72 L 11 # 22
 Yseboodt, Lennart Philips
 Comment Type E Comment Status A Editorial
 "... to the whole effective system end to end resistance/current unbalance (E2EP2PRunb),..."
 E2EP2PRunb should stand for 'system end to end resistance unbalance'.
 SuggestedRemedy
 Replace by
 "... to the whole effective system end to end resistance unbalance (E2EP2PRunb),..."
 Response Response Status C
 ACCEPT.

Cl 33 SC 33.2.7.4a P 72 L 19 # 23
 Yseboodt, Lennart Philips
 Comment Type E Comment Status A Editorial
 Space missing between number and 'ohm' symbol. 3 occurrences.
 SuggestedRemedy
 Add space.
 Response Response Status C
 ACCEPT.
 EZ

Cl 33 SC 33.2.7.4a P 72 L 21 # 24
 Yseboodt, Lennart Philips
 Comment Type E Comment Status A Editorial
 Annex 33B is for autoclass not P2P unbalance
 SuggestedRemedy
 Use Annex 33A.
 Response Response Status C
 ACCEPT IN PRINCIPLE.
 Move Autoclass Annex to 33C (and update reference in text).

Cl 33 SC 33.2.7.4a P 72 L 27 # 25
 Yseboodt, Lennart Philips
 Comment Type E Comment Status A Editorial
 Ohm sign after formula does not match style of other formulas.
 SuggestedRemedy
 Ohm sign smaller and bottom right.
 Response Response Status C
 ACCEPT.
 EZ

Cl 33 SC 33.2.7.4a P 72 L 33 # 26
 Yseboodt, Lennart Philips
 Comment Type E Comment Status A Editorial
 Rpair_min is italic
 SuggestedRemedy
 Change Pair_min to non-italic
 Response Response Status C
 ACCEPT.
 EZ

IEEE P802.3bt D1.1 4-Pair Power over Ethernet 4th Task Force review comments

Cl 33 SC 33.2.7.6 P74 L 6 # 27
 Yseboodt, Lennart Philips
 Comment Type E Comment Status A Editorial
 Remove space at end of scentence
 Original text: "... PSE may remove power from that pair set . The cumulative duration of TCUT-2P is measured with a sliding window of at least 1 second width."
 SuggestedRemedy
 "... PSE may remove power from that pair set. The cumulative duration of TCUT-2P is measured with a sliding window of at least 1 second width."
 Response Response Status C
 ACCEPT.
 EZ

Cl 33 SC 33.2.7.7 P74 L 16 # 28
 Yseboodt, Lennart Philips
 Comment Type E Comment Status A Editorial
 a pai set is not correct
 SuggestedRemedy
 'a pai set' should be 'a pair set'
 Response Response Status C
 ACCEPT IN PRINCIPLE.
 "a pairset"
 EZ

Cl 33 SC 33.2.7.7 P75 L 1 # 29
 Yseboodt, Lennart Philips
 Comment Type E Comment Status A Editorial
 The definitions of I_PSEUT-2P and I_PSELT-2P make use of variables that do not exist.
 SuggestedRemedy
 Change Tcutmin-2P to T_CUT-2P min
 Change Tcutmax-2P to T_CUT-2P max
 Change Ilimmin-2P to I_LIM-2P min
 Response Response Status C
 ACCEPT IN PRINCIPLE.
 Editor has license to fix all similar errors.
 Line 1-37 on page 75 and others.

Cl 33 SC 33.2.7.7 P75 L 46 # 30
 Yseboodt, Lennart Philips
 Comment Type E Comment Status A Editorial
 "A PSE in the POWER_ON state may remove power from a pair set without regard to T lim when the pair set voltage no longer meets the V port_PSE-2P specification."
 Tlim is lowercase letters, should be uppercase subscript.
 SuggestedRemedy
 T_LIM
 Response Response Status C
 ACCEPT.
 EZ

IEEE P802.3bt D1.1 4-Pair Power over Ethernet 4th Task Force review comments

Cl 33 SC 33.2.7.8 P 75 L 54 # 31
 Yseboodt, Lennart Philips

Comment Type E Comment Status A Editorial

Remove space at end of scentence.
 Original text: "The specification for TOff in Table 33-11 shall apply to the discharge time from VPort_PSE-2P to VOff of a pair set with a test resistor of 320 k attached to that pair set . In addition, it is recommended that the ..."

SuggestedRemedy

"The specification for TOff in Table 33-11 shall apply to the discharge time from VPort_PSE-2P to VOff of a pair set with a test resistor of 320 k attached to that pair set. In addition, it is recommended that the ..."

Response Response Status C

ACCEPT.

EZ

Cl 33 SC 33.2.7.10 P 76 L 14 # 32
 Yseboodt, Lennart Philips

Comment Type E Comment Status A Editorial

"P Class is the class power defined in 33.2.6 and Equation (33-3), or ..."

SuggestedRemedy

Parentheses around Equation number are unneeded. Remove.

Response Response Status C

ACCEPT IN PRINCIPLE.

Editor to consult style guide and see whether the parantheses are needed or not. If not, remove them from all equation references.

EZ

Cl 33 SC 33.2.6 P 78 L 1 # 33
 Yseboodt, Lennart Philips

Comment Type E Comment Status A Pres: MPS

"Editor's Note: Yair to review AC MPS for 4-pair."
 Pending acceptance of AC MPS removal for Type 3+4, this note is redundant.

SuggestedRemedy

Remove note.

Response Response Status C

ACCEPT.

Wait for presentation.

Cl 33 SC 33.3.2 P 81 L 12 # 34
 Yseboodt, Lennart Philips

Comment Type E Comment Status A Editorial

4-pair capable is not consistent

SuggestedRemedy

change to 'four-pair'

Response Response Status C

ACCEPT.

EZ

Cl 33 SC 33.3.2 P 81 L 43 # 35
 Yseboodt, Lennart Philips

Comment Type E Comment Status A Editorial

"Type 3 PDs advertise a class signature of 4, 5, or 6, while Type 4 PDs advertise a class signature of 7 or 8."
 Because this is in the paragraph that describes Class4+ PDs the intent is clear.
 The sentence alone however is incorrect.

SuggestedRemedy

"Such Type 3 PDs advertise a class signature of 4, 5, or 6, while Type 4 PDs advertise a class signature of 7 or 8."

Response Response Status C

ACCEPT.

EZ

IEEE P802.3bt D1.1 4-Pair Power over Ethernet 4th Task Force review comments

Cl 33 SC 33.3.3.5 P 85 L 54 # 36
 Yseboodt, Lennart Philips
 Comment Type E Comment Status A Editorial
 Figure caption is missing
 SuggestedRemedy
 "Figure 33-16 - PD state diagram"
 Response Response Status C
 ACCEPT.
 EZ

Cl 33 SC 33.3.5.1 P 89 L 50 # 37
 Yseboodt, Lennart Philips
 Comment Type E Comment Status A Editorial
 "Type 3 PDs operating with a maximum power draw corresponding to class 0-3 respond to 1-Event classification by returning a Class signature 0, 1, 2, or 3 in accordance with the maximum power draw, PClass_PD."
 PClass_PD not in subscript.
 SuggestedRemedy
 change 'P_Class_PD' to sub_script
 Response Response Status C
 ACCEPT.
 EZ

Cl 33 SC 33.3.7 P 95 L 10 # 38
 Yseboodt, Lennart Philips
 Comment Type E Comment Status A Editorial
 V_PP is in capital letters PP
 SuggestedRemedy
 change V_PP to V_pp
 Response Response Status C
 ACCEPT.
 EZ

Cl 33 SC 33.2.4.7 P 46 L 5 # 39
 Yseboodt, Lennart Philips
 Comment Type E Comment Status A PSE SD
 Finding related sub diagrams is not easy in state diagram Fig 33-9a.
 SuggestedRemedy
 Add figure number in the empty box of the sub state diagrams
 Response Response Status C
 ACCEPT.

Cl 33 SC 33.2.4.7 P 46 L 26 # 40
 Yseboodt, Lennart Philips
 Comment Type E Comment Status A PSE SD
 POWER_DENIED is a state, not a sub diagram. It should a subdiagram (dashed box) called "Power Denied" with Figure number 33-9e.
 SuggestedRemedy
 Rename block and refer to Figure 9e.
 Response Response Status C
 ACCEPT.

Cl 33 SC 33.2.5.0a P 53 L 41 # 41
 Yseboodt, Lennart Philips
 Comment Type E Comment Status A Connection Check
 "If the voltage at the PI, on either pair set, rises above V valid max, defined in Table 33-4, the PSE shall reset the PD by bringing the voltage at the PI below V off max, defined in Table 33-7."
 Table reference is wrong.
 SuggestedRemedy
 Remove:
 33-7 => 33-11.
 Response Response Status C
 ACCEPT IN PRINCIPLE.
 Change 33-7 to 33-11.
 Possible OBE by comment 209.

IEEE P802.3bt D1.1 4-Pair Power over Ethernet 4th Task Force review comments

CI 33 SC 33.2.6 P 59 L 15 # 42
 Yseboodt, Lennart Philips
 Comment Type E Comment Status A Editorial
 Line weight in Table 33-8-PSE classification configurations is inconsistent
 SuggestedRemedy
 Make this in the same way as in the related table 33-15a (page 89)
 Response Response Status C
 ACCEPT.
 This may be due to revision tracking.
 Kousi and Lennart to discuss.
 EZ

CI 33 SC 33.2.6 P 60 L 22 # 43
 Yseboodt, Lennart Philips
 Comment Type E Comment Status A Pres: Autoclass
 "Editor's Note: Measurement method and PSE margin for Autoclass still need to be addressed."
 This has been done (by adopting comment to D1.1).
 See yseboodt_Autoclass_measurement_baseline_v120.pdf (July meeting)
 SuggestedRemedy
 Remove note.
 Response Response Status C
 ACCEPT.
 Wait for presentation.

CI 33 SC 33.2.7 P 66 L 33 # 44
 Yseboodt, Lennart Philips
 Comment Type E Comment Status A Editorial
 Add a reference to the new section on Tpod. [Table 33-7, Item 1b].
 SuggestedRemedy
 Change additional information of item 1b to read "See 33.2.7.TBD, 33.2.7.5"
 Response Response Status C
 ACCEPT.
 EZ

CI 33 SC 33.3.7 P 95 L 15 # 45
 Yseboodt, Lennart Philips
 Comment Type E Comment Status A Editorial
 Table 33-18, item 11, the a) and b) are not needed and not referred to and inconsistent with the other tables.
 SuggestedRemedy
 Remove a) and b).
 Response Response Status C
 ACCEPT.
 EZ

CI 33 SC 33.3.7.3 P 96 L 39 # 46
 Yseboodt, Lennart Philips
 Comment Type E Comment Status X Pres: Inrush
 "Input inrush current at startup is limited by the PSE if C_Port per pair set < 180 mF, as specified in Table 33-11."
 Cport is not defined in Table 33-11
 SuggestedRemedy
 Cport is defined in Table 33-18. Change reference.
 Proposed Response Response Status W
 waiting for presentation.

IEEE P802.3bt D1.1 4-Pair Power over Ethernet 4th Task Force review comments

Cl 33 SC 33.4.9 P 110 L 32 # 47
 Yseboodt, Lennart Philips

Comment Type E Comment Status A Editorial

"The configuration of "channel" and "permanent link" is defined in Figure 33-24. Type 2, 3 and 4 Midspan PSE cabling system requirements are specified in ."

Unbearable suspense. Where are they specified?!

SuggestedRemedy

Response Response Status C

ACCEPT IN PRINCIPLE.

Hey Mr. Smartass. If you look at -2012 you will see they are specified in 33.1.4.1.

add "33.1.4.1" after "in"

EZ

Cl 33 SC 33.4.9.1.3 P 114 L 50 # 48
 Yseboodt, Lennart Philips

Comment Type E Comment Status A Editorial

Remove space at end of scentence.
 Original text: "...or exceed the values specified in Table 33-20 ."

SuggestedRemedy

"...or exceed the values specified in Table 33-20."

Response Response Status C

ACCEPT.

EZ

Cl 33 SC 33.4.9.1.4c P 115 L 34 # 49
 Yseboodt, Lennart Philips

Comment Type E Comment Status A Editorial

Remove space after parenthesis opening
 Original text: "Midspan PSEs intended for operation with 10GBASE-T (variants 5 and 6 in Clause 33.4.9.1) are additionally required to"

SuggestedRemedy

"Midspan PSEs intended for operation with 10GBASE-T (variants 5 and 6 in Clause 33.4.9.1) are additionally required to"

Response Response Status C

ACCEPT.

EZ

Cl 33 SC 33.5.1.1 P 118 L 10 # 50
 Yseboodt, Lennart Philips

Comment Type E Comment Status A Editorial

4-pair is not consistent in Table 33-21.

SuggestedRemedy

change to four-pair (two times in table)

Response Response Status C

ACCEPT.

EZ

Cl 33 SC 33.5.1.1 P 118 L 10 # 51
 Yseboodt, Lennart Philips

Comment Type E Comment Status A Management

"1 = Deny 4-pair power when connection check return Dual
 0 = Do not deny 4-pair power when connection check returns Dual"

Bad language.

SuggestedRemedy

"1 = Deny 4-pair power when connection check returns dual-signature
 0 = Do not deny 4-pair power when connection check returns dual-signature"

Response Response Status C

ACCEPT IN PRINCIPLE.

OBE by comment 271

IEEE P802.3bt D1.1 4-Pair Power over Ethernet 4th Task Force review comments

CI 33 SC 33.5.1.1.1a P 118 L 42 # 52
 Yseboodt, Lennart Philips
 Comment Type E Comment Status A Editorial
 4-pair not consistent
 SuggestedRemedy
 change to four-pair (three times)
 Response Response Status C
 ACCEPT.
 EZ

CI 33 SC 33.6.3.4 P 127 L 53 # 53
 Yseboodt, Lennart Philips
 Comment Type E Comment Status A Editorial
 Table 33-23 "Attribute to state diagram variable cross-reference"
 is not nicely separated over the pages.
 SuggestedRemedy
 Move the whole table to the next page.
 Response Response Status C
 ACCEPT.
 EZ

CI 33 SC 33A.4 P 153 L 13 # 54
 Yseboodt, Lennart Philips
 Comment Type E Comment Status A Editorial
 Space between 3 and %.
 SuggestedRemedy
 Make 3 % => 3%.
 Response Response Status C
 ACCEPT.
 EZ

CI 33 SC 33A.4 P 154 L 3 # 55
 Yseboodt, Lennart Philips
 Comment Type E Comment Status A Editorial
 dimensions should have spaces between number and dimension.
 Except procent.
 SuggestedRemedy
 Change 100m to 100 m.
 Response Response Status C
 ACCEPT IN PRINCIPLE.
 Editor to consult style guide to make sure this is correct and then act accordingly.
 There are other comments along this same line.
 EZ

CI 33 SC 33.2.2 P 28 L 28 # 56
 Yseboodt, Lennart Philips
 Comment Type ER Comment Status A Editorial
 Comment #28 Draft 1.0 not implemented.
 SuggestedRemedy
 Implement #28/D1.0.
 Response Response Status C
 ACCEPT.
 This fixes the crooked line in figure Figure 33-5b.
 EZ

CI 33 SC 33.2.4.4 P 39 L 5 # 57
 Yseboodt, Lennart Philips
 Comment Type ER Comment Status A Editorial
 Comment #227 D1.0 partially implemented.
 SuggestedRemedy
 Remove column pse_dll_capable from Table 33-3.
 See yseboodt_Table_33_3.pdf
 Response Response Status C
 ACCEPT IN PRINCIPLE.
 OBE by comment 15.

IEEE P802.3bt D1.1 4-Pair Power over Ethernet 4th Task Force review comments

CI 33 SC 33.2.7.4a P71 L 51 # 58
 Yseboodt, Lennart Philips

Comment Type ER Comment Status A Editorial

"The value of K which is based on curve fit and is dimensionless, for a Type 3 and Type 4 system that operates as 4-pair system is given by Equation (33-4b)."

Wrong Equation reference.

SuggestedRemedy

Change to:
 "The value of K which is based on curve fit and is dimensionless, for a Type 3 and Type 4 system that operates as 4-pair system is given by Equation 33-4a."

Response Response Status C

ACCEPT.

EZ

CI 33 SC 33.2.4.6 P43 L 8 # 59
 Yseboodt, Lennart Philips

Comment Type ER Comment Status A Editorial

The paragraph on line 8 through 12 uses the construct x_sub_y as literal text. The intention was for 'y' to become subscript.

SuggestedRemedy

Implement subscripts.

Response Response Status C

ACCEPT.

EZ

CI 33 SC 33.2.4.7 P47 L 1 # 60
 Yseboodt, Lennart Philips

Comment Type ER Comment Status A PSE SD

In subdiagrams of the statemachine, we have T3 coming in without a source visible.

SuggestedRemedy

Add "pse_reset + error_condition * (mr_pse_enable = enable)" to T3 arrow.

Response Response Status C

ACCEPT.

CI 33 SC 33.2.6 P59 L 13 # 61
 Yseboodt, Lennart Philips

Comment Type ER Comment Status A Editorial

Comment #42 Draft 1.0 not implemented.

SuggestedRemedy

Implement #42/D1.0.

Response Response Status C

ACCEPT.

EZ

Kousi and Lennart to discuss.

CI 33 SC 33.2.6.2 P62 L 21 # 62
 Yseboodt, Lennart Philips

Comment Type ER Comment Status A PSE Classification

"When connected to a single-signature PD, a PSE shall classify the PD only once or both of the pair sets."

SuggestedRemedy

"When connected to a single-signature PD, a PSE shall classify the PD only once on one or both of the pair sets."

Response Response Status C

ACCEPT IN PRINCIPLE.

OBE by comment 109.

CI 33 SC 33.3.7 P95 L 15 # 63
 Yseboodt, Lennart Philips

Comment Type ER Comment Status A Editorial

Table 33-18, item 11 defines V_On and V_Off. This is a clash with identically named V_Off from Table 33-11, Item 16. These Voffs do something totally different.

SuggestedRemedy

Rename Table 33-18 V_On to V_On_PD.
 Rename Table 33-18 V_Off to V_Off_PD.
 Change all references to the PD V_Off and PD V_On to the new V_Off_PD and V_On_PD.

Response Response Status C

ACCEPT.

EZ

IEEE P802.3bt D1.1 4-Pair Power over Ethernet 4th Task Force review comments

Cl 33 SC 33.3.7.4 P 97 L 5 # 64
 Yseboodt, Lennart Philips

Comment Type ER Comment Status A Editorial

"At any static voltage at the PI, class 6 or class 8 PDs in operating condition, the peak power shall not exceed P Class at the PSE PI for more than T CUT min, as defined in Table 33-11 and 5% duty cycle."

Bad phrasing + extra space in 'class'.

SuggestedRemedy

"For class 6 and class 8 PDs in any operating condition with any static voltage at the PI, the peak power shall not exceed P_Class at the PSE PI for more than T_CUT min, as defined in Table 33-11 and with 5% duty cycle."

Response Response Status C

ACCEPT.

EZ

Cl 33 SC 33.3.7.10 P 100 L 54 # 65
 Yseboodt, Lennart Philips

Comment Type ER Comment Status A Editorial

"... shall not exceed Icont-2Punb as specified ..."

SuggestedRemedy

"... shall not exceed I_con-2P-unb as specified ..."

Response Response Status C

ACCEPT IN PRINCIPLE.

OBE by comment 218.

EZ

Cl 33 SC 33B P 155 L 1 # 66
 Yseboodt, Lennart Philips

Comment Type ER Comment Status A Editorial

Change bars are missing.

SuggestedRemedy

Add change bars here, and also in the other Annexes where they are missing.

Response Response Status C

ACCEPT.

EZ

Cl 79 SC 79.3.2.5 P 162 L 37 # 67
 Yseboodt, Lennart Philips

Comment Type ER Comment Status A Editorial

"Poweris the effective..."
 Space missing.

SuggestedRemedy

"Power is the effective..."

Response Response Status C

ACCEPT.

EZ

Cl 79 SC 79.3.2.6b P 164 L 2 # 68
 Yseboodt, Lennart Philips

Comment Type ER Comment Status A Editorial

Comment D1.0/#123 not implemented.

SuggestedRemedy

Implement D1.0/#123.

Response Response Status C

ACCEPT.

EZ

IEEE P802.3bt D1.1 4-Pair Power over Ethernet 4th Task Force review comments

CI 33 SC 33.1.4.1 P 23 L 12 # 69
 Yseboodt, Lennart Philips

Comment Type T Comment Status A Cabling

"Type 2 operation requires Class D, or better, cabling as specified in ISO/IEC 11801:1995, and Type 3 operation requires Class D or better cabling as specified in ISO/IEC 11801:2002"

Is inconsistent with Table 33-1 which refers to the 2002 version of ISO/IEC 11801 for Type 2.

Note: if we choose for different cable requirements between Type 2 and Type 3, we hint to the user that these are not interoperable between Type 2 and Type 3. Probably not what we want.

SuggestedRemedy

TF to discuss how to make consistent.

Response Response Status C

ACCEPT IN PRINCIPLE.

Change Type 2 in table 33-1 back to 1995 reference.

CI 33 SC 33.1.4.1 P 23 L 15 # 70
 Yseboodt, Lennart Philips

Comment Type T Comment Status A Cabling

"Type 3 operation requires Class D or better cabling as specified in ISO/IEC 11801:2002"
 Does this not also apply to Type 4 ?

SuggestedRemedy

"Type 3 and Type 4 operation requires Class D or better cabling as specified in ISO/IEC 11801:2002"

Response Response Status C

ACCEPT.

CI 33 SC 33.2.4.4 P 35 L 38 # 71
 Yseboodt, Lennart Philips

Comment Type T Comment Status D Pres: PSE SD

IPort-2P is also per pair set
 original text:
 "Inrush-2P
 Output current per pair set during POWER_UP (see Table 33-11 and Figure 33-13).
 IPort-2P
 Output current (see 33.2.7.6)."

SuggestedRemedy

"IPort-2P
 Output current per pair set (see 33.2.7.6)."

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

We need to be careful. We should not change the Type 1/2 State Diagram variables if we are going to leave that diagram as is. We need to create new variables for Type 3/4.

Group to discuss.

CI 33 SC 33.2.4.4 P 39 L 5 # 72
 Yseboodt, Lennart Philips

Comment Type T Comment Status X Pres: Types

A Type 4 PSE is distinct from a Type 3 PSE in ways other than power (Vpse min, polarity, must implement 4P).

A Type 4 PSE that is powering below class 7 should still be a Type 4 PSE.
 Currently Table 33-3 requires a Type 4 PSE to have class_num_events = 5, possibly restricting it to Class 7 and 8.

(This is an updated version of the comment against D1.0).

Presentation on this topic "Type 4 Classrange"

SuggestedRemedy

Add class_num_events 1, 2 and 4 also for Type 4.

Proposed Response Response Status W

Waiting for Presentation

IEEE P802.3bt D1.1 4-Pair Power over Ethernet 4th Task Force review comments

Cl 33 SC 33.2.7 P 68 L 2 # 73
 Yseboodt, Lennart Philips

Comment Type T Comment Status A PSE Power

Items 13, 21, 23 and 24 only list Type 1 and 2.
 These all seem valid also for the new Types.

SuggestedRemedy

Change PSE Type to 'All'.

Response Response Status C

ACCEPT.

Cl 33 SC 33.2.7 P 69 L 16 # 74
 Yseboodt, Lennart Philips

Comment Type T Comment Status A

Table 33-11, item 21.
 Tdbo is only defined for Type 1,2.
 It remains valid also with Type 3 and Type 4 endspans.

SuggestedRemedy

add Type 3,4 to this row.

Response Response Status C

ACCEPT IN PRINCIPLE.

OBE by comment # 73

Cl 33 SC 33.2.7.4 P 71 L 26 # 75
 Yseboodt, Lennart Philips

Comment Type T Comment Status A Editorial

"For Type 3 and Type 4 PSEs, I Con-2P as specified in Table 33-11 shall be met when there is no end to end pair-to-pair current unbalance. When end to end pair-to-pair current unbalance is present, the I Con-2P may increase up to the value of I Con-2P-UNB as specified by Table 33-11 item 4a. In addition to I Con-2P as specified in Table 33-11, the PSE shall support the following AC current waveform parameters per pair set, while within the operating voltage range of V Port_PSE-2P :"

The shall statement is unclear.

SuggestedRemedy

"In addition to ICon-2P and ICon-2P-unb as specified in Table 33-11, the PSE shall support the following AC current waveform parameters, while within the operating voltage range of V Port_PSE :"

Response Response Status C

ACCEPT.

EZ

IEEE P802.3bt D1.1 4-Pair Power over Ethernet 4th Task Force review comments

Cl 33 SC 33.2.5.0a P 53 L 41 # 76
 Yseboodt, Lennart Philips

Comment Type T Comment Status R Connection Check

For connection check, first we say:
 "In addition, only tests that result in a voltage at the PSE PI that is below V valid (max) as specified in Table 33-4 shall be used to determine whether a single-signature or dual-signature is attached to the two pair sets in the link section."

And then:
 "If the voltage at the PI, on either pair set, rises above V valid max, defined in Table 33-4, the PSE shall reset the PD by bringing the voltage at the PI below V off max, defined in Table 33-7."

Since it is not allowed to use voltages > Vvalid(max), we do not need to define this.

SuggestedRemedy

Remove:
 "If the voltage at the PI, on either pair set, rises above V valid max, defined in Table 33-4, the PSE shall reset the PD by bringing the voltage at the PI below V off max, defined in Table 33-7."

Response Response Status C

REJECT.

Just because the voltage is in the valid range when the PSE makes it's decision, does not mean that the voltage never left that range. For example, if a PD got plugged in during the CC and the PSE figure out the correct answer in the 2nd half of the CC.

Cl 33 SC 33.2.7 P 66 L 33 # 77
 Yseboodt, Lennart Philips

Comment Type T Comment Status A PSE Power

Tpud value is TBD. [Table 33-7, Item 1b].

SuggestedRemedy

Tdelay-2P = 80ms
 Tinrush-2p = [50ms - 75ms]
 Therefore a T_pud = 4ms seems reasonable.

Response Response Status C

ACCEPT IN PRINCIPLE.

Delete Item 1b ("Tpud") from Table 33-11 (page 66, line 32).

Add to 33.2.7.5 (page 72, line 50, after first sentence of first paragraph):

"Type 3 and Type 4 PSEs that apply power to both pairsets when connected to a single-signature PD shall reach POWER_ON on both pairsets within T_inrush-2P max, starting with the first pairset transitioning into the POWER_UP state."

Cl 33 SC 33.3.7.4 P 96 L 53 # 78
 Yseboodt, Lennart Philips

Comment Type T Comment Status A Editorial

"V Overload is the PD PI voltage when the PD is drawing the permissible P Peak_PD."
 Voverload is missing -2P.

SuggestedRemedy

Change 'Voverload' to 'Voverload-2P'.

Response Response Status C

ACCEPT.

EZ

IEEE P802.3bt D1.1 4-Pair Power over Ethernet 4th Task Force review comments

CI 33 SC 33.3.7.4 P97 L 2 # 79
 Yseboodt, Lennart Philips

Comment Type T Comment Status A Editorial

"At any static voltage at the PI, and any PD operating condition, with the exception of class 6 or class 8 PDs, the peak power shall not exceed P Class_PD max for more than T CUT min, as defined in Table 33-11..."
 TCUT min is missing -2P suffix. (Line 2)

"At any static voltage at the PI, c lass 6 or class 8 PDs in operating condition, the peak power shall not exceed P Class at the PSE PI for more than T CUT min, as defined in Table 33-11..."
 TCUT min is missing -2P suffix. (Line 6)

SuggestedRemedy

Change 'TCUT min' to 'TCUT-2P min'.

Response Response Status C

ACCEPT.

EZ

CI 33 SC 33.3.7.4 P97 L 6 # 80
 Yseboodt, Lennart Philips

Comment Type T Comment Status A Editorial

"At any static voltage at the PI, c lass 6 or class 8 PDs in ..." Extra space in 'c lass'.

SuggestedRemedy

Change to 'class'.

Response Response Status C

ACCEPT IN PRINCIPLE.

OBE by comment 64.

CI 33 SC 33.3.7.5 P99 L 15 # 81
 Yseboodt, Lennart Philips

Comment Type T Comment Status A Editorial

T_CUT min is not a defined parameter

SuggestedRemedy

Change to T_CUT-2P min

Response Response Status C

ACCEPT.

EZ

CI 33 SC 33.3.7.5 P99 L 19 # 82
 Yseboodt, Lennart Philips

Comment Type T Comment Status A Editorial

"During PSE transient conditions in which the voltage at the PI is undergoing dynamic change, the PSE is responsible for limiting the transient current drawn by the PD for at least T LIM min as defined in Table 33-11."
 TLIM is not defined

SuggestedRemedy

Change TLIM to TLIM-2P.

Response Response Status C

ACCEPT.

EZ

CI 33 SC 33.2.3 P32 L 12 # 83
 Yseboodt, Lennart Philips

Comment Type TR Comment Status A Editorial

In Table 33-2, header row, "Alternative B" is wrong.

SuggestedRemedy

Replace by "Alternative B(S)"

Response Response Status C

ACCEPT IN PRINCIPLE.

OBE by comment 162.

EZ

IEEE P802.3bt D1.1 4-Pair Power over Ethernet 4th Task Force review comments

CI 33 SC 33.2.7 P 69 L 28 # 84
 Yseboodt, Lennart Philips

Comment Type TR Comment Status A PSE Power

Note 1:
 "The total port current of both pairs of the same polarity shall not exceed P Type /V
 $Port_PSE = 0.5 * (P\ Type / V\ Port_PSE_2P) * (1+a)$
 $+ 0.5 * (P\ Type / V\ Port_PSE_2P) * (1-a)$, where a is the effect of system end to end pair to
 pair resistance/current unbalance that
 is not specified in the standard explicitly."

Note 1 has a few problems:
 - it contains a shall, which is not appropriate for a note
 - a is undefined
 - it puts an additional total current restriction that would require a PSE to maintain a
 dynamically levered current limit over the two pairsets
 - The total maximum current according to this note is exactly enough to deliver PType
 which leaves no margin to set the current cut-off in certain classes.

SuggestedRemedy

Replace the note by:
 "In a compliant system, under normal operating conditions, the total current of pairs with
 the same polarity will not exceed $Ptype/Vport_pse-2P =$
 $(Icon_2P_unb) + (2 * Icon_2P - Icon_2P_unb) "$

Response Response Status C

ACCEPT IN PRINCIPLE.

OBE by comment 113 (note removed).

CI 33 SC 33.2.7 P 70 L 54 # 85
 Yseboodt, Lennart Philips

Comment Type TR Comment Status A PSE Power

Description of the new T_pud value is needed.

SuggestedRemedy

Add a new section 33.2.7.x "Pair set power up delay".
 Content:
 "A PSE that will power a single signature PD using both pairsets shall transition both pair
 sets to
 the POWER_UP state with a maximum delay of T_pud between the transition of the first
 pair set to POWER_UP and
 the transition of the second pair set to POWER_UP."

Response Response Status C

ACCEPT IN PRINCIPLE.

OBE by comment 77.

CI 33 SC 33.2.7.4 P 71 L 40 # 86
 Yseboodt, Lennart Philips

Comment Type TR Comment Status A Editorial

"Rchan is the channel loop resistance as defined in 33.1.4; this parameter has a worst-
 case value of R Ch , defined in Table 33-1"

Rchan is not defined in 1.4.
 Rchan worst case value depends on 2P or 4P power.

SuggestedRemedy

"Rchan is the channel DC loop resistance; this parameter has a worst-
 case value of R_Ch when powering using one pair set and R_Ch/2 when
 powering using two pair sets. Rch is defined in Table 33-1."

Response Response Status C

ACCEPT IN PRINCIPLE.

"Rchan is the channel DC loop resistance; this parameter has a worst-
 case value of R_Ch. Rch is defined in Table 33-1."

CI 33 SC 33.2.7.5 P 72 L 48 # 87
 Yseboodt, Lennart Philips

Comment Type TR Comment Status R PSE Inrush

"POWER_UP mode occurs on each pair set between the PSE's transition to the
 POWER_UP state on that
 pair set..."
 transition to the POWER_UP state is not correct

SuggestedRemedy

'transition to the POWER_ON state'

Response Response Status C

REJECT.

POWER_UP is correct.

IEEE P802.3bt D1.1 4-Pair Power over Ethernet 4th Task Force review comments

CI 33 SC 33.2.6 P 76 L 33 # 88
 Yseboodt, Lennart Philips

Comment Type TR Comment Status A PSE Power

CommentID: LEN1
 Nearly every variable in Table 33-11 has a corresponding description in the sections following the table.
 PType does not. With the addition of the new Types (3 and 4) we now need a definition that makes sense.

SuggestedRemedy

Insert a section with number 33.2.7.12 "Type power" and bump up the following section numbers.

Content:
 "P_Type (min) is the minimum power a PSE must support to enable the highest class that a PSE of that Type can support.
 Type 3 PSEs are not required to support P_Type if they are restricted to class 5 power or lower.
 Type 4 PSEs are not required to support P_Type if they are restricted to class 7 power or lower."

"Type 4 PSEs shall not source more power than P_Type max as specified in Table 33-11 for a duration longer than 1 second."

Response Response Status C

ACCEPT IN PRINCIPLE.

Insert a section with number 33.2.7.12 "Type power" and bump up the following section numbers.

Content:
 "P_Type (min) is the minimum power a PSE must support to enable the highest class that a PSE of that Type can support.
 Type 3 PSEs are not required to support P_Type if they are restricted to class 5 power or lower.
 Type 4 PSEs are not required to support P_Type if they are restricted to class 7 power or lower."

"Type 4 PSEs shall not source more power than P_Type max as specified in Table 33-11 calculated with any sliding window with a width of 1 (TBD) second."

Add ", 33.2.7.12" to Additional information column for item 12. Update all references (particularly in Table 33-11) to new section numbers created by inserting section 33.2.7.12.

CI 33 SC 33.2.6 P 77 L 33 # 89
 Yseboodt, Lennart Philips

Comment Type TR Comment Status A Pres: MPS

"The PSE shall monitor either the DC MPS component, the AC MPS component, or both."

There is no need for Type 3/4 PSEs to support multiple MPS mechanisms as this wastes power.

SuggestedRemedy

Baseline in yseboodt_baseline_mps_ac_v100.pdf (or updated version).

Response Response Status C

ACCEPT IN PRINCIPLE.

Accept yseboodt_baseline_mps_ac_v101.pdf as baseline text.

CI 33 SC 33.3.5 P 87 L 3 # 90
 Yseboodt, Lennart Philips

Comment Type TR Comment Status A 4PID

"A Type 3 or Type 4 dual-signature PD shall present a valid detection signature on the unpowered pair

** in order to receive 4-pair power from Type 3 and Type 4 PSEs **."

The part of the sentence in ** ** seems to indicate that Type 3/4 PDs can 'reject' 4P power by showing an invalid signature on the unpowered pair. This extra statement weakens the 'shall' and reduces clarity.

SuggestedRemedy

Strike the part of the line between ** and **.

Response Response Status C

ACCEPT IN PRINCIPLE.

OBE by comment 156.

IEEE P802.3bt D1.1 4-Pair Power over Ethernet 4th Task Force review comments

CI 33 SC 33.3.5.2 P 91 L 12 # 91
 Yseboodt, Lennart Philips

Comment Type TR Comment Status R PD Classification

Table 33-16a does not have a row for Type 3 / Class 0 PDs.
 There is no reason to disallow this.

SuggestedRemedy

Add row with following values:
 PD Type, Class, class_sig_A, class_sig_B
 3, 0, 0, 0

Response Response Status C

REJECT.

Lennart to submit comments next time to remove all references to class 0 for type 3/4.

CI 33 SC 33.3.7 P 94 L 5 # 92
 Yseboodt, Lennart Philips

Comment Type TR Comment Status A PD Power

Table 33-18 currently lists two different parameter descriptions for Pclass_PD:
 0-5 + 7 says "Input average power, Class x"
 6 + 8 says "Input guaranteed available average power, Class y"

This was done to enable extended power, because the original wording implicitly forbids exceeding the input average power.
 Extended power is only allowed for PDs in Class 6 or 8, this is mentioned several times in later normative text.
 The word 'guaranteed' may be confusing (are the others not guaranteed?)

SuggestedRemedy

Solution 1:

- We keep a distinction between 'extended' and 'normal' classes also in Table 33-18
- Strike the word 'guaranteed' in Table 33-18 for Class 6 and Class 8
- Editor to update section 33.3.7.2 also (remove 'guaranteed')

Solution 2:

- Remove distinction between 'extended' and 'normal' classes in Table 33-18
- Extended power rules do NOT change, only allowed for Class 6+8!
- Relabel parameter for Item 4/Pclass_PD for ALL classes to:
 "Input available average power, Class x"
- Editor to update section 33.3.7.2 also (remove 'guaranteed')

Solution 3:

- No changes.

Commenters preference is solution 2.

Response Response Status C

ACCEPT IN PRINCIPLE.

Implement solution #2 in suggested remedy.

Would OBE comment 147.

IEEE P802.3bt D1.1 4-Pair Power over Ethernet 4th Task Force review comments

Cl 33 SC 33.3.7 P 94 L 46 # 93
 Yseboodt, Lennart Philips

Comment Type TR Comment Status A PD Power

Value of Input current transient (absolute value) (Table 33-18, item 8) is TBD for Type 3 and Type 4.

SuggestedRemedy

Since this actual value results from intrinsic properties of the PD, and because both PSE and PD need to interoperate with legacy Types, it would be almost meaningless to have a different value for Type 3 and 4.

Replace TBD by 4.70 for Type 3 and Type 4 (and merge with Type 1/2 line).

Response Response Status C

ACCEPT.

Cl 33 SC 33.2.4.6 P 43 L 8 # 94
 Yseboodt, Lennart Philips

Comment Type TR Comment Status R PSE Power

According to this paragraph, a PSE is allowed to use the Ilim(min) of the PSE Type, regardless of the attached PD.
 Corner example: a Type 4 PSE may allow currents up to 1.9A to a Class 1 PD.
 This would only happen under fault conditions obviously.

Issues:

- The channel may be incapable of supporting this current (Type 1 channel would be valid in this example)
- Can be of indefinite duration
- Would allow the PD to self-destruct with a "substantial" power budget
- Current text would even allow the PSE to mix and match, eg. T_lim from Type 1 and I_lim from Type 4.

SuggestedRemedy

Since we are now supporting much higher power, while not previously a feature, PSEs now should protect the channel and downstream PD.

Delete the whole statement (lines 8 to 13).

Revert Type 2 text back to the original:

"When a Type 2 PSE powers a Type 1 PD, the PSE shall meet the PI electrical requirements of a Type 1 PSE, but may choose to meet the electrical requirements of a Type 2 PSE for I_{Con}, I_{LIM}, T_{LIM}, and P Type (see Table 33-11)."

Add:

"When a Type 3 or Type 4 PSE powers a PD of lower Type (Type_PD) than its own Type (Type_PSE), the PSE shall meet the PI electrical requirements of the PD Type (Type_PD), except for I_{Con}-2P, T_{LIM}-2P and PType see (Table 33-11), for which the PSE shall meet the requirements of any PSE Type, Type_PD <= PSE Type <= Type_PSE.
 The PSE shall use I_{Con}-2P, T_{LIM}-2P and PType parameters from the same Type.
 If, based on the outcome of physical layer classification and connection check, the PD Type cannot be determined, the PSE shall use the lowest Type the PD could be for Type_PD."

Response Response Status C

REJECT.

Comment is rejected because this is not necessary behavior and is a feature rather than a requirement. This allows PSEs to use a single current limit and not dynamically change it.

IEEE P802.3bt D1.1 4-Pair Power over Ethernet 4th Task Force review comments

CI 33 SC 33.2.6 P 58 L 12 # 95
 Yseboodt, Lennart Philips
 Comment Type **TR** Comment Status **A** PSE Classification
 "Rchan is the channel DC pair loop resistance."
 Needs to be updated for 2P and 4P.
 SuggestedRemedy
 "Rchan is the channel DC loop resistance."
 Response Response Status **C**
 ACCEPT.

CI 33 SC 33.2.6 P 58 L 18 # 96
 Yseboodt, Lennart Philips
 Comment Type **TR** Comment Status **A** PSE Classification
 Table 33-7.
 Comment #101 implemented incorrectly.
 SuggestedRemedy
 Undo changes. Then:
 Add "," before "whichever" in all entries.
 Replace "less" with "lower" in all entries.
 Response Response Status **C**
 ACCEPT.
 Comment 101 from D1.0 clearly said:
 "Don't implement suggested remedy.
 Add "," before "whichever" in all entries.
 Replace "less" with "lower" in all entries."
 EZ

CI 33 SC 33.2.6.3 P 64 L 45 # 97
 Yseboodt, Lennart Philips
 Comment Type **TR** Comment Status **A** Pres: Autoclass
 There is no specification on how a PSE is to measure the power consumed during
 Autoclass.
 SuggestedRemedy
 See yseboodt_Autoclass_measurement_baseline_v120.pdf (July meeting)
 Response Response Status **C**
 ACCEPT.

Wait for presentation

CI 33 SC 33.2.7 P 65 L 44 # 98
 Yseboodt, Lennart Philips
 Comment Type **TR** Comment Status **A**
 "33.2.7 Power supply output
 PSE behavior conforms to the state diagrams in Figure 33-9, Figure 33-9 continued, and
 Figure 33-10.
 When the PSE provides power to the PI, it shall conform with Table 33-11."
 We need to comply with LPS (Limited Power Supply) requirements.
 To that effect we have introduced P_Type max for Type 4 at 99.9W
 This alone is not enough and we need to introduce a normative statement.
 If comment LEN1 is adopted, this comment is OBE.
 SuggestedRemedy
 Insert at the end of 33.2.7 (Power supply output):
 "Type 4 PSEs shall not source more power than P_Type max as specified in Table 33-11
 for a duration longer than 1 second."
 Response Response Status **C**
 ACCEPT IN PRINCIPLE.
 OBE by comment 88

IEEE P802.3bt D1.1 4-Pair Power over Ethernet 4th Task Force review comments

Cl 33 SC 33.2.7 P 66 L 33 # 99
 Yseboodt, Lennart Philips

Comment Type TR Comment Status A PSE Power

Page 74, line 15 says:
 "Power shall be removed from the pair set of a PSE before the pair set current exceeds the "PSE upperbound template" in Figure 33-14."

This essentially allows a PSE to disconnect 1 pairset from a PD that is in over-current. This over-current will then instantly be carried by the remaining pairset, causing high thermal stress.

We cannot expect that a PSE can synchronize the shutdown of two pair sets perfectly, as this would preclude separate controllers, but we should specify the maximum time and try to limit thermal stress on the PD and PSE as much as possible.

SuggestedRemedy

Add the following line to Table 33-11:

1c, "Power down delay between pair sets for single-signature PDs, T_pdd, s, , TBD, (3,4), See 33.2.7.TBD, 33.2.7.5

I would prefer a value of 6ms for T_pdd (=Tlim for Type 4), TF to discuss.

Add a new section to explain item 1c (after the Tpod section):
 "A PSE that is powering a single signature PD of class 5 or higher and turns a pair set off, shall turn the remaining pair set off within T_pdd of turning off the first pair set."

Response Response Status C

ACCEPT IN PRINCIPLE.

OBE by comment 240.

Do Not Implement the following...

Add the following line to Table 33-11:

1c, "Power down delay between pair sets for single-signature PDs, T_pdd, s, , TBD, (3,4), See 33.2.7.TBD, 33.2.7.5

Add a new section to explain item 1c (after the Tpod section):
 "A PSE that is powering a single signature PD of class 5 or higher and turns a pairset off shall turn the remaining pair set off within T_pdd of turning off the first pairset."

Cl 33 SC 33.3.7 P 95 L 20 # 100
 Yseboodt, Lennart Philips

Comment Type TR Comment Status A PD Power

No PD Type in Table 33-18 for items 12 and 13

SuggestedRemedy

Set PD Type to 'All'.

Response Response Status C

ACCEPT.

EZ

Cl 33 SC 33.3.7.4 P 97 L 43 # 101
 Yseboodt, Lennart Philips

Comment Type TR Comment Status A PD Power

Formula 33-11a describes the maximum current for PDs in class 6 or 8 and is TBD.

SuggestedRemedy

Eq 33-11a:
 $I_{portmax} = P_{Class} / V_{PSE}$ (Ampere)

where

I_portmax is the RMS input current
 P_Class is the allocated class power as defined in 33.2.6 and Equation 33-3
 V_PSE is the voltage at the PSE PI as defined in 1.4.426

Response Response Status C

ACCEPT.

IEEE P802.3bt D1.1 4-Pair Power over Ethernet 4th Task Force review comments

CI 33 SC 33.3.7 P 98 L 13 # 102
 Yseboodt, Lennart Philips

Comment Type TR Comment Status A PD Power

"When the input voltage at the PI is static and in the range of V Port_PD defined by Table 33-18, the transient current drawn by the PD shall not exceed 4.70 mA/ms in either polarity. This limitation applies after inrush has completed (33.3.7.3) and before the PD has disconnected."

Refer to pair sets rather than PI.

SuggestedRemedy

"When the input voltage at the PI is static and in the range of V Port_PD defined by Table 33-18, the transient current drawn by a single-signature PD shall not exceed 4.70 mA/us in either polarity. A dual-signature PD shall not exceed 4.70 mA/us in either polarity per pairset in the same conditions. This limitation applies after inrush has completed (33.3.7.3) and before the PD has disconnected."

Response Response Status C

ACCEPT.

CI 79 SC 79.3.2.4 P 161 L 2 # 103
 Yseboodt, Lennart Philips

Comment Type TR Comment Status A Editorial

Table 79-4 does not allow a Type 3/4 PSE/PD to identify itself. We should define how these devices fill out the fields.

SuggestedRemedy

Add to section 79.3.2.4
 "A Type 3 or Type 4 device shall set the bits in 'power type' to (TBD)".

Response Response Status C

ACCEPT.

CI 33 SC 33.2.7.5 P 72 L 50 # 104
 Jones, Chad Cisco

Comment Type T Comment Status D Pres: Inrush

HOLD OVER for Ken Bennett:
 There is a recommendation that POWER_UP mode persist for the complete duration of TInrush in section 33.2.7.5 of the existing standard. Commensurately, there is a recommendation against using LEGACY POWER_UP in section 32.2.4.4. This is because legacy power-up can end POWER_UP mode prior to the end of PD Inrush. The result of an early exit of POWER_UP mode is that current is not limited to the levels in figure 33-13, and inrush current could exceed expected values for a PD, potentially damaging an existing Type 1 or Type 2 PD. Type 3 and Type 4 PSE's could deliver higher currents during PD Inrush in this scenario, increasing the probability of damage to a legacy PD.

The recommendations used in the existing standard have been applied to Type 3 and Type 4 PSE's in the draft. The suggested remedy makes it a requirement for Type 3 and Type 4 PSE's. For reference, the existing text is shown below:

However, for practical implementations, it is recommended that the POWER_UP mode on a pair set persist for the complete duration of TInrush-2P, as the PSE may not be able to correctly ascertain the conclusion of a PD's inrush behavior.

SuggestedRemedy

Change the text to:
 However, for practical implementations, it is recommended that POWER_UP mode in Type 1 and Type 2 PSE's persist for the complete duration of TInrush-2P, as the PSE may not be able to correctly ascertain the conclusion of a PD's inrush behavior. Type 3 and Type 4 PSE's shall remain in POWER_UP mode until the TInrush_2P period in table 33-11 is met.

Proposed Response Response Status O

Waiting for Yair's presentation.

IEEE P802.3bt D1.1 4-Pair Power over Ethernet 4th Task Force review comments

Cl 33 SC 33.2.4.4 P 39 L 6 # 105
 Jones, Chad Cisco

Comment Type T Comment Status D Types

HOLD OVER for Lennart Yseboodt:
 A Type 4 PSE is distinct from a Type 3 PSE in ways other than power (Vpse min, polarity, must implement 4P).
 We do not want to prevent Type 4 PSEs from providing also power below class 7.
 Currently Table 33-3 requires a Type 4 PSE to have class_num_events = 5, possibly restricting it to Class 7 and 8.

SuggestedRemedy

Add class_num_events 1, 2 and 4 also for Type 4.

Proposed Response Response Status Z

REJECT.

This comment was WITHDRAWN by the commenter.

Replaced by comment #72.

Chad, please withdraw this comment.

Cl 33 SC 33.3.7 P 94 L 48 # 106
 Jones, Chad Cisco

Comment Type TR Comment Status X Pres: Inrush

HOLD OVER for Dave Dwelley:
 Table 33-18, item 9: Change to "per pair set capacitance" allows 360uF. We changed this to 180uF per Straw Poll 2 in Pittsburgh.

SuggestedRemedy

Change back to "PD capacitance"
 Chair note: This is done? It's now called "PI capacitance during MDI_POWER states" and "C_port"

Proposed Response Response Status W

Wait for presentation

Cl 33 SC 33.3.7.3 P 96 L 48 # 107
 Jones, Chad Cisco

Comment Type TR Comment Status D PD Inrush

HOLD OVER for Yair Darshan:
 We don't want to wait 50- 75msec in Type 3 and 4 systems for linrush to be ended if not required due to measuring PD voltage/current/time profile by the PSE and knowing that it was ended earlier.
 In some large mutiport systems time for all ports to be ON is affected by Tinrush*N. N number of ports and PSE power supply power capability and its response to dynamic load behavior.

SuggestedRemedy

To add Editor Note at the end of 33.3.7.3.

To address the following issues:

1. Shortening Tinrush if PSE has the knowledge that PD is done with its Inrush.
2. Fastening Tinrush by allowing higher linrush_max during Tinrush time frame to shorten Tinrush with big PD capacitors.

Proposed Response Response Status Z

REJECT.

This comment was WITHDRAWN by the commenter.

Yair resubmitted this comment. Chad, please withdraw this one.

IEEE P802.3bt D1.1 4-Pair Power over Ethernet 4th Task Force review comments

Cl 33 SC 33.2.7.5 P 73 L 2 # 108
 Jones, Chad Cisco

Comment Type TR Comment Status D Pres: Inrush

HOLD OVER for Yair Darshan:
 It is usefull to allow higher Inrush current than 450mA after TBD time from POWER UP start for the following reasons:
 a)Reducing dynamic stress on the MOSFET during POWER UP and
 b)Reach faster startup with lower probability for startup oscilations
 c) Handle different load behaviour during startup that is time dependent.

SuggestedRemedy

Add the following text after line 36.
 The maximum inrush current sourced by the PSE per pair set may exceed the per pair set PSE inrush template in Figure 33-13 only TBD msec after POWER UP has started and shall not exceedd ILIM-2P maximum as specified by Table 33-11 item 9.

Proposed Response Response Status Z

PROPOSED REJECT.

This comment was WITHDRAWN by the commenter.

Waiting for Yair's presentation.

Cl 33 SC 33.2.6.2 P 20 L 20 # 109
 Johnson, Peter Sifos Technologies

Comment Type E Comment Status A PSE Classification

Typo - '...classify the PD only once or both of the pair sets.'

Replace 'or' with 'on'.

SuggestedRemedy

...classify the PD only once on both of the pair sets.

Response Response Status C

ACCEPT IN PRINCIPLE.

Replace with "classify the PD only once. Classification events may appear on one or both pairsets."

See comment 227, 182, 62

Cl 33 SC 33.3.5 P 88 L 36 # 110
 Johnson, Peter Sifos Technologies

Comment Type E Comment Status A Editorial

...., Data Link Layer classification

Add "DLL" here since that is the term used in the Table 33-15a

SuggestedRemedy

...., Data Link Layer (DLL) classification

Response Response Status C

ACCEPT.

EZ

Cl 33 SC 33.2.4.4 P 35 L 52 # 111
 Johnson, Peter Sifos Technologies

Comment Type T Comment Status X Pres: Inrush

legacy_powerup state variable definition.

This refers to a commonly implemented inrush behavior associated with 802.3af and many 802.3at PSE's whereby inrush is deemed completed as soon as port voltage is in a nominal range. This behavior is not recommended in 802.3at because Type-2 PSE's are allowed to set Type-2 parameters for Icut and Ilim upon the completion of inrush meaning all PD's that delay or stagger inrush loads might not experience inrush current limiting at all resulting in effective inrush currents at 684mA or higher. Type-3 and Type-4 may allow even higher inrush currents to Type-1 / Type-2 PD's if they implement the "traditional" legacy_powerup. This should be avoided.

SuggestedRemedy

legacy_powerup....

FALSE: The PSE does not support legacy power up. Type-3 and Type-4 PSEs shall use this value. It is highly recommended Type-1 and Type-2 PSEs use this value.

Proposed Response Response Status W

Wait for Yair's Inrush presentation.

IEEE P802.3bt D1.1 4-Pair Power over Ethernet 4th Task Force review comments

Cl 33 SC 33.2.7 P 66 L 51 # 112
 Johnson, Peter Sifos Technologies

Comment Type T Comment Status A Editorial

Table 33-11 Item 4:

All 3 versions of Icon-2P specifications appear to need to reference paragraph 33.2.7.4.

SuggestedRemedy

Add 'See 33.2.7.4' to Type 3,4 4-pair mode.

Response Response Status C

ACCEPT IN PRINCIPLE.

OBE by comment 6.

EZ

Cl 33 SC 33.2.7 P 67 L 7 # 113
 Johnson, Peter Sifos Technologies

Comment Type T Comment Status A PSE Power

Table 33-11, Item 4a., Icon-2P-unbal

The specified MAXIMUM value for Icon-2P-unb is actually less than Ilim_min and load currents below Ilim_min can be sourced indefinitely by a PSE according to figure 33-14, the operating current template. So Icon-2P-unbal cannot be a MAXIMUM value for PSE source current, even in a perfectly balanced system.

Are these in fact MINIMUM values? If so, then they are only applicable to one pair set and in accordance with footnote 1, the other pair must provide some value less than Icon-2P.

There is also a second problem that Icon-2P-unbal is an absolute value and not PSE voltage dependent like Icon and Pclass. This disparity undermines the benefit of specifying Icon and Pclass as formulas.

SuggestedRemedy

This is a tough one to solve given the current structure of Table 33-11.

One possibility would be to specify 'Icon' as the minimum total continuous current on all powered pair sets, noting that with Type-1 and Type-2 and perhaps certain cases of Type-3, there is only one powered pair set. In this case, the minimum for Icon is Pclass/Vport-PSE-2p regardless of pair-to-pair unbalance.

Then separately specify 'Icon-Pair-max' as the minimum total continuous current on a single pair set including effects of pair-to-pair unbalance. For 2-pair powering, this would be Icon but for 4-Pair powering, would be a formula used to compute maximum pair set current assuming Vport-PSE-2p and worst case system unbalance.

Response Response Status C

ACCEPT IN PRINCIPLE.

Adopt darshan_05_0715-REV003.docx as new text and table related to Icon, Icon-2p_unb and related material with editorial license to fix typos and spacing errors.

IEEE P802.3bt D1.1 4-Pair Power over Ethernet 4th Task Force review comments

Cl 33 SC 33.2.7.4 P 71 L 27 # 114
 Johnson, Peter Sifos Technologies

Comment Type T Comment Status A PSE Power

For Type 3 and Tyep-4 PSEs, Icon-2P as specified in Table 33-11 shall be met when there is no end to end pair-to-pair current unbalance. When end to end pair-to-pair current unbalance is present, the Icon-2P may increase up to the value of Icon-2P-UNB...."

These sentences suggests that somehow the PSE KNOWS of the presence of end-to-end unbalance and then MAY increase Icon-2P UP TO Icon-2P-unb as a result. This is confusing and hard to interpret.

SuggestedRemedy

No replacement language is suggested at this time and the fix may require changes in Table 33-11.

If Icon were always enforced as a sum of all powered pair sets, then in terms of furnishing minimum required power (continuous output current) to a PD, there is no concern about pair-to-pair unbalance at all.

Beyond this, any means by which a PSE escalates Icon-2P to Icon-2P-unb needs to be clarified. For example, a PSE could 'KNOW' that pair-to-pair unbalance should be considered following a Single Signature connection check. Conversely, a Dual Signature PD with dissimilar class signatures might exempt the PSE from Icon-2P-unb escalation.

Response Response Status C

ACCEPT IN PRINCIPLE.

OBE by comment 113.

Cl 33 SC 33.2.7 P 69 L 28 # 115
 Johnson, Peter Sifos Technologies

Comment Type T Comment Status A PSE Power

1 The total port current to both pairs of the same polarity shall not exceed $PType/Vport_PSE = 0.5*(PType/Vport_PSE_2P)*(1+a) + 0.5*(PType/Vport_PSE_2P)*(1-a)$, where a is the effect....

This is not a true. A PSE may furnish up to Ilim-2P_min continuously according to Figure 33-14, the operating current template. Ilim-2P_min is greater than $0.5*(PType/Vport_PSE_2P)$ that really represents the minimum required output power of a PSE port operating at Vport_PSE-2P_min.

SuggestedRemedy

The solution here depends on any structural changes to Icon-2P and Icon-2P-unb that might be forthcoming.

One option is to simply remove the footnote altogether.

Response Response Status C

ACCEPT IN PRINCIPLE.

OBE by comment 113.

Cl 33 SC 33.2.7.4a P 72 L 17 # 116
 Johnson, Peter Sifos Technologies

Comment Type T Comment Status A Unbalance

...The sum of the current of all pairs with the same polarity shall not exceed Pclass/VPSE.....

This statement is not true. At the PSE interface, current can continuously be sourced up to the value of Ilim_min-2P as shown in Figure 33-14, the operating current template. Pclass/VPSE is the minimum required current capacity at the PSE interface given a particular Pclass_PD.

Also, "VPSE" is not a defined parameter in Table 33-11.

SuggestedRemedy

Remove this statement.

Response Response Status C

ACCEPT.

IEEE P802.3bt D1.1 4-Pair Power over Ethernet 4th Task Force review comments

Cl 33 SC 33.3.5 P 89 L 1 # 117
 Johnson, Peter Sifos Technologies

Comment Type T Comment Status R PD Classification

Table 33-15a

While we have improved the PSE portion of this table, the PD portion has become confusing now that it is separate. It can be simplified.

SuggestedRemedy

Replace 33-15a with:

Type	Class	Class Signature	DLL
1,3	0-3	see Table 33-16	Optional
2,3	4	see Table 33-16	Mandatory
3	5-6	see Table 33-16a	Mandatory
4	7-8	see Table 33-16a	Mandatory

Remove footnote from Table 33-15a.

Remove following sentence "Type 2, Type 3, and Type 4 PDs implement...." as it is completely redundant with the table now.

Response Response Status C

REJECT.

This would remove the physical layer requirements from this table. There are other errors as well.

Cl 33 SC 33.2.7.7 P 74 L 16 # 118
 Bullock, Chris Cisco Systems

Comment Type E Comment Status A Editorial

Pair set is missing an 'r'.

SuggestedRemedy

Change "a pai set" to "a pair set"

Response Response Status C

ACCEPT IN PRINCIPLE.

OBE by comment 28

EZ

Cl 33 SC 33A.3 P 153 L 10 # 119
 Bullock, Chris Cisco Systems

Comment Type E Comment Status A

The section defines Intra pair resistance unbalance.....not Inter pair resistance unbalance

SuggestedRemedy

Change "Inter Pair Resistance Unbalance" to "Intra Pair Resistance Unbalance"

Response Response Status C

ACCEPT.

I agree that this should be Intra Pair. Where did "Inter" come from?

Would OBE comment 196

Cl 33 SC 33.2.3 P 32 L 5 # 120
 Bullock, Chris Cisco Systems

Comment Type ER Comment Status A Editorial

A PSE device may provide power via one or both the of two valid four-wire connections.

The words "the of" should be "of the"

SuggestedRemedy

Replace:

A PSE device may provide power via one or both the of two valid four-wire connections.

With:

A PSE device may provide power via one or both of the two valid four-wire connections.

Response Response Status C

ACCEPT.

EZ

IEEE P802.3bt D1.1 4-Pair Power over Ethernet 4th Task Force review comments

CI 33 SC 33.2.5.5 P 56 L 51 # 121
 Bullock, Chris Cisco Systems

Comment Type ER Comment Status A Editorial

Reference to table is wrong. Ropen is defined in Table 33-6, not Table 33-4.

SuggestedRemedy

Change "Ropen as defined in Table 33-4," to "Ropen as defined in Table 33-6,"

Response Response Status C

ACCEPT IN PRINCIPLE.

OBE by comment 204.

EZ

CI 33 SC 33.2.7.4a P 72 L 7 # 122
 Bullock, Chris Cisco Systems

Comment Type ER Comment Status A Editorial

"PSE PI Pair-to-Ppair-to-pairair" should be "PSE PI Pair-to-pair"

SuggestedRemedy

Change "PSE PI Pair-to-Ppair-to-pairair" to "PSE PI Pair-to-pair"

Response Response Status C

ACCEPT IN PRINCIPLE.

OBE by comment 232.

EZ

CI 33 SC 33.2.5.1 P 55 L 8 # 123
 Bullock, Chris Cisco Systems

Comment Type TR Comment Status A Connection Check

Table 33-4:

Voc and Isc should also apply to connection check state.

For Item 1 and 2, change Additional information column to include Connection Check.

SuggestedRemedy

Change "In Detection state only" to "In Detection state or Connection Check state"

Response Response Status C

ACCEPT.

EZ

CI 33 SC 33.2.4.6 P 41 L 22 # 124
 Bullock, Chris Cisco Systems

Comment Type TR Comment Status D PSE SD

If connection check is performed prior to detection, a result of invalid will keep you from entering detection state. As such, an result of "open_circuit on one of the pair sets" should not cause an "invalid" result.

SuggestedRemedy

replace "open_circuit on one of the pair sets" to "open_circuit on both of the pair sets"

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

OBE by comment # 7.

IEEE P802.3bt D1.1 4-Pair Power over Ethernet 4th Task Force review comments

Cl 33 SC 33.3.7.3 P 96 L 47 # 125
 Picard, Jean Texas Instruments

Comment Type TR Comment Status D Pres: Inrush

The note needs some clarifications, Cport is the capacitance the PSE will see during inrush and operation.

SuggestedRemedy

Cport per pair set is the port capacitance seen by an attached PSE during startup and steady-state operation on two twisted pairs.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Cport per pair set is the port capacitance seen by an attached PSE during startup and steady-state operation on a pair set.

Cl 33 SC 33.1.4 P 23 L 13 # 126
 Shariff, Masood CommScope

Comment Type T Comment Status A Cabling

Comment: text incorrectly identifies ISO/IEC 11801:2002 as lacking the additional requirement on DC loop resistance, this applies to ISO/IEC 11801:1995, but not 2002. Additionally, specification does not imply which requirements link to Cat 5e and which to cat 5, or, if they are all the same.

SuggestedRemedy

rewrite as follows:

Type 2 operation requires Class D or better cabling as specified in ISO/IEC 11801:1995 with the additional requirement that channel DC loop resistance shall be 25 ohms or less. These requirements are also met by Category 5 cable and components as specified in ANSI/TIA/EIA-568-A and Category 5e or better cabling components specified in ANSI/TIA-568-C.2. Type 3 operation requires Class D or better cabling as specified in ISO/IEC 11801:2002. These requirements are also met by Category 5e or better cable and components specified in ANSI/TIA-568-C.2.

Response Response Status C

ACCEPT IN PRINCIPLE.

Replace with:

Type 2 operation requires Class D or better cabling as specified in ISO/IEC 11801:1995 with the additional requirement that channel DC loop resistance shall be 25 ohms or less. These requirements are also met by Category 5 cable and components as specified in ANSI/TIA/EIA-568-A and Category 5e or better cabling components specified in ANSI/TIA-568-C.2. Type 3 and Type 4 operation requires Class D or better cabling as specified in ISO/IEC 11801:2002. These requirements are also met by Category 5e or better cable and components specified in ANSI/TIA-568-C.2.

See comments 248, 160.

IEEE P802.3bt D1.1 4-Pair Power over Ethernet 4th Task Force review comments

CI 33 SC 33.1.4 P 22 L 45 # 127
 Shariff, Masood CommScope
 Comment Type T Comment Status A Cabling

Baseed on initial information received from IEEE 802.3bt, the maximum current per pair studied and specified in drafts ISO/IEC TR 29125 Ed2 and TIA TSB 184-A are 1000 mA per pair with all 4 pairs powered. Repeating the work with higher currents will take a lot of time and effort.

SuggestedRemedy

Adjust the maximum Icont-2p_unb from 1087 mA to 1000 mA in the Editors note:

Type 4: Icont-2p=865mA, Icont-2p_unb=1087mA

Response Response Status C

ACCEPT IN PRINCIPLE.

Change Note to:

Editor's Note: Type 3 and Type 4 current for extended power are presently under study in this draft.

These numbers should converge to Icon-2p_unb in Table 33-11.

Liason underway with TIA and others to study the effect of unbalance on temperature rise. Liason links can be found at <http://www.ieee802.org/3/bt/public/mar15/Liaisons.pdf>

CI 33 SC 33.1.1 P 20 L 5 # 128
 Shariff, Masood CommScope
 Comment Type T Comment Status A Cabling

The sentence below is confusing and does not include TIA specifications.

Type 2 operation requires ISO/IEC 11801:1995 Class D or better cabling, and Type 3 operation requires ISO/IEC 11801:2002 Class D or better cabling, and a derating of the cabling maximum ambient operating temperature.

SuggestedRemedy

Rewrite the sentences as shown below:

Type 2 operation requires Class D or better cabling as specified in ISO/IEC 11801:1995 with the additional requirement that channel DC loop resistance shall be 25 ohms or less. These requirements are also met by Category 5 cable and components as specified in ANSI/TIA/EIA-568-A and Category 5e or better cabling components specified in ANSI/TIA-568-C.2. Type 3 operation requires Class D or better cabling as specified in ISO/IEC 11801:2002. These requirements are also met by Category 5e or better cable and components

Response Response Status C

ACCEPT IN PRINCIPLE.

Current style is to not have objectives in the clause.

Remove section 33.1.1.

CI 33 SC 33.A.4 P 153 L 31 # 129
 Shariff, Masood CommScope
 Comment Type T Comment Status A Cabling

Draft ISO/IEC TR 29125 Ed2 and TIA TSB-184-A both have 7% maximum channel pair to pair resistance unbalance values and for consistency annex 33A should reflect the same.

SuggestedRemedy

Change pair to pair DCRUNB from 7.5 % to 7 % globally including any calculations that use pair to pair resistance unbalance. Hopefully this may change the 1087 mA Rcont_2p_unb from 1087 mA to 1000 mA bringing the max current within the scope of ISO TR 29125 Ed2 and TIA TSB 184-A?

Response Response Status C

ACCEPT.

IEEE P802.3bt D1.1 4-Pair Power over Ethernet 4th Task Force review comments

CI 33 SC 33.2.7 P 68 L 3439 # 130
 Darshan, Yair Microsemi

Comment Type ER Comment Status A Editorial

This comment was accepted in D1.0 and was not executed in D1.1
 Table 33-11 item 17, additional information column, line 12
 The text: "The pair set with highest current" is not clear since we are looking at two pairs of the same polarity and we care of the pair with the highest current and not the pair-set (which is the positive and negative pairs of a pair set) with the highest current.

SuggestedRemedy

Change to "The pair with highest current" in two locations

Response Response Status C

ACCEPT IN PRINCIPLE.

This is from comment 347 D1.0: Don't implement, instead:

Change to:

"Applies to highest current pair."

CI 33 SC Annex 33C P 155 L 13 # 131
 Darshan, Yair Microsemi

Comment Type T Comment Status A Editorial

In June 2015 comment cycle D1.0 we have accepted comment #360 to adopt pages 3 and 4 of darshan_01_0615.pdf. Page 4 (Annex C) was not inserted in D1.1.

SuggestedRemedy

To insert page 4 from
http://www.ieee802.org/3/bt/public/jun15/darshan_01_0615_rev_013a.pdf to PAGE 55 after Annex B.

Response Response Status C

ACCEPT.

EZ

CI 33 SC 33.3.7 P 94 L 37 # 132
 Darshan, Yair Microsemi

Comment Type T Comment Status A PD Power

Table 33-18 item 7:
 In June we have changed eq-33-12a to be used for all classes above class 4.
 We need to update Table 33-18 item 7 accordingly.

SuggestedRemedy

Table 33-18 item 7:
 1. Change the row with the parameter: Peak operating power, class 5 as follows:
 parameter name: Change to: Peak operating power, class 5, 6, 7 and 8.
 Max value: Change from 1.11xPclass_PD to 1.05xPclass_PD
 PD Type: change to 3, 4.
 2. Delete the next rows of item 7 for classes 6, 7, and 8.

Response Response Status C

ACCEPT.

CI 33 SC 33.2.4.4 P 36 L 49 # 133
 Darshan, Yair Microsemi

Comment Type TR Comment Status D Pres: PSE SD

At the system level we need to know if we have over load condition over pair set A and pair set B.
 The current text says "...over at least one pair set.." means that if we know the status on pair set A it is sufficient and it is not.
 What about the status of pair set B?
 As a result, the variable ovid_detected text need to be updated.

SuggestedRemedy

Change from:
 A variable indicating if the PSE output current over at least one pair set has been in an overload condition (see 33.2.7.6) for..."

To:
 A variable indicating if the PSE output current over 1st pair-set or 2nd pair set has been in an overload condition (see 33.2.7.6) for..."

Proposed Response Response Status W

waiting for presentation

IEEE P802.3bt D1.1 4-Pair Power over Ethernet 4th Task Force review comments

Cl 33 SC 33.3.7.3 P 96 L 27 # 134
 Darshan, Yair Microsemi

Comment Type TR Comment Status X Pres: Inrush

33.3.7.3 Input inrush current
 Inrush current per pair-set is drawn beginning with the application of input voltage at the pair set compliant with Vport_PD-2P requirements as defined in Table 33-18, and ending before TInrush-2P min per Table 33-11. After TInrush-2P min, the PD shall not exceed its per pair set current threshold corresponding to its class level.

 The time point when PD Inrush is ending is not function of PSE Tinrush Timer. It is only a function of the PD internal design that regardless of the choices it has to use Cport between 5uF to 180uF e.g. for Type 1 and 2 and load current of up to 350mA during POWERUP phase, it has to complete linrush within 50msec which is the number equivalent to Tinrush_min at Table 33-11 which is a PSE requirements. See detailed analysis in darshan_01_0715.pdf, titled: "Only PD affects PD POWERUP Tinrush max (Not the PSE Tinrush Timer).

SuggestedRemedy

See detailed analysis and updated suggested remedy in darshan_01_0715.pdf.

Change lines 26-27 from:

"Inrush current per pair set is drawn beginning with the application of input voltage at the pair set compliant with Vport_PD-2P requirements as defined in To:
 "Inrush current per pair set is drawn beginning with the application of input voltage at the pair set compliant with Vport_PD-2P requirements as defined in Table 33-18, and ends when Vport_PD-2P reaches steady state within time duration TInrush-2P min per Table 33-11. After TInrush-2P min, the PD shall not exceed its per pair set current threshold corresponding to its class level."
 "

Proposed Response Response Status W
 waiting for presentation.

Cl 33 SC 33.3.7.3 P 96 L 48 # 135
 Darshan, Yair Microsemi

Comment Type TR Comment Status X Pres: Inrush

(WAS ALSO IN D1.0 COMMENT #334)
 We don't want to wait 50- 75msec in Type 3 and 4 systems for linrush to be ended if not required due to measuring PD voltage/current/time profile by the PSE and knowing that it was ended earlier.
 In some large mutiport systems time for all ports to be ON is affected by Tinrush*N. N number of ports and PSE power supply power capability and its response to dynamic load behavior.

SuggestedRemedy

Withdrawn comment #334 from D1.0.

Proposed Response Response Status W
 Waiting for presentation.

Cl 33 SC 33.2.7.5 P 73 L 15 # 136
 Darshan, Yair Microsemi

Comment Type TR Comment Status X Pres: Inrush

It is usefull to allow higher Inrush current than 450mA after TBD time from POWER UP start for the following reasons:
 a)Reach faster startup with lower probability for startup oscilations
 b)Handle different load behaviour during startup that is time dependent e.g.1: Adress the issue of some PDs that turn ON full power during POWERUP. e.g.2: Supports PDs with high input capacitance to reach steady state faster.
 I doesnt add any burden on PSE as PSE move from Inrush limits to ILIM any way.
 See darshan_02_0715.pdf

SuggestedRemedy

Add the following text after line 36.

The maximum inrush current sourced by the PSE per pair set may exceed the per pair set PSE inrush template in Figure 33-13 only TBD msec after POWER UP has started and shall not exceedd ILIM-2P maximum as specified by Table 33-11 item 9.

Proposed Response Response Status W
 I asked for a presentation on this for July. Is there one?

IEEE P802.3bt D1.1 4-Pair Power over Ethernet 4th Task Force review comments

Cl 33 SC 33.3.7 P 94 L 48 # 137
 Darshan, Yair Microsemi
 Comment Type **TR** Comment Status **A** Pres: *Inrush*
 Update Cport_min
SuggestedRemedy
 Make the following updates for Table 33-18 item 9 and related text per page 5 of darshan_04_0715.pdf
Response Response Status **C**
 ACCEPT IN PRINCIPLE.
 Adopt page 3 of darshan_04_0715-REV007A.docx

Cl 33 SC 33.2.4.4 P 35 L 45 # 138
 Darshan, Yair Microsemi
 Comment Type **TR** Comment Status **D** PSE *Inrush*
 There is missing word "only" in the text:
 The text "This variable is provided for PSEs that (only)monitor the per pair set voltage output and use that information".
 The above text should match lines 46-47 that do use the word "only" which is the correct intent:
 lines 46-47 says:
 Using only the PI pair set voltage information may be insufficient..."
SuggestedRemedy
 Repalce The text "... for PSEs that monitor the per pair set voltage output and use that information"
 with:
 "... for PSEs that monitor only the per pair set voltage output and use that information"
Proposed Response Response Status **W**
 PROPOSED REJECT.
 Yair, if we add the word only, then this variable would not apply to PSEs that use more than the output voltage. Thus, your PSE would not be allowed to leave inrush early. I don't think this is what you want.

Cl 33 SC 33.3.7.3 P 90 L 43 # 139
 Darshan, Yair Microsemi
 Comment Type **TR** Comment Status **X** Pres: *Inrush*
 The following comment addresses linrush in Table 33-11 item 5a and PD Cport max to be supported by PSE linrush. Since both parameters are tied together, they are addressed at the same comment.
 See details in darshan_02_0715.pdf titled: Type 3 and 4 PD Cport_max to be supported by PSE linrush_min.
SuggestedRemedy
 1. No changes to Table 33-11 item 5a linrush. It is in line with the work done on September 2014.
 2. For capacitance value for Type 3 and 4 for SS and DS PD:
 see darshan_02_0715.pdf.
Proposed Response Response Status **W**
 Waiting for presentation.

IEEE P802.3bt D1.1 4-Pair Power over Ethernet 4th Task Force review comments

CI 33 SC 33.2.7.4b P 72 L 40 # 140
 Darshan, Yair Microsemi

Comment Type TR Comment Status A Pres: Unbalance

We need to complete the TBD in clause 33.2.7.4b. It addresses the test setup and test conditions for completion the infrastructure work needed for PSE PI P2PRUNB.
 1. In previous drafts we add the equations needed for designing Rpair_max/min relationship in order to guarantee compliance with system E2EP2Plunb/Runb objectives (see equation 33-4b).
 As we already know, E2EP2P_lunb is function of power level and we care only for the worst case condition at maximum system operating power class level.
 Due to th efact that E2EP2P_lunb is decreased when load power is increased, we need to define equation 33-4b for each operating class.
 So far we have supplied the requirements for Type 3 and Type 4 maximum power i.e. class 6 and 8 and we need to complete it for class 5 and 7 as well. This part will be addressed by expanding equation 33-4b to include requirements for class 5 and 7.
 2.In order to check for compliance, we need test setup that will include Channel and PD effective resistance to ensure that the PSE under test meets the requirements. This part will be cover by Annex B which is a normative Annex.

SuggestedRemedy

Follow the details of the suggested remedy at pages 2-5 at darshan_06_0715.pdf for updated comment and suggested remedy.
 The title of this presentation/attachment is:
 "ANNEX 33B [Normative] PSE PI Pair-to-Pair Resistance/Current Unbalance"

Response Response Status C

ACCEPT IN PRINCIPLE.

Adopt pages 2-5 of darshan_06_0715-REV008.docx as baseline text

CI 33 SC 33.2.4.6 P 42 L 12 # 141
 Schindler, Fred Seen Simply

Comment Type TR Comment Status A

Existing text,
 "Values:open_circuit: The PSE has detected an open circuit. This value is optionally returned by a PSE performing detection using Alternative B, or by Type 3 and 4 PSEs performing detection over each pair set, if either pair set yields an open circuit."
 Limits implementations that want to power one or both pair sets.

SuggestedRemedy

Replace the existing text called out with,
 "Values: open_circuit: The PSE has detected an open circuit on the pair set used for detection for PSE Types that will use this information to power only on one pair set. This value is optionally returned by PSE Types performing detection using Alternative B, that will used this information to power only on one pair set. The PSE has detected an open circuit on both pair sets used for detection for Type 3 or 4 PSEs, which will use this information to power on both pair sets."

Response Response Status C

ACCEPT IN PRINCIPLE.

This value of the variable is optional and is only used to skip the backoff timer. This behavior applies to any PSE that sees an open circuit on alt B, but is overridden by valid_A.

Remedy: Remove Type 3/4 text added to open_circuit value. (should restore original text)

CI 33 SC 33.2.4.7 P 52 L 19 # 142
 Schindler, Fred Seen Simply

Comment Type ER Comment Status A PSE SD

The Editor's note references figure 33-9, will not be modified because the Task Force decided to keep the legacy Type 1 and Type 2 PSE state diagram. Variables deny_dual_sig_4p_power and maintain_4pair_power do not exist anymore. The 4PID state diagram needs to be developed.

SuggestedRemedy

Replace the Editors note starting on line 29 and ending on line 40, with

Editor's Note: The State diagram shown in Figure 33-9(TBD) needs to incorporate the 4PID requirements that are also covered in section 33.2.5.6.

Response Response Status C

ACCEPT.

See comment 260.

IEEE P802.3bt D1.1 4-Pair Power over Ethernet 4th Task Force review comments

CI 33 SC 33.2.5.6 P 60 L 12 # 143
 Schindler, Fred Seen Simply

Comment Type **TR** Comment Status **A** PSE Classification

Dual Signature PDs may present different classification values on each pair set. Therefore, PSEs powering both pair sets need to identify the PD class to meet the PD power requested. A Dual Signature, PDs with isolated loads will need to see the classification steps to achieve mutual ID.

SuggestedRemedy
 Strike the "(TBD)" in the draft sentence on line 12.

The text reads, "Subsequent to successful detection, all Type 3 and Type 4 PSEs perform classification using at least one of the following: Multiple-Event Physical Layer classification; or Multiple-Event Physical Layer classification and Data Link Layer classification. Both pair sets attached to a Dual-signature PD shall be classified by Type 3 and Type 4 PSEs that will deliver 4-pair power.

Response Response Status **C**
 ACCEPT.

CI 33 SC 33.2.7.7 P 74 L 16 # 144
 Schindler, Fred Seen Simply

Comment Type **ER** Comment Status **A** Editorial

Typo "pai".

SuggestedRemedy
 Replace with "pair".

Response Response Status **C**
 ACCEPT IN PRINCIPLE.

OBE by comment 28

EZ

CI 33 SC 33.3.1 P 80 L 47 # 145
 Schindler, Fred Seen Simply

Comment Type **TR** Comment Status **X** Pres: PD PI

New PD Types will need to accept up to 57V on each pair set. Fix text, The PD shall withstand any voltage from 0 V to 57 V at the PI indefinitely without permanent damage.

SuggestedRemedy
 Replace the Draft text with,
 Type 1 and Type 2 PDs shall withstand any voltage from 0 V to 57 V at the powered pair set indefinitely without permanent damage. Type 3 and Type 4 PDs shall withstand any voltage from 0 V to 57 V on both pair sets indefinitely without permanent damage.

Proposed Response Response Status **W**
 Waiting for Presentation

See comment 189, 5

CI 33 SC 33.3.2 P 81 L 43 # 146
 Schindler, Fred Seen Simply

Comment Type **TR** Comment Status **A**

The Draft text does not support all Type 3 variants. The existing text,

Type 3 and Type 4 PDs operating with a maximum power draw corresponding to Class 4 or greater implement both Multiple-Event Physical Layer classification (see 33.3.5.2) and Data Link Layer classification (see 33.6). Type 3 PDs advertise a class signature of 4, 5, or 6, while Type 4 PDs advertise a class signature of 7 or 8.

SuggestedRemedy
 Replace the Draft sentence with,
 Type 3 and Type 4 PDs operating with a maximum power draw corresponding to Class 4 or greater implement both Multiple-Event Physical Layer classification (see 33.3.5.2) and Data Link Layer classification (see 33.6). Type 3 PDs advertise a class signature of 0 through 6, while Type 4 PDs advertise a class signature of 7 or 8.

Response Response Status **C**
 ACCEPT IN PRINCIPLE.

OBE by comment 35.

Those other variants are covered in text above the cited text.

EZ

IEEE P802.3bt D1.1 4-Pair Power over Ethernet 4th Task Force review comments

Cl 33 SC 33.3.7 P94 L 16 # 147
 Schindler, Fred Seen Simply

Comment Type ER Comment Status A PD Power

The word "guaranteed" means a formal assurance that certain conditions shall be fulfilled. It is used in Table 33-18 item 4 in two places. On page 95, line 52 and on page 96 line 3.

The word was used to differentiate between average power and average power used for extended power that may be exceeded. This word has caused confusion for me and others (see Draft 1.0 #172). For example, a reader of Table 33-18 sees "Input average power, Class 5" min is 40.0 W but the next line says "Input guaranteed available average power, Class 6" min is 51.0 W. Now I am worried that the Class 5 has less commitment to the minimum value than the Class 6 minimum value, which is not the case.

The comment Editor provided this guidance for #172, I believe this word was added as part of the Extended Power work and is needed to distinguish between those classes with extended power and those without.

I believe less confusion will result by striking the word "guaranteed". Table 33-18 already references section 33.3.7.2, which provides the sentence,

If such a PD has additional information and does not cause the PSE to source more than PClass it may exceed the maximum input guaranteed average power.

The change provides the same details. Designers that want to use extended power may uses the exception pointed out in section 33.3.7.2.

SuggestedRemedy

Strike the word "guaranteed" in all Draft locations.

Response Response Status C

ACCEPT IN PRINCIPLE.

OBE by comment 92

Cl 33 SC 33.5.1.1.1 P 118 L 42 # 148
 Schindler, Fred Seen Simply

Comment Type ER Comment Status A Management

Section reference is 33.5.1.1.1a
 The variable deny_dual was deleted, and referencing text should be fixed.

SuggestedRemedy

Strike the Draft referenced text.

33.5.1.1.1a Deny dual-signature PD 4-pair power
 The provision of 4-pair power to dual-signature PDs by physical layer 4-pair ID shall be inhibited by setting bit 11.6 to one. Writing a one to this register bit shall set deny_dual_sig_4pair_power to true, and writing a zero to this register bit shall set deny_dual_sig_4pair_power to false.

Replace Table 33-21 bit(s) 11.6 name column with reserved and description as "Ignore when read", and R/W column as "RO".

Response Response Status C

ACCEPT IN PRINCIPLE.

OBE by comment 271

Cl 33 SC 33.3.7.5 P 98 L 17 # 149
 Schindler, Fred Seen Simply

Comment Type ER Comment Status A PD Power

Draft text,
 "Class 6 or Class 8 PDs, shall operate below the PD extended template defined in Figure 33-18."

may confuse the reader because not context is provided on why the extended template exists.

SuggestedRemedy

Add a period to the sentence on line 19 ending in Figure 33-18. Then add the following sentence after the corrected sentence.

See 33.3.7.2 for details on Class 6 and Class 8 PD allowances.

Response Response Status C

ACCEPT.

EZ

IEEE P802.3bt D1.1 4-Pair Power over Ethernet 4th Task Force review comments

Cl 33 SC 33.3.7.6 P 99 L 48 # 150
 Schindler, Fred Seen Simply

Comment Type TR Comment Status D Pres: Transient

New PD Types need to have their current demands constrained. The text region to be modified is,

A Type 1 PD with input capacitance of 180 µF or less requires no special considerations with regard to transients at the PD PI. A Type 2 PD with peak power draw that does not exceed PClass_PD max and has an input capacitance of 180 µF or less requires no special considerations with regard to transients at the PD PI. PDs that do not meet these requirements shall comply with the following:

— A Type 1 PD input current shall not exceed the PD upperbound template (see Figure 33-18) after TLIM min (see Table 33-11 for a Type 1 PSE) when the following input voltage is applied. A current limited voltage source is applied to the PI through a RCh resistance (see Table 33-1). The current limit meets Equation (33-14) and the voltage ramps from VPort_PSE min to VPort_PSE max at 2250 V/s.

A Type 2 PD shall meet both of the following:

a) The PD input current spike shall not exceed 2.5 A and shall settle below the PD upperbound template (see Figure 33-18) within 4 ms. During this test, the PD PI voltage is driven from 50 V to 52.5 V at greater than 3.5 V/µs, a source impedance of 1.5 Ω, and a source that supports a current greater than 2.5 A.

b) The PD shall not exceed the PD upperbound template beyond TLIM min under worst-case current draw under the following conditions. The input voltage source drives VPD from VPort_PSE min to 56 V at 2250 V/s, the source impedance is RCh (see Table 33-1), and the voltage source limits the current to MDI ILIM per Equation (33-14).

Suggested Remedy

Replace referenced Draft text starting on line 48 with,

A Type 1 PD with input capacitance of 180 µF or less requires no special considerations with regard to transients at the PD PI. Type 2, Type 3, and Type 4 PDs, with peak power draw that does not exceed PClass_PD max and has an input capacitance of 180 µF or less requires no special considerations with regard to transients at the PD PI. PDs that do not meet these requirements shall comply with the following:

- The input current for Type 1 and Type 3 PDs consuming less than class-4 power levels, shall not exceed the PD upperbound template (see Figure 33-18) after TLIM min (see Table 33-11 for Type 1 and Type 3 PSEs) when the following input voltage is applied. A current limited voltage source is applied to the PI through a RCh resistance (see Table 33-1). The current limit meets Equation (33-14) and the voltage ramps from VPort_PSE min to

VPort_PSE max at 2250 V/s.

A Type 2, Type 3 PDs consuming more than class-4 power levels, and Type 4 PDs, shall meet both of the following:

a) The PD input current spike shall not exceed 2.5 A and shall settle below the PD upperbound template (see Figure 33-18) within 4 ms. During this test, the PD PI voltage is driven from 50 V to 52.5 V at greater than 3.5 V/µs, a source impedance of 1.5 [ohms], and a source that supports a current greater than 2.5 A.

b) The PD shall not exceed the PD upperbound template beyond TLIM min under worst-case current draw under the following conditions. The input voltage source drives VPD from VPort_PSE min to 56 V at 2250 V/s, the source impedance is RCh (see Table 33-1), and the voltage source limits the current to MDI ILIM per Equation (33-14).

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Replace referenced Draft text starting on line 48 with,

A Type 1 PD with input capacitance of 180 µF or less requires no special considerations with regard to transients at the PD PI. Type 2, Type 3, and Type 4 PDs, with peak power draw that does not exceed Pclass_PD max and has an input capacitance of 180 µF (TBD) or less requires no special considerations with regard to transients at the PD PI. PDs that do not meet these requirements shall comply with the following:

- The input current for Type 1 and Type 3 PDs consuming less than class-4 power levels, shall not exceed the PD upperbound template (see Figure 33-18) after TLIM min (see Table 33-11 for Type 1 and Type 3 PSEs) when the following input voltage is applied. A current limited voltage source is applied to the PI through a RCh resistance (see Table 33-1). The current limit meets Equation (33-14) and the voltage ramps from Vport_PSE min to Vport_PSE max at 2250 V/s.

Type 3 PDs consuming more than class-4 power levels, and Type 4 PDs, shall meet both of the following:

a) The PD input current spike shall not exceed 2.5 A and shall settle below the PD upperbound template (see Figure 33-18) within 4 ms. During this test, the PD PI voltage is driven from 50 V to 52.5 V at greater than 3.5 V/µs, a source impedance of 1.5 [ohms], and a source that supports a current greater than 2.5 A.

B) The PD shall not exceed the PD upperbound template beyond TLIM min under worst-case current draw under the following conditions. The input voltage source drives VPD from Vport_PSE min to 56 V at 2250 V/s, the source impedance is RCh (see Table 33-1), and the voltage source limits the current to MDI ILIM per Equation (33-14).

IEEE P802.3bt D1.1 4-Pair Power over Ethernet 4th Task Force review comments

Cl 33 SC 33.3.8 P 102 L 31 # 151
Schindler, Fred Seen Simply

Comment Type ER Comment Status A Editorial

The legacy table 33-19 had Iport_MPS removed and then added to Table 33-19a. The note below Table 33-19 references the current moved to Table 33-19a.

SuggestedRemedy

Either combine Table 33-19 and 33-19a to create Table 33-19 or move the note, NOTE—A Type 1 or 2 PD with Cport > 180 μF or a Type 3 PD with Cport > TBD uF PDs may not be able to meet the IPort_MPS specification in Table 33-19 during the maximum allowed port voltage droop (VPort_PSE max to VPort_PSE min with series resistance RCh). Such a PD should increase its IPort min or make other such provisions to meet the Maintain Power Signature.

If the note is moved, correct the Table reference "Table 33-19" to "Table 33-19a".

Response Response Status C

ACCEPT IN PRINCIPLE.

Move note to below Table 33-19a and change reference to "-19a" in the note.

EZ

Cl 33 SC 33.4.1 P 104 L 13 # 152
Schindler, Fred Seen Simply

Comment Type TR Comment Status A References

Several changes were made to reference the latest IEC 62368-1 rather than IEC 60950-1 (without date). Now the standard refers to both standards. The IEC 62368-1 supersedes the old specification.

I do not know whether the sections referenced have changed. However, if they have, then it is not clear which standard the IEEE is referencing to meet the IEEE requirements. If the reference sections have not changed then the older specification is satisfactory.

SuggestedRemedy

The Task Force should review the new specification to determine if changes have been made to the IEEE referenced sections. If these sections have changed then the group should review whether the changes are acceptable for the .3BT specification. If they are then strike "IEC 60950-1 and" from the Draft.

If the IEC specifications are the same the group should decide whether referencing the new standard is necessary. More legacy IEC specifications exist than new ones. Therefore, I would prefer that the Draft strike "and IEC 62368-1".

Response Response Status C

ACCEPT IN PRINCIPLE.

Fred to check for changes in the specs and resubmit comment against D1.2.

No changes from accepting this comment.

IEEE P802.3bt D1.1 4-Pair Power over Ethernet 4th Task Force review comments

Cl 33 SC 33.3.7.3 P 96 L 46 # 153
Schindler, Fred Seen Simply

Comment Type ER Comment Status D Pres: Inrush

The PD inrush requirements are dependent on PSE operations that are not disclosed in the PD section.

SuggestedRemedy

Add the following note above the existing note on line 46.

NOTE-PDs may be subjected to PSE POWER_ON current limits during inrush when the PD input voltages reaches 99% of steady state or when PSE time Tinrush expires. See 33.2.7.4 for PSE details.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Add the following note above the existing note on line 46.

NOTE-PDs may be subjected to PSE POWER_ON current limits during inrush when the PD input voltages reaches 99% of steady state or when PSE time Tinrush expires. See 33.2.7.4 for details.

Cl 33 SC 33.5.1.1.4 P 119 L 36 # 154
Schindler, Fred Seen Simply

Comment Type TR Comment Status A Management

The text,
"Setting bits 11.3:2 to '11' shall allow the PSE to use both PSE Pinout Alternative A and PSE Pinout Alternative B simultaneously."
is implementation specific. Some PSE will not power Alternatives simultaneously.

SuggestedRemedy

Strike the text "simultaneously" in the referenced sentence.

Then replace Table 33-21 11.3:2 Description, reference 11, which is "Reserved" with, "PSE pinout Alternative A and Alternative B."

Response Response Status C

ACCEPT.

Cl 33 SC 33.5.1.2 P 120 L 11 # 155
Schindler, Fred Seen Simply

Comment Type TR Comment Status A Management

Table 33-22 does not cover all required options for new Types.
I have run out of time to provide a complete solution.

SuggestedRemedy

Add Editor's Note: Table 33-22 requires new fields to support new Types and features.
Reviewers are encouraged to provide the required definitions.

Alternatively, have the Task Force provide the definitions.

Response Response Status C

ACCEPT.

Add Editor's note suggested.

IEEE P802.3bt D1.1 4-Pair Power over Ethernet 4th Task Force review comments

Cl 33 SC 33.3.4 P 86 L 54 # 156
 Schindler, Fred Seen Simply

Comment Type TR Comment Status A 4PID

The existing sentence,
 "When a Type 1 or Type 2 PD becomes powered via the PI, it shall present a non-valid detection signature on the set of pairs from which it is not drawing power. A Type 3 or Type 4 dual-signature PD shall present a valid detection signature on the unpowered pair in order to receive 4-pair power from Type 3 and Type 4 PSEs. Any PD may indicate the ability to accept power on both pair sets using LLDP variable 4P-ID in Table 79-6b or TBD."

Does not complete address all PD Types and some text may confuse the reader.

SuggestedRemedy

Replace the sentence with,
 "When a Type 1 or Type 2 PD or Type 3 or Type 4 Single Signature PD becomes powered via the PI, it shall present a non-valid detection signature on the set of pairs from which it is not drawing power. A Type 3 or Type 4 dual-signature PD shall present a valid detection signature on the unpowered pair. Any PD may indicate the ability to accept power on both pair sets using LLDP variable 4P-ID in Table 79-6b or TBD."

Alternatively this better option could be used,
 "When a Type 1 or Type 2 PD or Type 3 or Type 4 Single Signature PD becomes powered via the PI, it shall present a non-valid detection signature on the set of pairs from which it is not drawing power. A Type 1 or Type 2 PD, or Type 3 or Type 4 dual-signature PD shall present a valid detection signature on the unpowered pair. Any PD may indicate the ability to accept power on both pair sets using LLDP variable 4P-ID in Table 79-6b or TBD."

Response Response Status C

ACCEPT IN PRINCIPLE.

Looking for better language, but the following text seems to be technically correct.

Replace the sentence with,

"A Type 1, Type 2, or single-signature Type 3 or Type 4 PD that is powered over only one pairset shall present a non-valid detection signature on the unpowered pairset. A dual-signature Type 3 or Type 4 PD that is powered over only one pairset shall present a valid detection signature on the unpowered pairset."

Make: "Any PD may indicate the ability to accept power on both pairsets using LLDP variable 4P-ID in Table 79-6b or TBD."
 a new paragraph.

Cl 33 SC 33.3.4 P 87 L 4 # 157
 Schindler, Fred Seen Simply

Comment Type ER Comment Status A Editorial

Fix typo "variable 4P-ID"

SuggestedRemedy

Replace with "variable PD 4P-ID".

Response Response Status C

ACCEPT.

EZ

Cl 33 SC 33.3.8 P 102 L 41 # 158
 Balasubramanian, Koussalya self

Comment Type E Comment Status A Editorial

The note below Table 33-19 referencing lport_mps doesnt belong there as Table 33-19 doesnt contain lport_mps any more.

SuggestedRemedy

Move the note below Table 33-19a

Response Response Status C

ACCEPT IN PRINCIPLE.

OBE by comment 151.

EZ

IEEE P802.3bt D1.1 4-Pair Power over Ethernet 4th Task Force review comments

Cl 33 SC 33.1.1 P L # 159
Balasubramanian, Koussalya self

Comment Type ER Comment Status A Editorial

The last statement "and derating of the cabling maximum ambient operating temperature" when read along with the full sentence, doesnt imply clearly that this applies to both Type 2 and 3.

SuggestedRemedy

Make the last statement "derating..." separate sentence and include type 3 and 2 to be clear.

New statement should read "... class D or better cabling. A derating of the cabling maximum ambient operating temperature is needed for both Type 2 and Type 3 operation".

Response Response Status C

ACCEPT.

EZ

Cl 33 SC 33.1.4.1 P 23 L 15 # 160
Balasubramanian, Koussalya self

Comment Type ER Comment Status A Cabling

The statement "...with the additional requirement that channel DC loop resistance shall be 25ohms or less" when read along with full sentence is not clear that it applies to both Type 2 and Type 3.

SuggestedRemedy

Make "with the additional requirement that channel DC loop resistance shall be 25Ohms or less" into a separate sentence and add Type 2 and Type 3 explicitly. The new sentence would be - "The additional requirement that channel DC loop resistance shall be 25Ohms or less shall be met for Type 2 and Type 3 operation".

Response Response Status C

ACCEPT IN PRINCIPLE.

OBE by comment # 126.

Cl 33 SC 33.1.4.1 P 23 L 24 # 161
Balasubramanian, Koussalya self

Comment Type ER Comment Status A Cabling

Type 4 details are missing.

SuggestedRemedy

Add an editor's note to include Type 4 details.

Response Response Status C

ACCEPT IN PRINCIPLE.

OBE by comment 70

Cl 33 SC 33.2.3 P 32 L 10 # 162
Balasubramanian, Koussalya self

Comment Type T Comment Status A Editorial

Column 4 title of Table 33-2 is not in sync with Table 33-2a

SuggestedRemedy

Change title of 4th column in Table 33-2 to Alternative B(S) to be in sync with Table 33-2a

Response Response Status C

ACCEPT.

EZ

Cl 33 SC 33.2.4.6 P 43 L 8 # 163
Balasubramanian, Koussalya self

Comment Type TR Comment Status R Editorial

New variables Type_sub_PSE and Type_sub_PD are used without definition.

SuggestedRemedy

Define new variables Type_sub_PSE and Type_sub_PD.

Response Response Status C

REJECT.

The definition is contained within the sentence.

IEEE P802.3bt D1.1 4-Pair Power over Ethernet 4th Task Force review comments

Cl 33 **SC 33.3.7.4** **P 97** **L 45** # **164**
 Balasubramanian, Koussalya self
Comment Type **TR** **Comment Status** **A** *PD Power*
 Comment #370 on D1.0 changes original text which uses Equation 33-12 only for Class 4 to class 0 through 4. I believe this is not the intention.
SuggestedRemedy
 Go back to original text.
Response **Response Status** **C**
 ACCEPT IN PRINCIPLE.
 Remove "0 through" from line 45.
 EZ

Cl 33 **SC 33.2.4.7** **P 51** **L 2** # **165**
 Balasubramanian, Koussalya self
Comment Type **TR** **Comment Status** **A** *PSE SD*
 Figure 33-9g starts with off page connectors A, A1 etc., - which are not defined. We moved this figure over and called it Type 3 and 4 Class state diagram.
SuggestedRemedy
 Connections A, A1 need to be defined for Figure 33-9g.
Response **Response Status** **C**
 ACCEPT IN PRINCIPLE.
 State Diagram is being continually updated. This needs to be addressed to match the latest version.
 No changes to the text at this point. State diagram work to continue.

Cl 00 **SC 0** **P** **L** # **166**
 Walker, Dylan Cisco
Comment Type **E** **Comment Status** **A** *Editorial*
 Can we please reconsider the use of "pair set"?
SuggestedRemedy
 Replace all instances of "pair set" with "pairset" or "pair-set", whichever the TF prefers.
Response **Response Status** **C**
 ACCEPT IN PRINCIPLE.
 The task force would like to use "pairset".
 EZ

Cl 33 **SC 33** **P 19** **L 1** # **167**
 Walker, Dylan Cisco
Comment Type **ER** **Comment Status** **A** *Editorial*
 Section header wound up with "Autoclass" inserted within "Dependent" somehow.
 "33. Data Terminal Equipment (DTE) Power via Media DepAutoclassendent Interface (MDI)"
SuggestedRemedy
 Replace with "33. Data Terminal Equipment (DTE) Power via Media Dependent Interface (MDI)"
Response **Response Status** **C**
 ACCEPT.
 EZ

IEEE P802.3bt D1.1 4-Pair Power over Ethernet 4th Task Force review comments

Cl 33 SC 33.1.1 P 20 L 5 # 168
Walker, Dylan Cisco

Comment Type ER Comment Status A Editorial

This sentence is a bit confusing.

"Type 2 operation requires ISO/IEC 11801:1995 Class D or better cabling, and Type 3 operation requires ISO/IEC 11801:2002 Class D or better cabling, and a derating of the cabling maximum ambient operating temperature."

SuggestedRemedy

To keep the legacy Type 2 requirement clear, separate into 2 sentences.

"Type 2 operation requires ISO/IEC 11801:1995 Class D or better cabling and a derating of the cabling maximum ambient operating temperature. Type 3 operation requires ISO/IEC 11801:2002 Class D or better cabling and a derating of the cabling maximum ambient operating temperature."

Response Response Status C

ACCEPT IN PRINCIPLE.

OBE by comment # 159.

Cl 33 SC 33.1.3 P 21 L 45 # 169
Walker, Dylan Cisco

Comment Type E Comment Status A Editorial

There is a change bar that I cannot trace back to 2012.

SuggestedRemedy

Since there were missing change bars in D1.0, would like to ask the editor to double-check if this is an isolated anomaly.

Response Response Status C

ACCEPT.

It may be because we inserted something after this sentence.

EZ

Cl 33 SC 33.1.4 P 22 L 27 # 170
Walker, Dylan Cisco

Comment Type TR Comment Status A Cabling

In Table 33-1, we specify the Minimum Cabling Type for Type 2 to be Class D (ISO/IEC 11801:2002), but we specify ISO/IEC 11801:1995 in Section 33.1.1 and Section 33.1.4.1, in alignment with legacy text.

SuggestedRemedy

Update Table 33-1 to reflect Class D (ISO/IEC 11801:1995) for Type 2.

Response Response Status C

ACCEPT.

EZ

Cl 33 SC 33.2.2 P 25 L 40 # 171
Walker, Dylan Cisco

Comment Type E Comment Status A Editorial

Misplaced comma in "A Midspan PSE that results in a link that can support 1000BASE-T, and 10GBASE-T operation and optionally support 10BASE-T and 100BASE-TX operation (see Figure 33-7)."

SuggestedRemedy

Replace with "A Midspan PSE that results in a link that can support 1000BASE-T and 10GBASE-T operation, and optionally support 10BASE-T and 100BASE-TX operation (see Figure 33-7)."

Response Response Status C

ACCEPT.

EZ

IEEE P802.3bt D1.1 4-Pair Power over Ethernet 4th Task Force review comments

Cl 33 SC 33.2.2 P 28 L 17 # 172
Walker, Dylan Cisco

Comment Type ER Comment Status A Editorial

"Figure 33-5a-10BASE-T/100BASE-TX Alternative A and Alternative B Endpoint PSE location overview"

In every other figure, we've used "4-Pair" in the title instead of "Alternative A and Alternative B."

SuggestedRemedy

Rename Figure 33-5a:

"Figure 33-5a-10BASE-T/100BASE-TX 4-Pair Endpoint PSE location overview"

Response Response Status C

ACCEPT IN PRINCIPLE.

OBE by comment # 250.

Cl 33 SC 33.2.3 P 32 L 12 # 173
Walker, Dylan Cisco

Comment Type ER Comment Status A Editorial

Table 33-2 "Alternative B" column header does not match Table 33-2a.

SuggestedRemedy

Update Table 33-2 "Alternative B" column to "Alternative B(S)".

Response Response Status C

ACCEPT IN PRINCIPLE.

OBE by comment 162.

EZ

Cl 33 SC 33.2.4.4 P 34 L 40 # 174
Walker, Dylan Cisco

Comment Type TR Comment Status A

Values for variable "PD_signature" do not match the values shown within the do_connection_check function (see page 41, line 14) where the variable is assigned.

SuggestedRemedy

Change the value "Invalid" to "Open_circuit" as follows:

"Open_Circuit: Open circuit detected on both pairsets."

Also, modify the value "Single" to be the default case and applicable to PDs that operate over a single pairset:

"Single: Either connection check has not been performed or a single-signature PD configuration is connected through one or both of the two pairsets at the PI."

Corresponding comment entered against the variable values within the function flagged with DW1

Response Response Status C

ACCEPT IN PRINCIPLE.

Do not implement suggested remedy.

Remove "PD_Signature" from variable section since it is in the Functions section under "do_connection_check".

IEEE P802.3bt D1.1 4-Pair Power over Ethernet 4th Task Force review comments

CI 33 SC 33.2.4.6 P 41 L 17 # 175
Walker, Dylan Cisco

Comment Type **TR** Comment Status **D** PSE SD

Values for variable "PD_signature" within the do_connection_check function do not match the values shown in Section 33.2.4.4 (see page 34, line 40).

SuggestedRemedy

Delete the "Invalid" value.

Change the value "Open_circuit" as follows:

"Open_Circuit: Open circuit detected on both pairsets."

Modify the value "Single" to be the default case and applicable to PDs that operate over a single pairset:

"Single: Either connection check has not been performed or a single-signature PD configuration is connected through one or both of the two pairsets at the PI."

Corresponding comment entered against the variable values flagged with DW1

Proposed Response Response Status **W**

PROPOSED ACCEPT IN PRINCIPLE.

OBE by comment # 7.

CI 33 SC 33.2.4.3 P 34 L 29 # 176
Walker, Dylan Cisco

Comment Type **TR** Comment Status **X** Pres: PSE SD

To allow for PSEs that perform connection check before, during, between, or after detection, a new constant is needed to define the disparate pathways these PSEs take through the state diagram and their associated timing requirements.

SuggestedRemedy

Add constant "PSE_CC_DET_SEQ" as follows:

PSE_CC_DET_SEQ

A constant indicating the sequence in which the PSE performs connection check and detection.

Values: 1: Connection check and detection performed simultaneously

2: Connection check performed prior to detection

3: Connection check performed between detections

4: Connection check performed after detection

Proposed Response Response Status **W**

Wait for presentation.

CI 33 SC 33.2.5.0a P 53 L 12 # 177
Walker, Dylan Cisco

Comment Type **ER** Comment Status **A** Connection Check

In Section 33.2.5 (page 52, line 50), the following is stated: "In the following subclauses, the link is not called out to preserve clarity."

SuggestedRemedy

Replace:

"In addition, only tests that result in a voltage at the PSE PI that is below Vvalid(max) as specified in Table 33-4 shall be used to determine whether a single-signature or dual-signature is attached to the two pair sets in the link section."

With:

"In addition, only tests that result in a voltage at the PSE PI that is below Vvalid(max) as specified in Table 33-4 shall be used to determine whether a single-signature or dual-signature is attached to the two pair sets."

Response Response Status **C**

ACCEPT.

EZ

CI 33 SC 33.2.5.0a P 53 L 34 # 178
Walker, Dylan Cisco

Comment Type **TR** Comment Status **X** Pres: PSE SD

In Table 33-3a, under Additional Information for Item 2, it's stated that "Applies only when connected to a single-signature PD."

This may not be true if we allow connection check to occur between the 2 detections and don't want to create new timing parameters.

SuggestedRemedy

Presentation forthcoming to cover this and other aspects of connection check.

Proposed Response Response Status **W**

Wait for presentation

IEEE P802.3bt D1.1 4-Pair Power over Ethernet 4th Task Force review comments

Cl 33 SC 33.2.5.3 P 55 L 52 # 179
Walker, Dylan Cisco

Comment Type ER Comment Status A Editorial

This sentence still doesn't read well. We don't need to mention the link since section 33.2.5 (see page 52, line 50) states it won't be for clarity.

SuggestedRemedy

Replace:

"In the presence of an offset voltage up to Vos max and an offset current up to los max as specified in Table 33-5, a PSE shall accept as a valid PD detection signature a pair set within a link section with both of the following characteristics:"

With:

"In the presence of an offset voltage up to Vos max and an offset current up to los max (as specified in Table 33-5), a PSE shall deem a PD detection signature valid on a pairset with both of the following characteristics:"

Response Response Status C

ACCEPT IN PRINCIPLE.

OBE by comment # 3.

Cl 33 SC 33.2.6 P 57 L 37 # 180
Walker, Dylan Cisco

Comment Type ER Comment Status A Editorial

Move the DLL acronym to directly after the full name.

SuggestedRemedy

Replace:

"There are two forms of classification: Physical Layer classification and Data Link Layer classification (DLL)."

With:

"There are two forms of classification: Physical Layer classification and Data Link Layer (DLL) classification."

Response Response Status C

ACCEPT.

EZ

Cl 33 SC 33.2.6 P 60 L 20 # 181
Walker, Dylan Cisco

Comment Type ER Comment Status A PSE Power

"A PSE may choose not to power dual-signature PDs."

This is redundant. A PSE can deny power for any reason irrespective of PD architecture.

SuggestedRemedy

Remove it.

Response Response Status C

ACCEPT.

Cl 33 SC 33.2.6.2 P 62 L 21 # 182
Walker, Dylan Cisco

Comment Type ER Comment Status A PSE classification

Misspelling.

SuggestedRemedy

Replace:

"When connected to a single-signature PD, a PSE shall classify the PD only once or both of the pairsets."

With:

"When connected to a single-signature PD, a PSE shall classify the PD only once on both of the pairsets."

Response Response Status C

ACCEPT IN PRINCIPLE.

OBE by comment 109.

IEEE P802.3bt D1.1 4-Pair Power over Ethernet 4th Task Force review comments

CI 33 SC 33.2.7 P 68 L 46 # 183
 Walker, Dylan Cisco
 Comment Type T Comment Status D PSE MPS
 Table 33-11, Item 17b, Max column
 After rounding, the DC MPS max for the sum is not double the per pairset max of 0.005A, which looks a little strange.
 SuggestedRemedy
 Change 0.009 to 0.010.
 Proposed Response Response Status Z
 REJECT.
 This comment was WITHDRAWN by the commenter.
 The 9mA was chosen to add margin to the PD that only has to source 10mA.

CI 33 SC 33.2.7.4 P 71 L 45 # 184
 Walker, Dylan Cisco
 Comment Type ER Comment Status A Editorial
 K is not italicized.
 SuggestedRemedy
 Italicize K to match the other variable names.
 Response Response Status C
 ACCEPT.
 EZ

CI 33 SC 33.2.7.4a P 72 L 7 # 185
 Walker, Dylan Cisco
 Comment Type ER Comment Status A Editorial
 33.2.7.4a section heading has a duplicate "pair-to-pair" randomly inserted.
 SuggestedRemedy
 Replace:
 "33.2.7.4a PSE PI Pair-to-Ppair-to-pairair resistance and current unbalance"
 With:
 "33.2.7.4a PSE PI Pair-to-Pair resistance and current unbalance"
 Response Response Status C
 ACCEPT IN PRINCIPLE.
 OBE by comment 232
 EZ

CI 33 SC 33.2.7.7 P 74 L 16 # 186
 Walker, Dylan Cisco
 Comment Type ER Comment Status A Editorial
 Misspelling.
 SuggestedRemedy
 Replace:
 "Power shall be removed from a pai set of a PSE before the pair set current exceeds the "PSE upperbound template" in Figure 33-14."
 With:
 "Power shall be removed from a pairset of a PSE before the pair set current exceeds the "PSE upperbound template" in Figure 33-14."
 Response Response Status C
 ACCEPT IN PRINCIPLE.
 OBE by comment 28
 EZ

IEEE P802.3bt D1.1 4-Pair Power over Ethernet 4th Task Force review comments

Cl 33 SC 33.2.9.1.2 P 78 L 23 # 187
Walker, Dylan Cisco

Comment Type **TR** Comment Status **A** PSE MPS

The following sentence is redundant and should be removed according to the Editor's Note on page 66, line 9.

"The PSE may remove power from both pair sets if the DC MPS has been absent for duration greater than TMPDO on either pair set."

SuggestedRemedy

Delete the sentence.

Response Response Status **C**

ACCEPT.

Cl 33 SC 33.2.9.1.2 P 78 L 32 # 188
Walker, Dylan Cisco

Comment Type **ER** Comment Status **A** Editorial

Table 33-12 pertains to AC MPS, not DC MPS.

SuggestedRemedy

Relocate Table 33-12 to within Section 33.2.9.1.1.

Response Response Status **C**

ACCEPT.

EZ

Cl 33 SC 33.3.1 P 80 L 47 # 189
Walker, Dylan Cisco

Comment Type **TR** Comment Status **X** Pres: PD PI

The following sentence is ambiguous:

"The PD shall withstand any voltage from 0 V to 57 V at the PI indefinitely without permanent damage."

SuggestedRemedy

Presentation forthcoming.

Proposed Response Response Status **W**

Waiting for Presentation

See comment 5, 145

Cl 33 SC 33.2.5 P 52 L 46 # 190
Walker, Dylan Cisco

Comment Type **TR** Comment Status **A** PSE Power

If a PSE and a single-signature PD agree to transition from 4-pair to 2-pair power via LLDP, they should be allowed to transition back to 4-pair power - again via LLDP - without redetecting as long as the other pairset has not been powered down in the interim.

SuggestedRemedy

After:

"In any operational state, the PSE shall not apply operating power to a pair set until the PSE has successfully detected a valid signature over that pair set."

Insert:

"If a PSE and single-signature PD have agreed to transition from 4-pair power to 2-pair power over LLDP, 4-pair power may subsequently be resumed via negotiation over LLDP without another detection as long as power has not been removed from the other pairset in the interim."

Response Response Status **C**

ACCEPT IN PRINCIPLE.

(1)Keep the original sentence:

"In any operational state, the PSE shall not apply operating power to a pairset until the PSE has successfully detected a valid signature over that pairset."

(2)Add to end of section 33.2.7.1 (page 70, line 52):

"A Type 3 or Type 4 PSE that is connected to a class 0-4 single-signature PD and in the POWER_ON state may transition between 2-pair and 4-pair power at any time, including after the expiration of Tpon."

IEEE P802.3bt D1.1 4-Pair Power over Ethernet 4th Task Force review comments

CI 33 SC 33.3.6 P 93 L 5 # 191
Walker, Dylan Cisco

Comment Type ER Comment Status A PD Classification

The following sentence seems to imply that "pse_power_level" must be set to 2, 3, or 4, but it can remain at its default value of 1.

SuggestedRemedy
Change:

"After a successful Multiple-Event Physical Layer classification or Data Link Layer classification has completed, the pse_power_level is set to either 2, 3 or 4."

To:

"After a successful Multiple-Event Physical Layer classification or Data Link Layer classification has completed, the pse_power_level may be set to either 2, 3, or 4."

Response Response Status C
ACCEPT IN PRINCIPLE.

"After a successful Multiple-Event Physical Layer classification has completed the pse_power_level is set to either 2, 3, or 4."

After a successful Data Link Layer classification has completed the pse_power_level is set to either 1, 2, 3 or 4."

CI 33 SC 33.5.1.1 P 118 L 10 # 192
Walker, Dylan Cisco

Comment Type TR Comment Status A Management

Table 33-21.

Bit 11.6 "Deny dual-signature PD 4-pair Power" doesn't need to exist since a PSE can deny power for any reason, irrespective of PD architecture.

SuggestedRemedy
Delete the row for bit 11.6 in Table 33-21, move bit 6 back into the Reserved range, and delete Section 33.5.1.1.1a, which describes "Deny dual-signature PD 4-pair Power".

Response Response Status C
ACCEPT IN PRINCIPLE.

OBE by comment # 271.

CI 33 SC 33.5.1.1 P 118 L 19 # 193
Walker, Dylan Cisco

Comment Type TR Comment Status A Management

Table 33-21.

The value of "11" for bits 11.3:2 has not been updated to reflect PSE support for both Alternative A and Alternative B.

SuggestedRemedy
Under Description for bits 11.3:2:

Replace: "1 1 = Reserved"

With: "1 1 = PSE pinout Alternative A and B"

Response Response Status C
ACCEPT.

EZ

CI 33 SC 33.5.1.1 P 118 L 24 # 194
Walker, Dylan Cisco

Comment Type TR Comment Status A Management

Table 33-21, bits 11.1:0, value "10 = Force Power Test Mode"

There aren't enough encodings to specify pairset specific Force Power Test Modes, which are of value.

SuggestedRemedy
Allocate 2 of the reserved bits to create a "Force Power Test Mode Pairset Selection" field, where:

11 = Both Alternative A and Alternative B powered when Force Power Test Mode enabled
10 = Alternative B powered when Force Power Test Mode enabled
01 = Alternative A powered when Force Power Test Mode enabled
00 = Reserved

Response Response Status C
ACCEPT IN PRINCIPLE.

Implement suggested remedy using bits 7:6

IEEE P802.3bt D1.1 4-Pair Power over Ethernet 4th Task Force review comments

Cl 33 SC 33.5.1.1.4 P 119 L 40 # 195
Walker, Dylan Cisco

Comment Type ER Comment Status A Management

Grammar. Also, "will never be assigned" was proven false by this Task Force for value "11", so suggest deleting it.

SuggestedRemedy

Change:

"The combinations '00' for bits 11.3:2 are reserved and will never be assigned."

To:

"The combination '00' for bits 11.3:2 is reserved."

Response Response Status C

ACCEPT.

EZ

Cl 33A SC 33A.3 P 153 L 11 # 196
Walker, Dylan Cisco

Comment Type ER Comment Status A Editorial

"33A.3 Inter Pair Resistance Unbalance"

This section describes resistance unbalance within a twisted pair, not between twisted pairs.

SuggestedRemedy

"33A.3 Intra Pair Resistance Unbalance"

Response Response Status C

ACCEPT IN PRINCIPLE.

OBE by comment 119.

Cl 00 SC P L # 197
Dwellely, David Linear Technology

Comment Type TR Comment Status D PD Power

Resubmitted comment from D1.0:

Table 33-18: Several symbols have -2p added to them. This breaks continuity with AF/AT - an AT device that claims to meet Vport_pd will not find a spec with that name anymore. New titles with "per pair set" can stay, as all valid AF/AT devices operated over a single pairset.

SuggestedRemedy

Remove -2p suffixes from Table 33-18, Items 1-3

Proposed Response Response Status Z

REJECT.

This comment was WITHDRAWN by the commenter.

I would like to hear the group's opinion on this.

Straw Poll:

Would you be willing to remove "-2p" from the af/at parameters that Dave shows makes no technical changes when removed?

Y: 10 N: 2

Cl 1 SC 1.4 P 18 L 17 # 198
Dwellely, David Linear Technology

Comment Type ER Comment Status A

I'm still not comfortable with "pair set". "Pair" and "set" are commonly used in the 802.3 standard, and combining them this way is non-unique and subject to search-and-replace errors. The original motion in September 2014 called out "pair-set", but that isn't much better. I prefer the term "pairset" - it's a new, unique word and isn't likely to be mistaken for something else. A search of 802.3-2012 finds zero instances of "pairset".

SuggestedRemedy

Change "pair set" to "pairset" throughout the draft.

Response Response Status C

ACCEPT IN PRINCIPLE.

OBE by comment # 166.

EZ

IEEE P802.3bt D1.1 4-Pair Power over Ethernet 4th Task Force review comments

CI 33 SC 33.1.4 P 22 L 34 # 199
 Dwelley, David Linear Technology

Comment Type T Comment Status A Cabling

Table 33-1 note 1: See Section 33.1.4.2. See informative annex 33A for channel pair-to-pair resistance unbalance.

Channel unbalance is important but doesn't belong in this note - this note covers Cabling Type, not cabling parameters. Section 33.1.4.1 (Cabling requirements) does belong in this note.

SuggestedRemedy

Change note 1 to: See Sections 33.1.4.1 and 33.1.4.2.

Response Response Status C

ACCEPT.

CI 33 SC 33.1.4 P 22 L 35 # 200
 Dwelley, David Linear Technology

Comment Type T Comment Status A Cabling

Table 33-1 Note 2: "In Type 3 and Type 4 operation, the current per pair set might be impacted by pair-to-pair system resistance unbalance. See details in 33-11 item 4a"

"might" isn't strong enough, and the reference is too narrow

SuggestedRemedy

Change Note 2 to: "In Type 3 and Type 4 operation, the current per pair set will be impacted by pair-to-pair system resistance unbalance. See Section 33.2.7.4a." (fix reference when finalized)

Response Response Status C

ACCEPT.

CI 33 SC 33.2 P 25 L 4 # 201
 Dwelley, David Linear Technology

Comment Type T Comment Status A Editorial

Note 3: "1-Event Classification of Type 3 is different from Type 1. Please refer to Table 33-10 items 11, 12 and Section 33.2.6.1 for details."

Marginal grammar, and Section 33.2.6.1, while covering 1-event classification, doesn't make any mention of the differences between Types 1 and 3

SuggestedRemedy

Change Note 3 to: "1-Event Classification differs between Types. Please refer to Table 33-10 items 11 and 12 for details."

...or add explanatory text to Section 33.2.6.1.

Response Response Status C

ACCEPT IN PRINCIPLE.

Change Note 3 to: "1-Event Classification differs between Types. Please refer to Table 33-10 items 11 and 12 for details."

CI 33 SC 33.2.4.1 P 33 L 41 # 202
 Dwelley, David Linear Technology

Comment Type T Comment Status A Editorial

"If power is to be applied, the PSE turns on power after a valid detection in less than Tpon as specified in Table 33-11. If the PSE cannot supply power within Tpon, it initiates and successfully completes a new detection cycle before applying power."

Missing "shalls" - both of these behaviors are mandatory.

SuggestedRemedy

Change sentences to: "If power is to be applied, the PSE shall turn on power after a valid detection in less than Tpon as specified in Table 33-11. If the PSE cannot supply power within Tpon, it shall initiate and successfully complete a new detection cycle before applying power."

Response Response Status C

ACCEPT IN PRINCIPLE.

Do not implement suggested remedy. The shalls are implied in PICS PSE4, but we shouldn't change them as we will change Type 1/2 PICs.

No changes to the text result from this comment.

IEEE P802.3bt D1.1 4-Pair Power over Ethernet 4th Task Force review comments

CI 33 SC 33.2.4.1 P 33 L 43 # 203
 Dwelley, David Linear Technology
 Comment Type E Comment Status A Editorial
 "See section 33.2.7.12 for complete details."
 Details in 33.2.7.12 are not anywhere near complete on this subject
 SuggestedRemedy
 Remove "complete"
 Response Response Status C
 ACCEPT.
 EZ

CI 33 SC 33.2.4.1 P 34 L 1 # 204
 Dwelley, David Linear Technology
 Comment Type E Comment Status A Editorial
 "If a PSE performing detection using Alternative B detects an open circuit (see 33.2.5.5) on the link section, then that PSE may optionally omit the detection backoff."
 33.2.5.5 repeats this text almost identically and refers to table 33-4, which is a broken link.
 SuggestedRemedy
 Change reference to: "(see Table 33-6)". Delete section 33.2.5.5 entirely.
 Alternately, fix section 33.2.5.5 (including correcting link to point to Table 33-6).
 Note: this is an old error from AT and may need to be submitted as a maintenance request
 Response Response Status C
 ACCEPT IN PRINCIPLE.
 Do no implement suggested remedy.
 In Section 33.2.5.5 Change "Table 33-4" to "Table 33-6".
 On page 34, line 1: Change sentence to:
 "If a PSE performs detection using Alternative B see 33.2.5.5."

CI 33 SC 33.2.4.1 P 34 L 1 # 205
 Dwelley, David Linear Technology
 Comment Type T Comment Status A Editorial
 If a PSE performing detection using Alternative B detects an open circuit (see 33.2.5.5) on the link section, then..."
 Link section is old AT language - the new BT term "pair set" is better
 SuggestedRemedy
 Change "link section" to "pair set"
 Response Response Status C
 ACCEPT IN PRINCIPLE.
 Change "link section to "pairset".
 EZ

CI 33 SC 33.2.5 P 52 L 50 # 206
 Dwelley, David Linear Technology
 Comment Type T Comment Status A PSE Detection
 "The PSE PI is connected to a PD through a link segment."
 Should be "link section"
 SuggestedRemedy
 Change "segment" to "section". Also, this paragraph should probably be swapped with the one above it.
 Note: this is an old error from AT and may need to be submitted as a maintenance request
 Response Response Status C
 ACCEPT.

IEEE P802.3bt D1.1 4-Pair Power over Ethernet 4th Task Force review comments

CI 33 SC 33.2.5.0a P 53 L 7 # 207
 Dwelley, David Linear Technology

Comment Type T Comment Status A Connection Check

"Type 3 and Type 4 PSEs that operate over both pair sets shall complete..."

"operate over" is somewhat ambiguous - does it mean that the PSE is about to operate over both pair sets, or that it contains hardware capable of operating over both pair sets? A PSE should not need to complete Connection Check if it is not preparing to provide 4P power.

SuggestedRemedy

Change "operate over" to "preparing to deliver 4-pair power"

Response Response Status C

ACCEPT IN PRINCIPLE.

Change "operate over both pair sets" to "will deliver power on both pairsets"

CI 33 SC 33.2.5.0a P 53 L 16 # 208
 Dwelley, David Linear Technology

Comment Type T Comment Status A Connection Check

"The connection check shall be completed before classification."

This implies that connection check should finish before classification finishes - I don't think that is what we want

SuggestedRemedy

Change sentence to: "The connection check shall be completed before classification is performed on any pairset."

This is a significant change from the existing text - we should make sure this is really what the group wants. An alternate fix would be: "The connection check shall be completed before the PSE enters POWER_UP." This is more flexible but may subject a NIC to classification voltages.

Response Response Status C

ACCEPT.

Your suggestion is what I intended when I wrote the text.

CI 33 SC 33.2.5.0a P 53 L 41 # 209
 Dwelley, David Linear Technology

Comment Type TR Comment Status A Connection Check

"If the voltage at the PI, on either pair set, rises above Vvalid max, defined in Table 33-4, the PSE shall reset the PD by bringing the voltage at the PI below Voff max, defined in Table 33-7."

This prevents operation over a 2P channel!

SuggestedRemedy

Change sentence to: "If the voltage on either pair set rises above Vvalid max, (defined in Table 33-4) during connection check, the PSE shall reset the PD by bringing the voltage at the PI below Voff max, (defined in Table 33-7) before performing detection."

Response Response Status C

ACCEPT IN PRINCIPLE.

Change sentence to: "If the voltage on either pair set rises above Vvalid max, (defined in Table 33-4) during connection check, the PSE shall reset the PD by bringing the voltage at the PI below Voff max, (defined in Table 33-11) before performing classification."

See comment 41.

CI 33 SC 33.2.5.1 P 55 L 4 # 210
 Dwelley, David Linear Technology

Comment Type T Comment Status A PSE Detection

Most of the parameters in Table 33-4 are not per pair set. In general, current specs apply per pair set while voltage specs do not.

SuggestedRemedy

Remove "per pair set" in table title. Add "per pair set" to parameter 2: "Short circuit current per pair set"

Response Response Status C

ACCEPT IN PRINCIPLE.

Dave D. to include this study in his "-2p" presentation for September.

No changes from accepting this comment.

IEEE P802.3bt D1.1 4-Pair Power over Ethernet 4th Task Force review comments

Cl 33 SC 33.2.9.1.2 P 78 L 23 # 211
 Dwelley, David Linear Technology

Comment Type E Comment Status A

"The PSE may remove power from both pair sets if the DC MPS has been absent for duration greater than TMPDO on either pair set."

Redundant text in light of page 66 line 7.

SuggestedRemedy
 Remove sentence.

Response Response Status C
 ACCEPT IN PRINCIPLE.

OBE by comment 187.

Cl 33 SC 33.3.5 P 89 L 32 # 212
 Dwelley, David Linear Technology

Comment Type T Comment Status A Editorial

"Type 2, Type 3 and Type 4 PDs implement both Multiple-Event class signature (see 33.3.5.2) and Data Link Layer classification (see 33.6)."

Missing "shall"

SuggestedRemedy
 "Type 2, Type 3 and Type 4 PDs shall implement both Multiple-Event class signature (see 33.3.5.2) and Data Link Layer classification (see 33.6)."

Response Response Status C
 ACCEPT.

EZ

Cl 33 SC 33.3.5.1 P 90 L 16 # 213
 Dwelley, David Linear Technology

Comment Type T Comment Status A PD Classification

Table 33-16: Class 0 min is still TBD

2mA min is consistent with text on page 61 line 42

SuggestedRemedy
 Replace TBD with 2mA

Response Response Status C
 ACCEPT IN PRINCIPLE.

OBE by comment 241.

Cl 33 SC 33.3.5.2 P 90 L 48 # 214
 Dwelley, David Linear Technology

Comment Type T Comment Status A Editorial

"The class advertised over each pair set is the total power requested by the PD over that pair set."

The word "total" is unnecessary and could be misleading - it implies the total power for the whole PD

SuggestedRemedy
 Delete "total": "The class advertised over each pair set is the power requested by the PD over that pair set."

Response Response Status C
 ACCEPT.

EZ

IEEE P802.3bt D1.1 4-Pair Power over Ethernet 4th Task Force review comments

Cl 33 SC 33.3.6 P 92 L 50 # 215
 Dwelley, David Linear Technology

Comment Type T Comment Status A PD Classification

"A Type 3 PD shall identify the PSE Type as either Type 1 or Type 2 if it is class 4 PD and be able to identify the PSE Type as Type 1, Type 2, or Type 3 if it is class 5 or 6 PD."

This sentence doesn't quite say what we want it to. It would be better split into two sentences.

SuggestedRemedy

Change to: "A Type 3 Class 1-4 PD shall identify the PSE Type as either Type 1 or Type 2. A Type 3 Class 5 or 6 PD shall identify the PSE Type as Type 1, Type 2, or Type 3."

Response Response Status C

ACCEPT IN PRINCIPLE.

Replace 1st 3 paragraphs of section 33.3.6 with:

A PD shall identify a PSE Type as a Type lower or equal to its own Type.

Cl 33 SC 33.3.7.3 P 96 L 28 # 216
 Dwelley, David Linear Technology

Comment Type TR Comment Status D Pres: Inrush

"After Tinrush-2P min, the PD shall not exceed its per pair set current threshold corresponding to its class level."

PDs are limited to power, not current, in POWER_ON mode. SS PDs are treated differently in this regard than DS PDs are.

SuggestedRemedy

Change to: "After Tinrush-2P min, a single-signature PD shall not exceed the power level, Pclass_pd, corresponding to its class level."
 "After Tinrush-2P min, a dual-signature PD shall not exceed its per pairset power level, Pclass_pd, corresponding to the class level advertised at that pairset."

Proposed Response Response Status W

PROPOSED ACCEPT.

Change to: "After Tinrush-2P min, the PD shall meet Pclass_pd as specified in Table 33-18."

Should we fix in the 33.3.7.2?

Cl 33 SC 33.3.7.6 P 100 L 8 # 217
 Dwelley, David Linear Technology

Comment Type T Comment Status R PD Power

"The current limit per pair set at the MDI (MDI ILIM-2P) is defined by Equation (33-14):"

MDI should be PI

SuggestedRemedy

Replace MDI with PI through line 15

Note: this is old text from AT and may need to be submitted as a maintenance request

Response Response Status C

REJECT.

This should be a maintenance request.

Cl 33 SC 33.3.7.10 P 100 L 51 # 218
 Dwelley, David Linear Technology

Comment Type E Comment Status A Editorial

"Type 3 PDs that are class 5 and above and Type 4 PDs from class 7 and above shall meet the following requirements when tested using the test setup and test conditions specified in 33.3.7.10.1: The current measured at any pair shall not exceed Icont-2Punb as specified in Table 33-11 item 4a."

Awkward phrasing.

SuggestedRemedy

Change to: "All Class 5 and higher PDs shall not exceed Icont_2p_unb (Table 33-11, item 4a) on either pair set when tested according to 33.3.7.10.1."

Response Response Status C

ACCEPT IN PRINCIPLE.

Change to: "All Class 5 and higher PDs shall not exceed I_con-2P-unb (Table 33-11, item 4a) on either pair set when tested according to 33.3.7.10.1."

EZ

IEEE P802.3bt D1.1 4-Pair Power over Ethernet 4th Task Force review comments

CI 33 SC 33.3.7 P 94 L 23 # 219
 Dwelley, David Linear Technology

Comment Type TR Comment Status D Pres: Inrush

Table 33-18 item 5: This places a new inrush requirement on Type 1/2 PDs when connected to a Type 3/4 PSE - can't do this

SuggestedRemedy

Move _2p text to item 5a, add PD Type "3,4"
 Restore original item 5 from AT

Proposed Response Response Status W

PROPOSED REJECT.

This is not a new requirement as we have now increased the max inrush current from 400mA total to 400mA per pairset (800 total). However, we do need to make sure this is in alignment with the PSE inrush numbers.

If PDs are limited to 400mA per pairset, they will work with existing Type 1 and Type 2 PSEs that supply at least 400mA over a single pairset.

CI 33 SC 33.3.7 P 94 L 25 # 220
 Dwelley, David Linear Technology

Comment Type TR Comment Status A PD Inrush

Table 33-18 item 6: "Inrush to operating state delay per pair set"

The per-pair-set requirement suggests a SS PD must delay until the 2nd pair set has completed inrush - an SS PD may not be able to tell

SuggestedRemedy

Move _2p text to item 6a, add new condition "Dual Signature PDs only"
 Restore item 6 to original AT text.

Response Response Status C

ACCEPT.

CI 33 SC 33.2.5.6 P 57 L 20 # 221
 Dwelley, David Linear Technology

Comment Type E Comment Status A 4PID

"4PID shall be initially (TBD) determined as a logical function of the detection state of both Alternative A and Alternative B pair sets, the result..."

"Alternative A and Alternative B" are redundant here

SuggestedRemedy

Remove "Alternative A and Alternative B"

Response Response Status C

ACCEPT.

Needs to be combined with comment 262.

CI 33 SC 33.2.6 P 58 L 20 # 222
 Dwelley, David Linear Technology

Comment Type E Comment Status R PSE Power

This feels like it's already been wordsmithed to death, but "supported" feels like the wrong word here

SuggestedRemedy

Change "supported" to "available" (also in Note 1).

Alternately, change to "Minimum power level the PSE must support at its output (Pclass)"

Response Response Status C

REJECT.

Need to find proper language.

IEEE P802.3bt D1.1 4-Pair Power over Ethernet 4th Task Force review comments

Cl 33 **SC 33.2.6** **P 59** **L 8** # **223**
 Dwelley, David Linear Technology

Comment Type T **Comment Status D** **PSE Classification**
 "A PSE shall meet one of the allowable classification permutations listed in Table 33–8."
 Lennart has improved Table 33-8 immensely, but now it is virtually identical to Table 33-3.
SuggestedRemedy
 Change reference to Table 33-3. Delete Table 33-8.
Proposed Response **Response Status Z**
 REJECT.
 This comment was WITHDRAWN by the commenter.
 OBE by comment that adopts new Table 33-3.
 Do not implement.

Cl 33 **SC 33.2.6.1** **P 60** **L 32** # **224**
 Dwelley, David Linear Technology

Comment Type T **Comment Status A** **PSE Classification**
 "The PSE shall provide to the PI VClass with a current limitation of IClass_LIM, as defined in Table 33–10 only for a pair set with a valid detection signature. Polarity shall be the same as defined for VPort_PSE-2P in 33.2.3 and timing specifications shall be as defined by Tpdcc in Table 33–10."
 This text appears in 33.2.6.1 but should apply to 33.2.6.2 as well
SuggestedRemedy
 Move text to 33.2.6 (perhaps near page 57 line 45)
Response **Response Status C**
 ACCEPT IN PRINCIPLE.
 Move text with following change to 33.2.6 (page 57, line 45):
 "The PSE shall provide to the PI VClass with a current limitation of IClass_LIM, as defined in Table 33–10 only for a pair set with a valid detection signature. Polarity shall be the same as defined for VPort_PSE-2P in 33.2.3 and timing specifications shall be as defined in Table 33–10."

Cl 33 **SC 33.2.6.2** **P 61** **L 5** # **225**
 Dwelley, David Linear Technology

Comment Type E **Comment Status A** **PSE Classification**
 "The PSE shall measure IClass and classify the PD based on the observed current according to Table 33–9."
 This text appears three times in this section (lines 5, 20, and 27)
SuggestedRemedy
 Remove all three lines. Add a new sentence near line 29: "In all CLASS_EVn states, the PSE shall measure IClass and classify the PD based on the observed current according to Table 33–9."
Response **Response Status C**
 ACCEPT IN PRINCIPLE.
 Remove all three lines and add:
 "In states CLASS_EV1, CLASS_EV2, and CLASS_EV3, the PSE shall measure IClass and classify the PD based on the observed current according to Table 33–9."
 at line 29.

Cl 33 **SC 33.2.6.2** **P 61** **L 47** # **226**
 Dwelley, David Linear Technology

Comment Type T **Comment Status A** **PSE Classification**
 "The class events shall meet the IClass_LIM current limitation. The mark events shall meet the IMark_LIM current limitation."
 This is the PSE section but these sound like PD requirements.
SuggestedRemedy
 Change sentences to: "The PSE shall limit class event currents to IClass_LIM, and shall limit mark event currents to IMark_LIM."
 Note: this is old text from AT and may need to be submitted as a maintenance request
Response **Response Status C**
 ACCEPT.

IEEE P802.3bt D1.1 4-Pair Power over Ethernet 4th Task Force review comments

CI 33 SC 33.2.6.2 P 62 L 20 # 227
 Dwelley, David Linear Technology

Comment Type T Comment Status A PSE Classification

"When connected to a single-signature PD, a PSE shall classify the PD only once or both of the pair sets."

Typo, but even when fixed, the meaning is not completely clear

SuggestedRemedy

"When connected to a single-signature PD, a PSE shall classify the PD only once, using either or both of the pair sets."

Response Response Status C

ACCEPT IN PRINCIPLE.

OBE by comment 109.

CI 33 SC 33.2.7 P 66 L 17 # 228
 Dwelley, David Linear Technology

Comment Type TR Comment Status D PSE Power

Resubmitted comment from D1.0:

Table 33-11: Several symbols have _2p added to them. This breaks continuity with AF/AT - an AT device that claims to meet Vport_pse will not find a spec with that name anymore. New titles with "per pair set" can stay, as all valid AF/AT devices operated over a single pairset.

SuggestedRemedy

Remove _2p suffixes from Items 1 and 4-10. Change Table 33-11 title to "PSE output electrical requirements per pair set for all PD classes, unless..."

Proposed Response Response Status Z

REJECT.

Dave D. has been assigned homework.

CI 33 SC 33.2.7 P 69 L 12 # 229
 Dwelley, David Linear Technology

Comment Type T Comment Status A Unbalance

Table 33-11 item 20: "Current unbalance" is the old 2P AT parameter - we have two unbalance specs now.

SuggestedRemedy

Change parameter title to "Inter-pair current unbalance" to match Annex 33A-3 title

Response Response Status C

ACCEPT IN PRINCIPLE.

Change parameter title to "Intra-pair current unbalance" to match Annex 33A-3 title

See comment 119, 196.

CI 33 SC 33.2.7 P 69 L 28 # 230
 Dwelley, David Linear Technology

Comment Type T Comment Status A PSE Power

Note 1: "The total port current of both pairs of the same polarity shall not exceed $P_{Type}/V_{Port_PSE} = 0.5*(P_{Type}/V_{Port_PSE_2P})*(1+a) + 0.5*(P_{Type}/V_{Port_PSE_2P})*(1-a)$, where a is the effect of system end to end pair-to-pair resistance/current unbalance that is not specified in the standard explicitly."

"Shall" in a note is not normative.

SuggestedRemedy

Delete Note 1. Move text to section 33.2.7.4a (where Additional Information for item 4a already points) - perhaps near page 72 line 13.

Response Response Status C

ACCEPT IN PRINCIPLE.

OBE by comment 113.

IEEE P802.3bt D1.1 4-Pair Power over Ethernet 4th Task Force review comments

Cl 33 SC 33.2.7.4 P71 L 26 # 231
 Dwelley, David Linear Technology

Comment Type E Comment Status A PSE Power

"For Type 3 and Type 4 PSEs, ICon-2P as specified in Table 33-11 shall be met when there is no end to end pair-to-pair current unbalance. When end to end pair-to-pair current unbalance is present, the ICon-2P may increase up to the value of ICon-2P-UNB as specified by Table 33-11 item 4a."

These two sentences belong in section 33.2.7.4a (which should be named 33.2.7.4.1)

SuggestedRemedy
 Move two sentences to the beginning of section 33.2.7.4a. Rename section to 33.2.7.4.1 (and .4b to .4.2).

Response Response Status C
 ACCEPT IN PRINCIPLE.

Icon specs should be in section 33.2.7.4 which is the Icon section, the other sections are unbalance sections.

Do not: implement suggested remedy.

Do: Rename section 33.2.7.4a to 33.2.7.4.1 and .4b to .4.2.

Cl 33 SC 33.2.7.4a P72 L 7 # 232
 Dwelley, David Linear Technology

Comment Type E Comment Status A Editorial

Typo: "Pair-to-Ppair-to-pairair"

SuggestedRemedy
 Fix

Response Response Status C
 ACCEPT.
 EZ

Cl 33 SC 33.2.7.7 P74 L 15 # 233
 Dwelley, David Linear Technology

Comment Type T Comment Status A PSE Power

"A PSE may remove power from the PI if the PI current meets or exceeds..."

I believe this should be per pair set, not sum of all pairsets (which is what PI implies).

SuggestedRemedy
 Change to: "A PSE may remove power from the PI if the current on a pair set meets or exceeds..."

Response Response Status C
 ACCEPT IN PRINCIPLE.

The current draft is confusing because Icut-2p is a pairset spec and the lowerbound template in Figure 33-14 has a TBD in it, but the goal was to be able to police the PD by total power drawn (as well as per pairset). I would prefer to see the other things fixed and this left alone (or cleaned up to show the true intention).

This results in no changes to the draft.

Cl 33 SC 33.2.7.8 P76 L 3 # 234
 Dwelley, David Linear Technology

Comment Type T Comment Status A Editorial

"...as long as the average voltage across the pair set is VOff."

Voff is a range.

SuggestedRemedy
 "...as long as the average voltage across the pair set is the range of VOff."

Alternate fix: "...as long as the average voltage across the pair set is below VOff_max."

Response Response Status C
 ACCEPT IN PRINCIPLE.

Replace with:
 "...as long as the average voltage across the pair set is below VOff max."
 EZ

IEEE P802.3bt D1.1 4-Pair Power over Ethernet 4th Task Force review comments

CI 33 SC 33.2.7.11 P 76 L 26 # 235

Dwellely, David Linear Technology

Comment Type T Comment Status A

"33.2.7.11 Current unbalance"

We have more than one kind of current imbalance now.

SuggestedRemedy

Change title to: "33.2.7.11 Inter-pair current unbalance"

Response Response Status C

ACCEPT IN PRINCIPLE.

Change title to: "33.2.7.11 Intra-pair current unbalance"

CI 33 SC 33.3.7.3 P 96 L 39 # 236

Yseboodt, Lennart Philips

Comment Type ER Comment Status D Pres: Inrush

The following three statements in D1.1 are correct but highly misleading:

"Input inrush current at startup is limited by the PSE if C_Port per pair set < 180 mF, as specified in Table 33-11."

"If C Port per pair set >=180 mF, input inrush current shall be limited by the PD so that I Inrush_PD per pair set max is satisfied."

"NOTE-- C port per pair set is the C port seen by an attached PSE on two twisted pairs"

The note changes the technical meaning of the first two statements.

SuggestedRemedy

"For single-signature PDs, the input inrush current at startup is limited by the PSE if C_Port < 180 uF, as specified in Table 33-11."

"For dual-signature PDs, the input inrush current at startup is limited by the PSE if C_Port per pair set < 180 uF, as specified in Table 33-11."

"A single-signature PD with C_Port > 180uF, or a dual-signature PD with C_Port > 180uF shall limit the input inrush current below I_Inrush_PD-2P max."

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Wait for presentation

"For single-signature PDs, the input inrush current at startup is limited by the PSE if C_Port < 180 uF, as specified in Table 33-11."

"For dual-signature PDs, the input inrush current at startup is limited by the PSE if C_Port per pair set < 180 uF, as specified in Table 33-11."

"A single-signature PD with C_Port > 180uF, or a dual-signature PD with C_Port per pair set > 180uF shall limit the input inrush current below I_Inrush_PD-2P max."

IEEE P802.3bt D1.1 4-Pair Power over Ethernet 4th Task Force review comments

Cl 33 SC 33.2.6 P 59 L 8 # 237
 Beia, Christian STMicroelectronics

Comment Type E Comment Status A Editorial

The text has to be updated since Table 33-8 title has changed

SuggestedRemedy

Change:
 A PSE shall meet one of the allowable classification permutations listed in Table 33-8.
 With
 A PSE shall meet one of the allowable classification configurations listed in Table 33-8.

Response Response Status C

ACCEPT.

EZ

Cl 33 SC 33.2.6.3 P 65 L 11 # 238
 Beia, Christian STMicroelectronics

Comment Type T Comment Status A Autoclass

Table 33-10a
 Item 3 Autoclass margin definition has a lot of sub-cases, which may confuse the reader.
 The margin seems to be quite linear with the power per pair set , so I suggest to simplify
 the table referring to that.

SuggestedRemedy

Replace Item 3 Autoclass marin, all rows with:

Item	Parameter	Symbol	Units	Min	Max	Additional Information
3	Autoclass Margin, 2 pair		%	0.14	Pclass	
3	Autoclass Margin, 4 pair		%	0.07	Pclass	

Response Response Status C

ACCEPT.

Cl 33 SC 33.3.8 P 103 L 34 # 239
 Beia, Christian STMicroelectronics

Comment Type T Comment Status A PD MPS

Table 33-19a
 A convenient way for the PD to change the MPS from Type 1,2 timings to Type 3,4 timings
 is to keep the same frequency of the pulses and change the duty cycle.
 This was the reason why Type 3,4 TMPDO_PD was set to 318ms until Draft 1.0.
 Changing it to 300ms adds design complexity to the PD.
 TMPDO for type 3,4 PSE can be kept to 320ms leaving a little margin between PSE and
 PD specs.

SuggestedRemedy

Restore Table 33-19a, last row (Item 3, Parameter PD drop out period TMPDO_PD)

MAX: 318 ; PD Type 3,4 ; if long first class event (TLCF)

Response Response Status C

ACCEPT IN PRINCIPLE.

Change TMPDO_PD max to 310ms.

Cl 33 SC 33.2.7.7 P 74 L 17 # 240
 Beia, Christian STMicroelectronics

Comment Type TR Comment Status A Pres: PSE Power Removal

When connected to an overloaded single signature PD, it is recommended that Type 3,4
 PSEs remove power from both pair sets before the current exceeds PSE upperbund
 template on one pair set.
 This avoids increasing the turn-off time of the overloaded PD, with the additional time spent
 with the whole 4-pair current flowing into a single pair set.
 Note that is not required that the 2 pair sets turn off together if the sum of the two turn-off
 times don't exceed Tcut-2P max (or the PSE upperbound template).

See presentation.

SuggestedRemedy

Add the sentence:
 When connected to a single signature PD, a Type 3 or Type 4 PSE shall remove power
 from both pairsets before the current exceeds the "PSE upperbound template" on either
 pairset.

Response Response Status C

ACCEPT IN PRINCIPLE.

Add the sentence:
 When connected to a single signature PD, a Type 3 or Type 4 PSE should (TBD) remove
 power from both pairsets before the current exceeds the "PSE upperbound template" on
 either pairset.

IEEE P802.3bt D1.1 4-Pair Power over Ethernet 4th Task Force review comments

Cl 33 SC 33.3.5.1 P 90 L 16 # 241
 Beia, Christian STMicroelectronics

Comment Type TR Comment Status A PD Classification

Table 33-16

The minimum Class 0 current for Type 3 PDs ensures the proper recognition of the mark event discharging the PD port voltage after Class event.
 As a worst case, the max input PD capacitance (120nF) has to drop from Vclass max (20.5V) to Vmark_th min (10.1V) in less than Tme min (6ms).

For the PD is helpful to take some time to filter the Vmark threshold, so it is suggested to complete the discharge in less than 2ms.

The calculation gives $I_{class} = C_{in} * (V_{class} - V_{mark}) / T_{discharge} = 624 \mu A$.

Choosing $I_{class} \min = 1 \text{mA}$, $T_{discharge}$ becomes 1.25ms, which gives extra margin to the classification timings with no added complexity.

SuggestedRemedy

Replace "TBD" in Table 33-16 line 2, column 3, with 1.00

Response Response Status C

ACCEPT.

Will be OBE by comment 213

Cl 33 SC 33.2.9.1.1 P 77 L 35 # 242
 Beia, Christian STMicroelectronics

Comment Type TR Comment Status A Pres: MPS

It is very hard for a PD to swith between a condition where the AC MPS component requirements are present, to a condition where those requirements are absent. Since there is no easy way for a froze up PD to reboot, it may be convenient to take advantage of the absence of a DC MPS component.
 In order to preserve legacy behavior, the new requirement is for Type3 and Type4 PSE only.
 See also the relevant presentation.

SuggestedRemedy

Change the sentence:
 The PSE shall monitor either the DC MPS component, the AC MPS component, or both.

With:
 Type1 and Type2 PSEs shall monitor either the DC MPS component, the AC MPS component, or both.
 Type3 and Type4 PSEs shall monitor the DC MPS component and shall not monitor the AC MPS component.

Response Response Status C

ACCEPT IN PRINCIPLE.

OBE by comment 89.

IEEE P802.3bt D1.1 4-Pair Power over Ethernet 4th Task Force review comments

Cl 33 SC 33.3.8 P 102 L 26 # 243
 Beia, Christian STMicroelectronics

Comment Type TR Comment Status A Pres: MPS

It is very hard for a PD to swith between a condition where the AC MPS component requirements are present, to a condition where those requirements are absent. Since there is no easy way for a froze up PD to reboot, it may be convenient to take advantage of the absence of a DC MPS component.
 In order to preserve legacy behavior, the new requirement is for Type3 and Type4 PSE only.
 See also the relevant presentation.

SuggestedRemedy

Replace the text:

Powered PDs that no longer require power shall remove both the current draw and impedance components of the MPS. To cause PSE power removal, the impedance of the PI should rise above Zac2 as specified in Table 33–12

With

Powered PDs that no longer require power, and identify the PSE as Type 1 or Type 2, shall remove the current draw and impedance components of the MPS. To cause Type 1 and Type 2 PSE power removal, the impedance of the PI should rise above Zac2 as specified in Table 33–12

Powered PDs that no longer require power, and identify the PSE as Type 3 or Type 4, shall remove the current draw component and may remove the impedance component of the MPS.

Response Response Status C

ACCEPT.

Waiting for presentation.

Cl 33 SC 33.2.7 P 69 L 28 # 244
 Beia, Christian STMicroelectronics

Comment Type TR Comment Status A PSE Power

Table 33-11

Footnote 1:

"The total port current of both pairs of the same polarity shall not exceed $P_{Type}/V_{Port_PSE} = 0.5 * (P_{Type}/V_{Port_PSE_2P}) * (1+a) + 0.5 * (P_{Type}/V_{Port_PSE_2P}) * (1-a)$, where a is the effect of system end to end pair-to-pair resistance/current unbalance that is not specified in the standard explicitly"

introduces a "shall" requirement and at the same time leaves the "a" parameter undefined. It should be just an explicative note instead.

SuggestedRemedy

Modify the footnote 1 as follows:

The total port current of both pairs of the same polarity can be calculated as $P_{Type}/V_{Port_PSE} = 0.5 * (P_{Type}/V_{Port_PSE_2P}) * (1+a) + 0.5 * (P_{Type}/V_{Port_PSE_2P}) * (1-a)$, where a is the effect of system end to end pair-to-pair resistance/current unbalance that is not specified in the standard explicitly.

Response Response Status C

ACCEPT IN PRINCIPLE.

OBE by comment 113.

Cl 33 SC 33.3.2.6.2 P 64 L 24 # 245
 Beia, Christian STMicroelectronics

Comment Type TR Comment Status A PD Classification

Table 33-10

The long finger classification timings (85ms min and 100ms max) have not changed since Draft0.4, so the TBDs can be removed

SuggestedRemedy

remove TBD from Table 33-10, item 12, column Min and column Max

Response Response Status C

ACCEPT.

IEEE P802.3bt D1.1 4-Pair Power over Ethernet 4th Task Force review comments

Cl 33 SC 33.1.1 P 20 L 5 # 246
 Zimmerman, George CME Consulting, Inc.

Comment Type T Comment Status D Editorial

"Type 2 operation requires ISO/IEC 11801:1995 Class D or better cabling, and Type 3 operation requires ISO/IEC 11801:2002 Class D or better cabling, and a derating of the cabling maximum ambient operating temperature."
 Change inadvertently removes existing statement that Type 2 requires reduction in maximum operating temperature.

SuggestedRemedy

Rewrite as two sentences:
 "Type 2 operation requires ISO/IEC 11801:1995 Class D or better cabling, and Type 3 operation requires ISO/IEC 11801:2002 Class D or better cabling. Type 2 and Type 3 operation additionally require a derating of the cabling maximum ambient operating temperature."

Proposed Response Response Status Z

REJECT.

This comment was WITHDRAWN by the commenter.

OBE by comment # 159.

EZ

Cl 33 SC 33.1.4 P 22 L 34 # 247
 Zimmerman, George CME Consulting, Inc.

Comment Type T Comment Status A Cabling

(note 2)"In Type 3 and Type 4 operation, the current per pair set might be impacted by pair-to-pair system resistance unbalance. See details in 33-11 item 4a."
 The first sentence of the note gives no guidance, the column already says nominal. Reference to 33-11 lacks proper identifier (>>Table<< 33-11), and information as to what to find there.

SuggestedRemedy

Strike "In Type 3 and Type 4 operation, the current per pair set might be impacted by pair-to-pair system resistance unbalance. "
 Replace "See details in 33-11 item 4a." with
 "For details on resistance unbalance effects, see Table 33-11 item 4a."

Response Response Status C

ACCEPT IN PRINCIPLE.

OBE by comment # 200

Cl 33 SC 33.1.4.1 P 23 L 13 # 248
 Zimmerman, George CME Consulting, Inc.

Comment Type TR Comment Status A Cabling

"Type 2 operation requires Class D, or better, cabling as specified in ISO/IEC 11801:1995, and Type 3 operation requires Class D or better cabling as specified in ISO/IEC 11801:2002, with the additional requirement that channel DC resistance shall be 25ohms or less. These requirements are also met by Category 5e or better cable and components as specified in ANSI/TIA-568-C.2; or Category 5 cable and components as specified in ANSI/TIA/EIA-568-A."

Text incorrectly identifies ISO/IEC 11801:2002 as lacking DC loop resistance requirements (this applies to ISO/IEC 11801:1995) and additionally confuses requirements for type 2 and type 3 which are now different (one is ISO 1995 one is 2002) further, the ordering of the equivalence to TIA specs is reversed from the ISO specs, adding to the confusion.

SuggestedRemedy

Rewrite as separate sentences, replacing as follows:
 "Type 2 operation requires Class D, or better, cabling as specified in ISO/IEC 11801:1995, with the additional requirement that channel DC loop resistance shall be 25fÇ or less. These requirements are also met by Category 5 cable and components as specified in ANSI/TIA/EIA-568-A. Type 3 operation requires Class D or better cabling as specified in ISO/IEC 11801:2002. These requirements are also met by Category 5e or better cable and components as specified in ANSI/TIA-568-C.2."

Response Response Status C

ACCEPT IN PRINCIPLE.

OBE by comment # 126.

IEEE P802.3bt D1.1 4-Pair Power over Ethernet 4th Task Force review comments

CI 33 SC 33.1.4.1 P 23 L 19 # 249
 Zimmerman, George CME Consulting, Inc.

Comment Type TR Comment Status R Cabling

"Under worst-case conditions, Type 2 and Type 3 operation requires a 10 °C reduction in the maximum ambient operating temperature of the cable when all cable pairs are energized at ICable (see Table 33-1), or a 5 °C reduction in the maximum ambient operating temperature of the cable when half of the cable pairs are energized at ICable. Additional cable ambient operating temperature guidelines for Type 2, Type 3, and Type 4 operation are provided in ISO/IEC TR 29125 [B49]1 and TIA TSB-184 [B61]"

First, we should not be specifying the installation conditions here, but rather refer to the cabling standards (TIA-TSB-184-A and the ISO TR).
 Second, Does Type 2 operation, which is 2 pairs in a 4 pair sheath EVER have all cable pairs energized? isn't it half the cable pairs?

SuggestedRemedy

Replace as follows:

"Reduction in the maximum ambient operational temperature may be required for Type 2 and Type 3 operation. When half the cable pairs are energized, as is the case in 2 pair operation, a less reduction is required. For details on the effects of installation conditions and currents on cable temperature rise associated with Type 2, Type 3 and Type 4 operation, see ISO/IEC TR 29125 [B49]1 and TIA TSB-184 [B61]."

Response Response Status C

REJECT.

This paragraph existed before this project. All we have done is add Type 3 (and eventually 4) to it. Changing it may change Type 1/2 behavior.

This can be filed as a maintenance request.

CI 33 SC 33.2.2 P 28 L 17 # 250
 Zimmerman, George CME Consulting, Inc.

Comment Type TR Comment Status A Editorial

"Figure 33-5a—10BASE-T/100BASE-TX Alternative A and Alternative B Endpoint PSE location overview"
 Title of figure 33-5a is inconsistent with other titles, (33-5b, 33-7a, and 33-7b), should reference 4 pair operation.

SuggestedRemedy

Change title of figure 33-5a is to be consistent with other titles, (33-5b, 33-7a, and 33-7b):
 "Figure 33-5a—10BASE-T/100BASE-TX 4-Pair Endpoint PSE location overview"

Response Response Status C

ACCEPT.

EZ

CI 33 SC 33.2.3 P 33 L 26 # 251
 Zimmerman, George CME Consulting, Inc.

Comment Type TR Comment Status A 4-Pair Power

"While a PSE may be capable of both Alternative A and Alternative B, PSEs shall not operate both Alternative A and Alternative B on the same link segment simultaneously." (strikeout)
 Type 1 and Type 2 PSEs still have the striken restriction - need to rewrite rather than just strike out. Additionally, reference to 'link segment' is unneeded and inaccurate. The alternatives are the pinouts, the link section, has no pinout.

SuggestedRemedy

Reinstate as:

"While a PSE may be capable of both Alternative A and Alternative B, Type 1 and Type 2 PSEs shall not operate both Alternative A and Alternative B simultaneously. Type 3 and Type 4 PSEs may operate simultaneously on both Alternatives."

Response Response Status C

ACCEPT.

CI 33 SC 33.2.4 P 33 L 31 # 252
 Zimmerman, George CME Consulting, Inc.

Comment Type TR Comment Status A PSE State Diagram

"The PSE shall provide the behavior of the state diagrams shown in Figure 33-9, Figure 33-9 continued, and Figure 33-10."

This statement now applies only to Type 1 and Type 2 PSEs.
 While we know that it doesn't apply to Type 3 & 4, we also don't know what behavior relates to Types 3 & 4 yet, but a statement is needed.

SuggestedRemedy

Change to : "Type 1 and Type 2 PSEs shall provide the behavior ..."
 Insert: "Type 3 and Type 4 PSEs shall provide the behavior of the state diagrams shown in Figures (TBD)."

Response Response Status C

ACCEPT.

EZ

IEEE P802.3bt D1.1 4-Pair Power over Ethernet 4th Task Force review comments

Cl 33 SC 33.2.4.1 P 33 L 45 # 253
 Zimmerman, George CME Consulting, Inc.

Comment Type T Comment Status D 4-Pair Power

"It is possible that two separate PSEs, one that implements Alternative A and one that implements Alternative B (see 33.2.1), may be attached to the same link segment."

This applies only to two-pair PSEs.

SuggestedRemedy

insert "two-pair" so it says "It is possible that two separate two-pair PSEs".

Proposed Response Response Status Z

PROPOSED REJECT.

This comment was WITHDRAWN by the commenter.

This applies to all PSEs. Two 4-Pair PSEs could end up attached to the same cable (Alt A from one and Alt B from the other). They could still work.

This paragraph is completely informative and only explains the reason for the next paragraph.

Cl 33 SC 33.2.4.4 P 35 L 8 # 254
 Zimmerman, George CME Consulting, Inc.

Comment Type ER Comment Status A Editorial

"Editor's Note: State machine to include early exit at any point prior to power up. Language above suggests 4PID prior to classification, commentators are encouraged to provide language consistent with 4PID by power-up."

Language above has been modified to not mention classification, so the issue is fixed.

SuggestedRemedy

Delete Editor's note.

Response Response Status C

ACCEPT.

EZ

Cl 33 SC 33.2.4.4 P 33 L 43 # 255
 Zimmerman, George CME Consulting, Inc.

Comment Type T Comment Status X Pres: Inrush

"legacy_powerup:
 This variable is provided for PSEs that monitor the PI per pair set voltage output and use that information to indicate the completion of PD inrush current during POWER_UP operation. Using only the PI pair set voltage information may be insufficient to determine the true end of PD inrush current; use of a fixed TInrush-2P period is recommended. A variable that is set in an implementation-dependent manner.
 Values:TRUE:The PSE supports legacy power up; this value is not recommended.
 FALSE:The PSE does not support legacy power up. It is highly recommended that new equipment use this value."

Doesn't this only apply to 2 pair PSEs? At a minimum, there should be no legacy-power-up 4pair PSEs.

SuggestedRemedy

insert "two pair" so it reads, "This variable is provided for two-pair PSEs"

Add to TRUE: (after 'not recommended'), "and is not allowed for 4-pair PSE operation."

Proposed Response Response Status W

Wait for Yair's Presentation.

IEEE P802.3bt D1.1 4-Pair Power over Ethernet 4th Task Force review comments

CI 33 SC 33.2.4.4 P 37 L 4 # 256
 Zimmerman, George CME Consulting, Inc.

Comment Type TR Comment Status A PSE SD

"pd_dll_power_type
 A control variable output by the PSE power control state diagram (Figure 33-27) that indicates the type of PD as advertised through Data Link Layer classification.
 Values:1: PD is a Type 1 PD (default)
 2: PD is a Type 2 PD
 3: PD is a Type 3 PD
 4: PD is a Type 4 PD"

A dual of this variable will be needed for mutual identification, not requiring it to be "dll". - pd_power_type.

SuggestedRemedy

Add Editor's note reminding that mutual identification will require a similar variable "pd_power_type", or, if mutual ID is adopted, add the variable as follows:
 "pd_power_type
 A control variable determined by mutual identification that indicates the type of PD."
 Values:1: PD is a Type 1 PD (default)
 2: PD is a Type 2 PD
 3: PD is a Type 3 PD
 4: PD is a Type 4 PD"

Response Response Status C

ACCEPT IN PRINCIPLE.

Add the editor's note suggested.

We need to be careful of the type/power relationship.

CI 33 SC 33.2.4.6 P 43 L 4 # 257
 Zimmerman, George CME Consulting, Inc.

Comment Type ER Comment Status A Editorial

"Editor's Note: "Classification not complete" in above paragraph needs to be clear. Team to pay close attention to above paragraph during reviews."

Text doesn't refer to above text, the term does not appear in that text or has been modified. (it wasn't in 1.0 either)

SuggestedRemedy

Delete editor's note.

Response Response Status C

ACCEPT IN PRINCIPLE.

The note should say "Mutual identification not complete". Please change the note accordingly.

CI 33 SC 33.2.4.6 P 43 L 8 # 258
 Zimmerman, George CME Consulting, Inc.

Comment Type ER Comment Status A Editorial

"When a PSE powers a PD of lower Type (Type_sub_PD) than its own native type (Type_sub_PSE), the PSE shall meet the PI electrical requirements of a Type 1 PSE the PD Type(Type_sub_PD), except for ICon-2P, ILIM-2P, TLIM-2P, and PType (see Table 33-11), for which the PSE shall meet the requirements of any PSE Type, Type_sub_PD <= PSE Type <= Type_Sub_PSE."

sub should indicate subscripts. also wording of "for which the PSE shall meet the requirements of any PSE Type" is odd.

SuggestedRemedy

implement subscripts indicated by _sub_

Reword requirement so that it makes sense, "for which the PSE shall select to meet the requirements of it's type or a lesser type such that Type_sub_PD<=..."

Response Response Status C

ACCEPT.

IEEE P802.3bt D1.1 4-Pair Power over Ethernet 4th Task Force review comments

CI 33 SC 33.2.4.7 P 45 L 40 # 259
 Zimmerman, George CME Consulting, Inc.

Comment Type ER Comment Status A Editorial

"Figure 33-9—PSE state diagram (continued)"

Title should follow that of Figure 33-9- Type 1 and Type 2 PSE state diagram"

SuggestedRemedy

Change title to match Fig 33-9: "Figure 33-9— Type 1 and Type 2 PSE state diagram (continued)"

Response Response Status C

ACCEPT.

EZ

CI 33 SC 33.2.4.7 P 52 L 30 # 260
 Zimmerman, George CME Consulting, Inc.

Comment Type ER Comment Status A PSE SD

Editor's Note: State diagram shown in figure 33-9 should include the following
 1) Process to do connection check following DETECT_EVAL and prior to any classification.

After connection
 check set variable pd_4pair_candidate = (valid_AB)*[(PD_signature = Single) +
 (PD_signature =
 Dual) * (!deny_dual_sig_4p_power)].

2) Set maintain_4pair_power to initial value of pd_4pair_candidate at POWER_UP state.
 3) Add an additional exit condition - !maintain_4pair_power from the POWER_ON state to the POWER_

DENIED state. Change exit D from POWER_ON state to

"power_not_available*!short_detected*!
 ovlid_detected*tmpdo_timer_not_done*!option_vport_lim+!maintain_4pair_power".If
 maintain_4pair_power is false then power must be removed from at least one pair set."

Editor's note has been overtaken by other changes, needs updating to deal with deleted variables. Items 2 & 3 no longer apply, item 1 is modified.

SuggestedRemedy

Replace lines 29 to 33 with:

Editor's Note: State diagram shown in figure 33-9 should include the following

1) Process to do connection check following DETECT_EVAL and prior to any classification.
 After connection check set variable pd_4pair_candidate = (valid_AB)*[(PD_signature =
 Single)."

(delete items 2 & 3, lines 34 to 40).

Response Response Status C

ACCEPT IN PRINCIPLE.

OBE by comment # 142

CI 33 SC 33.2.5.3 P 56 L 24 # 261
 Zimmerman, George CME Consulting, Inc.

Comment Type ER Comment Status A Editorial

"In a multiport system, the implementor should maintain DC isolation..."

"implementor" has been globally changed to "implementer" in 802.3bx revision project.

SuggestedRemedy

Change "implementor" to "implementer" throughout document.

Response Response Status C

ACCEPT.

EZ

IEEE P802.3bt D1.1 4-Pair Power over Ethernet 4th Task Force review comments

CI 33 SC 33.2.5.6 P 57 L 19 # 262
 Zimmerman, George CME Consulting, Inc.

Comment Type T Comment Status A 4PID

"4PID shall be initially (TBD) determined as a logical function of the detection state of both Alternative A and Alternative B pair sets, the result of connection check as described in 33.2.5.0 and the results of other system information."

mutual identification is obviously needed, and is omitted from this list of specific information.

SuggestedRemedy

add ", mutual identification" after 33.2.5.0 and before "and" to read:
 "4PID shall be initially (TBD) determined as a logical function of the detection state of both Alternative A and Alternative B pairsets, the result of connection check as described in 33.2.5.0, mutual identification, and the results of other system information."

Response Response Status C
 ACCEPT.

CI 33 SC 33.2.7 P 65 L 48 # 263
 Zimmerman, George CME Consulting, Inc.

Comment Type TR Comment Status A PSE Power

"PSE behavior conforms to the state diagrams in Figure 33–9, Figure 33–9 continued, and Figure 33–10."

This restatement of the earlier requirement needs modification to point to Type 1 and Type 2 PSEs only, and may need an additional statement for Type 3 & 4 PSEs to point to TBD state diagram.

SuggestedRemedy

Delete the redundant restatement "PSE behavior conforms to the state diagrams in Figure 33–9, Figure 33–9 continued, and Figure 33–10."

Alternatively, change to read: "Type 1 and Type 2 PSE behavior conforms to the state diagrams in Figure 33–9, Figure 33–9 continued, and Figure 33–10. Type 3 and Type 4 PSE behavior conforms to the state diagrams in Figures (TBD)."

Response Response Status C
 ACCEPT IN PRINCIPLE.

Delete the redundant restatement "PSE behavior conforms to the state diagrams in Figure 33–9, Figure 33–9 continued, and Figure 33–10."

CI 33 SC 33.2.7 P 66 L 1 # 264
 Zimmerman, George CME Consulting, Inc.

Comment Type ER Comment Status A

"Editor's Note: Update the above sentence to reference Type 3/4 state diagram when state diagram is complete."

No need to wait if you know it needs to be done, just put in the TBDs where needed.

SuggestedRemedy

Delete editor's note.

Response Response Status C

ACCEPT.

See comment 263.

CI 33 SC 33.2.7 P 70 L 1 # 265
 Zimmerman, George CME Consulting, Inc.

Comment Type E Comment Status A Editorial

"4Item 17b applies to PSEs that implement MPS detection by measuring sum of the pair set currents of the same polarity."

Note 4 is on new page - should be with table and previous notes.

SuggestedRemedy

change formatting in notes to keep with next for notes 1-3, note 4 doesn't need keep with next.

Response Response Status C

ACCEPT.

"keep with next" is an attribute in Frame to keep things together.

IEEE P802.3bt D1.1 4-Pair Power over Ethernet 4th Task Force review comments

CI 33 SC 33.2.7.1.2 P 76 L 40 # 266
Zimmerman, George CME Consulting, Inc.
Comment Type TR Comment Status A Editorial
"For Type 3 and Type 4 PSEs, when connected to a single-signature PD, both pair sets must reach the POWER_ON state within Tpon after detection on last pair set."
"must"? shouldn't this be "shall"?
SuggestedRemedy
change "must" to "shall"
Response Response Status C
ACCEPT.
EZ

CI 33 SC 33.2.9.1.2 P 78 L 23 # 267
Zimmerman, George CME Consulting, Inc.
Comment Type E Comment Status A PSE MPS
"The PSE may remove power from both pair sets if the DC MPS has been absent for duration greater than TMPDO on either pair set."
additional restatement of permission to remove power from both pair sets.
SuggestedRemedy
delete sentence.
Response Response Status C
ACCEPT IN PRINCIPLE.
OBE by comment 187.
EZ

CI 33 SC 33.4.9.1 P 113 L 20 # 268
Zimmerman, George CME Consulting, Inc.
Comment Type T Comment Status D AES
"10GBASE-T connector or telecom outlet Midspan PSE"
what is a '10GBASE-T connector'? is it the 10GBASE-T MDI connector?
SuggestedRemedy
change 'connector' to 'MDI connector'
Proposed Response Response Status Z
REJECT.
This comment was WITHDRAWN by the commenter.
Need someone with knowledge in this area to answer this.

CI 33 SC 33.4.9.1 P 113 L 38 # 269
Zimmerman, George CME Consulting, Inc.
Comment Type T Comment Status A AES
"For up to 1000BASE-T operation, NEXT loss for Midspan PSE devices"
This should include 1000BASE-T, but exclude 10GBASE-T.
SuggestedRemedy
Replace "for up to 1000BASE-T operation" with "For operation with 1000BASE-T and lower rates".
Response Response Status C
ACCEPT.

CI 33 SC 33.4.9.1.2 P 114 L 19 # 270
Zimmerman, George CME Consulting, Inc.
Comment Type T Comment Status A AES
"For 1000BASE-T operation, insertion loss" should be for rates up to 1000BASE-T, inclusive.
802.3bz is expected to also use these rates, so operation other than 10G would be ok too.
SuggestedRemedy
Replace "for 1000BASE-T operation, " with "For other than 10GBASE-T operation, "
Response Response Status C
ACCEPT.

IEEE P802.3bt D1.1 4-Pair Power over Ethernet 4th Task Force review comments

Cl 33 SC 33.5.1.1 P 118 L 10 # 271
Zimmerman, George CME Consulting, Inc.

Comment Type **TR** Comment Status **A** Management

Table 33-21 (register 11), bit 6, "Deny dual-signature PD 4-pair Power"
- the variable this was supposed to set was removed, the bit is no longer needed.
Also described in 33.5.1.1.1a

SuggestedRemedy

No change needed to Table 33-21
Delete row for bit 11.6
Reinstate the reserved bits as 11.15:6
Delete new section 33.5.1.1.1a Deny dual-signature PD 4-pair power (lines 40-47)

Response Response Status **C**
ACCEPT.

Cl 33 SC 33.3.4 P 86 L 54 # 272
Darshan, Yair Microsemi

Comment Type **TR** Comment Status **A** 4PID

The text:
"When a Type 1 or Type 2 PD becomes powered via the PI, it shall present a non-valid
detection signature on the set of pairs
from which it is not drawing power"

In order to maintain interoperability with all PSEs and PDs in terms of backfeed voltage
that supports invalid signature on the un powered pairs specifically in SS PD, this
requirements need to be applied for all PDS.

SuggestedRemedy

Change from:
When a Type 1 or Type 2 PD becomes powered via the PI, it shall present a non-valid
detection signature on the set of pairs
from which it is not drawing power

To
When a Single Signature PD Type 1 or Type 2 PD or Type 3 or Type 4 becomes powered
via the PI, it shall present a non-valid detection signature on the set of pairs from which it is
not drawing power"

Response Response Status **C**
ACCEPT IN PRINCIPLE.

OBE by comment 156.