

Towards a baseline proposal for a 100 Gb/s SMF PHY 500 m using single wavelength PAM4 modulation 100GBASE-DR

Authors on next page

Authors

- Chris Cole, Finisar
- Hai-Feng Liu, Intel
- Matt Brown, APM
- Dave Lewis, Lumentum
- Marco Mazzini, Cisco
- Brian Welch, Luxtera
- Mark Kimber, Semtech
- Atul Gupta, Macom
- Gary Nicholl, Cisco
- Matt Traverso, Cisco

Supporters

- Sudeep Bhoja, Inphi
- Tom Palkert, Macom
- Hanan Leizerovich, Multiphy
- Justin Abbott, Lumentum
- Drew Guckenberger, Molex
- Francesco Caggioni, APM
- Kohichi Tamura, Oclaro
- Tom Issenhuth, Microsoft
- Jeff Twombly, Credo Semiconductor
- Haoli Qian, Credo Semiconductor
- Phil Sun, Credo Semiconductor
- Tad Hofmeister, Google
- Bharat Tailor, Semtech
- Ed Ulrichs, Source Photonics
- Jeff Maki, Juniper
- Pirooz Tooyserkani, Cisco
- Scott Schube, Intel
- David Malicoat, HPE
- Vineet Salunke, Cisco
- Brad Booth, Microsoft
- Rob Stone, Broadcom
- Dave Ofelt, Juniper
- Kiyo Hiramoto, Oclaro
- Marek Tlalka, Macom

802.3cd Objectives: v3 (*)

100 Gb/s Ethernet PHYs

- Define a two-lane 100 Gb/s PHY for operation over
 - copper twin-axial cables with lengths up to at least 3m.
 - printed circuit board backplane with a total channel insertion loss of $\leq 30\text{dB}$ at 13.28125 GHz.
 - MMF with lengths up to at least 100m
 - SMF with lengths up to at least 500m
- Define a 100 Gb/s PHY for operation over SMF with lengths up to at least 2 km **

(*) http://www.ieee802.org/3/cd/P802d3cd_objectives_v3.pdf

** adopted by Task Force. Not yet ratified by Working Group

802.3cd Objectives – Path Forward Proposal

Proposed path forward

- Replace the current 100Gb/s PHY objectives with the following:
 - Define a two-lane 100 Gb/s PHY for operation over
 - Copper twin-axial cables with lengths up to at least 3m.
 - Printed circuit board backplane with a total channel insertion loss of $\leq 30\text{dB}$ at 13.28125 GHz.
 - MMF with lengths up to at least 100m
 - Define a single lane 100 Gb/s PHY for operation over duplex SMF with lengths up to at least 500 m, consistent with IEEE P802.3bs Clause 124
- Update the CSD inline with the new objectives
 - See brown_3cd_02_0916

Baseline Proposal for single lane duplex SMF 100 Gb/s PHY up to 500 m

- 100GBASE-DR, to be consistent with the latest 400GBASE-DR4 in Clause 124, but
 - with 1 lane instead of 4 lanes
 - with penalties consistent with a channel allowing up to 4 discrete reflectances of -35 dB
 - leveraging PCS per nicholl_3cd_01_0716

Proposed Straw Poll

Straw Poll #:

I would support adopting traverso_3cd_01_0916 as the baseline to address the single lane 100 Gb/s PHY for operation over duplex SMF with lengths up to at least 500 m.

- Y: N: A: