

ERL Proposals for KR and C2C

Mau-Lin Wu, Tobey P.-R. Li, Cheng-Wei Tsai, Po-Hsiang Huang, Ching-Ku Liao
MediaTek

For IEEE 802.3ck Ad-Hoc

Supporters

- Phil Sun, Credo
- Adee Ran, Intel

Outlines

- Background
- TX ERL sensitivity analysis
 - R_d , z_p , Z_c , C_p , C_b
- Summary & proposals

One page summary

- In TP0v of D1p3, it requires device/package model based on COM parameters to derive ERL reference value
 - However, device/package model was defined from COM calculation point-of-view, not ERL
 - ERL is sensitive to some parameters, reference ERL by COM parameters is NOT the case of minimum ERL within valid COM parameters
- Provide supporting materials for Comment #202, #203
- Analysis
 - Sweeping some parameters to check the minimum ERL values & derive dERL accordingly
 - z_p, C_p, C_b, Z_c, R_d
- Results
 - By considering z_p, Z_c, R_d valid ranges, $dERL = -3 \text{ dB}$ is proposed

TX ERL reference values – sensitivity analysis


- One measured TP0 to TP0v test fixture
 - IL = 2.12 dB @ 26.56 GHz
- Sweep device/package parameters to check ERL sensitivity & find min ERL in the valid range
 - Valid range show in right-hand-sided table
- COM spread sheet
 - In appendix

Parameters	Value in D1p3	Valid range	Note
R_d (Ohm)	50	45 ~ 55	50 +/- 10%
z_p (mm)	31	12 ~ 31	
Z_c (Ohm)	87.5	80 ~ 95	87.5 +/- 10%
C_p (fF)	87	<= 87	
C_b (fF)	30	<= 30	


- R_d = single-ended termination resistance
- z_p = transmission line length
- Z_c = transmission line characteristics impedance
- C_p = single-ended package capacitance at package-to-board interface
- C_b = single-ended device bump capacitance

TX TDR and ERW with Sweeping R_d

- TDR with sweeping R_d (Ohm)



- Effective reflection waveform (ERW) with sweeping R_d (Ohm) – N_bx = 21




- Observing from TDR & ERW
 - It's obvious that $R_d = 50$ Ohm is not the case with minimum ERL
 - $R_d = 55$ Ohm is
- ERL parameter, T_{fx} , is derived from TDR
 - at the starting time of the boundary when impedance going down from around 100 Ohm (at the TPO) to 85 Ohm (due to C_p)

TX ERL with Sweeping R_d

- ERL ($z_p = 31$ mm, $C_p = 87$ fF, $C_b = 30$ fF)

	Reference			
R_d (Ohm)	40	45	50	55
Tfx (ns)			2.158	
KR ($N_{bx} = 21$)	20.80	20.59	18.60	17.04
C2C ($N_{bx} = 6$)	20.05	19.91	17.84	16.34

- +/- 10% manufacturing variation of R_d and Z_c shall be considered
- Reference ERL is sensitive to R_d
 - dERL shall be -1.50 ~ -1.56 dB
- Q: What's the COM values of $R_d = 50$ vs. 55 Ohm?
 - Shown in next slide



COM Analysis of 8 KR baseline Channels – Sweeping R_d


- 8 KR baseline channels
 - List in slide 6 of [heck_3ck_01_0519.pdf](#)
 - COM excel sheet in appendix
- Observations
 - COM is not sensitive to R_d +/- 10%
 - < 0.2 dB for critical channels with COM \approx 3.0 dB
 - Could be included in 3 dB COM margin
- Proposal
 - No touch to COM parameters, such as R_d , Z_c
 - COM variation due to R_d +/- 10% & Z_c +/- 10% could be covered by 3 dB margin
 - ERL variation due to R_d & Z_c variation could be covered by negative dERL spec

Channel	$R_d = 50$ (Ohm)	$R_d = 55$ (Ohm)	dCOM (dB)
Cable_BKP_28dB_0p575m_more_isi	2.85	2.78	-0.07
Cable_BKP_16dB_0p575m_more_isi	5.75	5.29	-0.46
CaBP_BGAVia_Opt2_28dB	4.69	4.55	-0.14
Std_BP_12inch_Meg7	4.08	4.10	0.02
DPO_IL_12dB	6.55	6.18	-0.37
OAch4	2.88	2.75	-0.13
CAch3_b2	3.90	3.72	-0.18
Bch2_b7p5_7	2.84	2.67	-0.17

TX ERL with Sweeping z_p

- ERL ($C_p = 87 \text{ fF}$, $C_b = 30 \text{ fF}$, $R_d = 50 \text{ Ohm}$)


	Reference										
Pkg length (mm)	11	13	15	17	19	21	23	25	27	29	31
Rd (Ohm)	50										
Tfx (ns)	2.158										
KR ($N_{bx} = 21$)	20.39	19.33	19.21	18.63	18.94	18.61	18.37	19.12	18.50	18.77	18.60
C2C ($N_{bx} = 6$)	17.56	16.84	17.11	16.92	17.50	17.37	17.35	18.29	17.69	18.00	17.84




- Maximum package length doesn't mean minimum ERL
 - Let's observe ERW in next slide
- Allocate dERL to cover reference ERL variation due to package length variation
 - KR: -0.23 dB, C2C: -1.00 dB

TX TDR and ERW with Sweeping z_p

- TDR with sweeping z_p (mm)



- Effective reflection waveform (ERW) with sweeping z_p (mm) – $N_{bx} = 21$



- Observing from ERW

- The major reflection contributes from re-reflection due to ' C_p ' & ' C_b ', while the location depends on z_p
- The ERL fluctuation observed by sweeping z_p is due to 'Time gating weighting function, $G_{rr}(t)$ ' to generate Effective reflection waveform

TX ERL with Sweeping Z_c, C_p, C_b

- Sweeping Z_c – similar as R_d case
 - $Z_c = 80 \text{ Ohm}$ has the minimum ERL, which requires $-0.48 \sim -0.54 \text{ dERL}$ to cover its variation
- Sweeping C_p, C_b
 - It's obviously that larger C_p & C_b cause smaller ERL
 - If we shall $C_p = 87 \text{ fF}$ & $C_b = 30 \text{ fF}$ is the maximum capacitance we can accept, we don't need to allocate dERL for these two parameters
- Detailed information of sweeping Z_c, C_p, C_b can be found in the appendix

ERL Sensitivity Analysis – Summary of KR

- By considering ERL variation due to z_p, Z_c, & R_d,
 - dERL shall be at least = (-0.23) + (-0.48) + (-1.56) = -2.27
- Sweeping z_p with Z_c = 80 & R_d = 55
 - dERL is -2.27
- Proposal
 - dERL = -3 dB

KR case (N_bx = 21)	Parameter settings	Min calculated ERL by sweeping parameters				
		D1p3	z_p	Z_c	R_d	z_p, Z_c=80, R_d=55
z_p (mm)		31	23	31	31	27
C_p (fF)		87	87	87	87	87
C_b (fF)		30	30	30	30	30
Z_c (Ohm)		87.5	87.5	80	87.5	80
R_d (Ohm)		50	50	50	55	55
ERL (dB)		18.60	18.37	18.12	17.04	16.33
dERL (dB)			-0.23	-0.48	-1.56	-2.27

ERL Sensitivity Analysis – Summary of C2C

- By considering ERL variation due to z_p, Z_c, & R_d,
 - dERL shall be at least = (-1.00) + (-0.54) + (-1.50) = -3.04
- Sweeping z_p with Z_c = 80 & R_d = 55
 - dERL is -2.66
- Proposal
 - dERL = -3 dB

C2C case (N_bx = 6)	Parameter settings	Min calculated ERL by sweeping parameters				
		D1p3	z_p	Z_c	R_d	z_p, Z_c=80, R_d=55
z_p (mm)		31	13	31	31	13
C_p (fF)		87	87	87	87	87
C_b (fF)		30	30	30	30	30
Z_c (Ohm)		87.5	87.5	80	87.5	80
R_d (Ohm)		50	50	50	55	55
ERL (dB)		17.84	16.84	17.30	16.34	15.18
dERL (dB)			-1.00	-0.54	-1.50	-2.66

Proposals

- Propose dERL = -3 dB in Table 163-5
- Propose dERL = -3 dB in Table 120F-1

Thank You

COM spread sheet – IEEE KR for ERL

- ERL22 for TX ERL
- ERL11 for RX ERL

Table 93A-1 parameters			
Parameter	Setting	Units	Information
f_b	53.125	GBd	
f_min	0.05	GHz	
Delta_f	0.01	GHz	
C_d	[1.2e-4 1.2e-4]	nF	[TX RX]
L_s	[0.12, 0.12]	nH	[TX RX]
C_b	[0.3e-4 0.3e-4]	nF	[TX RX]
z_p select	[1 2]		[test cases to run]
z_p (TX)	[31.31; 181.8]	mm	[test cases]
z_p (NEXT)	[0 0; 0 0]	mm	[test cases]
z_p (FEXT)	[0 0; 0 0]	mm	[test cases]
z_p (RX)	[29.29; 181.8]	mm	[test cases]
C_p	[0.87e-4 0.87e-4]	nF	[TX RX]
R_0	50	Ohm	
R_d	[50 50]	Ohm	[TX RX]
A_v	0.413	V	
A_fe	0.413	V	
A_ne	0.608	V	
L	4		
M	32		
filter and Eq			
f_r	0.75	*fb	
c(0)	0.54		min
c(-1)	[-0.34:0.02:0]		[min:step:max]
c(-2)	[0.02:0.12]		[min:step:max]
c(-3)	[-0.6:0.02: 0]		[min:step:max]
c(1)	[-0.2:0.05:0]		[min:step:max]
N_b	12	UI	
b_max(1)	0.85		
b_max(2_N_b)	[0.3 0.2*ones(1,10)]		
b_min(1)	0.3		
b_min(2_N_b)	[0.05:-0.03*ones(1,10)]		
g_DC	[-20:1:0]	dB	[min:step:max]
f_z	21.25	GHz	
f_p1	21.25	GHz	
f_p2	53.125	GHz	
g_DC_HP	[-6:1:0]		[min:step:max]
f_HP_PZ	0.6640625	GHz	

I/O control		
DIAGNOSTICS	1	logical
DISPLAY_WINDOW	1	logical
CSV_REPORT	1	logical
RESULT_DIR	\results\100GEL_KR_{date}\	
SAVE FIGURES	0	logical
Port Order	[3 4 1 2]	
RUNTAG	KR_eval_	
COM CONTRIBUTION	0	logical
Operational		
COM Pass threshold	3	dB
ERL Pass threshold	8	dB
DER_0	0.0001	
T_r	0.0075	ns
FORCE_TR	1	logical
Local Search	2	
BREAD_CRUMBS	1	logical
SAVE_CONFIG2MAT	1	logical
TDR and ERL options		
TDR	1	logical
ERL	1	logical
ERL_ONLY	1	logical
TR_TDR	0.01	ns
N	200	
beta_x	0	
rho_x	0.618	
fixture delay time	[2.40e-9 2.14e-9]	port1 port2
TDR_W_TXPKG	1	UI
N_bx	21	UI
Tukey_Window	1	logical
Noise, jitter		
sigma_RJ	0.01	UI
A_DD	0.02	UI
eta_0	8.20E-09	V^2/GHz
SNR_TX	33	dB
R_LM	0.95	

Table 93A-3 parameters		
Parameter	Setting	Units
package_t1_gamma0_a1_a2	[0 0.00909 0.002772]	
package_t1_tau	0.006141	ns/mm
package_z_c	[87.5 87.5 ; 92.5 92.5]	Ohm
Table 92 - 12 parameters		
Parameter	Setting	
board_t1_gamma0_a1_a2	[0 3.8206e-04 9.5909e-05]	
board_t1_tau	5.790E-03	ns/mm
board_z_c	100	Ohm
z_bp (TX)	110.3	mm
z_bp (NEXT)	110.3	mm
z_bp (RX)	110.3	mm
C_0	[0.29e-41]	nF
C_1	[0.19e-4]	nF
Include PCB	0	logical
Floating Tap Control		
N_bg	3	0 1 2 or 3 groups
N_bf	3	taps per group
N_f	40	UI span for floating taps
bmaxg	0.05	max DFE value for floating taps
B_float_RSS_MAX	0.02	rss tail tap limit
N_tail_start	25	(UI) start of tail taps limit
ICN parameters		
f_v	0.594	*fb
f_f	0.594	*Fb
f_n	0.594	*Fb
f_2	40.000	GHz
A_ft	0.600	V
A_nt	0.600	V
Receiver testing		
RX_CALIBRATION	0	logical
Sigma BBN step	5.00E-03	V

COM spread sheet – IEEE C2C for ERL

- ERL22 for TX ERL
- ERL11 for RX ERL

Table 93A-1 parameters			
Parameter	Setting	Units	Information
f_b	53.125	Gbd	
f_min	0.05	GHz	
Delta_f	0.01	GHz	
C_d	[1.2e-4; 1.2e-4]	nF	[TX RX]
L_s	[0.12, 0.12]	nH	[TX RX]
C_b	[0.3e-4; 0.3e-4]	nF	[TX RX]
z_p_select	[1 2]		[test cases to run]
z_p(TX)	[31.31; 1.8 1.8]	mm	[test cases]
z_p(NEXT)	[0 0; 0 0]	mm	[test cases]
z_p(FEXT)	[0 0; 0 0]	mm	[test cases]
z_p(RX)	[29 29; 1.8 1.8]	mm	[test cases]
C_p	[0.87e-4; 0.87e-4]	nF	[TX RX]
R_0	50	Ohm	
R_d	[50 50]	Ohm	[TX RX]
A_v	0.413	V	
A_fe	0.413	V	
A_ne	0.608	V	
L	4		
M	32		
filter and Eq			
f_r	0.75	*fb	
c(0)	0.54		min
c(-1)	[-0.28;0.02;0]		[min:step:max]
c(-2)	[0.02;0.1]		[min:step:max]
c(-3)	[-0.04;0.02; 0]		[min:step:max]
c(1)	[-0.1;0.05;0]		[min:step:max]
N_b	6	UI	
b_max(1)	0.65		
b_max(2,N_b)	[0.15 0.1*ones(1,4)]		
b_min(1)	0.3		
b_min(2,N_b)	[0.05 -0.04*ones(1,4)]		
g_DC	[-20:1:0]	dB	[min:step:max]
f_z	21.25	GHz	
f_p1	21.25	GHz	
f_p2	53.125	GHz	
g_DC_HP	[-4:1:0]		[min:step:max]
f_HP_PZ	0.6640625	GHz	

I/O control			
DIAGNOSTICS	1	logical	
DISPLAY_WINDOW	1	logical	
CSV_REPORT	1	logical	
RESULT_DIR	\results\100GEL_KR\{date}\		
SAVE_FIGURES	0	logical	
Port Order	[3 4 1 2]		
RUNTAG	KR_eval_		
COM_CONTRIBUTION	0	logical	
Operational			
COM Pass threshold	3	dB	
ERL Pass threshold	8	dB	
DER_0	1.00E-05		
T_r	0.0075	ns	
FORCE_TR	1	logical	
Local Search	2		
BREAD_CRUMBBS	1	logical	
SAVE_CONFIG2MAT	1	logical	
TDR and ERL options			
TDR	1	logical	
ERL	1	logical	
ERL_ONLY	1	logical	
TR_TDR	0.01	ns	
N	200		
beta_x	0		
rho_x	0.618		
fixture delay time	[2.40e-9 2.14e-9]	port1 port2	
TDR_W_TXPKG	1		
N_bx	6	UI	
Tukey_Window	1	logical	
Noise, jitter			
sigma_RJ	0.01	UI	
A_DD	0.02	UI	
eta_0	2.00E-08	V^2/GHz	
SNR_TX	33	dB	
R_LM	0.95		


Table 93A-3 parameters		
Parameter	Setting	Units
package_t1_gamma0_a1_a2	[0.000909 0.0002772]	
package_t1_tau	0.006141	ns/mm
package_Z_c	[87.5 87.5 ; 92.5 92.5]	Ohm
Table 92 - 12 parameters		
Parameter	Setting	Units
board_t1_gamma0_a1_a2	[0.38206e-04 9.5909e-05]	
board_t1_tau	5.790E-03	ns/mm
board_Z_c	100	Ohm
z_bp(TX)	110.3	mm
z_bp(NEXT)	110.3	mm
z_bp(FEXT)	110.3	mm
z_bp(RX)	110.3	mm
C_O	[0.29e-4]	nF
C_I	[0.19e-4]	nF
Include PCB	0	logical
Floating Tap Control		
N_bg	0	0 1 2 or 3 groups
N_bf	3	taps per group
N_f	40	UI span for floating taps
bmax	0.05	max DFE value for floating taps
B_float_RSS_MAX	0.02	rss tail tap limit
N_tail_start	25	(UI) start of tail taps limit
ICN parameters		
f_v	0.594	*fb
f_f	0.594	*fb
f_n	0.594	*fb
f_2	40.000	GHz
A_ft	0.600	V
A_nt	0.600	V
Receiver testing		
RX_CALIBRATION	0	logical
Sigma BBN step	5.00E-03	V

COM spread sheet – IEEE KR for COM


Table 93A-1 parameters				I/O control			Table 93A-3 parameters		
Parameter	Setting	Units	Information	DIAGNOSTICS	1	logical	Parameter	Setting	Units
f_b	53.125	GBd		DISPLAY_WINDOW	0	logical	package_tl_gamma0_a1_3	[0.0009909 0.0002772]	
f_min	0.05	GHz		CSV_REPORT	1	logical	package_tl_tau	0.006141	ns/mm
Delta_f	0.01	GHz		RESULT_DIR	\results\100GEL_KR_(date)\		package_Z_c	[87.5 87.5 ; 92.5 92.5]	Ohm
C_d	[1.2e-4 1.2e-4]	nF	[TX RX]	SAVE_FIGURES	0	logical			
L_s	[0.12, 0.12]	nH	[TX RX]	Port Order	[1 3 2 4]				
C_b	[0.3e-4 0.3e-4]	nF	[TX RX]	RUNTAG	KR_eval_				
z_p select	[1 2]		[test cases to run]	COM_CONTRIBUTION	0	logical			
z_p (TX)	[12 31,1 8 1.8]	mm	[test cases]	Operational					
z_p (NEXT)	[12 29,1 8 1.8]	mm	[test cases]	COM Pass threshold	3	dB			
z_p (FEXT)	[12 31,1 8 1.8]	mm	[test cases]	ERL Pass threshold	8	dB			
z_p (RX)	[12 29,1 8 1.8]	mm	[test cases]	DER_0	0.0001				
C_p	[0.87e-4 0.87e-4]	nF	[TX RX]	T_r	0.0075	ns			
R_0	50	Ohm		FORCE_TR	1	logical			
R_d	[50 50]	Ohm	[TX RX]	Local Search	2				
A_v	0.413	V		BREAD_CRUMBS	1	logical			
A_te	0.413	V		SAVE_CONFIG2MAT	1	logical			
A_ne	0.608	V		TDR and ERL options					
L	4			TDR	1	logical			
M	32			ERL	1	logical			
filter and Eq				ERL_ONLY	0	logical			
f_r	0.75	*fb		TR_TDR	0.01	ns			
c(0)	0.54		min	N	3500				
c(-1)	[-0.34 0.02 0]		[min:step:max]	beta_x	0				
c(-2)	[0.02 0.02 0.12]		[min:step:max]	rho_x	0.618				
c(-3)	[-0.06 0.02 0]		[min:step:max]	fixture_delay_time	[0 0]	port1 port2			
c(1)	[-0.2 0.05 0]		[min:step:max]	TDR_W_TXPKG	0				
N_b	12	UI		N_bx	21	UI			
b_max(1)	0.85			Tukey_Window	1	logical			
b_max(2..N_b)	[0.3 0.2*ones(1,10)]			Noise_jitter					
b_min(1)	0.3			sigma_RJ	0.01	UI			
b_min(2..N_b)	[0.05 -0.03*ones(1,10)]			A_DD	0.02	UI			
g_DC	[-20 1.0]	dB	[min:step:max]	eta_0	8.20E-09	V^2/GHz			
f_z	21.25	GHz		SNR_TX	33	dB			
f_p1	21.25	GHz		R_LM	0.95				
f_p2	53.125	GHz		Receiver testing					
g_DC_HP	[-6 1.0]		[min:step:max]	RX_CALIBRATION	0	logical			
f_HP_PZ	0.6640625	GHz		Sigma_BBN_step	5.00E-03	V			

TX TDR and ERW with Sweeping Z_c

- TDR with sweeping Z_c (Ohm)




- Effective reflection waveform (ERW) with sweeping Z_c (Ohm) – $N_{bx} = 21$



TX ERL with Sweeping Z_c

- ERL ($z_p = 31 \text{ mm}$, $C_p = 87 \text{ fF}$, $C_b = 30 \text{ fF}$)


	Reference								
$Z_c (\text{mm})$	80	82.5	85	87.5	90	92.5	95	97.5	100
$R_d (\text{Ohm})$					50				
$T_{fx} (\text{ns})$					2.158				
$KR (N_{bx} = 21)$	18.12	18.37	18.50	18.60	18.64	18.65	18.63	18.56	18.47



TX ERL with Sweeping C_p

- ERL ($z_p = 31$ mm, $C_b = 30$ fF)

	Reference						
C_p (fF)	25	50	75	87	100	125	150
R_d (Ohm)				50			
T_{fx} (ns)				2.158			
KR ($N_{bx} = 21$)	19.20	19.08	18.77	18.60	18.40	18.01	17.61
C2C ($N_{bx} = 6$)	18.66	18.48	18.06	17.84	17.60	17.16	16.74



TX ERL with Sweeping C_b

- ERL ($z_p = 31$ mm, $C_p = 87$ fF)

	Reference								
C_b (fF)	25	30	50	75	100	125	150		
R_d (Ohm)			50						
T_{fx} (ns)			2.37						
KR ($N_{bx} = 21$)	18.84	18.60	17.64	16.57	15.63	14.82	14.10		
C2C ($N_{bx} = 6$)	18.08	17.84	16.91	15.87	14.96	14.17	13.47		

