

# ITU-T G.9806AM3 UPDATE

IEEE 802.3 WORKING GROUP PLENARY

TASK FORCE: GREATER THAN 50 GB/S BIDIRECTIONAL OPTICAL ACCESS PHYS

MARCH 2023

JUN SHAN WEY, VERIZON, USA

HIROTAKA NAKAMURA, NTT, JAPAN

DEREK NESSET, HUAWEI, GERMANY

JOHN JOHNSON, BROADCOM, USA

TAKUYA KANAI, NTT, JAPAN

FABRICE BOURGART, ORANGE, FRANCE

# Background

- 100G-BiDi ad hoc group formed for G.9806Am3 is progressing discussion
  - Monthly meetings
  - Target date for consent of class S(0-15 dB) is the next ITU-T SG15 plenary on April 2023
  - Target date for consent of class B-(0-23 dB) is ITU-T SG15 plenary on November 2023
- This contribution updates the strawman PMD parameters discussed by 100G-BiDi ad hoc meeting
  - The main change is to split the class S budget into 2 ranges
    - S lower (0-10 dB)
    - and S upper (5-15dB)
  - Limits the link dynamic range
  - Alleviates potential Rx overload issue from previous Strawman

# Previous strawman

Items	Unit	S Class Specification
Modulation format		PAM4
Nominal modulation rate	Gbit/s	53.125
Wavelengths	nm	$1304.6 \pm 1$ nm, $1309.1 \pm 1$ nm
Mean launch power MAX	dBm (AVP)	TBD
Launch power in OMAouter (min) - For TDECQ < 1.6 dB - For 1.6 dB < TDECQ < 3.6 dB	dBm	+3.0 +1.4 + TDECQ
Launch power in OMAouter minus TDECQ (min)	dBm	1.4
Transmitter and dispersion eye closure for PAM4 (TDECQ) max	dB	3.6
Receiver sensitivity (OMA) - For TECQ < 1.6 dB - For 1.6 dB < TECQ < 3.6 dB	dBm	-12.5 -14.1 + TECQ
Damage threshold MAX	dBm	TBD
$ TDECQ - TECQ $ (max)	dB	2.5
Optical path penalty MAX (Informative)	dB	2.5
Extinction ratio MIN (Note 3)	dB	5.0
Bit error ratio		Less than $2.4 \times 10^{-4}$

Results in +5dBm OMA  
into APD Rx



# Increasing dynamic range

- The following have been considered to increase the dynamic range
  - Use of stronger FEC (e.g. 1e-2 BER from G.9804.2) to improve Rx sensitivity
  - Adaptive APD bias control to increase the overload
- Stronger FEC has been put to one side as network operators require full 100G service rate
- Adaptive APD bias control is understood to permit  $\sim 0\text{dBm}$  overload

# Strawman PMD parameters for G.9806Am3

Items	Unit	$S_L$ Class Specification	$S_U$ Class Specification
Modulation format		PAM4	PAM4
Nominal modulation rate	Gbit/s	53.125	53.125
Wavelengths	nm	$1304.6 \pm 1$ nm, $1309.1 \pm 1$ nm	$1304.6 \pm 1$ nm, $1309.1 \pm 1$ nm
Mean launch power max	dBm	-0.7 + margin (0.5dB?)	4.3 + margin (0.5dB?)
Launch power in OMAouter (min) - For TDECQ < 1.6 dB - For 1.6 dB < TDECQ < 3.4 dB	dBm	-2.3 -3.9 + TDECQ	+2.7 1.1 + TDECQ
Transmitter and dispersion eye closure for PAM4 (TDECQ) max	dB	3.4	3.4
Receiver sensitivity (OMA) - For TECQ < 1.6 dB - For 1.6 dB < TECQ < 3.6 dB	dBm	-12.8 -14.4 + TECQ	-12.8 -14.4 + TECQ
Receiver OMA max		-0.5 + margin (0.5dB?)	-0.5 + margin (0.5dB?)
Damage threshold MAX	dBm	0.5 + margin (0.5dB?)	0.5 + margin (0.5dB?)
$ TDECQ - TECQ $ (max)	dB	2.5	2.5
Optical path penalty MAX (Informative)	dB	2.5	2.5
Extinction ratio MIN (Note 3)	dB	5.0	5.0
Bit error ratio		Less than $2.4 \times 10^{-4}$	Less than $2.4 \times 10^{-4}$

# Power budgets



# 100G BiDi PtP adhoc group -time plan-

Ad hoc meeting is held once a month at 14:00- 15:00 CEST (Geneva Time).

7<sup>th</sup> : 2023.3.2 (Thu.)

8<sup>th</sup> : 2023.4.13 (Thu.)

9<sup>th</sup> : 2023.5.11 (Thu.)

	Oct.	Nov.	Dec.	Jan. 2023	Feb.	Mar.	Apr.	May
ITU-T	▲ ITU interim 10/25-27	▲ ITU interim 11/29-12/1	▲ ITU interim 12/6-12/8	▲ ITU interim 1/17-18	▲ ITU interim 2/21-23	▲ ITU interim 3/21-23	▲ ITU Plenary 4/24-27	
IEEE		▲ Plenary 11/14-18		▲ Interim 1/16		▲ Plenary 2 <sup>nd</sup> week in Mar.		▲ Interim 2 <sup>nd</sup> week in May
100G Bidi adhoc	▲ 2nd 10/13	▲ 3rd 11/22	▲ 4th 12/9	▲ 5th 1/12	▲ 6th 2/9	▲ 7th 3/2	▲ 8th 4/13	▲ 9th 5/11

Now

# Summary

- ITU-T G.9806Am3 project are developing specifications based on technologies well-supported by industry
- Specification alignment between ITU-T and IEEE is essential for the ecosystem
- Class S in G.9806Am3 target consent in the April 2023 ITU-T SG15 Plenary  
The adhoc group must conclude its work and **reach consensus by 17 March**
- Requests to IEEE 802.3 participants
  - Feedback of strawman PMD parameters to the ITU-T 100G BiDi PtP adhoc group
  - IEEE 802.3 participants are encouraged to join the ITU-T 100G BiDi PtP adhoc group.  
Contact to its co-chairs;  
Dr. Hirotaka Nakamura [hirotaka.nakamura.by@hco.ntt.co.jp](mailto:hirotaka.nakamura.by@hco.ntt.co.jp)  
Dr. Derek Nessel [derek.nessel@huawei.com](mailto:derek.nessel@huawei.com)



THANK YOU