```
2
                     REVISION REQUEST
3
    +-----
    DATE: 04 October 2024
5
    NAME: Charity Reed
6
    COMPANY/AFFILIATION: UNH-IOL
7
   E-MAIL: creed@iol.unh.edu
8
9
   REQUESTED REVISION:
10
     STANDARD: 802.3-2022
11
    CLAUSE NUMBER: Figure 149-24
12
     CLAUSE TITLE: Receive state diagram
13
   PROPOSED REVISION TEXT:
14
    Replace
15
16
    "(rx cnt = 16) * ((rs check = BAD) + !frame boundary"
17
18
    with
19
20
    "(rx cnt = 16) * ((rs check = BAD) + !frame boundary)"
21
22
    from the transition from the CHECK READ state to the BAD FRAME state
23
24
    RATIONALE FOR REVISION:
25
    There is an unclosed parenthese in the exit condition from the
26
    CHECK READ state to the BAD FRAME state. This parenthese should be
    closed after the final condition. Removing the parenthese does not make
27
28
    sense as that would mean the state diagram would transition to the
29
    BAD FRAME state after loading the first symbol into rx oam.
30
31
    IMPACT ON EXISTING NETWORKS:
32
    This change will impact any 2.5GBASE-T1, 5GBASE-T1, or 10GBASE-T1 PHY
33
    implementations that treated the condition as if it were "(rx cnt = 16)
34
    * (rs check = BAD) + !frame boundary".
35
36
    +-----
37
    |Please attach supporting material, if any
38
    |Submit to:- David Law, Chair IEEE 802.3
39
    |and copy:- Adam Healey, Vice-Chair IEEE 802.3
40
           E-Mail: stds-802-3-maint-req@ieee.org
41
   |At:-
42
43
               +------ For official use -----+
                | REV REQ NUMBER: 1467
44
               | DATE RECEIVED: 04 October 2024
45
46
               | EDITORIAL/TECHNICAL
47
               | ACCEPTED/DENIED
48
               | BALLOT REQ'D YES/NO
49
               | COMMENTS:
50
    +----
51
   | For information about this Revision Request see -
52
   |http://www.ieee802.org/3/maint/requests/revision history.html#REQ1467 |
    +-----
53
54
```